

**GENUINE PARTS****INSTALLATION INSTRUCTIONS****DESCRIPTION: ALLOY WHEEL LOCK KIT M12 & M14****APPLICATION:****Wheel Lock Kit 999H1-A7003**

Nissan: 350Z 17"/18"(non-Rays), Altima, Altima Coupe, 2004-2016 Armada, Cube, 2005-2021 Frontier 16" 6-Spoke/18", 2009-2010 GT-R, 2010~ GT-R Premium, 2018~ GT-R Pure, 2012-2016 GT-R Black, 2014 GT-R Track, Juke, Leaf, 1995-2011 Maxima, 2003-2018 Murano, (ex. 2003-2005 18"), 2013-2016 Pathfinder 16" 6-Spoke/18", Quest, Rogue, Sentra, Xterra 16" 6-Spoke, Versa, Versa Note, 2004-2015 Titan, 2016~ Titan (Light Duty-Factory Wheel), Kicks

Infiniti: 2003-2008 FX35/FX45 19", 2003-2007 G35 Coupe, 2003-2006 G35 Sedan, M35/M45 (ex. 18"), JX35, Q45 19", 2013-2015 QX60

Wheel Lock Kit 999H1-A7009

Nissan: 350Z 18"/19" Rays, 2005-2021 Frontier 16" 5-Spoke/17", 2013 -2016 Pathfinder 16" 5-Spoke/17", Xterra 16" 5-Spoke/17", 2017~ Titan (Light Duty - Accessory Wheel), ~2022 Frontier , 2023 Nissan Arya

Wheel Lock Kit 999W2-VR000

Nissan: 2003-2005 Murano 18"

Infiniti: 2003-2008 FX35/FX45 18", M35/M45 18", Q45 17"/18", 2004-2010 QX56

Wheel Lock Kit 999W2-JT000

Nissan: 370Z, 2012~ Maxima, 2017~ Pathfinder, 2019~ Murano, 2023~ Z

Infiniti: EX35, EX37, 2009-13 FX35, FX37, 2009-13 FX45, FX50, G25, 2008 G35 Cpe, 2007-08 G35 Sed, G37, M37/M56, Q40, Q50, Q60, Q70, QX50, 2016~ QX60, QX70, QX55 2023 Nissan Z

Wheel Lock Kit 999W2-3X000

Nissan: 2016~ Titan (Heavy Duty - Factory Wheel), 2017~ Armada

Infiniti: 2011-2013 QX56, QX80

Wheel Lock Kit T99W2-4X000

Nissan: 2015~ GT-R Nismo, 2017~ GT-R Track

KIT CONTENTS:

Item	Qty.	Part Description	Service Part Number
A	4	Wheel Lock	Not Serviceable- Part of Kit
B	1	Key	
C	1	Instruction Card	
D	1	ID Card	
E	1	Order Form with Envelope	
F	1	Plastic Wire Tie	

TOOLS REQUIRED:

- Wire Brush
- Torque Wrench
- Vehicle Lug Wrench (if equipped)
- 21mm Hex Socket

INSTALLATION CAUTIONS:**CAUTION**

- Use of an impact wrench may cause permanent damage to the wheel lock and key. If in doubt about the wheel lock application, ask your dealer for assistance.
- Do not use oil or grease on the wheel stud or wheel lock. This could cause the wheel lock to become loose.