ASTON MARTIN

V12 Vantage S

**Aston Martin Owners' Club (AMOC)**

**An invitation to join the Aston Martin Owners' Club**

The sporting spirit of the 1930s exists today in one of the world's most exclusive car clubs. Enthusiasts in nearly 60 countries are united by an interest in iconic cars with an enviable pedigree. Enjoy the company of like-minded owners in a wide range of activities: social evenings, weekends away or motoring tours. Something more competitive? AMOC Concours are a benchmark for connoisseurs of fine motorcars. A need for speed? We organise track days, sprints and hill climbs as well as circuit racing in venues such as Silverstone, Goodwood and Lime Rock in the USA.


The Aston Martin Owners' Club
Drayton St. Leonard,
Wallingford,
Oxford,
England,
OX10 7BG
Telephone: +44 (0) 1865 400 400
Facsimile: +44 (0) 1865 400 200
E-Mail: hqstaff@amoc.org
Website: www.amoc.org









## Aston Martin Heritage Trust


The Aston Martin Heritage Trust is an educational charity dedicated to the preservation, promotion and enhancement of the near 100 year history of Aston Martin. Its world class collection comprising the automotive museum, substantial archive and collection of historical artefacts is housed in the magnificently restored Grade II* listed barn in Oxfordshire which it shares with the Owners Club. As a member of the Owners' Club you become a member and supporter of the Trust, so please log on to our web site for more information, or better still pay us a visit and see the collection for yourself.


The Aston Martin Heritage Trust
Drayton St. Leonard,
Wallingford,
Oxford,
England,
OX10 7BG
Telephone: +44 (0) 1865 400 414
Facsimile: +44 (0) 1865 400 200
E-Mail: secretary@amht.org.uk
Website: www.amht.org.uk









Introduction ..... 1
Vehicle Security ..... 2
Before Driving ..... 3
Controls ..... 4
Driving ..... 5
Climate Control ..... 6
Audio ..... 7
Hands-Free Phone ..... 8
Satellite Navigation ..... 9
Maintenance ..... 10
Specifications ..... 11
Service ..... A
Aston Martin Warranty ..... B
Aston Martin Assistance ..... C
Alphabetical Index ..... D

Every effort has been made to make sure that the information provided in this Owner's Guide is accurate and up-to-date. However neither the manufacturer or the Dealer, by whom this Owner's Guide is supplied, will in any circumstances be held responsible for any inaccuracy or the consequences thereof. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form, electronic, mechanical, photocopying, recording or other means without prior written permission from Aston Martin Lagonda Limited.

The manufacturer reserves the right to vary specifications without notice in accordance with its policy of continual product improvement.

Produced by the Technical Publications Department
Aston Martin Lagonda Limited
Banbury Road,
Gaydon,
Warwick,
CV35 0DB
England
Telephone: (+44) 01926 644300
Fax: (+44) 01926 644733

Issue 1: September 2013
Part Number: ED23-19A321-AA

# Introduction


Welcome ..... 1.2
Warnings, Cautions and Notes ..... 1.3
Component Location ..... 1.3
Vehicle Identification ..... 1.4
Data Recording ..... 1.4
Reporting Safety Defects ..... 1.5
Vehicle Provenance ..... 1.5




# Welcome

Welcome to your new Aston Martin V12 Vantage S.

This Owner's Guide, along with other publications included in your literature pack, provides information which will enhance your pleasure from owning and driving your Aston Martin.

This Owner's Guide has been designed to explain the vehicle's operation and to make the control of its systems easy to understand and operate. All new owners are recommended to carefully study the contents of this Owner's Guide prior to driving.

This Owner's Guide forms part of the essential vehicle equipment for homologation purposes and must stay with the vehicle at all times.

## Aston Martin Franchise Dealers

A full list of Aston Martin Dealers worldwide, where sales and service are provided by companies with the facilities, knowledge and factory trained personnel can be found at:

www.astonmartin.com

Every effort is made to make sure that the information given in the dealer list is accurate and up-to-date. However changes amongst holders of the Aston Martin franchise can occur. Neither Aston Martin nor any listed Importer or Dealer shall in any circumstances be held liable for any inaccuracy, or the consequences thereof.

Dealers listed all aim to conform to Aston Martin standards of excellence in both sales and service. However, all vehicles sold as Aston Martins are required to meet local legislation requirements.

Should service be required in a country other than that in which this vehicle was originally purchased, every effort will be made to meet the owner's requirements, but the availability of certain parts may be affected by differences in vehicle and component specifications.

If the nearest Aston Martin Dealer is unable to help, contact Aston Martin directly:

Aston Martin Lagonda Limited,
Banbury Road,
Gaydon,
Warwick,
CV35 0DB,
England
Telephone: (+44) (0)1926 644300
Facsimile: (+44) (0)1926 644733

Aston Martin Dealers are independent traders, they are not the Company's Agents, and therefore have no authority to bind the Company or to enter into any financial or other commitments on the Company's behalf.

Only Aston Martin Dealers are authorised to carry out warranty work.

## Aston Martin Authorised Body Repairers

A full list of Aston Martin Authorised Body Repairers worldwide can be found at:

www.astonmartin.com

All Aston Martin Approved Body Repair centres have been assessed and audited to Aston Martin Body Repair Centre standards in either Category A or B.

***Category A:*** Repairs to the bonded aluminium structure and all paint related and light structural damage.

***Category B:*** All paint related and light structural damage.

Every effort is made to make sure that the information given in the Aston Martin Authorised Body Repairers list is accurate and up-to-date. However changes can occur. Neither Aston Martin nor any Aston Martin Authorised Body Repairer shall in any circumstances be held liable for any inaccuracy, or the consequences thereof.

## Aston Martin Authorised Service Centres

A full list of Aston Martin Authorised Service Centres can be found at:

www.astonmartin.com

All Aston Martin Approved Service Centres have been assessed and audited to Aston Martin standards.

Every effort is made to make sure that the information given in the Aston Martin Authorised Service Centres list is accurate and up-to-date. However changes can occur. Neither Aston Martin nor any Aston Martin Authorised Service Centre shall in any circumstances be held liable for any inaccuracy, or the consequences thereof.

## Warnings, Cautions and Notes

The following Warnings, Cautions and Notes are used within this Owner's Guide to call your attention to specific types of information.

**Warnings**

***Warning: Provided to show procedures which must be followed precisely to help avoid the risk of personal injury.***

**Cautions**

***Provided to show procedures which must be followed precisely to reduce the possibility of damage to your vehicle.***

**Notes**

*Provided to show procedures which will help to avoid difficulties in the operation of your vehicle.*

## Component Location

All directions for locating components are described as viewed from the driver's seat, i.e. the fuel filler flap shown on this diagram will be described as 'located at the rear left side of the vehicle'.



## Vehicle Identification

The Vehicle Identification Number (VIN) is shown in the left side bottom corner of the windscreen.




The VIN Plate, attached to the front subframe behind the engine bay front cross member (viewed from above), is model and market dependent:




The VIN is also stamped into the floorpan in the right side footwell.

*To view the VIN stamped into the floorpan lift the carpet up, from the front, and then lift the sound deadening material.*

## Data Recording

Computers in your vehicle are capable of recording detailed data, potentially including but not limited to information such as:

- The use of restraint systems including seat belts by the driver and passengers.
- Information about the performance of various systems and modules in the vehicle.
- Information related to engine, throttle, steering, brake or other system status.

Any of this information could potentially include information regarding how the driver operates the vehicle, potentially including but not limited to information regarding vehicle speed, brake, throttle application or steering input. This information may be stored under regular operation, in a crash or near crash event.

This information may be read out and used by:

- Aston Martin
- Service and repair facilities
- Law enforcement or government agencies
- Others who may assert a right or obtain your consent to know such information.

## Reporting Safety Defects

If you believe that your vehicle has a safety defect which could cause a crash or could cause injury or death, you should immediately inform your Aston Martin Dealer or the manufacturers After Sales Operation at the address shown.

Aston Martin Lagonda Limited,
After Sales Operations,
Banbury Road,
Gaydon,
Warwick,
CV35 0DB,
England
Telephone: +44 (0)1926 644700
Facsimile: +44 (0)1926 644733

## Vehicle Provenance

**Model:**

**Body Colour:**

**Interior Colour:**

**Fascia Colour:**

**Vehicle Identification Number:**

As on the VIN plate

**First Owner:**

Selling Dealer

Delivery Date

**Second Owner:**

Selling Dealer

Delivery Date

**Third Owner:**

Selling Dealer

Delivery Date

**Fourth Owner:**

Selling Dealer

Delivery Date

**Fifth Owner:**

Selling Dealer

Delivery Date

**Sixth Owner:**

Selling Dealer


Delivery Date

ASTON MARTIN

ASTON MARTIN

# Vehicle Security


Introduction ..... 2.2
Aston Martin Tracking ..... 2.2
Emotion Control Unit ..... 2.5
Emergency Key ..... 2.6
Unlocking and Opening ..... 2.6
Locking ..... 2.7
Master Locks ..... 2.8
Boot Lid ..... 2.8
Deadlocking ..... 2.10
Automatic Lock ..... 2.10
Approach Light ..... 2.11
Homesafe ..... 2.11
Alarm ..... 2.12
Reduced Guard ..... 2.12
Passive Anti-Theft System ..... 2.13
Garage Door Opener ..... 2.14
Personalisation ..... 2.16

## Introduction

This vehicle is protected by an electronic security system which includes:

- Remote arm and disarm
- Perimeter sensing
- Remote door, boot lid, fuel flap release lock and unlock
- Guard reduction mode
- Alarm siren with battery backup[1]
- Random code encryption to prevent electronic scanning or grabbing of the vehicle key identity code
- Interior movement sensor
- Tilt Sensor

Vehicle protection is enhanced by a Passive Anti-Theft System (PATS) which provides engine immobilisation if the wrong vehicle key is used.

When the security system is armed, any attempt to forcibly open a door, the boot lid or the bonnet will result in full alarm operation.

### Garage Door Opener

Option

As a security precaution make sure that all programming is erased in the HomeLink system before selling this vehicle (Refer to 'Garage Door Opener', page 2.14).

## Aston Martin Tracking

The Aston Martin Tracking system is a stolen vehicle tracking system. It uses the latest Global Positioning System (GPS) and Global System for Mobile communications (GSM) technology providing pinpoint accuracy and unparalleled service levels.

The system, which is discretely installed in the vehicle, is an easy-to-use system that provides the following important features:

**Automatic Driver Recognition**

Alerts the Aston Martin Tracking Secure Operating Centre immediately if your vehicle is stolen, even if the thief has your keys.

**Engine Start Inhibit**

Activated by the Secure Operating Centre with Police authorisation, to prevent the engine from being restarted.

**Tamper Alert**

Activated when the system battery is disconnected or discharged, or when the system wiring is cut.

**Tow-Away Alert**

Triggered when motion is detected with the ignition switched off and the driver card is not present.

1. Markets where audible sirens are permitted.

**System Health Check**

Regular automatic self diagnostic check.

**Transport Mode**

Set by the Secure Operating Centre when the vehicle owner has confirmed the vehicle is being transported. This will prevent false alerts being generated.

**Vehicle Servicing Mode**

Set by the Secure Operating Centre when the vehicle has been given to the Aston Martin Dealer for maintenance.

**Theft History**

Minute by minute theft log helps Police secure convictions.

**Pinpoint GPS Tracking**

Accurate to within 10 metres.

**International GSM Coverage**

Roaming SIM card gives coverage across more than 180 countries.

**European Coverage**

Local language Police liaison and stolen vehicle recovery across Europe.

Countries covered by Aston Martin Tracking System:

Albania, Austria, Belarus, Belgium, Bosnia and Herzegovina, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France (Monaco), Germany, Greece, Hungary, Ireland, Italy (Vatican City, San Marino), Latvia, Lithuania, Luxembourg, Macedonia, Malta, Montenegro, Netherlands, Norway, Poland, Portugal, Romania, Russia, Serbia, Slovakia, Slovenia, South Africa, Spain (Andorra, Gibraltar), Sweden, Switzerland (Liechtenstein), Turkey, Ukraine and United Kingdom.

**Insurance Accreditation**

Conforms to the highest European accreditations for stolen vehicle tracking systems - Thatcham, Incert (formerly Assuralia) and SCM and is approved by major insurers.

**Aston Martin Approved**

The only vehicle tracking system approved for all Aston Martin vehicles.

## How the System Works

The Aston Martin Tracking system is supplied with two unique driver cards. An authorised driver must have a driver card in their possession when using the vehicle.

*Do not leave the driver card inside the vehicle or with the vehicle key. It should be kept in a safe place and always separately from your vehicle keys.*

The system automatically arms itself after the vehicle ignition has been switched off for 70 seconds and the driver card is out of range (approximately 3 metres).

The system will automatically disarm itself when the driver card is bought back in range of the vehicle.

If your vehicle is driven approximately 100 metres and the driver card has not been detected, a silent alert is transmitted to the Secure Operating Centre to inform the advisors of a potential unauthorised movement of your vehicle. The advisors then contact you.

To avoid an alert being generated, if the engine has been started and the driver card is not in your possession, switch the ignition off and call the Secure Operating Centre for advice.

The system will additionally:

- Send an alert if your vehicle is lifted or towed away without the keys.
- Send an alert if your vehicle battery is disconnected or discharged.
- Send an alert if the GPS antenna has been disconnected.
- Send a monthly health check message to the Secure Operating Centre to confirm full system functionality.

Please consult your Aston Martin Dealer for details and subscription rates.

## If your Vehicle is Stolen

After an alert has been received, the Secure Operating Centre advisors attempt to contact you using the telephone number(s) that you supplied at the time of registration. A minimum of two telephone numbers must be provided at the time of activation of the contract.

The Police are not contacted until the advisors have spoken with you. This is to comply with Police procedures so that Police time is not wasted with false alarms.

Once the theft has been confirmed with you, the advisors will ask you to contact the Police to report the theft and to call the advisor back immediately with a Police incident number. Receipt of an alert does not constitute a confirmed theft, as Police Forces require key holder verification of a theft.

The Secure Operating Centre then liases with the relevant Police Force to seek to recover your vehicle.

If your vehicle is outside the UK, the Secure Operating Centre work with the Police in their local language across Europe to recover your vehicle quickly.

In order to prevent your vehicle being moved following a theft, the Secure Operating Centre under instruction from the Police, may temporarily prevent the vehicle's engine from restarting.

Once the Police have secured the stolen vehicle, arrangements are made with you for the vehicle to be collected. The Police may require it to be taken to a secure compound for further investigation.

You will be liable for any statutory Police recovery and storage charges, payable directly to the Police.

## Additional Information

### False Alarms

To avoid unnecessary alerts, contact the Secure Operation Centre to inform them of any potential false alarm. Excessive false alerts may result in a charge.

### Damage Check

If you are involved in an accident or if your vehicle battery has been disconnected for any reason (for example, body work repair or paint re-spray), you must call Aston Martin Tracking Customer Services so that they can test the system to check that it is still functioning correctly.

## Change of Details

Should any of your personal details change, you must call Aston Martin Tracking Customer Services. For example:

- Changing the registration plate on the vehicle.
- Selling the vehicle.
- Change of address.
- Change of mobile phone number.
- New owner buying a pre-owned vehicle already fitted with Aston Martin Tracking System.

# Emotion Control Unit

## Contact Details

**Aston Martin Tracking 24 Hour Secure Operating Centre**: 0844 239 0035

**Or from abroad**: +44 (0) 208 305 2026


**Aston Martin Tracking Customer Services**: 0844 239 0032

(Monday to Friday - 08.30 to 17.30)

**Or from abroad**: 0844 239 5404

*When registering for the Aston Martin Tracking System, you are also provided with all the same details and contact numbers needed if your vehicle is stolen. Keep these details safe and not in the vehicle otherwise you will not be able to refer to it if your vehicle is stolen.*

The vehicle is supplied with three vehicle keys[1] (Emotion Control Units), a glass key, a spare key and an emergency key.



Keep the spare key in a safe place. Do not leave a vehicle key in the vehicle when unattended.

*If a vehicle key is lost, contact your Aston Martin Dealer.*

## Vehicle Key Security Functions




***[1] LOCK:*** Press and release for one step vehicle locking and to arm the security system. The vehicle will deadlock after 25 seconds.

***[2] UNLOCK:*** Press and release for one step vehicle unlocking.

***[3] BOOT OPEN:*** Press once to release the boot lid catch (Refer to 'Boot Lid', page 2.8).

***[4] APPROACH LIGHT:*** Press to set the front, rear side and interior lamps to ON (Refer to 'Approach Light', page 2.11).

1. Manufactured by STRATTEC 8D33-70290-BG.

## Emergency Key



In the unlikely event that either the vehicle key fails to operate or the vehicle battery is fully discharged use the emergency key to lock or unlock the vehicle.

Insert the emergency key in the door lock and turn fully towards the front of the vehicle, then release, to centrally lock the vehicle, disable the boot lid and fuel flap release switches. The security system will not arm.

To centrally unlock the vehicle, enable the boot lid and fuel flap release switches, turn fully towards the rear of the vehicle, then release. If the security system was armed, the alarm will start.

To stop the alarm insert the vehicle key (even if the vehicle key has lost all power) into the ignition control and move to position 'II' (ignition ON).

*If the vehicle battery is fully discharged the emergency key will only lock or unlock a door.*

*Even if the vehicle key has lost all power it will start the engine if required.*


*Memory seats (optional): The front seats and door rear view mirrors will not move to a preset position if the vehicle is unlocked using the emergency key.*

*If the emergency key is lost, contact your Aston Martin Dealer.*

## Unlocking and Opening

Stand within 5 m of the vehicle, point the vehicle key towards the vehicle and press the ***UNLOCK*** button. To show that the security system has been disarmed, the direction indicators will flash twice. All vehicle doors will unlock.

Push at point A and grab the emerging door release. Pull the door release to open the door.




If a door is opened while driving a warning sound will be heard until the door is closed.

*If preferred you can unlock the driver's door only with the first press of the button and the rest of the vehicle with a second press (Refer to 'Personalisation', page 2.16).*

*For ease of use at night white LEDs are incorporated into the door handles. An LED will come ON in the door handles when the vehicle is unlocked. A door LED will go OFF once the door is opened. If a door is not opened the LEDs will go OFF after two minutes.*

*If the vehicle has been opened using the spare key and the driver seat or door rear view mirrors have been adjusted, the seat and door rear view mirrors will move to the positions memorised by the key which is being used (Refer to 'Seat Memory Function', page 3.6).*

*As the vehicle is unlocked, the interior lamps will come ON for five minutes. The lamps will go OFF 30 seconds after doors are closed or when the vehicle is started.*

*If the door is left open the door puddle lamp will go OFF after eight minutes.*

## Unlocking From Inside the Vehicle

***If reduced guard was not set to ON before locking the vehicle, deadlocking, interior movement and tilt sensors (optional) are enabled. Passengers will not be able to unlock a door from the inside.***

If reduced guard or automatic lock was set to ON before the vehicle was locked, one pull of a door handle will centrally unlock the doors, a second pull of the door handle will open that door.

(Refer to 'Automatic Lock', page 2.10).

(Refer to 'Reduced Guard', page 2.12).

Vehicle unlock from inside can be set to automatic unlock when the vehicle key is removed from the ignition control. With automatic unlock ON only one pull of a door handle will open that door (Refer to 'Personalisation', page 2.16).

When opening a door from inside the vehicle after reduced guard has been set to ON, the security system alarm will start. Press the ***UNLOCK*** button on the vehicle key to stop the alarm (there is approximately a ten second delay before the alarm is stopped).

***If passengers are to stay in the vehicle after it has been locked, reduced guard must be set to ON before locking. This will let a passenger open a door from inside the vehicle.***

Make sure that all the doors, the boot lid and the bonnet are closed (the vehicle will not lock if a door is left open). Stand within 5 m of the vehicle, point the vehicle key towards the vehicle and press the ***LOCK*** button once to lock the doors, disable the boot lid and fuel flap release switches and arm the security system. The direction indicators will flash once as the security system is armed (Refer to 'Personalisation', page 2.16).

The driver's seat and both door rear view mirror positions are memorised and will be recalled the next time the vehicle is opened using the same vehicle key.

*The security system will arm and the doors will deadlock after 25 seconds.*

*If the vehicle is locked with the boot lid open, the vehicle will lock and arm but deadlocking, tilt and interior movement sensors will not operate. Close the boot lid to arm the complete security system.*

### Automatic Re-locking

If the vehicle is locked and then unlocked but a door or the boot lid is not opened within two minutes, the vehicle will automatically lock and arm again.

## Master Locks




All doors, fuel flap and boot lid release switches may be locked and unlocked by using the master lock switch (A). Press the switch to lock. Press again to unlock.

If the vehicle is locked using the master lock switch, one pull of a door handle will centrally unlock the doors, a second pull of the door handle will open that door.

The master lock switch will operate for seven minutes after the vehicle key has been removed from the ignition control, if the vehicle is not locked using the vehicle key.

The master lock switch will not operate if the vehicle has been locked from the outside.

Operation of the master lock switch will override automatic lock (Refer to 'Automatic Lock', page 2.10).

*When the vehicle is unlocked using the master lock switch the LED in each door handle will come ON (for 10 seconds or until the door is opened). This may aid access for passengers at night time.*

*In the event of a vehicle accident the doors will automatically unlock.*

## Boot Lid

### To Open the Boot Lid





Press the ***BOOT OPEN*** button on the vehicle key **once** to enable the release catch, then press the boot lid button (A) and lift the lid. Press the button **twice** (within three seconds) to enable the boot lid catch and release the lid. Lift the lid.

*If the vehicle is locked and armed the security system will disarm and the direction indicators will flash twice when the boot is opened. The doors will stay locked (Refer to 'Personalisation', page 2.16).*


## Opening from Inside the Vehicle

Pull back on the boot lid release switch (B). The boot lid catch will release. Lift the lid.




## To Close the Boot Lid

Grasp the leather pull (C) and pull the boot lid down, then push the boot lid down and make sure that its catch engages. If the boot lid is slammed shut, this is overridden. Press the ***LOCK*** button on the vehicle key to lock the lid. The direction indicators will flash once as the security system is armed (Refer to 'Personalisation', page 2.16).




*Always make sure that the boot lid is securely closed after use. The boot interior lamps will stay ON for seven minutes if the boot lid is left partially open and the vehicle key is removed from the ignition control.*

## Vehicle Locked - Boot Lid Open


***Do not leave the vehicle key in the boot. If the boot lid is closed there will be no access to the contents of the boot.***

*To use a battery conditioner the boot lid has to be left open (boot lid down but not latched).*

If the vehicle is locked while the boot lid is open, the vehicle will lock and arm (deadlocking, tilt and interior movement sensors will not operate). If the boot lid is then closed (latched) deadlocking, tilt and interior movement sensors will operate and the whole vehicle will be locked and armed.

## Boot Lid Emergency Open

The boot lid can be opened from inside the boot by pulling the luminous emergency release handle (D).




## Deadlocking

***If passengers are to stay in the vehicle after locking, reduced guard must be ON before locking.***

The vehicle will automatically deadlock after 25 seconds after arming the security system. When the vehicle is deadlocked, the doors cannot be opened from the inside by pulling the interior door handle.

To open the doors use the vehicle key.

## Automatic Lock

When automatic lock is set to ON the doors and the boot lid will automatically lock as vehicle speed reaches 7 km/h. This function prevents unwanted access to the vehicle when stopped at traffic lights, etc.

Press ***MENU*** on the centre console. Navigate to *<Car settings...> Enter <Lock settings...> Enter <Automatic settings...>*. Select *<Doors auto lock>* or *<Doors auto unlock on key out>*. Press ***ENTER*** to toggle between ON and OFF.

Then press and hold ***BACK*** to accept and return to the main screen.

***<Doors auto lock>:*** Set to ON: Doors and the boot lid automatically lock when the vehicle moves off.

Set to OFF: Doors and the boot lid will not lock when the vehicle moves off.

***<Unlock on key out>:*** Set to ON: The front doors and the boot lid automatically unlock when the vehicle key is removed from the ignition control.

Set to OFF: One pull of a door handle will centrally unlock all doors, a second pull of the door handle will open that door.

*Automatic lock is factory set to ON (Refer to 'Personalisation', page 2.16).*

*In the event of a vehicle accident all doors will automatically unlock.*

## Approach Light

When approaching the vehicle the side and interior lamps can be set to ON by pressing the ***APPROACH LIGHT*** button on the vehicle key.

The time that the lamps stay ON is programmable (Refer to 'Personalisation', page 2.16).

## Homesafe

When exiting the vehicle and the vehicle key has been removed from the ignition control, flash the main beam (pull the left side stalk up and release without latching) to set homesafe ON. The main beam and rear lamps will then stay ON for a determined amount of time and then go OFF.

The time that the main beam and rear lamps stay ON is programmable (Refer to 'Personalisation', page 2.16).


## Alarm

When the alarm has started a siren will be heard for a 25 seconds cycle (ten cycles maximum) and the direction indicators flash for five minutes after which the security system returns to the armed state. The doors and boot lid will stay locked throughout.

*Markets where visible alarm signals and audible sirens are permitted.*

Stop the alarm at any time by pressing the ***UNLOCK*** button on the vehicle key or by inserting the vehicle key into the ignition control (position 'II'). There is approximately a ten second delay before the alarm is stopped).

*Insert the key to position 'II' by using the flat of a finger, as shown.*



### Interior Movement Sensor

When the vehicle is locked and armed the interior movement sensor will sense movement inside the vehicle. If movement is detected it will start the alarm.

### Tilt Sensor

When the vehicle is locked and armed the tilt sensor will sense if the vehicle is tilted, for example, if the vehicle is being raised on a jack. If vehicle tilt is detected it will start the alarm.

## Reduced Guard

***⚠ Warning: If a passenger is to stay in the vehicle after it has been locked, reduced guard must be set to ON before locking. In an emergency this will let a passenger open a door from inside the vehicle.***

When reduced guard is ON deadlocking, interior movement and tilt sensors (option) are set to OFF. This will let a passenger open a door from the inside by pulling the interior door handle and a passenger or animals to be left in the vehicle with the security system armed.

If a door is opened from the inside, while reduced guard is ON, the security system alarm will start. Press the ***UNLOCK*** button on the vehicle key to stop the alarm at any time.

Reduced guard is set by using the car settings menu. Press ***MENU*** on the centre console. Navigate to *<Car settings...> Enter <Reduced guard...>*. Select *<Activate once>* or *<Ask on exit>* and press ***ENTER*** to toggle between ON and OFF. Then press and hold ***BACK*** to accept and return to the main screen.

***<Ask on exit>:*** Set to ON: Each time the vehicle key is moved from ignition position 'II' (ignition ON) to ignition position 'I' or '0' the message PRESS ENTER TO REDUCE GUARD. PRESS EXIT TO CANCEL will show in the message centre. The message will time out after one minute and reduced guard will not come ON.

Set to OFF: No message will show and reduced guard will not come ON.

***<Activate once>:*** Set to ON: Reduced guard will come ON for one time. Set to ON each time reduced guard is required.

Set to OFF: Reduced guard will not come ON.

*Reduced guard stays ON until the vehicle key is inserted in the ignition control and moved to position 'II' (ignition ON).*

The Passive Anti-Theft System (PATS) is a fully automatic engine immobiliser.

*If a vehicle key is lost, a duplicate key can be created and programmed from the spare key by your Aston Martin Dealer.*

## Starting the Engine

When the security system is disarmed and the vehicle key is in the ignition control, the PATS controller sends a signal to the vehicle key. The vehicle key must respond with a valid code before engine start will be enabled. If a valid code is received, the ignition system will operate normally. If the vehicle key code is not received, or is invalid, engine start stays disabled.

## Alarm Status

The alarm status is shown by the red symbol (A) on the instrument cluster.




## Fault Mode

If the alarm symbol starts to flash at a faster rate when the alarm is not ON, then the alarm may have been previously triggered or there may be a fault. If this continues, consult your Aston Martin Dealer.

# Garage Door Opener

(Option: Available with automatic dim mirror only.)

The garage door opener (HomeLink® Universal Transceiver) operating buttons and transceiver are located in the interior rear view mirror.

The transceiver can be programmed to transmit the radio frequencies of up to three different transmitters used to operate garage doors, entry gates, home lights, security systems, or other radio frequency operated devices.

*A full list of radio frequency operated devices can be either obtained via the HomeLink Hot-line or through the HomeLink compatibility list which is provided on the HomeLink website.*

For information, or for assistance, contact your Aston Martin Dealer.

Alternatively contact HomeLink directly at www.homelink.com or call the HomeLink Hot-line:

Toll-free: 008000 0466 354 65

or

+49 6838 907-277 (In certain countries difficulties may be experienced trying to reach the toll-free number by some providers.)

***Warning: Do not use the transceiver with any garage door opening system that lacks the safety stop and reverse feature as required by safety standards. A garage door opening system which cannot detect an object, signalling the door to stop and reverse, does not meet current safety standards. Using a garage door opening system without these features increases risk of serious injury or death.***

***Warning: When programming the transceiver to a garage door opening system, make sure that people, the vehicle and objects are out of the way to prevent potential harm or damage as the gate or garage door will operate during the programming.***

*Keep the original transmitter for future use or programming procedures if, for example, you purchase a new vehicle.*

*This device may suffer from interference if operated in the vicinity of a mobile or fixed station transmitter. This interference is likely to affect the hand-held transmitter as well as the in-vehicle transceiver.*


*The manufacturer is not responsible for any radio or TV interference caused by unauthorised modifications to this equipment. Such modifications could void the user's authority to operate the equipment.*

## Programming

*Step 1 erases all programming. It only requires completing if programming HomeLink for the first time or when erasing all existing programming. It does not have to be followed to program the other HomeLink buttons.*

*The HomeLink buttons can be reprogrammed individually but not individually erased. Step 1 must be completed to erase all programming.*

1. Press and hold the two outer HomeLink buttons, releasing only when the HomeLink LED begins to flash after 20 seconds. All three buttons are now cleared. The HomeLink system is now in setting mode.
   As a security precaution make sure that all programming is erased in the HomeLink system before selling this vehicle.



2. Hold the original remote control of the device to be programmed at a distance of 10-30 cm away from the HomeLink transmitter unit keeping the LED in view all the time.
   The distance between the remote control and the transmitter unit depends on the system being programmed. You may require several attempts at different distances. Maintain each setting position for at least 15 seconds before trying out another.
3. Using both hands, simultaneously push the remote control button and the desired button (1, 2 or 3).
4. The LED will flash, first slowly and then rapidly. When the LED flashes rapidly, release both buttons. The rapid flashing LED shows successful programming of the new frequency signal.



## Operation

The vehicle should be within the operating range of the gate or garage door opener and the ignition should be ON.

The HomeLink system operates the garage door opener (or other device) in exactly the same way as the original remote control.

When you have programmed the HomeLink system, press the appropriate button 1, 2, or 3 on the control panel to operate the garage door opener.

The LED will come ON when the button on the control panel is pressed.



📖 *For convenience, the original remote control of the device may also be used at any time.*

In the case of a standard code, the HomeLink LED is constantly ON throughout the transmission process. For use with compatible systems, no further action is necessary.

If HomeLink now does not operate the garage door opener (or other device), this may be because the original remote control has a rolling code feature.

## Rolling Code Synchronisation

Check, by going through the following steps, whether or not the garage door opener (or other device) is equipped with a rolling code feature.

- Look in the garage door opener manual for clarification
- The remote control apparently programs HomeLink but HomeLink does not operate the garage door opener
- Press and hold down the programmed HomeLink button. With a rolling code system, the HomeLink LED flashes quickly for a short time and then stays ON constantly for two seconds. This pattern repeats itself for up to 20 seconds

If HomeLink was programmed with a rolling code system, then after the end of the programming period it must be synchronised with this system again before it will function correctly.

Follow the instructions below for Rolling Code Synchronisation (the procedure will take less time with a second person to help).

The vehicle must be within operating range of the garage door opener and the ignition set to ON. Make sure you comply with the safety instructions even when synchronising the rolling code.

1. Locate the Training button (programming button) on the garage door opener motor head unit. Exact location and colour of the button may vary by gate or garage door opener brand (refer to the operating instructions of the garage door opener 'Training additional remote controls').
2. Press the Training button (programming button) on the garage door opener motor head unit (which will usually set a 'training' LED to ON).

   Following step 2, there are typically 30 seconds in which to initiate step 3.
3. Firmly press and release the programmed HomeLink button. Press and release the HomeLink button a second time to complete the training process. (Some garage door openers may require this procedure a third time to complete the training).

The garage door opener should now recognise the HomeLink signal and operate when the HomeLink button is pressed.

The next two buttons may now be programmed if this has not previously been done.

## Reprogramming

If a HomeLink button has been programmed to operate a device, and you now wish to use this button to operate a different device, proceed as follows. This procedure will erase the existing programming of the respective HomeLink button.

1. Press the appropriate HomeLink button 1, 2, or 3 which requires reprogramming and keep holding it for about 20 seconds until the LED starts flashing slowly. Do not release until step 4 has been completed.
2. When the LED begins to flash slowly (after approximately 20 seconds), hold the remote control of the device you wish to use approximately 10-30 cm away from the HomeLink transmitter unit - keeping the LED in view.

   The distance between the remote control and the HomeLink transmitter unit depends on the system being learned. You may require several attempts at different distances. Maintain each setting position for at least 15 seconds before trying out another.
3. Now press the remote control and keep it pressed.
4. The HomeLink LED will flash, first slowly and then rapidly. When the LED begins to flash rapidly, release both buttons.

## Personalisation

A number of security functions can be personalised.



***[1] ON/OFF:*** Infotainment centre ON and OFF.

***[2] SCREEN:*** Shows options, menus and information.

***[3] TUNING:*** Turn (left or right) to navigate in the menus.

***[4] MENU:*** Opens the main menu.

***[5] ENTER:*** Select in the menu or open a selection.

***[6] JOYSTICK:*** Navigate in the menus.

***[7] BACK:*** Navigate back in the menu or cancel a selection.

## Selection

With the vehicle key in ignition position 'I' or 'II', press ***MENU*** and navigate to the required setting and press ***ENTER***. Use the ***JOYSTICK*** to make a selection and press ***ENTER*** to accept.

## Menu

**1) Car settings...**
1) Reduced guard...
  1) Activate once
  2) Ask on exit
2) Mirror settings...
  1) Auto mirror fold flat enabled
  2) Reverse mirror dip settings...
    1) Auto
    2) Passenger only
    3) Passenger and driver
3) Lock settings...
  1) Automatic settings...
    1) Doors auto lock
    2) Doors auto unlock on key out
  2) Doors unlock...
    1) All doors
    2) Driver door, then all
4) Light settings...
  1) Lock confirm. light
  2) Unlock confirm. light
  3) Approach light duration...
    1) 30, 60 or 90 seconds
  4) Homesafe light duration...
    1) 30, 60 or 90 seconds
5) Information...
  1) VIN number...

ASTON MARTIN
ASTON MARTIN

# Before Driving


Checks Before Driving....3.2
Seat Adjustment....3.2
Lightweight Seat....3.3
Sport Seat....3.4
Seat Memory Function....3.6
Steering Wheel....3.8
Interior Mirrors....3.8
Door Mirrors....3.9
Restraints System....3.10
Seat Belts....3.11
Airbags....3.14
Child Safety....3.15
Passenger Airbag Deactivation....3.17
ISOFIX Anchors....3.18
Tether Anchors....3.19
Automatic Locking Retractors....3.20
Child Seats....3.21
Cabin Storage....3.26
Boot Cover....3.28
Accessory Sockets....3.29
Ashtray and Cigar Lighter....3.29
Electric Windows....3.30
Reading Lamps....3.31
Coat Hooks....3.31




## Checks Before Driving

Inspect your vehicle to make sure that everything is according to the information and specifications in this Owner's Guide.

### Outside the Vehicle:

- Visually check the road wheels, nuts and tyres.
- Check that all windows, mirrors and lamps are clear and unobstructed.
- Check that the boot lid, bonnet and fuel filler flap are securely closed.
- Check the operation of all lamps.

### Once Inside the Vehicle:

- Check that the doors are securely closed.
- Check that the seat, mirrors and steering wheel adjustments are correct.
- Check that all gauges and symbols are reading correctly.
- Check that all passengers have fastened their seat belts.

## Seat Adjustment

***⚠ Warning: Do not attempt to adjust the drivers seat whilst driving.***

***! The vehicle key must only be inserted into the ignition control with the two indents first, as shown. To insert the larger end first the key may damage the ignition control.***




The seats can be adjusted while the vehicle key is in the ignition control. Gently insert the vehicle key up to position 'I' (press down until the instrument cluster and infotainment centre lights come ON) and release.

They can also be adjusted:

- Up to six minutes after a door is unlocked and before the vehicle key is inserted into the ignition control.
- Up to six minutes after the vehicle key is removed from the ignition control.

If the seat operation times out:


- Place the vehicle key in the ignition control.
- Close or open a door.

The seat adjustment controls are located each side of the centre console (A).



# Lightweight Seat






***[1] :*** Raise or lower the **front** of the seat.

***[2] :*** Move the seat **forwards** or **rearwards**.

***[3] :*** Raise or lower the **rear** of the seat.


***[4] :*** Tilt the seat **forwards** or **rearwards** to adjust the seat back angle.

## Lumbar Support

Two adjustable lumbar pads are located in the seat back.


To adjust the lumbar pad position:

1. Grab the top of the seat back panel (A) and pull away from the seat.
2. Locate the lumbar pads (B). Pull them from their Velcro fixings and place in to a new position as required.




📖 *Avoid placing the lumbar pads on the strip of Velcro which secures the seat back panel (C).*


3. Install the seat back trim (D).




4. Repeat as required to find the correct lumbar support position.

## Easy Access

***⚠ Warning: Make sure that no person is sitting in the seat while Easy Access is being used. Forward movement will continue further than normal seat forward movement.***




Easy Access allows the seat to be moved forward, to provide greater access to the rear environment. Each seat has an Easy Access button located on each end of the dashboard (E). To move a seat press and hold the button (on the first press the seat will move forward). Movement will continue until the button is released.

If the button is released and pressed again within three seconds, movement will continue in the same direction. If the button is released and pressed again after four seconds the seat will start to move in the opposite direction. When moving rearwards the seat will return to its original position while the button stays pressed.

Locking the vehicle with a double press (vehicle key) will also return the seat to its driving position.

# Sport Seat


## Seat Head Restraints




The driver and front passenger seats include non-adjustable head restraints (A), which limit the rearward travel of the head in a rear impact and may reduce whip lash injuries. When sitting in the seats make sure that the seat back is in an upright position and that the rear of the head is positioned in the centre of the head restraint area. The head restraints are most effective when the distance between the rear of the head and the head restraint is kept to a minimum.

## Seat Adjustment

*Memory Seats: When making seat adjustments, i.e. moving the seat base rearwards, raising or lowering the seat base, the seat back will motor forwards whenever it approaches trim panels located behind it. If the seat back is tilted backwards the seat base will move forwards if the seat back approaches trim panels.*




***[1] :*** Raise or lower the **front** of the seat.

***[2] :*** Move the seat **forwards** or **rearwards**.

***[3] :*** Raise or lower the **rear** of the seat.

***[4] :*** Tilt the seat **forwards** or **rearwards** to adjust the seat back angle.

***[5] :*** Press forwards or rearwards to increase or reduce the **lower lumbar support**.

***[6] :*** Press forwards or rearwards to increase or reduce the **upper lumbar support**.

***[7] :*** Press to the rear for the **lower** heat setting, press to the front for the **higher** heat setting. A LED shows which heat level is ON. Press to the centre position for OFF (LEDs OFF).[1]


*The ignition must be ON before the heated seat and lumbar support can be operated.*




1. Optional.

## Seat Back Release

Press and hold in button A to release the seat back, once the seat has been moved forward release the button and manually move the seat back forwards.




*In the unlikely event of power failure a manual release strap is provided in the seat back. Pull and hold the strap to release the seat back and then move the seat back forward.*



## Seat Memory Function

***⚠ Warning: Make sure that there is nothing in front of, behind, or under the seat during adjustment.***

***⚠ Warning: To avoid injury, make sure that children do not play with the switches.***

***⚠ Warning: If the seat accidentally begins to move, press any seat control button to stop the seat.***

The position of the driver and passenger seats can be memorised and recalled.

Three different driving position profiles can be entered in the memory. The memory position of the driver's seat also includes both door rear view mirrors.

The memory function buttons are located in the seat adjustment controls which are located each side of the centre console (A).



## Setting a Preset Position

***⚠ Warning: Do not attempt to adjust the seat whilst driving.***

Adjust the seat and the door rear view mirrors to the desired position. The mirror memory operates only when adjusting the driver's seat. For mirror adjustment, (Refer to 'Door Mirrors', page 3.9).

Push both the memory button (M) and the desired setting button (1, 2 or 3) simultaneously and release. A chime is heard and a message will show in the message centre to confirm[1]. By repeating these steps and pressing an unused button, a second and third driving position can be stored in the memory.




1. Driver's seat only.

*When making adjustments to a set driving position, reset the new position in the same memory channel. The previous memory is erased when a new driving position is entered.*

### Recalling a Memorised Position

Once in the seat press and hold button 1, 2 or 3 (depending on which position required) until all movement is stopped. The seat and door mirrors (when adjusting the driver's seat) move to the programmed position. If the button is released all movement will stop, press and hold again to continue movement.

### Memory Using the Vehicle Key

When the vehicle is locked using the vehicle key, the driver's seat and both door rear view mirrors will remember their positions. The next time the vehicle is opened using the same vehicle key, the seat and door rear view mirrors will move to the memorised position once the door handle is used.

*The seat and door rear view mirrors only move if they have been moved previously, i.e. the spare vehicle key has been used and the seats or mirrors have been moved.*

### Emergency Stop

If the seat accidentally begins to move, press any seat control button to stop the seat.


## Steering Wheel

***⚠ Warning: Do not adjust steering wheel whilst driving.***

***⚠ Warning: Make sure that the steering column is fully locked in position. The reach and tilt release lever must be fully up, in line with the steering column.***

### Reach and Tilt

The reach and tilt angle of the steering wheel are adjusted by using the release lever (A). Pull the release lever downwards and manoeuvre the steering wheel to the required position. Hold the steering wheel in the required position and lock it by pulling the release lever up.




## Interior Mirrors

### Rear View Mirror

#### Automatic Dim


Adjust the mirror on its ball mounting until a satisfactory rear view is obtained.

The rear view mirror will dim automatically if the glare from the headlamps of following vehicles becomes too bright. The mirror will return to normal view as unwanted glare reduces to an acceptable level. If the mirror is dimmed when reverse gear is selected the mirror will revert to normal view.




### Vanity Mirror

A vanity mirror is located in each sun visor.



# Door Mirrors

To adjust the door mirrors select the left or right mirror (B). Then move the joystick (A) up, down, left or right to adjust the selected mirror.




📖 *The vehicle key must be at position 'I' or 'II' in the ignition control before the door mirrors can be adjusted.*

📖 *An amber LED shows the selected mirror.*

## Heated Mirrors

When the heated rear window is ON the heaters in the door mirrors will operate for 6.5 minutes.

## Auto Fold Function

When the vehicle is locked using the vehicle key or master lock switch the mirrors will automatically fold in flat against the doors. They return to the driving position once the vehicle is unlocked.

This function can be enabled or disabled. Press ***MENU*** on the console and navigate to *<Car settings...> Enter <Mirror settings...> Enter <Auto mirror fold flat enabled>*. Press ***ENTER*** to toggle between ON and OFF, then press and hold ***BACK*** to accept and return to the main screen.

***! If the vehicle has not been locked or unlocked and the mirrors have been folded using the power fold function then the mirrors will stay folded until placed in the driving position using the power fold function again.***

📖 *Door mirror vibration can occur if the mirrors have been moved manually (folded or unfolded), either intentionally or accidentally. To reset the linkage operate the power fold function once to fold or unfold the mirrors.*

## Power Fold Function

The power fold mirror function lets you fold or unfold the door mirror assemblies manually.

Insert the vehicle key to position 'I' or 'II' in the ignition control. Move the mirrors to the folded or unfolded position by pressing down and releasing both the left and right mirror select switches (B) together.

## Reverse Dip Function

This function gives a better view to the rear of the vehicle while reversing.

When reverse gear is selected:

***Automatic Mode:*** When reverse gear is selected the door mirrors automatically move to the first preset dip position. If the mirror requires further lowering, press down and release the mirror joystick (A) again. If the mirror is lowered too far, press the mirror joystick up and release.

***Manual Mode:*** Press down and release the mirror joystick (A). This will lower the door mirrors to preset position 1 dip. If the mirror requires further lowering, press down and release the joystick again. If the mirror is lowered too far, press the mirror joystick up and release.

In manual or automatic mode the mirrors return to driving view when reverse gear is de-selected or when either mirror button (B) is pressed.

**Reverse Mirror Dip Settings**

Press ***MENU*** (C) and navigate to *<Car settings...> Enter <Mirror settings...> Enter <Reverse mirror dip settings...>*. Select *<Auto (reverse gear selected)>*, *<Passenger only>* or *<Passenger and driver>*.

Press ***ENTER*** to toggle between ON and OFF. Then press and hold ***BACK*** to accept and return to the main screen.

***<Auto>:*** If set to ON: The door mirrors dip automatically when reverse gear is selected.

If set to OFF: The door mirrors stay in manual mode.

***<Passenger only>:*** Only the passenger door mirror dips.

***<Passenger and driver>:*** Passenger and driver door mirrors dip.

The restraints system gives protection to the driver and passenger in a variety of impact conditions. The system consists of:

- Driver and passenger safety belts with pre-tensioners and load limiting systems
- Driver and passenger dual-stage airbags
- Front Passenger Airbag Deactivation (PAD) switch

All of these systems are controlled by a Restraints Control Module (RCM). In a collision the RCM will analyse information from various sensors, including crash and seat occupancy conditions. Based on this information the RCM will deploy the appropriate safety devices. During a crash, the RCM may or may not operate the safety belt dual pre-tensioners and none, one, or both stages of the dual-stage airbag supplemental restraints.

If the pre-tensioners or airbags do not operate in a collision it does not mean that something is wrong with the system. Rather, it means the system determined the accident conditions (crash severity, belt usage, etc.) were not appropriate to operate these safety devices.

Front airbags are designed to operate only in frontal and near-frontal collisions, not rollovers, side-impacts, or rear-impacts unless the collision causes sufficient longitudinal deceleration.

## Determining if the System is Operational

A warning symbol in the instrument cluster  shows the condition of the system. A difficulty with the system is shown by one or more of the following:

- The warning symbol will flash or stay ON.
- The warning symbol does not come ON immediately after the ignition is set to ON.

If either of these conditions occur, even intermittently, have the restraint system serviced at your Aston Martin Dealer immediately. Unless serviced, the system may not operate correctly in the event of a collision.

# Seat Belts

Aston Martin strongly recommend the use of seat belts.

***⚠ Warning: Seat belts should not be worn with straps twisted.***

***⚠ Warning: Each belt assembly must only be used by one occupant; it is dangerous to put a belt around a child being carried on the passengers lap. Do not put an adult seat belt around two children.***

***⚠ Warning: When installed, the seat belt webbing must not contact any sharp edges which could abrade or cut the webbing during normal use or in an accident. If necessary, the webbing must be protected.***

***⚠ Warning: Care should be taken to avoid contamination of the webbing with polishes, oils and chemicals, and particularly battery acid. Cleaning may safely be carried out using mild soap and water. The belt should be replaced if webbing becomes frayed, contaminated or damaged.***

***⚠ Warning: Wearing your seat belt is crucial to your safety. Not wearing a seat belt increases chance of serious injury or death in the event of an accident.***

***⚠ Warning: Be sure that you and your passenger always fasten their seat belts and use them correctly even though airbags are provided.***

***⚠ Warning: Reclining the seat back decreases protection provided by the seat belt in the event of a crash. Adjust the seat back to an upright position. Make sure that the seat back is locked in place. Otherwise it could move forward in the event of a sudden stop or crash and cause injury.***

***⚠ Warning: Seat belts are designed to bear upon the bony structure of the body, and should be worn low across the front of the pelvis, chest and shoulders; wearing the lap section of the belt across the abdominal area must be avoided.***

***⚠ Warning: Never place shoulder portion of belt under your arm or behind your back.***

***⚠ Warning: Always remove from your pockets rigid or breakable objects, i.e. spectacles or a mobile phone, which could be trapped under seat belts, possibly causing injury in the event of an accident.***

***⚠ Warning: Expectant mothers should seek medical advice on the most appropriate way to wear the seat belt.***

***⚠ Warning: Seat belts must be kept clean so that the retractor works correctly. Make sure that belt webbing is not twisted, looped, frayed or obstructed in any way. If in doubt about condition or operation of seat belt installation, have it checked by your Aston Martin Dealer.***

***⚠ Warning: No modifications or additions should be made by the user which will either prevent seat belt adjusting devices from operating, or prevent seat belt assembly from being adjusted to remove slack. Never install accessories on your seat belts.***

***⚠ Warning: Seat belts should be adjusted as firmly as possible, consistent with comfort, to provide the protection for which they have been designed. A slack belt will greatly reduce the protection afforded to the wearer.***

***⚠ Warning: It is essential to replace the entire seat belt assembly after it has been worn in a severe impact even if damage to the seat belt assembly is not obvious.***

## Pre-tensioner and Load Limiting

All seat belts are equipped with pre-tensioner and load limiting systems.

In most moderate frontal or near frontal accidents, the front airbag and all pre-tensioner systems will deploy simultaneously.

The pre-tensioners take up slack in the seat belts as the airbags are expanding. The load limiting system releases belt webbing in a controlled manner to reduce belt force on the passenger's chest.

*In some moderate frontal or near frontal accidents, only the pre-tensioner system will deploy.*

## Seat Belt Reminder

A warning symbol in the instrument cluster will come ON and warning sound will be heard for six seconds (approximately) when the ignition is set to ON if the driver or passenger[1] seat belt is not fastened. (Market area dependent.)

If the driver seat belt is not fastened after 60 seconds or if the vehicle reaches 25 km/h a warning sound will be heard for 30 seconds, after which the warning sound will go ON and OFF and the warning symbol will continue to show until the seat belt is fastened.


The warning messages are always available, press the ***READ*** button to view stored messages.

1. If a passenger is sitting in the passenger seat.

## Seat Belt Fastening

*When parked on an incline, the seat belt may lock as it is withdrawn. This is not a fault. If the mechanism locks, release the belt tension and then pull the belt very gently to avoid operation of the inertia lock.*

Each seat has three point, inertia reel seat belts installed. Items 1, 2 and 3 show the three points of the seat belt. Item 3 is also the location of the belt buckle.




The inertia belt reels will automatically tension the belts to provide security with comfort. In the event of a collision or during severe braking, the belt reels will lock.

Pull out the seat belt, drawing the tongue over the shoulder and across the chest.


Push the tongue into the belt buckle latch until a positive click is heard.

Pull upwards on the diagonal belt to make sure that the latching is secure and to remove all slack from the belt.

Finally, double check that the lap belt is installed snugly, low down across the hips, and that there are no twists.



If it is necessary for a passenger to adjust their seat or seating position during a journey, the belt tension might be disturbed.



The passenger should therefore (as soon as it is safe to do so) gently pull down the shoulder run of the seat belt to create some slack and then immediately release it to re-tension the belt for the new seating position.



## Seat Belt Unfastening

Depress the button on the buckle. While holding the seat belt tongue allow the belt to slowly retract to its stored position.



## Child Seat Belt Fastening

***⚠ Warning: An infant or child that is not correctly restrained can be seriously injured or killed in a crash. Seat belts are designed for adults and larger children; infants and smaller children must be restrained in an approved child safety seat.***


Make sure that there is no slack in the webbing and that the restraint installs correctly across the child's rib cage and hips. These are the parts of the body most able to take the force of impact.

The lap strap should pass across the top of the child’s thighs, bearing on the pelvis, not on the abdominal area.

# Airbags

## Supplemental Restraints System

The vehicle is equipped with driver and passenger airbags. The airbags and seat belt pre-tensioners are electrically controlled by the restraints system.




The front airbags (A) only deploy in a serious front collision. The side airbags[1], located in the front seats (B) only deploy according to which side has been impacted in a serious side collision.

The purpose of the airbags is to provide **additional** protection for the driver and passengers in the event of a serious impact (front or side impacts). The airbags are supplementary to the seat belts.




Important airbag safety labels are located on the sun visors and on the end of the instrument panel (passenger side). Make sure that the instructions on these labels are read and complied with before driving the vehicle.

### Airbag Deployment

***⚠ Warning: The use of accessory seat covers may prevent the deployment of the side airbags and increase the risk of injury in an accident. Do not use accessory seat covers.***

***⚠ Warning: All passengers, including the driver, should always wear seat belts, whether or not an airbag is provided, to decrease the risk of injury or death in the event of a crash.***

***⚠ Warning: No objects whatsoever should be attached to the centre cover of the steering wheel or the front passenger fascia panel. Such objects could cause harm if the vehicle is in a collision severe enough to cause the airbags to deploy.***

Airbags inflate rapidly and with considerable force; there is therefore a risk of death or serious injury such as fractures, facial and eye injuries or internal injuries, particularly to passengers who are not correctly restrained by seat belts or are not sitting correctly when the airbags deploy. The risk of injury from a deploying airbag is greatest close to the trim panel covering the airbag.

1. Sport Seat Only.

The whole sequence of events from sensing the impact to full inflation of the airbag takes place in a fraction of a second. The noise and gas associated with the deployment of the airbags is not injurious to health.

Do not change, modify or tamper with the steering wheel, passenger side fascia or any other part of the airbag system. Such actions could disable the system or cause inadvertent airbag deployment.


The system will not deploy in the event of minor frontal or side impacts, such as contacts when parking.


The airbag system is not designed to protect against rear impacts.

All work on the airbag system must only be carried out by an Aston Martin Dealer.

***[A] :*** Front airbag deployment

***[B] :*** Seat side airbag deployment[1]




1. Sport seats only.

## Child Safety

**Aston Martin strongly recommends:**

- **Always use ISOFIX anchors where available.**
- **A child, regardless of age, should always be restrained when travelling in a vehicle.**

***⚠ Warning: Do not allow children to travel in a vehicle without restraint. An appropriate child seat or harness should always be used.***

***⚠ Warning: Each seat belt assembly must be used by only one passenger. It is dangerous to put a seat belt around a child being carried on the passengers lap.***

***⚠ Warning: Make sure that an installed child seat does not rest against the door, that the child sits correctly in the seat and does not lean close to, or against, the door or window.***

Your vehicle has the following devices for the installation of child restraints:

- Passenger Airbag Deactivation (PAD) switch (sport seat only)
- ISOFIX anchors[1][2]
- Passenger seats Automatic Locking Retractor (ALR) seat belts
- Tether anchor points[2]

## Child Seats and Front Passenger Airbag

***⚠ Warning: Do not place a child restraint on a seat with an active airbag.***

***⚠ Warning: With the exception of installing a child seat on the front passenger seat, do not set the PAD switch to OFF, as the front passenger will not receive the added protection of the airbag. Serious injuries or even death could occur.***

In the event of a serious frontal or side collision the vehicle airbag system is designed to deploy, to provide additional protection for the front seat occupants.

### Lightweight Seat

**Aston Martin strongly recommends not to install any child seat on the passenger seat of this vehicle.**

If a forward facing child seat is to be used in the passenger seat, follow the child seat manufacturer's instructions to secure the child seat and move the front passenger seat to its rearmost and lowest position.

### Sport Seat

***⚠ Warning: With the exception of installing a child seat on the front passenger seat, do not set the PAD switch to OFF, as the front passenger will not receive the added protection of the airbag. Serious injuries or even death could occur.***

***⚠ Warning: Never place a child in a child seat or on a booster cushion on the front passenger seat if the airbag is set to ON.***

If a child seat is to be used in the front passenger seat, the front passenger airbag **must** be set to OFF. Make sure that the child seat manufacturer's installation instructions are followed correctly.

*The PAD switch does not set the passenger seat side impact airbag or the seat belt pretensioners to OFF.*

1. Standard for installing child seats into cars and is intended to make the installation of child seats quick and simple
2. Sport seat only: No height adjust.

## Warning Labels

***⚠ Warning: Extreme Hazard: Do not use a rearward facing child restraint on a seat protected by an active airbag in front of it.***

The following warning labels (market area dependent) are located on the sun visors and on the end of the instrument panel (passenger side).







Sport Seat Only.

***⚠ Warning: Before installing a child seat on the passenger seat, the passenger airbag must be set to OFF.***


***⚠ Warning: Before driving always confirm that the PAD switch is in the appropriate position according to your requirements.***

***⚠ Warning: With the exception of installing a child seat on the passenger seat, do not set the PAD switch to OFF, as the passenger will not receive the added protection of the airbag. Serious injuries or even death could occur.***

📖 *The PAD switch does not set the passenger seat side impact airbags or the seat belt pre-tensioners to OFF.*

The Passenger Airbag Deactivation (PAD) switch lets the airbag protecting the passenger be set to OFF. When the PAD is set to OFF a child seat may be installed on the passenger seat. At ignition ON if the passenger airbag is set to OFF, then PASS AIRBAG OFF will show in the message centre.

The PAD switch is located on the passenger end of the instrument panel and is accessible when the front passenger door is open.




The PAD switch should be inspected by an Aston Martin Dealer if any of the following conditions occur:

- The PAD warning symbol does not come ON (for six seconds) when the ignition is set to ON and the passenger airbag is set to ON.
- The PAD warning symbol does not stay ON when the ignition is set to ON and the passenger airbag set to OFF.
- The PAD warning symbol stays ON when the ignition is set to ON and the passenger airbag is set to ON.

## Set the Airbag to ON or OFF

Insert the emergency vehicle key into the PAD switch and turn clockwise for the OFF position (airbag OFF) or counterclockwise for the ON position (airbag ON). Remove the key.

***Airbag ON:*** When the ignition is set to ON make sure that the PASS AIRBAG OFF symbol (A) comes ON for six seconds then goes OFF. Failure to follow the advice given above can endanger the life of the child.

***Airbag OFF:*** Make sure that the PASS AIRBAG OFF symbol stays ON when the ignition is ON.




## ISOFIX Anchors

Sport seat: No height adjust passenger seat only

***⚠ Warning: An unsecured child seat is dangerous. In a sudden stop or a collision it could move, causing serious injury or death to the child or other passengers. Make sure the child seat is correctly secured in place according to the manufacturer's instructions.***

***⚠ Warning: When installing the child seat, make sure that there are no seat belts or foreign objects near or around the ISOFIX anchors. If seat belts or a foreign object prevents the child seat from being securely attached to the ISOFIX anchors, the child seat could move in a sudden stop or collision causing serious injury or death to the child or other passengers.***

This vehicle is equipped with ISOFIX (International Standards Organisation FIX) anchors for the installation of child seats on the passenger seat. The anchors are located between the seat base and the seat back. The position of the anchors is shown by two tags at the base of the seat.



📖 *Motor the seat rearwards, to allow clearance for installing the child seat.*

Secure the child seat using the ISOFIX anchors, following the child seat manufacturer's instructions.

## Tether Anchors

Sport seat: No height adjust passenger seat only

***⚠ Warning: An infant or child that is not properly restrained can be seriously injured or killed in a crash. Seat belts are designed for adults and larger children; infants and smaller children must be restrained in an approved child safety seat.***

***⚠ Warning: Child restraint anchorages are designed to withstand only those loads imposed by correctly installed child restraints. Under no circumstances are they to be used for adult seatbelts, harnesses or for attaching other items or equipment to the vehicle.***

***⚠ Warning: Always follow the child seat manufacturer's instructions. Not following the child-seat manufacturer's instructions when installing the child seat is dangerous.***

***⚠ Warning: Make sure the child seat tether strap is free from obstructions above and below. Do not place any items on the tether strap between the child seat and the tether anchor point. Do not place tether strap over any items between the child seat and the tether anchor point.***

A tether is a strap that connects the top of a child seat to a tether anchor point on the vehicle to reduce excessive movement of the child seat in the event of a collision. The purpose of a tether strap is to provide additional protection for the child seat occupant in the event of a serious impact. The tether strap is supplementary to the seat belts.


Your vehicle has a tether anchor point for the passenger seat, which is located at the base, rear of the passenger seat.

### Correct Assembly of Tether Anchor

A tether anchor point is located at the base, rear of the front passenger seat. Motor the seat forward to access the tether anchor point.

Motor the seat forward to access the tether anchor point. Route the tether strap through the aperture in the seat back as shown. Engage the tether clip to the anchor point at the bottom of the passenger seat back (A) and make sure that the locking spring has fully closed to prevent accidental disengagement. Always make sure that the tether strap length is adjusted to remove any slack.

# Automatic Locking Retractors




***⚠ Warning: Always follow the child seat manufacturer's instructions. Not following the child-seat manufacturer's instructions when installing the child seat is dangerous.***

Aston Martin does not recommend any specific child seat for this vehicle **which require the use of the vehicle seat belt for installation**.

The Automatic Locking Retractor (ALR) system is designed to securely hold child seats. The ALR system temporarily locks the seat belt that is securing a child seat.

## ALR Operation

Gently pull out the seat belt until fully extended. The ALR system will only engage at the maximum extension point of the seat belt.

Thread the belt tongue through the child seat as instructed by the child seat manufacturer. Engage the tongue into the belt buckle.

Adjust the tongue position on the belt, if necessary, to make sure that the lower belt run is tight and then allow the upper run of the seat belt to fully retract until the child seat is securely held. The ALR system will be heard 'clicking' as the seat belt retracts.

When fully retracted, pull down on the upper run of the belt to check that the ALR lock has engaged.

*When parked on an incline, the seat belt may lock as it is withdrawn. This is not a fault. If the mechanism locks, release the seat belt tension and then pull the seat belt very gently to avoid operation of the inertia lock.*

The ALR system will disengage when the seat belt is fully retracted. The seat belt may then be worn when required as a normal seat belt. Once the ALR is disengaged, the seat belt must be fully extended to re-engage the system on the next occasion that a child seat is installed.

***⚠ Warning: Always follow the child seat manufacturer's instructions. Not following the instructions when installing the child seat is dangerous.***

***⚠ Warning: Do not seat a child aged 12 or younger, or weighing 36 kg or less in the car without an appropriate child seat or booster cushion.***

**Aston Martin strongly recommends not to install any child seat on the front passenger seat of this vehicle.**

## Use of Child Seats

Look for the following when selecting a child seat:

- It should have a label certifying that it meets the applicable Safety Standards.
- Carefully read the instructions supplied with the child seat. Make sure you understand them and can install and use the device correctly and safely in the vehicle.
- Make sure that the child seat is appropriate for the child's weight and development. The label required by the standard or regulations, or instructions for infant seats, usually provide this information.

An infant or child that is not correctly restrained can be seriously injured or killed in a crash. Seat belts are designed for adults and larger children; infants and smaller children must be restrained in an approved child seat.

Children could be endangered in a crash if their child seat is not correctly secured in the vehicle.

Never hold a baby or child on your lap while riding in the vehicle.

Consult with local manufacturers of forward facing restraint and booster cushions. These manufacturers can supply you with advice on the safety of their particular child restraints.

Check the seat manufacturers instructions for correct use and installation – use the correct size seat and correctly secure the seat in the vehicle in accordance with the manufacturers instructions. Be sure to read and follow the 'Installation and Use Instructions' provided with the child seat.

## Child Seats - ISOFIX Installation

***Sport Seat: No Height Adjust Passenger Seat***

| Mass Group[1] | | Size Class | Fixture | ISOFIX Positions |
|---|---|---|---|---|
| | | | | Front Passenger |
| | Carry Cot | F | ISO/L1 | X |
| | | G | ISO/L2 | X |
| '0' | Up to 10 kg (0-9 months) | E | ISO/R1 | IL[2] |
| '0+' | Up to 13 kg (0-18 months) | E | ISO/R1 | IL[2]. |
| | | D | ISO/R2 | X |
| | | C | ISO/R3 | X |
| 'I' | 9 to 18 kg (9 months to 4 years | D | ISO/R2 | X |
| | | C | ISO/R3 | X |
| | | B | ISO/F2 | IUF |
| | | B1 | ISO/F2X | IUF |
| | | A | ISO/F3 | IUF |
| 'II' | 15 to 25 kg (4 to 12 years) | - | - | X |
| 'III' | (22 to 36 kg (4 to 12 years)) | - | - | X |

1. As shown on the child safety seat packaging

2. Mass Group 0/0+ - Britax 'Cosy Tot ISOFIX' (Only to be installed with the semi-universal ISOFIX base, do not install with lap or diagonal seat belt).

***Table Key***

***IUF:*** Suitable for 'ISOFIX' forward child restraints systems of universal category approved for use in the mass group.

***IL:*** Suitable for particular ISOFIX Child Restraint Systems (CRS). These ISOFIX CRS are those of the 'specific vehicle', 'restricted', or 'semi-universal' categories.

***X:*** ISOFIX position not suitable for ISOFIX child restraint systems in this mass group or this size class.

Supplied under EC Directive 77/541 and ECE Regulation 16.04.

## Child Seats - Seat Belt Installation

***Lightweight Seat***

| Mass Group[1] | | Seating Position |
|---|---|---|
| | | Front Passenger |
| '0' | Up to 10 kg (0-9 months) | X |
| '0+' | Up to 13 kg (0-18 months) | X |
| 'I' | 9 to 18 kg (9 months to 4 years | X |
| 'II' | 15 to 25 kg (4 to 12 years) | X |
| 'III' | (22 to 36 kg (4 to 12 years)) | X |

1. As shown on the child safety seat packaging

***Sport Seat: Height Adjust Passenger Seat***

| Mass Group[1] | | Seating Position |
|---|---|---|
| | | Front Passenger |
| '0' | Up to 10 kg (0-9 months) | $U_2$ |
| '0+' | Up to 13 kg (0-18 months) | $U_2$. |
| 'I' | 9 to 18 kg (9 months to 4 years | $U_2$. |
| 'II' | 15 to 25 kg (4 to 12 years) | $U_2$. |
| 'III' | (22 to 36 kg (4 to 12 years)) | $U_2$. |

1. As shown on the child safety seat packaging
2. Move the passenger seat to its rearmost and highest position.

***Sport Seat: No Height Adjust Passenger Seat***

Consult with local manufacturers of forward facing restraint and booster cushions. These manufacturers can supply you with advice on the safety of their particular child restraints and also advice on installation instructions.

| Mass Group[1] | | Seating Position |
|---|---|---|
| | | Front Passenger |
| '0' | Up to 10 kg (0-9 months) | X |
| '0+' | Up to 13 kg (0-18 months) | X |
| 'I' | 9 to 18 kg (9 months to 4 years | X |
| 'II' | 15 to 25 kg (4 to 12 years) | X |
| 'III' | (22 to 36 kg (4 to 12 years)) | $L_2$ |

1. As shown on the child safety seat packaging
2. Mass Group II/III - Britax 'Evolva 2-3 ISOFIT'

***Table Key***

***L:*** Suitable for particular child restraint systems. These restraints may be of the 'specific vehicle', 'restricted' or 'semi-universal' categories.

***U:*** Suitable for 'universal' category restraints approved for this mass group.

***X:*** Seat position not suitable for children in the mass group.

****:*** Unsuitable for use with many child restraints due to limited space.

Supplied under EC Directive 77/541 and ECE Regulation 16.04.

## Britax ‘Evolva 2-3 ISOFIT’ Child Seat

***⚠ Warning: The lap or diagonal seat belt is only to be used to restrain the child in the child seat. Do not use the lap or diagonal seat belt to install the child seat. Always use the Britax ‘Evolva 2-3 ISOFIT child seat ISOFIT latches.***

To prevent any forward or backward movement of the Britax ‘Evolva 2-3 ISOFIT’ child seat it must be installed with the top of the child seat pressed firmly up against the top of the passenger seat - as shown below. To achieve this follow the child seat manufacturer’s instructions, along with the following instructions for the Aston Martin seat.




Motor the passenger seat fully to the rear and install the Britax ‘Evolva 2-3 ISOFIT’ child seat to the passenger seat ISOFIX bars as per the manufactures instructions. Adjust the height of the child seat headrest as required according to manufactures instructions. Tilt the passenger seat back forward until the top of the child seat comes into contact with the passenger seat - as shown.



# Cabin Storage

## Glove Box


Press the glove box button (A) to open. Push up to close.




## Trinket Box

(Non smoking option)

Lift the lid to open.



## Cup Holders

***⚠ Warning: Only use the cup holder when safe to do so.***

***⚠ Warning: Do not place hot drinks in the cup holder while the vehicle is in motion. There is a risk of scalding.***

***⚠ Warning: Use soft cups only. Hard cups or objects can cause personal injury in a collision.***



Cup holders are located in the front centre console.

## Cubby Box

The armrest cubby box has an iPod, USB ports, an auxiliary socket and an accessory socket.



## Door Pockets

Both doors have pockets, including a phone holder.



## Front Seat Pockets







# Boot Cover


**To Remove**

Detach the two boot lid cords and fold the rear section forward.







Slightly raise the boot cover up and then back. Lower and remove the cover to the rear.



**Storage**


Keep the rear section folded and turn the boot cover 180°. Place the cover in the rear section of the boot.





**To Install**

Insert the boot cover, from below, and locate the two rear pins. Raise the cover. Locate the two side pins up into the area provided in the trim panel. Slightly push forward and allow to drop into position. Install the two boot lid cords.




## Accessory Sockets

***⚠ Warning: Damage to electrical circuits will result if more than 10 amps is drawn from the accessory socket. Only connect accessories which are designed for use in a motor vehicle.***

***⚠ Warning: Prolonged use of an accessory socket when vehicle engine is set to OFF may seriously discharge battery.***

***! Foreign items can get into the socket and cause damage - always place the cover on the accessory socket when not in use.***




Accessory sockets are mounted in the front armrest cubby box and the boot right side wall (A) and may be used to power any 12 volt vehicle accessory requiring a current of less than 10 amps.

Read the manufacturer's instructions and make sure that you do not connect any device which would exceed current rating of the accessory socket.

## Ashtray and Cigar Lighter

Optional

***⚠ Warning: The cigar lighter is heated to 'red heat' when in use. Take care to avoid burns. Do not allow children to play with the cigar lighter.***

The cigar lighter may be used when the vehicle key is in ignition position 'I' or 'II'.



Push the lighter down until it clicks. The lighter will pop up when ready for use.

# Electric Windows

***Foreign items can get into the socket and cause damage - always place the lighter back into the accessory socket when not in use.***

Remove the ashtray by opening the lid and pulling the glass tray upwards. Install the tray by placing it into position and push down.



***Warning: Misuse of the window switches, especially by children, can result in injury due to entrapment in the window closure. Drivers must advise all passengers of the possible danger and make sure that all obstructions are clear before raising the window.***

*The windows can be operated up to one minute after the vehicle key is removed from the ignition control.*

Each vehicle door has its own window switch and the drivers door window switch can operate both windows.

To raise and lower the windows the vehicle key must be at ignition position 'I' or 'II'.




Lightly press and hold a window switch (A) to lower the window in one movement. Lightly press and release the window switch to lower the window in stages. Firmly press and release to lower the window with one touch.

Lightly pull back and hold to raise the window in one movement. Lightly pull back and release, to raise the window in stages. Firmly pull back and release to raise the window in one movement.

If power to the electric windows has been interrupted for any reason, they will fail to operate correctly until reset (Refer to 'Door Window Reset', page 10.28).

## Door Sealing

***⚠ Warning: Make sure that all passengers are clear when the window mechanism is operating.***

To minimise wind noise and to make sure that the window seal is watertight a door sealing system is used to provide a tight fit of the door glass to the seals around the top of the door opening.

When a door is opened, the window automatically lowers a small distance to clear the door seal. As the door is closed, the window automatically, after a pause, lifts against the body frame rubber seals.

## Reading Lamps

Reading lamps are located in the front environment. To operate the lamps (ON or OFF) press the individual switches mounted on the front centre console (A).

Unless set to OFF or ON they will continue to operate up to six minutes after the ignition is set to OFF.





## Coat Hooks

Coat hooks are located behind the driver and passenger seats (A).



# Controls


Controls Overview ..... 4.2
Instrument Cluster ..... 4.3
Information and Warning Symbols ..... 4.5
Centre Stack Controls ..... 4.7
Ignition Control ..... 4.9
Stalk Controls ..... 4.11
Vehicle Horn ..... 4.12
Master Lamp Switch ..... 4.12
Trip Computer ..... 4.13
Cruise Control ..... 4.15
Ambient Temperature ..... 4.16
Tyre Pressure Monitoring ..... 4.17




***[1] EASY ACCESS (LIGHTWEIGHT SEAT ONLY):*** Easy access allows the seat to be moved forward, to provide greater access to the rear environment. Each seat has an easy access button located on each end of the dashboard (Refer to 'Easy Access', page 3.4).

***[2] FUEL FLAP RELEASE:*** Press to open the fuel flap. Close the fuel flap by pressing down on the flap until the lock engages.



**Filler Flap Emergency Release:** (Refer to 'Fuel Filler Flap Emergency Release', page 5.15)

***[3] MASTER LAMP SWITCH:*** Four position master lamp switch, which controls the vehicle external lamps (OFF, side lamps, main lamps and AUTO) (Refer to 'Master Lamp Switch', page 4.12).

***[4] INSTRUMENT CLUSTER:*** (Refer to 'Instrument Cluster', page 4.3).

***[5] CENTRE STACK:*** (Refer to 'Centre Stack Controls', page 4.7).

***[6] GLOVE BOX RELEASE:*** Press to open the Glove box. Push the Glove box lid up to close.

***[7] AIRBAG DEACTIVATION:*** The passenger airbag **must** be set to OFF if a child seat is to be installed on the front passenger seat (Refer to 'Passenger Airbag Deactivation', page 3.17) (Sport seat only.)






***[1] FUEL GAUGE:*** Shows how much fuel is in the fuel tank. Refuel as soon as possible when the low fuel symbol comes ON.

***[2] SPEEDOMETER:*** Shows vehicle road speed.


***[3] MESSAGE CENTRE (LEFT):*** Shows the following:

- **Vehicle Speed:** Shows the vehicle road speed in a digital format.
- **Gear Range:** Shows the transmission position and current gear selection. Possible transmission positions and gear selection are in bold.

***[4] GEAR SHIFT INDICATOR DISPLAY (GSID) :*** Shows maximum revs. in the current gear or D when in auto drive mode and will flash red when the rev limiter is reached. H is displayed when in Hill Start Assist mode.



***[5] MESSAGE CENTRE (RIGHT):*** Shows the following:




- **Trip Meter (A):** Shows distances travelled since last reset of trip meters T1 and T2. Toggle between T1 and T2 by pressing ***T1/T2*** (E) for less than three seconds. Press ***T1/T2*** for more than three seconds to reset the trip meter on show.
- **Sport Mode Status (B):** Shows SPORT when sport mode is ON.
- **Cruise Status (C):** Shows CRUISE when cruise control is ON (Refer to 'Cruise Control', page 4.15).
- **Odometer (D):** Shows the total distance covered by the vehicle.



- **Driver Information and Warnings**
  Messages show if an unsatisfactory condition is detected. Message priority is shown by a red or amber triangle above the message display.
  **Red:** Potential personal danger or danger of damage to the vehicle.
  **Amber:** Advisory, shows possible degraded vehicle performance.
  Warning messages will show when the ignition is ON and will cycle automatically.
  View and acknowledge messages at any time by pressing the ***READ*** button (F).




- **Service Intervals**
  TIME FOR REGULAR SERVICE will be shown when a regular vehicle service is due. This message will show at ignition ON (for two minutes) until the regular service has taken place.
- **Trip Computer**
  The message centre (right) defaults to the trip computer when there are no messages to show.

***[6] TACHOMETER:*** Shows the engine speed in revolutions per minute x 1000.

***[7] ENGINE COOLANT TEMPERATURE GAUGE:*** Shows the temperature of the engine coolant.

**Digital Speedometer Location**

The digital speedometer can be displayed in either the left or right message centre depending on preference. All information in the opposing message centre moves to the other message centre side accordingly. To change the digital speedometer location, do the following:

Press **MENU** and navigate to <*Car Settings...*> **ENTER** < *Digital Speedometer...*> **ENTER** and select *Left* or *Right* to select the relevant message centre and press **ENTER** to confirm.

**Message Centre Clock**

The message centre clock is shown in the opposite message centre to the digital speedometer. The clock is shown in either 24 hour or 12 hour display. To change the time format, do the following:

Press **MENU** and navigate to <*Car Settings...*> **ENTER** < *Clock*> **ENTER** and select *24* or *12* to select the relevant time format for the clock and press **ENTER** to confirm.




*[1]* **LOW FUEL WARNING:** Comes ON when only approximately 13 ltr of fuel or 80 km distance is available. At 13 ltr / 80 km and 7 ltr / 40 km an audible 'beep' will sound and the 'estimated distance' message will show (for 20 seconds) in the message centre. The arrow head shows which side of the vehicle the fuel flap is.

*[2]* **LEFT TURN INDICATORS:** Flashes with the indicator or hazard warning lamps (Ignition ON).

*[3]* **HEADLAMPS:** Shows that the main beam of the headlamps is in use.

*[4]* **SIDE LAMPS:** Shows that the side lamps, dip or main beams are ON.

*[5]* **CHECK ENGINE:** Steady amber shows a fault in the engine management system. Continue driving only if there are no audible, visible or physical signs of degraded engine performance. Consult your Aston Martin Dealer as soon as possible.

Flashing amber shows a major fault in the engine management system. Stop immediately. Contact your Aston Martin Dealer.

*[6]* **IGNITION WARNING:** Comes ON when the ignition is set to ON and goes OFF when the engine is started and battery charging commences. Comes ON if battery charging fails whilst driving.

*[7]* **OIL PRESSURE WARNING:** Comes ON when the engine oil pressure falls below minimum. Do not continue driving if this symbol stays ON. Contact your Aston Martin Dealer immediately.

***⚠ Warning: Do not drive the vehicle if the Supplementary Restraint System (SRS) warning symbol stays ON. Have the system checked by an Aston Martin Dealer.***

***[8] SUPPLEMENTARY RESTRAINT SYSTEM:*** At vehicle key position 'I' and 'II' or on vehicle start up, this symbol comes ON for a few seconds as a readiness sign.

If it does not come ON, or if it does not go OFF after a few seconds, or if it comes ON whilst driving, the airbag self diagnostic system has detected a fault.

***⚠ Warning: Do not drive the vehicle if the seat belt warning symbol stays ON. Have the system checked by an Aston Martin Dealer.***

***[9] SEAT BELT WARNING:*** This warning symbol will come ON and a chime will sound for six seconds if the driver's seat belt is not fastened when the ignition is set to ON. The chime will continue to operate at different vehicle speeds until the seat belt is fastened (market dependant).

***[10] WARNING TRIANGLE:*** Shows red or amber depending on the warning or information message priority.

***⚠ Warning: If the brake warning symbol stays ON, after fully releasing the park brake do not drive the vehicle. Have the system checked by an Aston Martin Dealer.***

***[11] BRAKE BRAKE WARNING:*** At ignition ON this symbol comes ON when the park brake is applied and goes OFF when the park brake is fully released. If the symbol stays ON, after fully releasing the park brake, it shows that either the brake fluid level is low or that the brake pads require regular maintenance.

***⚠ Warning: If the ABS warning symbol stays ON, do not drive the vehicle. Have the system checked by an Aston Martin Dealer.***

***[12] ABS WARNING:*** If this symbol stays ON or comes ON while driving there is a fault in the ABS control circuits. Continue driving only if there are no audible, visible or physical signs of degraded brake performance. Consult your Aston Martin Dealer as soon as possible if this symbol stays ON.

***[13] TYRE PRESSURE:*** If this symbol stays ON or comes ON while driving, a tyre(s) air pressure is below specification.

***[14] DYNAMIC STABILITY CONTROL:*** When Dynamic Stability Control (DSC) is ON this symbol will flash when the DSC system is operating. If, while DSC is ON, the DSC symbol stays ON or it comes ON whilst driving, the DSC system has detected a fault. A DSC fault message will show in the message centre. Consult your Aston Martin Dealer as soon as possible.

***[15] REAR FOG LAMP:*** Shows if the rear fog lamps are ON.

***[16] RIGHT TURN INDICATORS:*** Flashes with the indicator or hazard warning lamps (Ignition ON).

***[17] PATS:*** When the alarm is on, this symbol flashes continuously (Refer to 'Passive Anti-Theft System', page 2.13).

***[18] HIGH COOLANT TEMPERATURE:*** Shows when the engine coolant temperature exceeds 120°C.

## Low Outside Temperature

***⚠ Warning: Even if the ICE WARNING message does not show, there is no guarantee that at low temperatures the road is free from ice.***

At temperatures below 4°C the message ICE WARNING is shown in the message centre, this shows to the driver that frost or ice is likely to form on road surfaces. The amber warning triangle ⚠ will also come ON. The message and warning triangle will continue to show until the outside temperature rises to a safer level.

## Warning Symbols




As the ignition is set to ON, the electronic control units complete a self check. During these checks the following symbols will come ON for five seconds and SYSTEM CHECK will show in the message centre. Under normal circumstances most warning symbols will go OFF at the end of the individual system check if system checks are satisfactory.





***[1] SATELLITE NAVIGATION SCREEN[1]:*** Opens when the Satellite Navigation system is set to ON (Refer to 'Satellite Navigation', page 9.1).

***[2] IGNITION CONTROL:*** Insert the vehicle key for ignition positions '0'. 'I', 'II' and engine start (Refer to 'Ignition Control', page 4.9).

***[3] TRANSMISSION CONTROLS:*** SportShift: auto drive, neutral, reverse and sport transmission buttons.

1. Not available in all markets.




***[4] AIRBAG STATUS (MARKET SPECIFIC):*** Shows the passenger airbag status (Refer to 'Passenger Airbag Deactivation', page 3.17).

***[5] DISPLAY:*** Shows options, menus and information.

***[6] HAZARD WARNING LAMP:*** Press to set the hazard warning lamps to ON or OFF.

***[7] CLOCK:***

- Vehicles with no satellite navigation:
  To set the time press ***MENU***. Go to *<Car settings...> Enter <Clock>*.
- Vehicles with Garmin satellite navigation:
  To set the time press ***NAV***. Use the satellite navigation screen and go to *<Settings> Enter <Time>*.

***[8] READ:*** Press to view and acknowledge messages.

***[9] AUDIO CONTROLS:*** (Refer to 'Audio', page 7.1).


***[10] CLIMATE CONTROLS:*** (Refer to 'Climate Controls', page 6.2).

***[11] MODE AND MENU NAVIGATION:*** Select functions and move back in the menus. Use the joystick to navigate for menus, music tracks, radio stations. Press to accept.

***[12] READING LAMPS:*** Driver and passenger reading lamps.

***[13] T1/T2:*** Select between two trip meters (Refer to 'Instrument Cluster', page 4.3).

***[14] REAR FOG LAMPS:*** Used with the dipped beam when fog or mist is causing restricted visibility. They **must** be set to OFF when visibility clears to reduce glare to the drivers of following vehicles.




***[15] DYNAMIC STABILITY CONTROL:*** The Dynamic Stability Control (DSC) system defaults to ON at each ignition ON. Press and hold for approximately four seconds for sport mode. Press and hold again for approximately four seconds to set DSC to OFF. Press and release to set DSC ON again (Refer to 'Dynamic Stability Control', page 5.11).

***[16] MASTER VEHICLE LOCK:*** Press to lock all doors and disable the boot lock switch. Press again to unlock (Refer to 'Master Locks', page 2.8).

***[17] PARKING ASSIST:*** Defaults to OFF at each ignition ON. Park assist comes ON when reverse gear is selected. Press and release to set parking assist to OFF (Refer to 'Parking Assist', page 5.16).

***[18] BOOT OPEN:*** Pull back up to open the boot lid.

***[19] ADAPTIVE DAMPING:*** The Adaptive Damping System (ADS) defaults to normal mode at each ignition ON. Press and release for ADS sport mode (button LED ON) (Refer to 'Adaptive Damping', page 5.13).

To access vehicle functions and to start the engine the vehicle key must be inserted in to the ignition control.



***⚠ Warning: Only use the vehicle key in the ignition control. Do not place any objects, including fingers, into the ignition control other than the vehicle key. Objects other than the vehicle key may cause the ignition control to fail.***

***! The vehicle key must only be inserted into the ignition control with the two indents first, as shown. Attempting to insert the larger end of the key first may damage the ignition control.***





## Position '0' (Ignition OFF)

Auxiliaries OFF (audio, satellite navigation, hands-free phone not available), steering lock ON. Seats can be adjusted.


Gently insert the vehicle key, indents first, into the ignition control. Press in until the key clicks into place, approximately 20 mm (A) then release. The key is docked at this point.

Remove by pulling the vehicle key from the ignition control.



## Position 'I' (Ignition OFF and Accessories ON)

Auxiliaries ON (audio, satellite navigation, hands-free phone available), steering lock ON.




- If already in position '0' gently press the key until the infotainment centre and the instrument cluster lamps come ON, a further 10 mm (B) and release for position 'I'.
- Or insert the key into the ignition control and move straight to position 'I'. Press in until the infotainment centre and the instrument cluster lamps come ON.


Remove by pulling the vehicle key from the ignition control.


## Position 'II' (Ignition ON)

Ignition and all other electrical systems ON, steering lock OFF.

***Do not press the clutch pedal down unless intending to start the engine.***

*Insert the key to position 'II' by using the flat of a finger, as shown.*






- If the key is already in position '0' or 'I' gently press the key until it is flush with the ignition control bezel and release.
- Or insert the key into the ignition control and move straight to position 'II'. Gently press the key until it is flush with the ignition control bezel and release.

The Instrument cluster lamps will come ON, the vehicle systems will wake up and the steering lock will release.

To start the engine from this position fully press the clutch pedal down and press the key fully in (Refer to 'Starting the Engine', page 5.3).

To remove the vehicle key from position 'II' press the key fully in **twice** (do not press the clutch pedal) and release. The key will gently return to position 'I'. Pull the key from the ignition control. Once in position 'I' after 10 seconds the steering lock will engage.

*If the vehicle key is pressed **fully** into the ignition control and released for position 'II', the key must be returned to position 'I' to start the engine.*


## Preventing Unnecessary Battery Drain

If the vehicle key is left in the ignition control (position '0'), some vehicle circuits will stay ON and unnecessary current will be drawn from the battery.

Always remove the vehicle key from the ignition control whenever the ignition is set to OFF.

# Stalk Controls

## Left Side Stalk



***Turn Signals :*** Press up for a right turn, press down for a left turn. Returns to the centre position on completion of a manoeuvre. Hold against spring pressure to show a lane change.

***Main and Dipped Beam :*** Pull forwards and latch for main beam. Pull forwards again and latch to return to dipped beam. Pull forwards and release without latching, at any time while the vehicle key is in the ignition control, to flash main beam ON and OFF.

Pull forwards and release without latching, when the vehicle key is removed, to start Homesafe (Refer to 'Homesafe', page 2.11).




***Trip Computer :*** Repeated pressing of the trip function button (A) moves through the trip computer displays (Refer to 'Trip Computer', page 4.13).

## Right Side Stalk




***Windscreen Wiper Control :***

***[1] :*** OFF.

***[2] :*** Automatic Wipe.

***[3] :*** Normal Speed Wipe.

***[4] :*** Fast Wipe.

***Demand Wipe:*** Pull the stalk forwards.


*The windscreen wipers will return to their park position if the ignition is set to OFF or the bonnet is unlatched, regardless of the right stalk position.*

***Speed Sensitive Wipe :*** If the wipers are at fast wipe, when the vehicle slows down (below 11 km/h) the wipers will go to normal wipe speed.

If the wipers are at normal speed when the vehicle slows down (below 11 km/h) the wipers will go to automatic wipe (position 2).

As soon as the vehicle speeds up (above 15 km/h) the wipers will return to their original setting.

***Automatic Rain Sensor Wiper Control :***




Automatic rain sensor wiper control increases or decreases the sensitivity in six steps (B). Sixth position (where the arrow is set to the bottom marker) gives the least sensitivity.

Switching from OFF to automatic wiper results in a single wipe to acknowledge that the wiper control is now automatic. Each time an increase in sensitivity is made a single wipe acknowledges the increase. No wipe occurs for a decrease.

*If the automatic rain sensor wiper control is not functioning correctly, check that the sensor located at the top of the windscreen is clean and clear of debris or dirt.*

***Windscreen Washer Control :*** Press the button (C) for more than one second to operate the windscreen washers. Operation continues until the button is released. When released the washers stop immediately but the wipers continue for a few strokes, ending with a pause and then a final wipe.




If used during normal wiper operation, the wipers operate continually irrespective of the washer operation.

***Headlamp Washers :*** Headlamp washers will operate automatically, once per journey (each ignition ON), if the windscreen washers are operated and the headlamps are ON.

## Vehicle Horn

To sound the horn press the centre pad of the steering wheel at any of the positions shown (A).




## Master Lamp Switch

1. All external lamps OFF.
2. Side, side marker, rear and registration plate lamps ON.
3. With the vehicle key at position 'II' in the ignition control, Headlamps ON, in addition to the side, side marker, rear and registration plate lamps.
4. With the vehicle key at position 'II' in the ignition control, if ambient light fades the side, side marker, rear and registration plate lamps and headlamps will switch ON automatically. If ambient light then increases, the side, side marker, rear and registration plate lamps and headlamps automatically go OFF. Automatic wipers are market specific.




*A light sensor at the top of the windscreen monitors ambient light levels for automatic lamps operation. Keep the windscreen clean and make sure that the sensor is not obscured. Obstructing the light in this area may lead to unwanted operation of the automatic lamps.*

## Lamps ON Warning

If the vehicle side lamps are ON, and the driver's door is opened after the vehicle key has been removed from the ignition control, an audible warning will sound for a period of five minutes. To stop the audible warning set the lamps to OFF. The audible warning will also stop when the driver's door is shut - the lamps will stay ON.

## Day Time Running Lamps

(Denmark, Norway and Sweden only)

The dipped beams and side lamps are permanently ON.

## Instrument Brightness




During the daylight hours the level of instrument brightness defaults to maximum brightness. During the twilight and night time hours a twilight sensor (A) located in the centre stack, automatically reduces the level of brightness to a preset level.

*If the twilight sensor is covered the level of brightness will stay low as if in night time mode.*




The level of brightness can be reduced by using the rotary control (B). If the brightness level has been adjusted, the twilight and night time brightness level will return to the previous setting on the rotary control, each time the sensor picks up the twilight hours.

Push the rotary control in and release to enable the control. Push in and release to lock the control.

# Trip Computer




Press the button (A) for less than three seconds cycles through the trip computer functions one at a time. Trip computer information is viewed in the message centre.

*If an information message shows, after reading and acting on the information provided press the **READ** button (B) to return to the trip display.*



***Range:*** Estimated travel distance with fuel available (no reset). The minimum distance shown will read 20 KM. Below this distance will show '- - -'.




***Average Fuel:*** Average fuel consumption since last reset. Press A for more than three seconds but less than five seconds to reset. Press A for five seconds or more will reset both the average fuel consumption and average speed. INFOCENTER IS RESET will be shown in the message centre. Press the ***READ*** button to acknowledge the message.




***Instantaneous Fuel:*** Shows the fuel consumption over the last three seconds of travel (no reset).




***Average Speed:*** Shows the average speed since last reset. Press A for more than three seconds but less than five seconds to reset. Press A for five seconds or more will reset both the average speed and average fuel consumption. INFOCENTER IS RESET will be shown in the message centre. Press the ***READ*** button to acknowledge the message.




***Present Speed:*** Shows the current vehicle speed.




*Driver aid only.*

*Trip computer default screen.*

***Tyre Pressure Monitor :*** Shows the current tyre pressure for all tyres (Refer to 'Tyre Pressure Monitoring', page 4.17).




***Blank Screen:*** Blank screen will show.

## Display Units

The display can be set to show metric or imperial units.

With the ignition ON press the ***READ*** button (C) and the Trip Computer button (D) together for three seconds to change the trip computer display units.



# Cruise Control

Cruise control can be used to maintain a selected vehicle speed (between 30 - 250 km/h) without having to use the accelerator.




***[1] RES :*** Resume the set speed retained in memory.

***[2] SET:*** Sets cruise control to ON.

Sets the speed, accelerate or decelerate.

***[3] CAN:*** Cancels cruise control but keeps the set speed in memory.

## Operation

***⚠ Warning: Only use cruise control when conditions are favourable, for example, straight, dry, open roads with light traffic.***

Press and hold the ***SET*** (+ or –) button to switch cruise control ON. When cruise control mode is ON 'CRUISE' will show in the message centre.

When travelling at the desired speed, which must be above 30 km/h, press the ***SET*** (+ or –) button. Cruise control will then engage and maintain that speed without the need to use the accelerator pedal. 'CRUISE - SET' will show in the message centre.

📖 *Under certain conditions cruise control will automatically set to OFF (Refer to 'Cruise Control Automatic OFF', page 4.16).*

📖 *Cruise control will automatically disengage when the brake pedal is pressed or when the vehicle speed falls below 30 km/h.*

## Changing the Set Speed

There are three ways to change the set speed:

- Accelerate or decelerate to the desired speed then press the ***SET*** (+ or –) button.
- Accelerate or decelerate to the desired speed by pressing and holding the ***SET*** (+ or –) button until the desired speed is obtained, then release.
- Accelerate or decelerate to the desired speed in steps of 2 km/h by briefly pressing and releasing the ***SET*** (+ or –) button until the desired speed is obtained.

## Resuming the Set Speed

***RES should only be used if the driver is aware of the set speed and intends to return to it.***

***It is not recommended to resume set speed when a low gear is selected as excessive engine speeds will occur.***

*Cruise control will not resume at speeds below 30 km/h. **RES** will not operate if the ignition has been set to OFF.*

If the vehicle is accelerated above the set speed, then the set speed will be resumed when the accelerator pedal is released.

If the ***CAN*** button is pressed, or the brake pedal is pressed, cruise control will disengage but the set speed memory will be kept. Press the ***RES*** button and the vehicle will return to the set speed.

## Cruise Control Automatic OFF

Cruise control will automatically set to OFF and clear the memory when:

- The ignition is set to OFF.
- The ***CAN*** button is pressed and held for a few seconds.
- A fault occurs. The cruise control system will set to OFF and cannot be used until the fault is cleared.
- The park brake is applied.

Cruise control will automatically set to OFF but the set speed will stay in the memory when:

- The ***CAN*** button is pressed once briefly.
- The brake pedal is pressed.
- Vehicle speed falls below 30 km/h.
- Neutral or Reverse gear positions are selected.
- If DSC is active.

## Ambient Temperature

The ambient temperature (outside temperature) is shown in the top right corner of the Infotainment centre display.

*If the vehicle has been travelling and then is stopped in a shaded or enclosed area the ambient temperature may rise, this is due to the heat from the engine bay. The ambient temperature display will show the true ambient temperature once the vehicle is moving again or the engine bay cools down.*

*If required the display units can be changed from °C to °F or °F to °C (Refer to 'Climate Controls', page 6.2).*

***⚠ Warning: Driving on a significantly under-inflated tyre causes the tyre to overheat and can lead to tyre failure. Under-inflation also reduces fuel efficiency and tyre tread life, and may affect the vehicle's handling and stopping ability.***

Each tyre should be checked monthly when cold, in the ambient air temperature that the vehicle is normally driven. Setting tyre pressures in a warm garage and then driving in a very low ambient may result in a low tyre pressure warning. Set the correct pressure recommended by the vehicle manufacturer on the vehicle placard or tyre inflation pressure label (if your vehicle has tyres of a different size than the size shown on the vehicle placard or tyre inflation pressure label, you should make sure of the correct tyre pressure for those tyres).

As an added safety feature, your vehicle has been equipped with a Tyre Pressure Monitoring System (TPMS) that sets a tyre pressure telltale (warning) symbol to ON (A) when one or more of the tyres is significantly under or over inflated. At the same time an image of vehicle in the message centre will show which tyre(s) have low or high air pressure and the current tyre pressure. When the tyre pressure telltale comes ON, stop and check your tyres as soon as possible, and inflate or deflate them to the correct pressure.

*📖 The TPMS is not a substitute for correct tyre maintenance, and it is the driver's responsibility to maintain correct tyre pressures, even if under-inflation has not reached the level to set the TPMS tyre pressure telltale symbol to ON.*

## Malfunction Telltale

Your vehicle has also been equipped with a TPMS malfunction telltale to show when the system is not operating correctly. The TPMS malfunction telltale is combined with the tyre pressure telltale.




When the system detects a malfunction, the telltale will flash for approximately one minute and then stay ON. This sequence will continue upon subsequent vehicle start-ups as long as the malfunction exists.

When the malfunction telltale is ON, the system may not be able to detect or send tyre pressure as intended. TPMS malfunctions can occur for a variety of reasons, including the installation of replacement or alternate tyres or wheels on the vehicle that prevent the TPMS from operating correctly.

Always check the TPMS malfunction telltale after replacing one or more tyres or wheels on your vehicle to make sure that the replacement or alternate tyres and wheels allow the TPMS to continue to function correctly.

## Operation

***⚠ When a tyre pressure warning is detected reduce the vehicle speed to an appropriate safe level and stop at the first safe and convenient place to inspect the tyre(s).***

At each ignition ON there is a short delay before tyre pressures are received, from the wheel and tyre transmitters, and shown in the message centre.

If the tyre telltale symbol comes ON while driving, reduce speed to 48 km/h and stop in safe place as soon as possible. Check the status of the tyre(s) in the message centre:

### Warning One




**Telltale Symbol**

Constant.

**Message Centre**

CHECK TYRES (for ten seconds) followed by an image which shows which tyre(s) is affected and the current tyre pressures.

**Fault**

Tyre pressure below or above specification.

**Action**

Check the tyre pressure of the affected tyre(s). Set the tyre pressure to the manufacturer's recommended pressure, as shown on the tyre label located on the edge of driver's door or the B-Pillar.

### Warning Two




**Telltale Symbol**

Flashing for 75 seconds then constant.

**Message Centre**

TYRE SYSTEM FAULT (for ten seconds) followed by an image which shows which tyre(s) is affected and the current tyre pressures or which transmitter is at fault.

**Fault**

System failure or tyre transmitter fault.

**Possible Cause**

- The TPMS sensors have become defective.
- Wheels and tyres have been installed which do not have TPMS sensors.
- An unapproved accessory is interfering with the TPMS.
- A general fault has been detected in the TPMS.

**Action**

Continue at a reduced speed of 48 km/h maximum. Check the control unit and the tyre transmitters at the earliest opportunity. Consult your Aston Martin Dealer.

### Display Units


The display can be set to show metric or imperial units.

With the ignition ON press the ***READ*** button (C) and the ***TRIP*** button (D) together for three seconds to change the trip computer display units.



# Driving


Driving Safety....5.2
Driving Techniques....5.2
Starting the Engine....5.3
SportShift Transmission....5.5
Auto Drive Buttons....5.5
Paddle Shift Controls....5.6
SportShift Features....5.7
Clutch Warnings....5.8
Footbrake....5.9
Anti-Lock Braking System....5.10
Park Brake....5.11
Dynamic Stability Control....5.11
Adaptive Damping....5.13
Fuel Filling....5.14
Catalytic Converters....5.15
Parking Assist....5.16

## Driving Safety

- Always wear your seat belt.
- Never drive under the influence of alcohol or drugs.
- Always obey all speed and traffic laws and regulations. Never drive faster than the posted speed limit or than conditions allow.
- Be particularly careful driving on slippery or wet surfaces.
- This vehicle is a high performance vehicle and has handling characteristics you may not be accustomed to. Familiarise yourself with the vehicle and always drive prudently, being aware of your own limitations and the limitations of the vehicle. As with other vehicles of this type, failure to operate the vehicle correctly can result in accident and injury.
- Follow the maintenance schedule approved in this guide.
- Never allow the vehicle to be driven by inexperienced drivers.

## Driving Techniques

Procedures for driving this vehicle may be unfamiliar to many new owners. To make sure that you have a safe and enjoyable entry into this new phase of Aston Martin motoring please take time to safely acquire the necessary new driving skills. Practise in safe, lower speed conditions before investigating the high performance potential of the vehicle.

Performance Driving Courses are available to enable customers not only to understand the control functions of their vehicle but also the basic principles of Performance Driving.

Contact your Aston Martin Dealer for further information.

### Wet Conditions

When driving in wet conditions, water can build up under your tyres so that they ride on a layer of water. This is called aquaplaning or hydroplaning. When this happens, you have little or no control.

Aquaplaning is more prone to happening at higher road speeds if there is a lot of water on the road and particularly if the tyres are also under inflated or approaching minimum tread depth.

It is important to take bends or curves at a safe, reasonable speed, particularly when driving on wet or slippery road surfaces.

**Slow down when it is raining**.

### Track Days

Before using this vehicle on track days contact your Aston Martin Dealer for vehicle set up, service parts and recommendations.

### Driving Through Deep Water

If in any doubt whether to drive through deep water, always take the side of caution to avoid potentially costly damage to the vehicle's engine or other essential systems.

***! Never drive in water deeper than the lower edge of the front bumper. Water can be splashed up into the engine air intakes located in the front upper grille and cause extensive damage to the engine or the vehicle may stall. Always proceed with extreme caution, especially when the depth is not known.***

When driving through water, traction or brake capability may be limited. Once through the water, always dry the brakes by driving slowly while applying light pressure on the brake pedal.

*Waves caused by other vehicles or natural causes can also splash water in the engine air intakes.*

## Running-In

This vehicle is fully hot tested during manufacture and no special running-in procedures are necessary. Nevertheless it is recommended to limit engine loads (e.g. by accelerating gently and by using lower gears on steep hills or when negotiating tight turns) during the first 1500 km/900miles.

***⚠ Warning: Only use the vehicle key in the ignition control. Do not place any objects, including fingers, into the ignition control other than the vehicle key. Objects other than the vehicle key may cause the ignition control unit to fail.***

***! In extreme low temperatures (-20°C and below) do not allow the engine to 'rev' above 4000 rpm, while at standstill or when moving off, until the coolant temperature gauge reaches normal operating temperature. Revving the engine before fully warmed up may cause severe engine and transaxle damage.***


***! Do not press the vehicle key while driving. If the key is pressed in and released the engine will stop. If the key is removed from the ignition control while driving the engine will stop but the steering lock will not engage until the vehicle has come to a complete stop.***

***! The vehicle key must only be inserted into the ignition control with the two indents first, as shown. Attempting to insert the larger end of the key first may damage the ignition control.***




*📖 Make sure that you are wearing appropriate footwear to efficiently operate the control pedals. Make sure that pedal movement is not restricted by floor mats or other objects trapped beneath pedals.*

## Ignition Sequence





***[1] :*** Position '0' (Ignition OFF)

***[2] :*** Position 'I' (Ignition OFF and Accessories ON)

***[3] :*** Position 'II' (Ignition ON)

***[4] :*** Engine start

## Engine Start



Check that the park brake is applied.

Fully press the clutch pedal down.

Insert the vehicle key into the ignition control and press the key fully in (the ignition control will show red), hold in until the engine starts then release.

The vehicle key will sit flush with the ignition control bezel while the engine is running. The ignition control will show a white light when the engine is running, and then fade out.

*When starting the engine the vehicle system will take short time (approximately one second) to complete a system check and release the steering lock before allowing the engine to crank.*

If the engine fails to start, release the key, then press the key fully in again **without the clutch pedal pressed down** and release. The key will gently return to position 'I'. Start the engine start procedure again.

## Starting From Cold

The Engine Control Module (ECM) automatically compensates for cold or warm start conditions and makes appropriate adjustments to the fuel and air mixture and ignition timing.

## Stopping the Engine




Press the vehicle key fully in and release. The engine will stop as the key returns to position 'I'. Withdraw the vehicle key from the ignition control.

## Maximum Engine Speed

The maximum safe engine speed is 7,000 rpm. If this speed is exceeded, fuel supply to the engine is reduced. As the engine speed reduces back to a safe level, fuel supply is progressively restored.

## SportShift Transmission

***⚠ Warning: Always secure the vehicle with the brakes when stopped. As with any transmission using a gearbox and clutch arrangement the vehicle will roll once the clutch is disengaged.***

Vehicles installed with the SportShift transmission have a manual gearbox and clutch arrangement. Most manual gearbox and clutch arrangements have a clutch pedal which when pressed lifts the clutch away from the flywheel, disengaging the engine from the drive line, enabling gearshifts. The SportShift transmission uses a Transmission Control Module and an Electro-hydraulic control unit to replace the clutch pedal and make gearshifts.

Two modes of gear selection are available.

### Auto Drive Mode


In auto drive mode gearshifts are made according to various driving parameters, i.e. road speed, current selected gear and accelerator demands. Forward, reverse and neutral gears are selected by using the auto drive buttons. While in auto drive mode move to paddle shift mode at any time by pulling back on either the upshift or downshift gearshift paddles, mounted behind the steering wheel.

### Paddle Shift Mode

In paddle shift mode forward gears and neutral are selected by using the paddles located behind the steering wheel. Neutral is selected by puling both paddles at the same time. Reverse is selected by using the auto drive buttons. While in paddle shift mode move to auto drive mode at any time by pressing the ***DRIVE*** button or pull and hold the upshift paddle for one second.

📖 *Neutral can also be selected by pressing the **N** auto drive button.*

## Auto Drive Buttons




***[1] SPORT:*** Press and release at any time while driving to start (button LED ON) and stop sport mode.

***[2] REVERSE:*** When stationary and with the footbrake applied, press and release to select reverse. When reverse is selected, ***R*** will show red in the Gear Position Indicator Display (GPID) (B) and a warning will be heard.


***[3] NEUTRAL:*** When stationary and with the footbrake applied, press and release to select neutral.

***[4] DRIVE:*** When stationary and with the footbrake applied, press and release to select forward gears.

*If the brake pedal is not pressed the message centre will show **PRESS BRAKE PEDAL** and a warning will sound.*

The message centre (A) shows the current gear selection R, D1, D2, etc., while the GPID (B) shows ***D*** (Drive), or ***R*** (Reverse) according to current gear position.

As vehicle speed reduces the SportShift system will open and close the clutch and downshift as engine speed drops.





## Kick-Down

Kick-down is used in circumstances where rapid acceleration is required, i.e. when overtaking. Kick-down is when the accelerator pedal is quickly depressed, causing the transmission to change down to the lowest gear possible to achieve maximum acceleration. The gear engaged depends on the road speed at the time of kick-down.

## Paddle Shift Controls

Forward gearshifts are selected by pulling back and releasing the gearshift paddles mounted on the steering column. Neutral is selected by pulling back both paddles together and releasing.

Reverse is selected by using the centre stack mounted auto drive buttons.




***[1] :*** Downshift paddle.

***[2] :*** Upshift paddle.


*Neutral can also be selected by pressing **N**.*

From reverse or neutral, and with the footbrake applied, pull back on either the upshift or downshift gearshift paddle to enter paddle shift mode. As the vehicle speed increases and decreases, make upshifts and downshifts by pulling and releasing the upshift or downshift gearshift paddle. A minimum upshift speed is required. When shifting up through the gears maintain foot pressure on the accelerator pedal.

*If a downshift request is not detected during speed reduction, downshifts will automatically occur as engine speed drops.*

*To achieve multiple downshift of gears, in SPORT mode pull and hold the downshift paddle to 'skip' gears and select the lower gear depending on vehicle deceleration, i.e. fifth to third gear. The GPID shows the next gear, for example, if fifth to third is selected, fourth is not shown.*

The message centre and the GPID will show the current gear selection. In SPORT mode an upshift occurs automatically for gears 1 and 2, therefore the GPID only flashes when it reaches the rev limiter.



If the vehicle engine speed reaches its upper operating limit in gears 3 and above an upshift will not be made until a paddle upshift request has been detected. To inform the driver that the upper operating limit has been reached the GPID gear symbol will change from white to flashing red.

The message centre also shows the current gear selected with an up or down arrow and shows the next gear when it needs selecting. For example, when in third gear and fourth gear needs selecting **3 ^4** is shown in the message centre.

## Hyper-shift

When an upshift is made with the engine speed at or above 5,500 rpm and the accelerator pedal is fully depressed the requested upshift will be accelerated, providing a quicker, sportier driving experience.

## Sport Mode

Sport mode gives you a more engaging driving experience. To maximise the vehicle's response the Engine Control Module (ECM) adjusts the engine throttle response, exhaust valve operation and available engine torque.




Sport mode can be selected while in auto drive or paddle shift modes. Press and release the ***SPORT*** button to enter or exit sport mode. The ***SPORT*** button LED will come ON and SPORT will show in the message centre when sport mode is ON.

***Auto Drive Mode:*** Upshifts and downshifts occur at higher engine speeds to provide a sportier drive.

***Paddle Shift Mode:*** Automatic upshifts are prevented, the upshift paddle must be pulled back and released to make an upshift (downshifts will occur automatically if the engine speed lowers to its minimum operating limits).

To maintain speed and smoothness while driving in paddle shift sport mode, the current gear shown in the Gear Position Indicator Display (GPID), will flash red at the optimum time to make an upshift.

# Clutch Warnings

## Clutch Self-Learn

After starting up, the Neutral button LED will flash for up to 4 seconds. After 4 seconds, the LED will stay on while in neutral. The LED flashes while the vehicle is doing a clutch self-learn. This will happen at every start (hot or cold). It will not prevent a gear being selected and driving away, but we recommend that you let the self-learn complete as it improves the driving experience.

There are five clutch temperature points and when they are reached during driving, a clutch self learn is activated. When the car comes to a stand still, with your foot on the brake, first gear will be disengaged, neutral is then selected automatically, **N** shows on the GPID, the NEUTRAL button flashes and the clutch self learn is activated. When it is finished, first gear is re-engaged, and **1** is shown in the GPID. This process takes 4 seconds to complete and occurs a maximum of 5 times during a drive cycle.

If the accelerator pedal is depressed during this time, then the clutch self learn will be cancelled.

Excessive demands placed on the clutch, for example, from holding the vehicle on an incline using the throttle only will operate a two stage clutch overheat warning.

## Stage One

The amber warning symbol will come ON, and a single audible warning will sound. The message centre will show the message CLUTCH OVERHEAT BRAKE OR PULL AWAY. The driver should reduce the demand on the clutch by increasing the demand on the accelerator pedal or releasing the accelerator pedal and applying the footbrake or park brake.

If the demand on the clutch is not reduced and the clutch temperature continues to increase, the second stage of clutch overheat strategy shall be invoked.

## Stage Two

The message CLUTCH PROTECT MODE and SHIFT COMFORT REDUCED will show as a rolling message with the amber triangle until the clutch temperature returns to normal operating limits. During this time gearshift and moving off performance will be degraded to let the clutch to cool.

## Limp-Home Mode

Certain SportShift system faults will place the vehicle into limp home mode. If the vehicle has gone into limp-home mode the message centre will show GEARBOX FAULT REDUCED FUNCTION. While in limp-home mode the vehicle can still be driven but only first, second and reverse gears will be available.

Sport mode will be not be available. Contact your Aston Martin Dealer.

# Footbrake

The footbrake operates through a vacuum boosted, dual (diagonal split) circuit, hydraulic system incorporating an Anti-lock Brake System (ABS).

***⚠ Warning: In the event of a brake failure bring the vehicle to a halt as soon as it is safe to do so. Do not continue to drive.***

***! If vacuum boost fails or one circuit fails the footbrake will still operate but with greater pedal pressure, increased pedal travel and longer stopping distances.***

***! After a long drive over salted or gritted roads or if driving in heavy rain, through water or a vehicle wash, the braking action may be delayed and increased braking pressure may be required.***

*Vacuum boost is only available while the engine is running.*

## Ceramic Brake Discs

***⚠ Warning: Track day use and high speed driving: For track use or high speed driving new brake pads must be subject to specific conditioning. Failure to correctly condition the pads may result in greatly reduced brake performance. Contact your Aston Martin Dealer.***

Carbon ceramic brake systems combine low weight with high performance, offering:

- Reduced unsprung weight (mass of components not supported by the suspension) - improving vehicle handling,
- Improved rate of wear characteristics,
- Improved braking performance.

*The rate of wear of the brake pads and discs will depend on driving style and usage conditions. Track day usage will increase the rate of wear of discs and pads.*

## Brake Warnings

***⚠ Warning: If the brake warning symbol comes ON, you should immediately be prepared for possible increased stopping distances and possible partial failure of the braking system.***

While driving, if the brake warning symbol (!) BRAKE comes ON, it shows either that:

- The park brake is not fully released.
- The brake pads require regular maintenance.
- The brake fluid level has fallen below an acceptable level.
- The Electronic Brake Distribution (EBD) system has stopped working.

*A warning message will show in the message centre.*

Stop, as soon as possible in a safe and convenient place. Apply the footbrake and make sure that the park brake is fully released. If the park brake is fully released and the warning symbol stays ON, **do not drive** the vehicle. Contact the nearest Aston Martin Dealer. It is essential that the brake system is checked immediately, preferably by an Aston Martin Dealer.

# Anti-Lock Braking System

*Brake Noise: The high performance brake system used on this vehicle is designed to provide optimal braking under all operating conditions. However, under all driving conditions an inherent characteristic of this braking system is some brake noise. Certain combinations of speed, braking forces and ambient conditions may also cause the brakes to squeal.*

The Anti-lock Braking System (ABS) helps prevent the road wheels from locking and skidding during emergency braking. This also assists the driver in maintaining steering and directional stability.

If, in an emergency braking situation, the braking force applied begins to exceed the tyre to road adhesion, the ABS operates to prevent the road wheels locking. When this happens a pulsating effect is felt through the brake pedal. This is a normal ABS effect.

## Safety

In all cases it is always the drivers responsibility to drive safely according to the law and with due regard to prevailing conditions. The fact that a vehicle is equipped with ABS must never let the driver to be tempted into taking risks which could affect his or her safety or that of other road users.

The addition of ABS cannot overcome the consequences of trying to stop in too short a distance, cornering at too high a speed, or the risk of aquaplaning (where the tyres are prevented from contacting the road surface by a layer of water).

The driver should always take road conditions into account. A slippery road surface always requires more braking distance for a given speed, even with ABS. Possible extensions of stopping distance compared to locked wheels may occur during ABS operation on slushy snow, gravel, sand or certain heavily corrugated or ridged warning sections of road surfaces.

If any braking system malfunction occurs, immediately have the Braking and ABS systems checked by your Aston Martin Dealer.

## ABS Warning

***⚠ Warning: If the ABS warning symbol comes ON, you should be aware that wheels could lock during extreme braking or when braking on slippery surfaces.***

ABS is monitored for correct operation while the ignition is ON. If a fault is detected, the ABS warning symbol (ABS) will come ON and the ABS will be partly or fully OFF. Normal braking will continue to function without ABS.

In the event of an ABS fault, consult your Aston Martin Dealer immediately.

## Park Brake

***Always fully apply the park brake before leaving the vehicle.***



### To Apply the Park Brake

Press the footbrake pedal firmly down. Keep the pedal pressed down and pull the park brake lever up until resistance is felt. At this point press the park brake button and continue to pull the park brake lever up to its fullest extent. Release the button and allow the lever to lower.

*To show that the park brake is applied the brake warning symbol on the instrument cluster will come ON (if the ignition is ON).*

### To Release the Park Brake

Press the footbrake pedal firmly down. Keep the pedal pressed down and pull the park brake lever up until resistance is felt. Pull up against the resistance and press the release button. Keep the button pressed and push the lever down. If the park brake lever is not fully OFF, the brake warning symbol will stay ON.

***Always check that the brake warning symbol is OFF before moving off. Do not attempt to drive the vehicle if the brake warning symbol stays ON.***

*An audible warning will sound if the vehicle is moving and the park brake is still applied.*

- If the vehicle is parked on a hill and facing uphill, select first gear and turn the steering wheel away from the kerb.
- If the vehicle is parked on a hill and facing downhill, select reverse gear and turn the steering wheel towards the kerb.

### Hill Start Assist

The hill start assist function gives assistance and safety for driving off on an incline. As you change from the brake to the accelerator pedal, the brake pressure is retained for brief a moment, the vehicle will remain stationary for long enough so that you can move off without rolling back.

The hill start assist function will work on inclines of 4% and greater. On inclines of less than 4%, the park brake should be applied when stationary to prevent roll-back.

## Dynamic Stability Control

***Warning: It is the driver's responsibility to drive safely according to the law and with due regard to prevailing conditions.***

***Warning: Dynamic Stability Control (DSC) must never let the driver be tempted into taking risks which could affect his or her safety or that of other road users. DSC cannot overcome consequences of applying too much engine power for prevailing conditions.***

Dynamic Stability Control (DSC) is a system designed to enhance driving safety by improving the vehicle handling when the tyres are at the limits of their grip capabilities. This is achieved through the reduction of engine torque and strategic application of the brakes at individual wheels.

## Driver Interface and Control

***If repair or replacement of the steering or other surrounding equipment is necessary, always refer to your Aston Martin Dealer. If the centre position of the steering deviates, the DSC system may not operate correctly because there is a sensor in the steering system which detects steering wheel position.***

***The DSC system may not operate correctly when using tyre chains or a temporary spare tyre.***

***Use tyres of the same manufacturer, brand, tread pattern and correct size specified for this vehicle on all four road wheels. Do not mix worn tyres.***

DSC has three modes of operation:

***ON:*** The DSC system sets to ON each time the engine is started. DSC is controlling engine torque and applying strategic application of the brakes at individual wheels.

While the DSC system operates to correct the vehicle stability the DSC symbol on the instrument cluster, will flash.




***TRACK MODE:*** Press and hold the DSC button (A) for four seconds and release. DSC TRACK MODE SELECTED will show in the message centre. This raises the thresholds at which the DSC system operates. While the DSC system operates to correct the vehicle stability the DSC symbol will flash.

***OFF:*** When in Track mode, press and hold the DSC button for four seconds and release to set the DSC to OFF. DSC OFF can not be selected from DSC ON. DSC FUNCTION OFF will show in the message centre. DSC is no longer controlling engine torque and applying strategic application of the brakes at individual wheels.

At any time while in track or off mode, press and release the DSC button to start DSC.

*When in Track mode or OFF, the DSC button LED will come ON and the amber warning triangle will be shown in the instrument cluster.*

### Fault Signs

A malfunction in the DSC control system will be shown by the following:

- The DSC symbol in the instrument cluster will come ON.
- A warning message will show in the message centre depending on the fault detected.

## Traction Control

***⚠ Warning: It is always the drivers responsibility to drive safely according to the law and with due regard to prevailing conditions.***

***⚠ Warning: Traction control must never let the driver be tempted into taking risks which could affect his or her safety or that of other road users.***

***⚠ Warning: Traction control cannot overcome consequences of applying too much engine power for prevailing conditions.***

Traction control is a function of DSC, and is operated in association with the DSC system. Traction control prevents excessive wheel spin at standing starts, or during acceleration. Wheel spin is usually caused by excessive use of the accelerator pedal, or slippery, loose or bumpy road surfaces.

To prevent excessive wheel spin and maintain vehicle stability in such situations the traction control system will:

- Brake either of the driven wheels when they start to slip
- And, or, adapt the engine torque to a level corresponding to the traction available on the road surface.

*These symptoms are normal and will clear as wheel spin is eliminated and normal engine power is restored.*

*If cruise control is on it will automatically go OFF when DSC is operating.*

During operation, the DSC warning symbol will flash. The driver may experience a loss in power or temporary 'misfire' as engine power is reduced.

If traction control cuts in when driving on extended icy or slippery surfaces, reduce engine power as necessary until the DSC warning symbol goes OFF.

Traction control is always ON when DSC is ON.

## Adaptive Damping

The Adaptive Damping System (ADS) is continuously ON, adjusting the damping characteristics at all four corners, according to vehicle body movement and monitored driver inputs. Sensors on the vehicle constantly measure the vehicle body movement and driver inputs – braking, steering, vehicle speed and throttle displacement. This information is then supplied to the ADS control unit which calculates the optimal damper characteristic at each corner at any given moment.

*ADS is independent of the Dynamic Stability Control (DSC) system.*

ADS has three modes of operation:

***Normal Mode:*** At ignition ON the ADS system defaults to normal mode which gives damping characteristics for everyday driving.

***Sport Mode:*** Press and release the ADS button (A) to start sport mode, which gives damping characteristics for a firmer ride.

While driving move to normal (button LED OFF) or sport (button LED ON) mode by pressing and releasing the ADS button.

***Track Mode:*** Press and hold the ADS button (A) for more than 1 second to start Track mode (button LED FLASHES) which provides damping characteristics suitable for track driving.


A message on the console confirms the damper mode has been switched. This message can be cleared with the Read button.

*When the ignition is switched off, the system latches to the last selected damper mode upon restarting.*


# Fuel Filling

*The fuel tank filler neck has a restricted opening which will only accept the fuel supply nozzle of unleaded fuel pumps.*

Open the fuel flap by pressing the fuel flap release button (A) located in the driver's footwell. If the filler flap will not open when the release button is pressed, use the fuel filler flap emergency release.




Turn the cap counterclockwise past resistance, then lift off. Place the cap into its holder. Install the cap by turning clockwise past resistance, until three ‘clicks’ are felt as the cap is fully tightened. Close and latch the fuel flap.




The fuel system will not let the fuel tank overfill but there will be times when the fuel nozzle will shut OFF prematurely. If this happens only try to fill the fuel tank one more time, continued attempts will result in fuel spillage. Wait 10 seconds before removing the refuelling nozzle.

**Fuel Filler Bowl**

To stop water gathering in the fuel filler bowl and flowing into the fuel tank, the fuel filler bowl has a pipe to let the water drain from the bowl. During fuel filling, check and make sure that any debris which may block the pipe is removed.

## Fuel Filler Flap Emergency Release

Remove the left side boot trim to access the manual fuel filler flap release. Pull the lever (B) to open the filler flap.




## Fuel Cut-OFF

In the event of a vehicle accident the vehicle electronics will enter crash mode. Power to the fuel pumps will stop, thereby reducing fire risk.

## Engine Oil Level

***It is important to check the engine oil level regularly. Running the engine with engine oil below the lower mark or above the upper mark can cause serious engine damage.***

Check the engine oil level every fourth fuel tank fill or weekly - which ever is the sooner.

## Catalytic Converters

***Warning: Do not park over dry grass, leaves or other combustible material. Significant fire risk exists because of residual heat in the catalytic converters.***

***Warning: Do not drive through deep water. Rapid cooling of catalysts may cause them to break up.***

Catalytic convertors convert harmful exhaust gasses into less noxious substances and so reduce environmental pollution. They operate at high temperatures and continue to radiate a considerable amount of heat after the ignition has been set to OFF.

Leaded fuel will cause irreparable damage to catalytic converters. If leaded fuel is inadvertently added to the fuel tank **do not start the engine, do not drive the vehicle**. Contact your Aston Martin Dealer immediately.

# Parking Assist

***⚠ Warning: Parking assist does not replace need for total vigilance and caution when parking or reversing.***

***! It is always the driver's responsibility to detect obstacles and estimate the vehicle's distance from them. Some overhanging objects, barriers, thin obstructions or painted surfaces which could possibly cause damage to the vehicle may not be detected by the system. Always be vigilant when reversing.***

***! Do not turn and hold the steering on full lock for any more than 10 seconds. If the steering is held on full lock for more than 10 seconds the power steering pump can fail.***

***! The rear sensors are not ON when neutral is selected, therefore care should be taken if moving the vehicle as the warning sound will not be heard.***

***! Do not clean the sensors with abrasive or sharp objects.***

*For reliable operation, the sensors in the front and rear bumpers should be kept free from ice, frost and grime.*

*When using a high pressure spray the sensors should only be sprayed briefly and not from a distance of less than 200 mm. Do not clean the sensors with abrasive materials.*

A warning will be heard when driving forwards or rearwards, if objects are detected within range of the vehicle.

## Front and Rear Parking Assist

***! If, for example, you are driving within a confined space such as a home garage, the outer sensors will detect the side walls and after three seconds the tone will stop. However, as movement continues, the inner sensors will eventually detect the rear wall and will start the tone again.***





***In heavy rain or similar adverse conditions, the rear parking assist sensors may not always be able to accurately measure distance to close objects. A fully laden vehicle or irregular obstacles may also cause inaccurate measurements.***

The parking assist system defaults to OFF when the ignition is set to ON. The system comes ON when reverse gear is selected, or if the parking assist button (A) is pressed at speeds below 15 km/h.




The system will set to OFF when the vehicle moves forwards above 15 km/h. The parking assist button LED will come ON when the system is set to ON. The LED will flash if a fault is detected in the system.

If an obstacle is detected at the front or rear of the vehicle, a series of beeps will be heard from the front or rear speaker respectively, which increases in rate as the vehicle nears the obstacle.

The beep becomes a continuous tone when an obstacle is detected at or within approximately 300 mm from the rear or 250 mm from the front of the vehicle.

If the system has a fault a single three second tone will be heard (only once per ignition cycle) and the parking assist button LED will blink when reverse gear is selected or the ignition is set to ON. The system is automatically disabled when a fault is detected.

*Parking assist may sound spurious tones if it detects an ultrasonic frequency using the same band as the sensors.*

*The system consists of inner and outer sensors. When manoeuvring forward into a garage, etc., the front outer sensors will cease detection if they detect a stationary or receding object for three seconds or more, this allows detection directly at the front of the vehicle in this type of manoeuvre.*

## Reversing Camera

Optional


***Warning: The parking camera does not replace the need for total vigilance and caution when parking or reversing.***

***It is always the driver's responsibility to detect obstacles and estimate the vehicle's distance from them. When parking or reversing make full use of rearward and forward vision and all mirrors to be aware of persons or objects in the vicinity of the vehicle. Take appropriate measures to protect them from danger.***

*For reliable operation, the parking camera lens in the rear bumper should be kept free from ice, frost and grime.*

*When using a high pressure spray the parking camera lens should only be sprayed briefly and not from a distance of less than 600 mm. Do not clean the camera lens with abrasive materials.*

In addition to the parking assist system, a rear parking camera, located above the rear registration number plate, gives a view of the rear of the vehicle as the vehicle is moved backwards while parking or reversing. When reverse gear is selected the camera view is shown on the satellite navigation screen.



If the satellite navigation is ON when reverse gear is selected the screen will show the camera view until reverse gear is deselected. When reverse gear is deselected the screen will continue to show the camera view for approximately ten seconds or when the vehicle reaches a speed of 16 kph (which ever is sooner), then return to the satellite navigation screen. Press and release the ***NAV*** button to move between the parking camera and satellite navigation screens, at any time, while reverse is selected.


If the satellite navigation is OFF the screen will raise when reverse gear is selected and lower when reverse gear is deselected.

The screen can be set to not raise when reverse gear is selected if the satellite navigation system is OFF. Press ***MENU*** on the console and navigate to *<Car Settings... > Enter < Disable Cam. if nav off>*. Press ***ENTER*** to set the camera ON or OFF, press ***BACK*** to return to the previous screen(s).

If the camera is set to OFF when the satellite navigation system is OFF, press ***NAV***, at any time while the transmission is in reverse gear, to raise the screen and operate the camera, if required.

At any time while in reverse gear, press and hold the ***NAV*** button to lower the screen, if required.

**Camera Operation**





The camera overlay shows the fixed movement angle of the rear of the vehicle with the road wheels on full lock (D) red lines and the actual movement of the vehicle road wheels (C) yellow lines. As the steering wheel is turned the yellow lines will show the predicted vehicle movement.

The outer edge of the two markers (E) show the width of the vehicle including the mirrors.

The distance from the beginning edge of the two markers (E) to the rear of the vehicle is 300 mm (B).

# Climate Control

Operating Tips ..... 6.2
Climate Controls ..... 6.2
Airflow Modes ..... 6.5
Automatic Operation ..... 6.6
Manual Operation ..... 6.7



## Operating Tips

- A solar sensor is installed on top of the instrument panel, this should not be covered when driving.
- The intake grille of the in-vehicle temperature sensor is located in the driver's knee bolster, close to the centre console. To maintain the optimum temperature this grille should not be obstructed.
- Moisture which forms on the evaporator in the air conditioning unit is discharged via a drain tube onto the road. After stopping, small puddles of water may form underneath the vehicle. This is normal and does not show a system malfunction.
- Operate the climate control system with the engine operating.
- Clear all obstructions like leaves, snow and ice from the bonnet and the air inlet in the front grille to improve the system efficiency.
- Windows can fog up easily in humid weather. Use the climate control system to demist the windows.
- To help demist the windows, operate the air conditioner to dehumidify the air.
- Use the 'outside air' position in normal conditions. The 'recirculated air' position should be used temporarily when driving on dusty roads or for quick cooling or heating of the interior.
- If the vehicle has been parked in direct sunlight during hot weather, open the windows to let warm air escape, then close the windows and operate the climate control system.
- Operate the climate control system at least once a month to keep internal parts lubricated.
- Have the climate control system checked before the weather gets hot. If the climate control system is low on refrigerant or has a malfunction, consult your Aston Martin Dealer.
- This vehicle is equipped with a pollen filter. It is necessary to change the filter periodically as shown in the scheduled maintenance. Consult your Aston Martin Dealer.
- Air conditioning may not function when the outside temperature approaches 0°C (indicator stays ON even when system is OFF).

## Climate Controls



***[1] DISPLAY:*** Shows options, menus and information.

***[2] AUTO:*** Press for automatic climate control operation (Refer to 'Automatic Operation', page 6.6).

***[3] TEMPERATURE:*** Set the required in vehicle temperature. Turn clockwise for hot and counterclockwise for cold. The selected temperature is shown on the ***DISPLAY***.

***[4] A/C:*** When in manual mode press and release to set the air conditioning ON or OFF.

***[5] HEATED REAR WINDOW:*** Press to operate the rear window heater. Goes OFF after 20 minutes if not manually set to OFF. When the heated rear window is ON the door mirror heaters will work for 6.5 minutes, then go OFF.

***⚠ Warning: Do not select recirculated air in cold or rainy weather, it can cause the interior glass to mist up.***

***[6] MAX***  ***:*** Press for maximum defrost or demist ON or OFF. Outside air intake is automatically selected and air conditioning is automatically started.

***[7] FAN SPEED:*** Turn to set the required fan speed (clockwise for fast speed and counterclockwise for low speed). The fan speed is shown on the ***DISPLAY***

***[8] AIR CIRCULATION:*** Controls the source of air entering the vehicle. Press to select recirculated air (button LED ON). Press again to select outside air as source.

Use the recirculated air position when going through tunnels, driving in congested traffic (high engine exhaust areas) or when maximum cooling is required. On start up the default position is outside air as source. Use this position for normal conditions and demisting.

***[9] AIRFLOW:*** Select the required airflow. The selected air flow mode is shown on the ***DISPLAY***(Refer to 'Automatic Operation', page 6.6).

## Display Units

To change the ***DISPLAY*** units to show Celsius (°C) or Fahrenheit (°F).

Press and hold in buttons 1 and 6 (A). Insert the vehicle key in the ignition control and move to position 'II' (ignition ON), then release the two buttons.





## Solar and Temperature Sensors

The automatic air conditioner function measures inside and outside temperatures, and sunlight. It then sets the interior temperature accordingly. To maintain effective operation do not obscure the following sensors:

***[1] :*** Solar sensor.

***[2] :*** In-vehicle temperature sensor.







# Airflow Modes

Press and release each button for an airflow mode. By pressing one or more buttons at a time, five airflow modes are available.





| Mode | Button(s) |
|---|---|
| Windscreen and Door Windows | A |
| *In addition a small bleed of air is directed into the face vents.* | |
| Face Only | B |
| Feet Only | C |
| *In addition a small bleed of air is directed to the face vents, the windscreen and door windows.* | |
| Windscreen, Door Windows and Feet | A+C |
| *In addition a small bleed of air is directed into the face vents.* | |
| Face and Feet | B+C |



## Adjusting the Vents

To adjust the air flow vents:



Press ***AUTO***. Using the ***TEMPERATURE*** dial set the required in-vehicle temperature (read the actual temperature setting in the top left of the ***DISPLAY***). The ***A/C*** button LED will come ON.

Adjustments to fan speed, air flow and air re circulation will be made automatically according to the set temperature, interior and exterior conditions.

*Maximum fan speed will not be available until the engine has reach its normal operating temperature.*

*When using the air conditioner, mist may come out from the vents. This is not a sign of trouble but a result of humid air being suddenly cooled.*

*If resetting climate control functions other than the fan speed, the fan speed will stay set as in automatic mode. Adjustments to the fan speed will cancel Auto Mode.*

## Defrost and Demist

***To defrost or demist the windscreen on vehicle start up in extreme cold weather conditions, run the engine at 1500rpm. Always make sure that neutral is selected and the park brake is applied.***

Press ***MAX*** . The outside air intake is automatically selected, the temperature is set to maximum and air conditioning is started.

*If the engine is cold the air conditioner will not start up until the engine has started to warm up.*

To cancel automatic defrost or demist either:

- Press ***MAX*** again.

or

- Press ***AUTO***.

or

- Press any of the airflow mode buttons.

*The automatic defrost setting times out after 6 minutes.*

Set the required:

- Fan speed
- Temperature
- Air flow.

*The fan speed and temperature setting will show on the **DISPLAY**.*

*When using the air conditioner, mist may come out from the vents. This is not a sign of trouble but a result of humid air being suddenly cooled.*

*Setting the temperature to maximum high or low will not provide the required temperature at a faster rate. To prevent cool air blowing from the vents when heating immediately after starting a cold engine, the amount of airflow is reduced until the air warms up.*

*The vehicle heater will continue to produce the selected temperature regardless of in-vehicle conditions.*

If dehumidifying is required, press the ***A/C*** button (button LED ON). To stop dehumidifying press ***A/C*** button (button LED OFF).

When maximum cooling is required, set the ***TEMPERATURE*** dial to the extreme cold position and press the ***AIR CIRCULATION*** button to the re circulated air position ( will show in the ***DISPLAY***), then set a fast fan speed.

## Defrost and Demist

***To defrost or demist the windscreen on vehicle start up in extreme cold weather conditions, run the engine at 1500rpm. Always make sure that neutral is selected and the park brake is applied.***

Press ***A/C***. Press the airflow button.

Set the required:

- Temperature
- Fan speed.

*If the engine is cold the air conditioning will not start up until the engine has started to warm up.*

*For maximum defrost or demist set the temperature and fan speed dials to maximum.*

# Audio


Audio Essentials ..... 7.2
Audio Controls ..... 7.4
FM and AM Radio Functions ..... 7.8
DAB Radio Functions ..... 7.10
Radio Data System ..... 7.11
Programme Type ..... 7.12
Enhanced Other Networks ..... 7.13
Automatic Frequency Updating ..... 7.13
Regional ..... 7.13
CD Changer Functions ..... 7.14
iPod and USB Functions ..... 7.15
Auxiliary Functions ..... 7.16

# Audio Essentials

## Aston Martin Audio

***Radio:*** Digital Audio Broadcasting (DAB) radio. 20 presets are available.

AM and FM radio[1]. 10 AM and 20 FM presets are available.

***CD:*** Six CD autochanger.

***iPod[2]:*** Connection port.

***USB Device:*** Connection port.

***Auxiliary Input:*** Connection port.

***Power Output:*** 700W.

***Surround Sound:*** Dolby Pro-Logic II.


## Speakers

***[1] :*** 100W centre-fill speaker.

***[2] :*** Two door-mounted 100W speakers, each with mid-range and tweeter units.

***[3] :*** Two rear environment 100W speakers, each with mid-range and tweeter units.

***[4] :*** 200W subwoofer housed under the rear environment left side.




1. Medium Wave (MW) and Long Wave (LW).
2. iPod is a trademark of Apple Inc.

## Bang & Olufsen Audio

Optional

***Radio:*** Digital Audio Broadcasting (DAB) radio. 20 presets are available.

AM and FM radio[1]. 10 AM and 20 FM presets are available.

***CD:*** Six CD autochanger.

***iPod[2]:*** Connection port.

***USB Device:*** Connection port.

***Auxiliary Input:*** Connection port.

***Power Output:*** 974W

**Speakers**

***[1] :*** Two 19 mm (soft dome) tweeters incorporating Acoustic Lens Technology (ALT).


***[2] :*** Centre: Two speakers: One 90 mm mid-range in closed cabinet and one 19 mm (soft dome) tweeter.

***[3] :*** Footwell: Two 140 mm woofers in closed cabinets.

***[4] :*** One 90 mm mid-range speaker, in closed cabinets, in each front door.

***[5] :*** One 200 mm subwoofer housed in closed cabinet under the rear environment left side.

***[6] :*** Two speakers: One 90 mm mid-range and one 19 mm (soft dome) tweeter in each rear quarter.




1. Medium Wave (MW) and Long Wave (LW).
2. iPod is a trademark of Apple Inc.


# Audio Controls

### Acoustic Lens Technology



Acoustic Lens Technology (ALT) gives a wide (180°) horizontal dispersion of high frequencies. This prevents the loss of critical sound and gives listeners an improved sense of space, staging and realism, even when not sitting in the optimal location[1] for listening to two-channel stereo reproductions.

Two motorised acoustic lenses, mounted on either side of the dashboard, rise when the system is set to ON and stay raised until the audio system is set to OFF.




***[1] ON/OFF:*** Press for audio ON and OFF.

***[2] VOLUME:*** Volume control.

***[3] KEYPAD:*** Use the numbers as menu short cuts. Press the number corresponding to the menu number.

***[4] DISPLAY:*** Shows options, menus and information.

***[5] SOUND:*** Press and hold to enter sound setting mode. Press repeatedly to move though settings, turn to select. When in iPod or USB mode a press and release will enable file viewing.

***[6] TUNING:*** Turn to manually search stations, change music tracks or navigate in the menus.

***[7] TP:*** Press to enable traffic broadcasts. Press again to disable.

***[8] SCAN:***

- **Radio:** Find and store the strongest stations.
- **CD's, iPod / USB:** 10 seconds of each track is played. Press once again to select a track.

***[9] AUTO:*** Automatic station search.

***[10] CD OPENING:*** Insert CDs.

1. For the optimal location to listen to two-channel stereo reproductions, the listener should be sitting equidistant from both loudspeakers on the apex of an equilateral triangle.

***[11] MENU:*** Opens the main menu.

***[12] AM/FM:*** Press to select radio as audio source.

***[13] MODE:*** Press repeatedly to select audio source.

***[14] ENTER:*** Select in the menu, open a selection or open a file.

***[15] JOYSTICK:*** Navigate in the menus.

- **Radio:** Press left or right to auto search the next station. Press and hold left or right to manually select a station. Press up or down to navigate in the menus or preset stations.
- **CD's:** Press left or right to move to the next or previous track. Press left or right and hold to search within a track or the whole CD. The search continues as long as the Joystick is pressed.
- **iPod** / **USB:** Press left or right to move to the next track or previous. Press left or right and hold to search within a track or the whole music folder. The search continues as long as the Joystick is pressed.

***[16] BACK:*** Press to move back one action. Press and hold to move back to the default screen.

***[17] CD EJECT:*** Press to eject CD.

***[18] SCROLL:***

- **Radio:** Navigate through the preset radio stations.
- **CD's, iPod** / **USB:** Navigate through the music tracks.

***[19] VOLUME:*** Volume control.




## Operation

The audio system is available with the vehicle key at least in position 'I' and is available until the vehicle key is removed from the ignition control.

If the audio system is ON when the ignition is set to OFF and the vehicle key removed, it will automatically start the next time the vehicle key is moved to position 'I'.

Press ***ON/OFF*** to set the audio system ON or OFF.

📖 *When the audio system is set to ON the volume will be at the same level it was when the audio system was set to OFF.*

The ***JOYSTICK***, ***ENTER*** and ***BACK*** will not operate if Satellite Navigation is selected (***NAV*** button LED ON) either press:

- The ***NAV*** button to deselect satellite navigation (***NAV*** button LED OFF),
- Or press any audio button other than ***BACK***, ***ENTER*** and ***JOYSTICK***

to access controls for audio.

📖 *Pressing the **AM/FM** or **MODE** buttons will move the current audio source.*

## Sound Source

To select radio, at any time while the audio system is ON, press the ***AM/FM*** button repeatedly to navigate between the radio bands.

To select other audio sound sources press the ***MODE*** button repeatedly to navigate through the sound source choices.

## Battery Protection Mode

Using the audio system, with the vehicle key at position 'I' (ignition OFF) will drain the battery charge. A warning message will show in the message centre when the battery charge is low (Refer to 'Battery Protection Mode', page 10.20).

## Menus

The audio menu is only available when the audio system is in use. Press ***MENU*** to access the main menu. The menu for the current audio source (i.e. radio, CD, iPod, etc.) will be available.

### Search Path

Menu paths are shown for each operation in the following format:

*<FM Menu...> Enter <Sound settings...> Enter*

Several menu options will require a cross in a box to select an option. Once the menu item is highlighted press ***ENTER*** to either check or uncheck the box. Then press and hold ***BACK*** to accept and return to the main screen.

📖 *In this chapter when asked to 'Press' a button, this means 'Press and release'. When this is not the case it will be clear in the text.*

## Active Sound Control

This vehicle has a speed-dependent volume feature known as Active Sound Control (ASC). This adjusts the volume automatically depending on the speed of the vehicle.

Press ***MENU*** and navigate to sound source menu, press ***ENTER***. Select *<Auto. volume control> Enter <Off>, <Low>, <Optimum>* or *<High> Enter*.

## Original Settings

### *Radio Functions*

Resets all radio settings to the original factory settings: Press ***MENU*** and navigate to *<FM Menu...> Enter <Advanced radio settings...> Enter <Reset all...> Enter*. Press ***ENTER*** again to confirm.

### *Sound Settings*

Resets all sound settings to the original factory settings: Press ***MENU*** and navigate to sound source menu, press ***ENTER***. Select *<Audio settings...> Enter <Reset all...> Enter*. Press ***ENTER*** again to confirm.

## Aston Martin Audio Sound Settings

To access sound settings press and hold ***SOUND*** to enter sound setting mode. Then press repeatedly until the required sound setting is shown on the ***DISPLAY***. Turn the ***TUNING*** dial to the desired setting.

*The level for the centre speaker can only be set if either Dolby Pro-Logic II or 3 Channel has been selected from the sound source menu.*

***Bass:*** Level for bass.

***Treble:*** Level for treble.

***Fader:*** Balance between the front and rear speakers.

***Balance:*** Balance between the left and right speakers.

***Surround:*** Level for surround sound.

***Subwoofer:*** Level for subwoofer.

***Centre:*** Level for centre speaker.

***Surround:*** Level for surround sound.

### Setting the Surround Sound

Press ***MENU*** and navigate to the sound source menu, press ***ENTER***. Select *<Audio Settings...> Enter <Surround (AM, FM, CD iPod or AUX)...> Enter <Dolby Pro-Logic II>, <3 Channel> or <Off> Enter*. Press and hold ***BACK*** to return to the main display. The symbol for Dolby Pro-Logic II is shown on the ***DISPLAY*** if Dolby Pro-Logic II is selected. '3CH' is shown on the ***DISPLAY*** if 3 Channel is selected. 'Off' means the system is in normal stereo mode. Dolby Pro-Logic II is not available in radio mode.

### Equaliser

Fine adjustment of the sound from the speakers: Press ***MENU*** and navigate to the sound source menu, press ***ENTER***. Select *<Audio Settings...> Enter <Equaliser...> Enter*. Move the ***JOYSTICK*** left or right to set the level. Use the ***JOYSTICK*** (up or down) to select the next frequency. Five frequencies can be adjusted. Press ***ENTER*** to save any changes and exit. Press ***BACK*** to exit without saving any changes.

### Dolby Surround Pro-Logic II

Dolby Surround Pro-Logic II, with its centre speaker in the dashboard, provides more realistic sound reproduction.

The normal left and right stereo channels are divided into left-centre-right. In addition, ambient surround sound is produced through the rear speaker channels.

Not available in Radio mode.

*Dolby Surround Pro-Logic II and the Dolby icon are trade-marks of Dolby Laboratories Licensing Corporation. The Dolby Pro-Logic II Surround System is manufactured under license from Dolby Laboratories Licensing Corporation.*



## Bang & Olufsen Audio Sound Settings

To access sound settings press and hold ***SOUND***. Then press repeatedly until the required sound setting is shown on the ***DISPLAY***. Turn the ***TUNING*** dial to the desired setting.

**Sound Focus**

The focus of the sound from the audio system can be optimised for either the driver or the driver and passenger. Select:

*The audio system detects seat occupancy by seat belt engagement.*

***Driver:*** The focus of the sound is optimised for the driver only.

***Front:*** The focus of the sound is optimised for both the driver and the passenger.

***Auto:*** The audio system automatically detects if driver only or driver and passenger(s) are in the vehicle.

**Other Sound Settings**

***Bass:*** Level for bass.

***Treble:*** Level for treble.

***Fader:*** Balance between the front and rear speakers.

***Balance:*** Balance between the left and right speakers.

***Surround:*** Level for surround sound.

# FM and AM Radio Functions

## Automatic Tuning

Select FM1, FM2 or AM using the ***AM/FM*** button. Press the ***JOYSTICK*** (left or right) to search for the next strong station.

Press left or right again to start a new search.

*If no stations are found press either button again to cancel.*

## Manual Tuning

There are two ways to tune into a station manually.

- Turn the ***TUNING*** dial to set the desired frequency.
- Press and hold the ***JOYSTICK*** (left or right).
  The frequency rolls slowly in the selected direction and increases speed after a few seconds.

Release the button when the desired frequency shows on the ***DISPLAY***. If the frequency needs adjusting, briefly touch one of the arrows.

## Storing Stations

10 stations can be stored for FM1, FM2 or AM (a total of 30 stations).

To store stations:

Tune to the desired station. Press and hold the ***KEYPAD*** button (0-9) where the station is to be stored. The sound will be muted for a couple of seconds and 'Station Stored' will show on the ***DISPLAY***.

Select a stored station by either pressing a ***KEYPAD*** (0 to 9) button or use the ***SCROLL*** button to scroll through the station list.

## Autostoring Stations

Up to ten AM or FM stations can be automatically tuned and stored in a separate memory.

Select FM1, FM2 or AM using the ***AM/FM*** button. Start the search by pressing and holding ***AUTO*** (more than two seconds).

'Autostoring.' shows on the ***DISPLAY*** and a number of strong stations (maximum ten) from the selected frequency band are stored in the autostore memory. It there are no stations that are sufficiently strong, 'No AST Found' shows on the ***DISPLAY***.

📖 *If more than ten stations are found, the ten strongest are selected. This function is particularly useful if you are in an area in which you are unfamiliar with the radio stations and their frequencies.*

The stations are stored on the ***KEYPAD*** (buttons 0-9). When the radio is in autostore mode, 'Autostoring' is shown on the ***DISPLAY***.

Return to the ordinary radio mode by pressing and releasing ***AUTO*** (less than 0.7 seconds). Pressing and releasing either ***AUTO*** or ***BACK*** will also cancel autostoring.

Select an Auto stored station by pressing ***AUTO***, then a ***KEYPAD*** (0 to 9) button or the ***SCROLL*** button to scroll through the station list.

## Automatic Search for Transmitter

'PI seek' shows on the **DISPLAY** when reception is poor for the selected station. The radio automatically searches for the strongest transmission for that station. 'PI seek Back to cancel' is shown on the ***DISPLAY*** until the station is found.

## Scanning

Scanning automatically searches for the next strong FM or AM station signals. When the radio finds a station, scanning pauses for approximately eight seconds, after which it continues.

Select FM or AM with the ***AM/FM*** button.

Press ***SCAN***. 'Scan' shows on the ***DISPLAY*** and each found station will play for approximately eight seconds. Press ***SCAN*** or ***BACK*** to accept the station.

📖 *If no stations are found press either button again to cancel.*

# DAB Radio Functions

Digital Audio Broadcasting (DAB) radio broadcasts digitally via a network of transmitters. DAB radio provides more stations, more information and a clearer sound quality.

**DAB Ensembles**

DAB ensembles are groups of DAB broadcasters that transmit multiple digital radio stations on a single radio transmission. There are usually between 6-10 radio stations per ensemble.

## Automatic Tuning

Select DAB1 or DAB2 using the ***AM***/***FM*** button. Press the ***JOYSTICK*** right to search for the next available station in the selected ensemble. At the end of that ensemble, pressing the ***JOYSTICK*** right again starts searching at the start of the next ensemble.

Press the ***JOYSTICK*** left to return to the previous station.

*If no stations are found press either button again to cancel.*

## Changing Stations

There are two ways to change a station.

- Turn the ***TUNING*** dial to locate another station.
- Press the ***JOYSTICK*** (left or right).

Continue until the desired station shows on the ***DISPLAY***. To select another station, repeat either procedure.

## Storing Stations

10 stations can be stored for DAB1 and DAB2 (total of 20 stations).

To store stations:

Tune to the desired station. Press and hold the ***KEYPAD*** button (0-9) where the station is to be stored. The sound will be muted for a couple of seconds and 'Station Stored' will show on the ***DISPLAY***.

Select a stored station by either pressing a ***KEYPAD*** (0 to 9) button or use the ***SCROLL*** button to scroll through the station list.

## Learn

Learn checks the radio frequencies and automatically repopulates the station list with all available stations. When the DAB radio finds a station, it may pause for a few seconds, after which it continues to check for stations.

Select DAB1 or DAB2 with the ***AM***/***FM*** button.

Select ***LEARN*** from the DAB menu. The ***DISPLAY*** then shows the progress status of the check, and once complete the station list is updated. The first station in the list is then played.

**DAB Text**

DAB radio allows more information to be shown in a scrolling format on the display.

To enable the DAB scrolling text:

Press ***MENU***. Navigate to *<DAB menu...> ENTER <DAB Text> ENTER* .

**Current Station Information**

To view current station information including the station ID, ensemble and ensemble ID:

Press ***MENU***. Navigate to *<DAB menu...> ENTER <Current Station Info> ENTER*.

**Station Link**

A DAB station link creates a link between the same DAB stations within different ensembles. Therefore if the radio reception on the current station drops below an acceptable level, the DAB system searches other ensembles and if the same station is found and has a better signal, then this station is then used. A 'no signal' message maybe shown whilst the system is searching.

To enable station links:

Press ***MENU***. Navigate to *<DAB menu...> ENTER <DAB Station Link> ENTER*.

**News**

News broadcasts can be set to interrupt the current DAB broadcast.

To enable the news broadcasts:

Press ***MENU***. Navigate to *<DAB menu...> ENTER <News> ENTER* . When news is ON, 'NEWS' will show on the display.

Press ***BACK*** during a news broadcast to cancel the broadcast. The news function stays ON and waits for the next news programme.

Radio Data System (RDS) is a system that links together specific network transmitters. It is used, for example, to tune the correct frequency of a station irrespective of the transmitter or the current audio source (e.g. CD). The system can also be used for receiving traffic information (TP) and for finding broadcasts of a specific type. Radio text is also a component of RDS. A radio station can transmit information about the radio programme currently being broadcast.

Messages with a programme code (such as news from RDS stations) will interrupt other audio sources at the volume set for this. As soon as the news broadcast is finished, the audio system returns to the previous audio source and resumes the previous volume setting.

📖 *Some radio stations do not use RDS or only use a limited range of its features*.

## Alarm

Alarms are transmitted automatically. The function cannot be set to OFF. 'Alarm!' is shown on the ***DISPLAY*** when an alarm message is broadcast. The function is used to warn motorists of serious accidents or disasters.

## News

Press ***MENU***. Navigate to *<FM Menu...> Enter <News> Enter*. When news is ON 'NEWS' will show on the ***DISPLAY***.

Press ***BACK*** during a news broadcast to cancel the broadcast. The news function stays ON and waits for the next news programme.

## News From Current Station

Press ***MENU***. Navigate to *<FM Menu...> Enter <Advanced Radio Settings....> Enter <News station...> Enter <News from current station> Enter*.

## Traffic Information (TP)

Press ***TP*** repeatedly to set TP ON and OFF.

When ON 'TP' is shown on the ***DISPLAY***. If the set station does not broadcast traffic information, 'TP)))' shows on the ***DISPLAY***.

Press ***BACK*** to exit the current traffic broadcast. TP stays ON and waits for the next traffic broadcast.

### TP From a Station or All Stations

Press ***MENU***. Navigate to *<FM Menu...> Enter <Advanced radio settings...> Enter <TP...> Enter <TP station...> Enter <TP from current station>* or *<TP from all stations> Enter*.

### TP Search

This function allows you to listen to traffic information when travelling between different areas and countries without selecting a station.

Press ***MENU***. Navigate to *<FM Menu...> Enter <Advanced radio settings...> Enter <TP...> Enter <TP search> Enter*.

### Radio Text

Some RDS stations broadcast information, such as about programme content and artists.

Press ***MENU***. Navigate to *<FM Menu...> Enter <Radio text> Enter*.

## Programme Type

Use the Programme Type (PTY) function to select between the various programme types.

Press ***MENU***. Navigate to *<FM Menu...> Enter <PTY...> Enter <Show PTY> Enter*.

When ON the station's programme type will be shown on the ***DISPLAY***, e.g. Current affairs, Information, Drama, Rock music, etc.

📖 *Not all radio stations have a PTY designation.*

### Searching for a Specific PTY

Press ***MENU***. Navigate to *<FM Menu...> Enter <PTY...> Enter <PTY...>*. Press ***ENTER*** for one or more of the listed programme types.

The PTY symbol on the ***DISPLAY*** comes ON when the first selection is made and the radio is set to stand-by for PTY.

Press ***BACK*** to go back.

Navigate to *<FM Menu...> Enter <PTY...> Enter <Search PTY> Enter*.

If the radio finds a station with the selected programme type, this is played.

If a station with the selected programme type can not be found, the ***DISPLAY*** shows 'No Station Found' and the radio returns to the previous frequency.

PTY is then on stand-by until the selected programme type is broadcast. When this happens, the radio automatically selects the station broadcasting the programme type.

### Clear All PTY

Press ***MENU***. Navigate to *<FM Menu...> Enter <PTY...> Enter <Clear all PTY...> Enter*.

The PTY symbol is removed from the ***DISPLAY*** and the radio returns to normal mode.

## Enhanced Other Networks

With Enhanced Other Networks (EON) ON, traffic announcements and news broadcasts interrupt radio programmes. The function has three levels:

***Local:*** Only interrupts if the signal is strong.

***Distant:*** Interrupts even if the signal is weak.

***Off:*** Does not interrupt even if the signal is weak.

### EON - ON or OFF

Press ***MENU***. Navigate to *<FM Menu...> Enter <Advanced radio settings...> Enter <EON...> Enter*. Select *<Local>, <Distant>* or *<Off> Enter*.

When ON 'EON' is shown on the ***DISPLAY***.

## Automatic Frequency Updating

The Automatic Frequency (AF) Updating function is normally ON and makes sure that the radio tunes to the strongest available transmitter.

Press ***MENU***. Navigate to *<FM Menu...> Enter <Advanced radio settings...> Enter <AF> Enter*.

When ON 'AF' is shown on the ***DISPLAY***.

## Regional

The regional function is normally OFF. When the function is ON you can continue to listen to a regional broadcasts even if the signal is weak.

Press ***MENU***. Navigate to *<FM Menu...> Enter <Advanced radio settings...> Enter <Regional> Enter*.

When ON 'Reg' is shown on the ***DISPLAY***.

# CD Changer Functions

## Loading CDs

***Use only 12 cm CDs. Do not use CDs with adhesive disc labels. The heat from the CD player can cause the label to come loose from the disc. The CD player could be damaged.***

***Do not use CDs that are warped or look warped (critical measurement for CD warp is 0.7 mm - anything more than this may cause problems). The CD player will not be able to hold the CD correctly (because of the warp), this may cause a jam in the CD player.***

*If the quality of the CD does not comply with the requirements of standard EN60908 or if it has been recorded using poor equipment, sound quality may be poor or playback interrupted.*

The CD changer can hold up to six discs.

Press the ***MODE*** button repeatedly to select CD. Select an empty position using the ***KEYPAD*** (buttons 1 to 6) or use the ***JOYSTICK*** (up or down). The ***DISPLAY*** shows which positions are empty. Make sure that 'Insert disc' is shown then insert a new disc.

The current CD that is playing is shown in green and is positioned above the other CDs. CD slots that contain a CD are shown in light grey. Empty CD slots are shown in dark grey. All CD and track information that is available is shown. This can include CD title, artist, track name and number.

## Selecting a CD

Select the CD to play using ***KEYPAD*** buttons 1-6 or the ***JOYSTICK*** (up or down). The number of the disc and track are shown on the ***DISPLAY***.

## Changing Tracks

Push the ***JOYSTICK*** (left or right), the ***SCROLL*** button, or turn the ***TUNING*** dial to play the next or previous track. The track number is shown on the ***DISPLAY***.

## Fast Forward and Rewind

Push and hold the ***JOYSTICK*** left or right to search forwards or backwards within a track or the whole disc. Searching continues for as long as the button is depressed.

## Random Play

Plays tracks from a CD or CDs in random order.

Press ***MENU***> Navigate to <*CD Menu...*> *Enter* <*Random...*> *Enter*. Select <*Off*>, <*Single disc*> or <*All discs*> *Enter* for the player to randomly choose from none, one or all CDs.

RND or RND ALL is shown on the ***DISPLAY*** while the function is ON. Push the ***JOYSTICK*** (left or right) or ***SCROLL*** button to select the next or previous random track.

Press ***BACK*** to cancel random play.

## Scan

Press ***SCAN*** to play the first ten seconds of each track. While a scan is in progress push ***SCAN*** again or ***BACK*** to play a track.

## Pause Mode

When the volume is at zero, play will pause. Start play again by turning the volume up.

### Disc Text - ON or OFF

Some CDs have title information. The information is shown as text on the ***DISPLAY***.

Press ***MENU***. Navigate to *<CD Menu...> Enter <Disc text> Enter*.

If information is stored on the disc, this is shown on the ***DISPLAY***.

### Ejecting One CD

Press ***EJECT***.

*For traffic safety reasons, the CD stays out for 12 seconds. The player will then draw back in the disc and set to pause mode. Press CD to start the player.*

### Ejecting all CDs

Press and hold ***EJECT*** (for longer than two seconds). The entire magazine is emptied, CD by CD. 'Eject all' is shown on the ***DISPLAY***.

This function can only be used when the vehicle is stationary and is interrupted if the vehicle starts to move. For traffic safety reasons, the ejected CD stays out for 12 seconds. It must then be removed, or the function is cancelled.

### iPod and USB Connection

*The iPod port is compatible with generation three iPods onwards.*

*The USB port is only compatible with USB storage devices, e.g. memory sticks.*


*On initial connection and on every engine start the system will synchronise with the connected device. This will take a short while to complete.*

*The iPod controls will not operate while connected to the vehicle audio system. All functionality will be from the vehicle audio system.*

Locate the iPod cable or the USB socket in the armrest cubby box and connect the:

- an iPod player via an iPod cable
- a USB device to the USB port.

If not already ON, set the audio system to ON. Repeatedly press the ***MODE*** button until either 'iPod' or 'USB' shows on the display.



The iPod or USB device can now be operated by the audio system. The iPod or USB is shown and accessed in the order of connectivity.

### Playing Tracks

Once the mode has been set to either iPod or USB play automatically starts.

### Selecting Tracks

Press the ***JOYSTICK*** down to show the music folder list. Select from **Tracks**, **Albums**, **Artists** and **Playlists** (if using an iPod) to navigate to the required music tracks. Press ***ENTER*** to open a folder or play a track.

### Pause Mode

Press ***ENTER*** to pause a track whilst playing. Press ***ENTER*** again to start play. When the volume is at zero, play will pause. Start play by turning the volume up.

### Fast Forward and Rewind

Press and hold the ***JOYSTICK*** (left or right) to search within a track or the whole music folder. The search continues as long as the ***JOYSTICK*** is held.

## Changing Tracks

Press the ***JOYSTICK*** (left or right), or the ***SCROLL*** button, or turn the ***TUNING*** dial to play the next or previous track.

### Scan

Press ***SCAN*** to play the first ten seconds of each track. While a scan is in progress press ***SCAN*** again or ***BACK*** to play the required track.

### Random

Plays tracks from the music folder(s) in random order.

Press ***MENU***. Navigate to *<iPod Menu...> or <USB Menu...> Enter <Random...> Enter*. Select *<Off>, <Folder>* or *<All> Enter* for the player to randomly choose from none, one or all music folders.

'RND' or 'RND ALL' is shown in the ***DISPLAY*** while the function is ON.

Press the ***JOYSTICK*** (left or right) or the ***SCROLL*** button to select the next or previous random track.

### RDS Radio Stations


News broadcasts (NEWS) and traffic information (TP) are also available when in USB or iPod mode. Refer to iPod and USB menus.

## Audio Device Connection

The auxiliary input socket is provided to connect audio devices which can not be connected using the iPod or USB connections.

*Only volume control will be available from the vehicle audio system. All other functionality will be from the audio device.*

Locate the auxiliary socket in the front armrest cubby box. Connect the audio device to the auxiliary socket using a suitable cable.



If not already ON, set the audio system to ON. Repeatedly press the ***MODE*** button until AUX shows on the ***DISPLAY***.

The media device now plays through the Infotainment system.

## Audio Device Volume

The vehicle audio system volume can be set at a higher or lower starting volume for the audio device.

Press ***MENU***. Navigate to *<AUX menu...> Enter <AUX input volume...> Enter*. Turn the ***TUNING*** dial to set the volume level.

Press and hold ***BACK*** to return to the main display.



# Hands-Free Phone


Introduction ..... 8.2
Hands-Free Functions ..... 8.2
Connecting a Phone ..... 8.4
Disconnecting a Phone ..... 8.5
Pairing Phones ..... 8.5
Selecting a Phone ..... 8.7
Using a Phone ..... 8.8
Phone Book ..... 8.9
Voice Mailbox ..... 8.9
Last Ten Numbers ..... 8.10
Hands-Free Menu ..... 8.10

## Introduction

A mobile device equipped with hands-free (Bluetooth) capability can be connected wirelessly to the vehicle's hands-free phone system. The vehicle's hands-free phone system then lets you have remote control of a range of the mobile phone's functions. The mobile phone can always be operated by its own keys regardless of whether or not it is connected.

The hands-free system is available when the vehicle key is in ignition position 'I' or 'II'. If, during a call, the vehicle key is moved to position '0' or removed the call will transfer to the mobile phone after approximately six seconds.

The system microphone is located in the vehicle roof above the drivers head and the speech from an incoming call is from the two door speakers.

The hands-free phone system will not recognise a mobile phone, even if it is 'paired' (Refer to 'Pairing Phones', page 8.5), if the mobile phone does not have Bluetooth enabled. For more information refer to the user's guide for your mobile phone.

The hands-free phone system does not support SMS (text messages).

## Hands-Free Functions




***[1] VOLUME:*** Volume control.

***[2] DISPLAY:*** Shows options, menus and information.

***[3] TUNING:*** Navigate through phone book and menus.

***[4] MENU:*** Opens the main menu.

***[5] ENTER:*** Press to answer or make a call, select in the menu or open a selection.

***[6] JOYSTICK:*** Navigate in the menus, move forwards or backwards when entering text and digits.

***[7] PHONE:*** Press to select hands-free mode or press and hold to cancel hands-free mode.

***[8] BACK:*** End a call, navigate back in the menu, cancel a selection or erase the previous character when entering text and numbers.

***[9] KEYPAD:*** Search through the phone book, speed dial or navigate in the menu.

***[10] CALL:*** Press to answer a call or press to return to hands-free mode from audio when hands-free mode is ON.

***[11] VOLUME:*** Volume control during a call.

***[12] SCROLL:*** Navigate in the menus.

***[13] CANCEL:*** Press to end a call or press to enter audio mode when hands-free mode is selected.




## Hands-Free Phone ON

When the hands-free system is ON the symbol will show in the ***DISPLAY***. During a call this symbol will change to . When a mobile phone is connected to the hands-free system the symbol will show in the ***DISPLAY***. If, after 30 seconds, the hands-free phone has not been used, the infotainment system will default to audio functions. Return to hands-free phone functions by pressing ***PHONE*** or **CALL**.

## Menus

The hands-free menu is available when the hands-free phone system is ON and selected. If not ON or not selected press ***PHONE***. Press ***MENU*** to access the main menu.

**Search Path**

Menu paths are shown for each operation in the following format:

*<Phone menu...> Enter <Phone settings...> Enter <Sounds and volume...>*

*In this chapter when asked to 'Press' a button, this means 'Press and release'. When this is not the case it will be clear in the text.*

Several menu options will require a cross in a box to select an option. Once the menu item is highlighted press ***ENTER*** to either check or uncheck the box. Then press and hold ***BACK*** to accept and return to the main screen.

**Call Menu**

Press ***MENU, ENTER*** or ***CALL*** during an ongoing call to access the following functions:

***Mute microphone:*** The hands-free system microphone is muted.

***Transfer call to mobile or Transfer call to vehicle:*** The call can be transferred to or from the mobile phone or the vehicle phone.

***Phone book:*** Access the phone book during a call.

*Some mobile phones will close the connection when the privacy function is used, this is normal. The vehicle system asks if you want to reconnect.*

## Audio Settings

### Call Volume

During a call the call volume can be regulated using the ***VOLUME*** dial or button.

### Audio System Volume

The audio source can be automatically muted for incoming calls:

Press ***MENU*** and navigate to *<Phone menu...> Enter <Phone settings...> Enter <Sounds and volume...> Enter <Mute radio> Enter*.

If mute radio is OFF select one of the audio sources to control the audio system volume during an ongoing call.

### Audio System Control

Not available during a call.

When the audio system is in operation while hands-free mode is ON press ***CALL*** to return to hands-free mode.

### Ring Volume

Press ***MENU*** and navigate to *<Phone menu...> Enter <Phone settings...> Enter <Sounds and volume...> Enter <Ring volume> Enter*. Adjust using the **TUNING** dial.

### Ring Signals

The vehicle system has integrated ring signals that can be selected:

Press ***MENU*** and navigate to *<Phone menu...> Enter <Phone settings...> Enter <Sounds and volume...> Enter <Ring signal> Enter <Select Ring signal 1, 2, 3 etc.> Enter*.

*The connected mobile phone's ring signal is not muted when one of the vehicles integrated signals is used.*

## Connecting a Phone

A connection between the vehicle hands-free system and a mobile phone is called a 'Paired Link'. When a paired link is set up the hands-free system remembers the mobile phone's ID.

Once the hands-free system and the mobile phone are paired, the hands-free system automatically connects every time the ignition is set to ON if the hands-free system (Press ***PHONE***) and the mobile phone are ON.

A mobile phone can be paired either using the vehicle hands-free system or by using the mobile phone.

The vehicle's hands-free system supports paired links with up to 10 mobile phones.

*The process of initiating a hands-free connection with a mobile phone varies per phone manufacturer. For more information refer to the user's guide for your mobile phone.*

## Disconnecting a Phone

The mobile phone will **automatically** disconnect when moved out of the hands-free system's range or Bluetooth is made unavailable on the mobile phone.

The mobile phone will **manually** disconnect when the hands-free system is set to OFF. Press and hold ***PHONE*** until is removed from the ***DISPLAY***. The function is also stopped when the ignition is set to OFF.

If the mobile phone has been disconnected from the hands-free system during an ongoing call, the call will transfer to the mobile phone.

*Some mobile phones require that the transfer is confirmed from the phone's keypad.*

## Pairing Phones

### Initial Pairing

Use this procedure when pairing the first mobile phone to the hands-free system. If the hands-free system is not ON or in use, press ***PHONE***.

The ***DISPLAY*** will show NO PAIRED PHONES. PRESS ENTER AND SELECT ADD A PHONE. Press ***EXIT*** to cancel. Press ***ENTER***.

The hands-free system will asked if Bluetooth is in discoverable mode (refer to the mobile phone manufacturer's instructions). If yes press ***ENTER***. After a short while a list of phones which are in range will be shown.

*If the symbol is shown in the **DISPLAY** when the ignition is ON, initial pairing can be completed using the mobile phone.*

Press the ***JOYSTICK*** (up or down), ***SCROLL*** button or turn the ***TUNING*** dial to navigate to the required mobile phone and press ***ENTER***. The ***DISPLAY*** will then ask for a passkey to be entered into the mobile phone. The mobile phone will prompt for the passkey. Enter the passkey into the mobile phone.

The ***DISPLAY*** will show PHONE CONNECTING... then, if successful, SYNCHRONISING.

Once synchronising has completed the mobile phone is ready for use.

*If the passkey is not entered after 20 seconds the screen will time-out.*

*Synchronising automatically places all the mobile phone contacts onto the vehicle system.*

## Pairing Additional Phones

### Pairing Using the Hands-Free System

*Disconnect any in use phones before pairing additional phones. If a phone is connected to the hands-free system pairing a new phone will not be possible until the hands-free system has no in use Bluetooth connections.*

*If, after 30 seconds, the hands-free phone has not been used, the infotainment system will default to audio functions. Return to hands-free phone functions by pressing **PHONE** or **CALL**.*

Check that the mobile phone has Bluetooth ON and visible. Check that the hands-free system is ON ( symbol will show in the ***DISPLAY***).

The hands-free system automatically searches for the last used phone. If the last used phone is not found a list of paired phones will show along with *<Add phone>*. Select *<Add phone>* to pair a new phone to the system.

If the last used phone is found press ***MENU*** and navigate to *<Phone Menu...> Enter <Bluetooth...> Enter <Change phone...> Enter <Add Phone...>*.

Press ***ENTER***. The hands-free system will asked if Bluetooth is in discoverable mode (refer to the mobile phone manufacturer's instructions). If yes press ***ENTER***. After a short while a list of phones which are in range and in discoverable mode will show.

Press the ***JOYSTICK*** (up or down), ***SCROLL*** button or turn the ***TUNING*** dial to navigate to the required mobile phone and press ***ENTER***.

The ***DISPLAY*** will then ask for a passkey to be entered into the mobile phone. The mobile phone will prompt for the passkey. Enter the passkey into the mobile phone.

The ***DISPLAY*** will show PHONE CONNECTING... then, if successful, SYNCHRONISING. Once synchronising has completed the mobile phone is ready for use.

*If the passkey is not entered after 20 seconds the screen will time-out.*

*Synchronising automatically places all the mobile phone contacts onto the hands-free system.*

### Pairing Using the Mobile Phone

*Disconnect any in use phones before pairing additional phones. If a phone is connected to the hands-free system pairing a new phone will not be possible until the hands-free system has no in use Bluetooth connections.*

Check that the hands-free system is selected ( symbol will show in the ***DISPLAY***).

Follow the mobile phone manufacturer's instructions to search and connect to a new Bluetooth device. The phone will search for discoverable Bluetooth devices in its range.

Select ASTON MARTIN from the device list. The phone will prompt for a passkey.

*If ASTON MARTIN does not show check that the hands-free system is selected and search again.*

Press ***MENU*** (on the vehicle) and move to *<Phone menu...> Enter <Bluetooth...> Enter <Connect from Mobile Phone> Enter*. The ***DISPLAY*** will then show a passkey, enter the passkey into the mobile phone.

The ***DISPLAY*** will show PHONE CONNECTING... then, if successful, SYNCHRONISING. Once synchronising has completed the mobile phone is ready for use.

📖 *If the passkey is not entered after 20 seconds the screen will time-out.*

📖 *Synchronising automatically places all the mobile phone contacts onto the vehicle system.*

## Removing a Paired Phone

### Using the Hands-Free System

Press ***MENU***. Navigate to *<Phone menu...> Enter <Bluetooth...> Enter <Remove Phone> Enter*.

A list of paired phones will show. Navigate to the required phone and press ***ENTER*** to erase or ***BACK*** to cancel.

## Disconnecting a Paired Phone

Press ***MENU***, and navigate to the Phone menu.

Select *Disconnect Phone*. The phone remains in the list, but is no longer paired to the vehicle's phone system.

# Selecting a Phone

📖 *The phone to be selected must have Bluetooth ON, visible and in close proximity to the hands-free phone system.*

A phone can be selected by using the phone itself or by using the hands-free system:

## Using the Mobile Phone

If not ON or not selected, press ***PHONE***.

Using the mobile phone, follow the manufacturer's instructions to search and connect to a Bluetooth device. The phone will search for discoverable Bluetooth devices in its range. Select ASTON MARTIN from the device list. Select Connect.

📖 *If ASTON MARTIN does not show check that the hands-free system is selected and search again. If ASTON MARTIN still does not show, then the mobile phone may not be paired (Refer to 'Pairing Phones', page 8.5).*

## Using the Vehicle Hands-Free System

With the hands-free system already selected, press ***MENU*** and navigate to *<Phone Menu...> Enter <Bluetooth...> Enter <Change Phone> Enter*. A list of paired phones will show (along with *Add phone*). Navigate to the required phone and press ***ENTER*** to change or ***BACK*** to cancel.

Or, if the hands-free system is not ON:

Press ***PHONE***. The system will then scan for the last used mobile phone. If found and it is the mobile required then press ***ENTER***. If the last phone is not found the **DISPLAY** will show a list of paired phones within range (with Bluetooth ON). Navigate to a phone and press ***ENTER*** to select that phone.

## Making a Call

Check that the hands-free system is selected ( symbol shows in the ***DISPLAY***).

Press ***PHONE*** on the centre stack, or ***CALL*** on the steering wheel controls.

- Press the ***JOYSTICK*** (up or down), ***SCROLL*** button, or turn the ***TUNING*** dial to select a contact from the phone book. Press ***CALL*** or ***ENTER*** to call.

Or

- Dial the number using the keypad and press ***CALL*** or ***ENTER*** to call. Press ***BACK*** to erase a number. Press and hold ***BACK*** to erase the whole number.

## Ending Calls

To end a call press ***CANCEL*** or ***BACK***.

## Reject a Call

Press ***CANCEL*** or ***BACK*** while the phone is ringing.

## Calling Using Voice Recognition

If the mobile phone supports voice dialling:

Press, hold and release ***CALL*** or ***ENTER***. The amount of time require to hold in ***CALL*** or ***ENTER*** is dependant on the mobile phone.

Once 'Voice Tag Dialling' shows on the ***DISPLAY***, allow one to two seconds before saying a name. The vehicle system will call the contact.

## Receiving Calls

To answer an incoming call press ***CALL*** or ***ENTER***.

## Automatic Answer - ON or OFF

The automatic answer function means that calls are accepted automatically after four rings.

Press ***MENU*** and navigate to *<Phone menu...> Enter <Phone settings...> Enter <Call options...> Enter <Automatic answer> Enter*.

## Phone Book

The mobile phone's phone book is synchronised automatically to the vehicle system at each connection.

If it is not required to synchronise to phone book:

Press ***MENU*** and navigate to *<Phone menu...> Enter <Phone settings...> Enter <Synchronising phone book> Enter*.

If the phone book contains a caller's contact information, this is shown in the ***DISPLAY***.

*If the mobile phone does not support copying of the phone book, 'List is empty' is shown when copying is finished.*

### Contact Search

Searching for contacts is only performed in the connected mobile phone's phone book. Either:

Press the ***JOYSTICK*** (up or down), ***SCROLL*** button, or turn the ***TUNING*** dial to bring up the contact list. Navigate to the contact. Press ***CALL*** or ***ENTER*** to call.

Or

Use the ***KEYPAD*** to search the phone book. Press and hold a key (2 to 9) which relates to the first letter of the contact's name. This starts a search in the phone book based on the key's first letter. Navigate to the contact. Press ***CALL*** or ***ENTER*** to call.

Or

Press ***PHONE***. Press ***MENU*** and navigate to *<Phone menu...>* ***ENTER****<Phone book...>****ENTER****<Search>****ENTER***. Using the ***KEYPAD***, enter the first few letters of the contact name, press ***ENTER***.

Navigate to a contact. Press ***CALL*** or ***ENTER*** to call.

## Voice Mailbox

To enter a voice mailbox number:

Press ***MENU*** and navigate to *<Phone menu...> Enter <Phone settings...> Enter <Call options...> Enter <Voice mail number> Enter <Enter the number> Enter*

Or

Press and hold ***KEYPAD*** number 1 to go to *<Voice mail number>*. Enter the number and press ***ENTER***.

Use the stored number by pressing 1 for several seconds.

To change the voice mail number go to *Voice mail number*. Press and hold ***BACK*** to erase the whole number or press and release to erase individual numbers. Once the number has been erased then enter a new number.

*If the mobile phone has the voice mail number already stored then this will be placed into the system when synchronising during pairing.*

## Last Ten Numbers

### Last Ten Dialled Numbers

Press ***ENTER***. Use the ***JOYSTICK*** (up or down), ***SCROLL*** button, or turn the ***TUNING*** dial to navigate to the required number. Press ***CALL*** or ***ENTER*** to call that number.

### Last Ten Missed and Received Numbers

Press ***MENU*** and navigate to *<Phone menu...> Enter <Last 10 missed calls>* or *<Last 10 received calls> Enter*.

Use the ***JOYSTICK*** (up or down), ***SCROLL*** button, or turn the ***TUNING*** dial to navigate to the required number. Press ***CALL*** or ***ENTER*** to call that number.

*Last ten dialled will also be available.*

## Hands-Free Menu

**1) Phone Menu...**
1) Last 10 missed calls
2) Last 10 received calls
3) Last 10 dialled calls
4) Phone book...
  1) Search
  2) Copy fr. mobile phone
5) Bluetooth...
  1) Change Phone...
  2) Remove Phone
  3) Connect from mobile phone
6) Phone settings...
  1) Call options...
    1) Automatic answer
    2) Voice mail number
  2) Sounds and volume...
    1) Ring volume
    2) Ring signals...
    3) Mute Radio
  3) Synchronising phone book

ASTON MARTIN
ASTON MARTIN

# Satellite Navigation


Introduction ..... 9.2
Important Safety and Product Information ..... 9.3
Map Data Information ..... 9.3
Navigation System Controls ..... 9.4
Find a Location ..... 9.7
Navigation Map ..... 9.10
Traffic ..... 9.12
Tools ..... 9.14
Customising the Navigation System ..... 9.15
Information ..... 9.17
Safety Cameras ..... 9.17
Contact Information ..... 9.17
Software License Agreement ..... 9.18
NAVTEQ® End User License Agreement ..... 9.18




# Introduction

© 2010 Garmin Ltd. or its subsidiaries

All rights reserved. Except as expressly provided herein, no part of this chapter may be reproduced, copied, transmitted, disseminated, downloaded or stored in any storage medium, for any purpose without the express prior written consent of Garmin. Garmin hereby grants permission to download a single copy of this chapter onto a hard drive or other electronic storage medium to be viewed and to print one copy of this manual or of any revision hereto, provided that such electronic or printed copy of this chapter must contain the complete text of this copyright notice and provided further that any unauthorised commercial distribution of this chapter or any revision hereto is strictly prohibited.

Information in this chapter is subject to change without notice. Garmin reserves the right to change or improve its products and to make changes in the content without obligation to notify any person or organisation of such changes or improvements. Go to the Garmin Web site (www.garmin.com) for current updates and supplemental information concerning the use and operation of this and other Garmin products.

Garmin® and the Garmin logo are trademarks of Garmin Ltd. or its subsidiaries, registered in the USA and other countries. nüMaps™ is a trademark of Garmin Ltd. or its subsidiaries. This trademark may not be used without the express permission of Garmin. microSD™ is a trademark of SD-3C, LLC. NAVTEQ is a trademark in the U.S. and other countries.

## Important Safety and Product Information

***⚠ Warning: Failure to avoid the following potentially hazardous situations could result in an accident or collision resulting in death or serious injury.***

***⚠ Warning: Always use your best judgement, and operate the vehicle in a safe manner. Do not become distracted by the navigation system while driving, and always be fully aware of all driving conditions. Minimise the amount of time spent viewing the screen while driving and use voice prompts when possible.***

***⚠ Warning: Do not input destinations, change settings, or access any functions requiring prolonged use of the navigation system controls while driving. Bring the vehicle to a halt in a safe and legal manner before attempting such operations.***

***⚠ Warning: When navigating, carefully compare information shown on the screen to all available navigation sources, including road signs, road closures, road conditions, traffic congestion, weather conditions, and other factors that may affect safety while driving. For safety, always resolve any discrepancies before continuing navigation, and defer to posted road signs and road conditions.***


***⚠ Warning: The navigation software is designed to provide route suggestions. It is not a replacement for driver attentiveness and good judgement. Do not follow route suggestions if they suggest an unsafe or illegal manoeuvre or would place the vehicle in an unsafe situation.***

## Map Data Information

Garmin uses a combination of governmental and private data sources. Virtually all data sources contain some inaccurate or incomplete data. In some countries, complete and accurate map information is either not available or is prohibitively expensive.

# Navigation System Controls



***[1] SCREEN:*** Shows maps and provides detailed information on route type, distance, etc.

***[2] BACK:*** Press to return to the previous menu or to undo a choice.

***[3] NAV:*** Press to enable or disable satellite navigation controls.

***[4] JOYSTICK:*** Navigate through different menu options, traffic messages, etc.

***[5] ENTER:*** Press to confirm, select or navigate from one submenu to the next submenu.


***[6] MAP ZOOM:*** Press the rocker switch up or down to zoom the map in or out.




## How to Set the Navigation System ON and OFF

*The screen shots shown in this manual may not exactly match the screens on your navigation system. The images used are intended for reference only.*

1. Set the vehicle key to ignition position I or II.
2. Press ***NAV*** (LED ON) on the centre stack. The Infotainment screen opens and the disclaimer is shown. Press ***ENTER*** to agree.




While the ***NAV*** button LED is ON the ***BACK***, ***ENTER*** and ***JOYSTICK*** functions only operate the navigation system. To use these functions for Audio or Hands-Free phone functions either:

- Press the ***NAV*** button again (button LED OFF).
- Press any audio button other than ***BACK***, ***ENTER*** and ***JOYSTICK***.

Press ***NAV*** (button LED ON) again to return to navigation controls.

*Pressing the **AM**/**FM** or **MODE** buttons will move the current audio source.*

*The navigation system can be accessed if the ignition is set to OFF. Always set the vehicle key to position 0 in the ignition control, and remove the vehicle key when the system is not in use to prevent the battery from discharging.*

### Navigation System OFF

At any time press and hold the ***NAV*** button until the system screen starts to close.

## Menu Navigation




***[1] :*** Find a destination (Refer to 'Find a Location', page 9.7)
***[2] :*** View the map (Refer to 'Location Map', page 9.7).
***[3] :*** System settings (Refer to 'System Settings', page 9.15).
***[4] :*** System tools (Refer to 'Tools', page 9.14)

## On-Screen Buttons

Select and hold ◀ to quickly return to the navigation menu.

Select ▼ or ▲ to scroll the screen.

## On-Screen Keyboard




***[1]*** ◀ ***or*** ▶***:*** Move the cursor.

***[2]*** ⌫***:*** Delete a character.

***[3]*** ␣***:*** Add a space.

***[4] 123:*** Enter numbers and special characters, such as punctuation marks.


***[5] MODE:*** Select the keyboard language.

# Find a Location

The Where To? menu provides several different categories you can use to search for locations.

## Points of Interest

The detailed maps loaded in the navigation system contain millions of points of interest, such as restaurants, hotels, and transportation.




### Point of Interest by Category

From the navigation menu, select *<Where To?> Enter < Points of Interest>*. Select a category.

If necessary, select a subcategory. Select an item.

### Point of Interest by Spelling the Name


*Narrow the search results by selecting a category prior to selecting Spell Name.*

From the navigation menu, select *<Where To?> Enter <Points of Interest> Enter < Spell Name>*.

Enter all or part of the name, and select *<Done>*.

Select an item.

### Location Map




After a destination is selected, the location shows on the map.

***[1] :*** Save this location to Favourites.

***[2] :*** View more information for the location.

***[3] :*** Explore the map.

***[4] :*** Return to the previous screen.

***[5] :*** Create a route to this location.

**Map Zoom**

To zoom in or out, select the up or down on the ***MAP ZOOM*** rocker switch mounted on the steering column.

**Start a Route to a Location**

Select a location. Select *<Go!>*.

**Set a Home Location**

Set your home location for the place you return to most often.

From the navigation menu, select *<Tools> Enter < My Data> Enter < Set Home Location>*.

Select *<Enter Your Address>, <Use Your Current Location>*, or *<Choose from Recently Found Locations>*.

**Go Home**

From the navigation menu, select *<Where To?> Enter <Go Home>*.

**Edit Home Location**

From the navigation menu, select *<Where To?> Enter < Favourites> Enter < Home>*.

Select *<Press for More> Enter <Edit>*. Select an option.

**Find an Address**

*Depending on the version of the maps loaded in your navigation system, the button names and the order of steps could be different from the steps below.*

From the navigation menu, select *<Where To?> Enter <Address>*.

If necessary, change the state, country, or province.

To enter a city name or postal code, select *<Spell City>*, enter the name or code, and select *<Done>*.

To search all cities, select *<Search All>*.

*Not all map data provides postal code searching.*

Enter the address number, and select *<Done>*.

Enter the street name, and select *<Done>*.

If necessary, select the street and or the address (Refer to 'Location Map', page 9.7).

**Location by Browsing the Map**

From the navigation menu, select *<Where To?> Enter < Browse Map>*(Refer to 'Location Map', page 9.7).

**Review Recently Found Places**

The navigation system stores the last 50 locations.

From the navigation menu, select *<Where To?> Enter <Recently Found>*.

**Clear the List of Recently Found Locations**

From the navigation menu, select *<Where To?> Enter < Recently Found> Enter <Clear> Enter < Yes>*.

All items in the list are removed, but this does not delete the actual location from your navigation system.

**Find an Aston Martin Dealership**

From the navigation menu, select *<Where To?> Enter <Dealerships>*. Select a dealer.

**Enter Coordinates**

If you know the geographic coordinates of your destination, you can use the navigation system to navigate to your destination using the latitude and longitude coordinates.

From the navigation menu, select *<Where To?> Enter <Coordinates>*.

Enter the coordinates, and select *<Done>*. Select *<Next>*.

**Change the Map Coordinate Format**

From the navigation menu, select *<Where To?> Enter <Coordinates> Enter <Format>*. Select a format.

**Location Using a Phone Number**

From the navigation menu, select *<Where To?> Enter <Phone Numbers>*.

Enter a phone number, and select *<Done>*. If an exact match is found for the phone number, the location is shown.

📖 *Searching by phone numbers is not available in all regions and on all maps.*

**Location in a Different Area**

From the navigation menu, select *<Where To?> Enter <Near>*.

Select *<Where I Am Now>, <A Different City>, <A Recent Destination>, <A Favourite Destination>, <My Current Route>*, or *<My Destination>*. Select <OK>.

**Find a Different City**

The navigation system lists all cities within a 20 mile radius of your current location.

From the navigation menu, select *<Where To> Enter <Cities>*.

Select an option:

- Select a city from the list of nearby cities that show
- Select *<Spell>* to enter the name of a city that does not appear on the list. Select an option.

📖 *The navigation system will navigate you to the centre of the selected city.*

**Favourites**

You can save places in your Favourites so you can quickly find them and navigate to them. Your home location is also stored in Favourites.

**Save Current Location**

From the main menu, select *<Tools> Enter <Where Am I?>*. Select *<Save Location>*.

**Save Found Places**

After searching for and finding a destination, you can save it as a Favourite. From the location map, select *<Save> Enter <OK>*.

**Find Favourites**

From the navigation menu, select *<Where To?> Enter <Favourites>*.

**Edit Favourites**

From the navigation menu, select *<Where To?> Enter <Favourites>*.

Select the location.

Select *<Edit>*.

Select an item to edit:

***<Change Name>:*** Enter a new name.

***<Change Map Symbol>:*** Select a new symbol used to mark this location on the map.

***<Change Phone Number>:*** Enter a different phone number.

***<Change Categories>:*** Select another category for the location.

**Delete Favourites**

From the main menu, select *<Tools> Enter <My Data> Enter <Delete Favourite(s)>*.

Select a Favourite. Select *<Delete> Enter <Yes>*.


# Navigation Map

## Map Features

***The speed limit icon feature is for information only and does not replace the driver's responsibility to abide by all posted speed limit signs and to use safe driving judgment at all times.***

***Garmin will not be responsible for any traffic fines or citations that you may receive for failing to follow all applicable traffic laws and signs.***

The route is marked with a magenta line. A checkered flag marks the destination. As you travel, the navigation system guides you to the destination with voice prompts, arrows on the map, and directions at the top of the map. If you depart from the original route, the system recalculates the route and provides new directions. A current speed icon may show as you travel on major roadways.




***[1] :*** Show the next turn, or upcoming junction, when available (Refer to 'Viewing the Turn List', page 9.11).

***[2] :*** Show the turn list.

***[3] :*** Change the data display.

***[4] :*** Show information about the trip.

## Viewing Trip Information

The navigation system shows the current speed and provides statistics about your trip.

To view trip information from the map, select the *Speed* field. If you make frequent stops, leave the navigation system ON so it can accurately measure elapsed time during the trip.

### Resetting Trip Information

From the trip information page, select <*Reset*>.

Select an option:


***<Reset Trip Data>:*** Reset the trip information.

***<Reset Max. Speed>:*** Reset the maximum speed.

Select <*OK*>.

## Viewing the Turn List

When navigating a route, you can view all of the turns for the whole route and the distance between turns.





From the map, select the text bar on the top of the map.

Select an option:

- Select a turn on the list to view information about the turn.
- To view the entire route on the map, select <*Show Map*>.

## Viewing the Next Turn


Before you can view the next turn in a route, you must be navigating a route.




From the map, select the next turn icon. The next turn screen is shown on the map, along with the distance and time left before you reach the turn.

## Junction View

When available, the navigation system may show a view of the upcoming junction and in which lane you should be driving will show. This feature is not available for all junctions.




Before you can view the junction, you must be navigating a route.

From the map, select the next turn icon. You can also view junctions from the turn list.

## Make Changes to the Current Route

Add stops, remove points, or change your destination while on route.

**Add One Point to Current Route**

From the navigation menu select <*Where To?*>. Search for and select the extra stop.

Select <*Go!*>. Select <*Add as a Via Point*> to add this stop before your destination.

**Add or Remove Multiple Points to the Current Route**

From the navigation menu, select <*Tools*> *Enter* <*Routes*>.

Select <*Active Route*> *Enter* <*Add or Remove Points*>.

Select the point or points to add or remove:

**<+>:** Add a point.

**<->:** Remove a point.

Select <*Yes*>.

**Changing the Destination of a Route**

While navigating a route, select to return to the navigation menu.

Select <*Where To?*>. Search for the location.

Select <*Go!*>. Select <*Start New Route*>.

## Detour

When navigating a route, you can use detours to avoid obstacles ahead of you, such as construction zones.

While navigating a route, select to return to the navigation menu. Select <*Detour*>.

If the current route is the only reasonable option, the navigation system might not calculate a detour.

## Stopping the Route

While navigating a route, select to return to the navigation menu. Select <*Stop*>.

# Traffic

Garmin is not responsible for the accuracy or timeliness of the traffic information.

Your navigation system can receive FM Traffic Message Channel (TMC) traffic content, which provides information on nearby traffic incidents and construction. The subscription is automatically enabled and does not require an additional subscription purchase. Traffic information is not available in all areas.

## Traffic Information

When you are within a traffic coverage area, your device will show traffic information. The navigation system must be in data range of an FM station transmitting traffic information.

## Traffic Icon

When traffic information is being received, a traffic icon appears on the map. The traffic icon changes colour to show the severity of traffic conditions.

| Colour | Severity | Meaning |
|---|---|---|
| Green | Low | Traffic is flowing freely |
| Yellow | Medium | Traffic is moving but there is a delay. There is moderate traffic congestion |
| Red | High | Traffic is not moving or moving very slowly. There is a severe delay |

## Traffic on Route

When calculating a route, the navigation system examines the current traffic and automatically optimises the route for the shortest time. If a severe traffic delay occurs on route while you are navigating, the device automatically recalculates the route.

You might still be routed through traffic if no better alternative routes exist.

### Manually Avoiding Traffic on Your Route

From the map, select .

Select <*Traffic On Route*>. If necessary, use the arrows to view other traffic delays on your route. Select <*Avoid*>.

## View the Traffic Map

The traffic map shows colour-coded traffic flow and delays on nearby roads.

From the map, select .

Select <*Traffic Map*> to view the traffic incidents on a map.

## Search for Traffic Delays

From the map, select .

Select <*Traffic Search*> to view a list of roads with traffic delays.

Select an item in the list to view delays on the road. If there is more than one delay, use the arrows to view additional delays.

# Tools

The Tools menu provides many features that are helpful when you are travelling.

## View Current Location Information

Use the Where Am I? page to view information about your current location. This feature is helpful if you need to tell emergency personnel your location.




From the navigation menu, select <*Tools*> *Enter* <*Where Am I?*>.

### Find Nearby Services

From the navigation menu, select <*Tools*> *Enter* <*Where Am I?*>.

Select <*Hospitals*>, <*Police Stations*>, <*Lodging*>, or <*Fuel*> to view the nearest locations in that category.

## Use Help

From the navigation menu, select <*Tools*> *Enter* <*Help to get information about using your navigation system*>.

### Search Help Topics

From the navigation menu, select <*Tools*> *Enter* <*Help*> *Enter* <*Search*>.

## Clear the Trip Log

From the navigation menu, select <*Tools*> *Enter* <*My Data*>.

Select <*Clear Trip Log*>.

## Routes

Up to 10 routes can be saved.

### Create and Save a Route

From the navigation menu, select <*Tools*> *Enter* <*Routes*> *Enter* <*New*>.

Find a location (Refer to 'Find a Location', page 9.7)as your starting point, and select <*Select*>. Find a location for your ending point, and select <*Select*>.

If necessary, find and select additional locations to add them as stops along the route. The navigation system calculates and saves the route.

### Navigate a Saved Route

From the navigation menu, select <*Tools*> *Enter* <*Routes*>.

Select a saved route. Select <*Go!*>.

Refer to Location Map (Refer to 'Location Map', page 9.7)for more information.

### Edit a Saved Route

From the navigation menu, select <*Tools*> *Enter* <*Routes*>.

Select a saved route. Select <*Edit*>.

Select an item to edit:

***<Change Name>:*** Enter a new name.

***<Add or Remove Points>:*** Add or remove points from the route, change the order of points along the route, and automatically order the points.

***<Manually Reorder Points>:*** Change the route order of the points.

***<Optimally Reorder Points>:*** To edit the route using the map.

***<Recalculate>:*** Recalculate the route.

***<Delete>:*** Remove this route.

Changes are automatically saved when you exit any of the route edit pages.

**Delete a Route**

Select *<Tools> Enter <My Data> Enter <Delete Selected Route(s)>*.

Select a route(s) to delete. Select *<Delete>*.

## World Clock

From the navigation menu, select *<Tools> Enter <World Clock>*.


Select a city name. Enter a new city name. Select *<Done>*.

If necessary, select a city option.

## Calculator

From the navigation menu, select *<Tools> Enter <Calculator>*.

1. From the navigation menu, select *<Settings>*.
2. Select the setting you want to change.




## System Settings

From the navigation menu, select *<Settings> Enter <System>*.

***GPS Simulator:*** Sets on the simulator to set the GPS mode to OFF and simulate navigation.

***Units:*** Change the units of measure for distance.

***Keyboard Layout:*** Selects QWERTY for a layout similar to a computer keyboard, or selects ABCDE for an alphabetical layout.

***About:*** Shows the navigation system software version number, the unit ID number, and information on other software features.

***Restore:*** Restores the system settings to factory default.

## Navigation Settings

From the navigation menu, select *<Settings> Enter <Navigation>*.

***Route Preference:*** Change the preference for calculating a route.

***Avoidances:*** Change the road types to avoid.

***Voice Prompts:*** Receive voice prompt directions.

***Restore:*** Restores the original navigation settings.

## Map Settings

From the navigation menu, select *<Settings> Enter <Map>*.

***Map Detail:*** Adjust the amount of detail shown on the map. More detail can result in a slower map redraw rate in some areas or at wider zoom levels.

***Map View:*** Change the map perspective.

- **Track Up:** Shows the map in two dimensions (2-D) with the direction of travel at the top.
- **North Up:** Shows the map in 2-D with north at the top.
- **3-D:** Shows the map in three dimensions (3-D) with the direction of travel at the top.

***Vehicle:*** Change the icon used to show your position on the map

***Trip Log:*** Show or hide the log of your travels.

***Map Data Layout:*** Change the amount of data visible on the map.

***Info:*** Shows the maps and the version of each map loaded on the navigation system. Select a map to enable (check mark) or disable (no check mark) that map.

***Restore:*** Restore the original map settings.

### Changing the Vehicle Icon

Select *<Settings> Enter <Map> Enter <Vehicle> Enter <Change>*.

Select the icon you want to use, and select *<Done>*.

### Clearing the Trip Log

From the navigation menu, select *<Tools> Enter <My Data> Enter <Clear Trip Log>*.

## Display Settings

From the navigation menu, select *<Settings> Enter <Display>*.

***Colour Mode:*** Set a light background (Day), a dark background (Night), or automatically switches between the two based on the sunrise time and the sunset time for your current location (Auto).

## Language Settings

From the navigation menu, select *<Settings> Enter <Language>*.

***Voice:*** Set the language for voice prompts.

***Text:*** Set all on-screen text to the selected language.

***Keyboard:*** Set the language for the keyboard.

***Restore:*** Restore the original language settings.

## Proximity Points Alerts Settings

From the navigation menu, select *<Settings> Enter <Proximity Points> Enter <Change> Enter <Audio>*.

***Proximity Alerts:*** Set the alerts ON or OFF when you approach safety cameras.

***Restore:*** Restore the original proximity points settings.

## Security Settings

From the navigation menu, select *<Settings> Enter <Security>*.

***Safe Mode:*** Set Safe Mode ON or OFF.

***Restore:*** Restore the original security settings.

## Information

When the navigation system has acquired satellite signals, the signal strength bars on the navigation menu are white  . The more white bars, the stronger the GPS signal.

If the navigation system is not receiving GPS signals, the bars will show red  .

For more information about GPS, go to www.garmin.com/aboutGPS.

### View Detailed GPS Signal Information

From the navigation menu, select *<Tools> Enter <Satellite Status>*.

## Safety Cameras

***Aston Martin and Garmin are not responsible for the accuracy of, or the consequences of using, a custom Points Of Interest (POI) or safety camera database.***

Safety camera information is available in some areas. For these areas, the navigation system includes the locations of hundreds of safety cameras. Your navigation system alerts you when you are approaching a safety camera and can warn you if you are driving too fast.

## Contact Information

Contact your Aston Martin dealership if you have questions while using your navigation system (Refer to 'Find an Aston Martin Dealership', page 9.8).

## Software License Agreement

BY USING THE ASTON MARTIN LAGONDA NAVIGATION SYSTEM, YOU AGREE TO BE BOUND BY THE TERMS AND CONDITIONS OF THE FOLLOWING SOFTWARE LICENSE AGREEMENT. PLEASE READ THIS AGREEMENT CAREFULLY.

Garmin grants you a limited license to use the software embedded in this device (the 'Software') in binary executable form in the normal operation of the product. Title, ownership rights, and intellectual property rights in and to the Software remain in Garmin. You acknowledge that the Software is the property of Garmin and is protected under the United States of America copyright laws and international copyright treaties. You further acknowledge that the structure, organization, and code of the Software are valuable trade secrets of Garmin and that the Software in source code form remains a valuable trade secret of Garmin. You agree not to decompile, disassemble, modify, reverse assemble, reverse engineer, or reduce to human readable form the Software or any part thereof or create any derivative works based on the Software. You agree not to export or re-export the Software to any country in violation of the export control laws of the United States of America.

## NAVTEQ® End User License Agreement

The software embedded in your Garmin product (the 'Software') is owned by Garmin Ltd. or its subsidiaries ('Garmin'). The third-party map data embedded in or accompanying your Garmin product (the 'Map Data') is owned by NAVTEQ North America LLC and/or its affiliates and is licensed to Garmin. Garmin also licenses information, text, images, graphics, photographs, audio, video, images and other applications and data from third party data providers ('Third Party Content Data').

The Map Data and Third Party Content Data are collectively the 'Data'. Both the Software and Data are protected under copyright laws and international copyright treaties. The Software and Data are licensed, not sold. The Software and Data are provided under the following license and are subject to the following terms and conditions which are agreed to by End User ('you' or 'your'), on the one hand, and Garmin and its licensors (including their licensors and suppliers) and affiliated companies on the other hand.

IMPORTANT: CAREFULLY READ THIS LICENSE BEFORE USING THIS PRODUCT. INSTALLING, COPYING, OR OTHERWISE USING THIS PRODUCT INDICATES YOUR ACKNOWLEDGMENT THAT YOU HAVE READ THIS LICENSE AND AGREE TO ITS TERMS. IF YOU DO NOT AGREE, RETURN THE COMPLETE PRODUCT WITHIN 7 DAYS OF THE DATE YOU ACQUIRED IT (IF PURCHASED NEW) FOR A FULL REFUND TO THE DEALER FROM WHICH YOU PURCHASED THIS PRODUCT.

### License Terms and Conditions

Garmin ('we' or 'us') provides you with storage media containing the computer Software (the 'Software') and the embedded or accompanying Data, including any 'online' or electronic documentation and printed materials (together called the 'Product' for purposes of this License Agreement), and grants you a limited, non-exclusive license to use the Product in accordance with the terms of this Agreement.

You agree to use this Data together with the Garmin product for solely personal, or if applicable, for use in your business' internal operations, and not for service bureau, time-sharing, resale or other similar purposes. Accordingly, but subject to the restrictions set forth in the following paragraphs, you may copy this Data only as necessary for your use to (I) view it, and (ii) save it, provided that you do not remove any copyright notices that appear and do not modify the Software or Data in any way.

You agree not to otherwise reproduce, copy, modify, decompile, disassemble, reverse engineer or create derivative works of any portion of the Product, and may not transfer or distribute it in any form, for any purpose, except to the extent permitted by mandatory laws. Garmin also reserves the right to discontinue offering any Data supplied by any third party supplier if such supplier ceases to supply such content or Garmin's contract with such supplier terminates for any reason.

**Restrictions**

Except where you have been specifically licensed to do so by Garmin, and without limiting the preceding paragraph, you may not use this Data with any products, systems, or applications installed or otherwise connected to or in communication with vehicles, and which are capable of dispatch, fleet management or similar applications where the Data is used by a central control centre in dispatching a fleet of vehicles. In addition, you are prohibited from renting or leasing the Data or the Garmin products containing the Data to any other person or third party. Only those rental car companies that are specifically authorised by Garmin in writing to rent Garmin products containing the Data to their rental customers are permitted to rent out such products.

**No Warranty**

This Product (including the Data) is provided to you 'as is,' and you agree to use it at your own risk. Garmin and its licensors (and their licensors and suppliers) make no guarantees, representations or warranties of any kind, express or implied, arising by law or otherwise, including but not limited to, content, quality, accuracy, completeness, effectiveness, reliability, merchantability, fitness for a particular purpose, usefulness, use or results to be obtained from the Product, or that the Data or server will be uninterrupted or error-free.

**Disclaimer of Warranty**

GARMIN AND ITS LICENSORS (INCLUDING THEIR LICENSORS AND SUPPLIERS) DISCLAIM ANY WARRANTIES, EXPRESS OR IMPLIED, OF QUALITY, PERFORMANCE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. NO ORAL OR WRITTEN ADVICE OR INFORMATION PROVIDED BY GARMIN OR ITS SUPPLIERS AND LICENSORS SHALL CREATE A WARRANTY, AND YOU ARE NOT ENTITLED TO RELY ON ANY SUCH ADVICE OR INFORMATION. THIS DISCLAIMER OF WARRANTIES IS AN ESSENTIAL CONDITION OF THIS AGREEMENT. Some States, Territories and Countries do not allow certain warranty exclusions, so to that extent the above exclusion may not apply to you.

**Disclaimer of Liability**

GARMIN AND ITS LICENSORS (INCLUDING THEIR LICENSORS AND SUPPLIERS) SHALL NOT BE LIABLE TO YOU: IN RESPECT OF ANY CLAIM, DEMAND OR ACTION, IRRESPECTIVE OF THE NATURE OF THE CAUSE OF THE CLAIM, DEMAND OR ACTION ALLEGING ANY LOSS, INJURY OR DAMAGES, DIRECT OR INDIRECT, WHICH MAY RESULT FROM THE USE OR POSSESSION OF THE INFORMATION; OR FOR ANY LOSS OF PROFIT, REVENUE, CONTRACTS OR SAVINGS, OR ANY OTHER DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF YOUR USE OF OR INABILITY TO USE THIS INFORMATION, ANY DEFECT IN THE DATA OR INFORMATION, OR THE BREACH OF THESE TERMS OR CONDITIONS, WHETHER IN AN ACTION IN CONTRACT OR TORT OR BASED ON A WARRANTY, EVEN IF GARMIN OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

GARMIN'S AND ITS LICENSORS' TOTAL AGGREGATE LIABILITY WITH RESPECT TO ITS OBLIGATIONS UNDER THIS AGREEMENT OR OTHERWISE WITH RESPECT TO THE GARMIN PRODUCT OR THE DATA SHALL NOT EXCEED $1.00.

Some States, Territories and Countries do not allow certain liability exclusions or damages limitations, so to that extent the above may not apply to you.

**Disclaimer of Endorsement**

Reference to any products, services, processes, hypertext links to third parties or other Data by trade name, trademark, manufacturer, supplier or otherwise does not necessarily constitute or imply its endorsement, sponsorship or recommendation by Garmin or its licensors. Product and service information are the sole responsibility of each individual vendor. The NAVTEQ name and logo, the NAVTEQ and NAVTEQ ON BOARD trademarks and logos, and other trademarks and trade names owned by NAVTEQ North America LLC may not be used in any commercial manner without the prior written consent of NAVTEQ.

**Export Control**

You agree not to export from anywhere any part of the Data provided to you or any direct product thereof except in compliance with, and with all licenses and approvals required under, applicable export laws, rules and regulations.

**Indemnity**

You agree to indemnify, defend and hold Garmin and its licensors (including their respective licensors, suppliers, assignees, subsidiaries, affiliated companies, and the respective officers, directors, employees, shareholders, agents and representatives of each of them) free and harmless from and against any liability, loss, injury (including injuries resulting in death), demand, action, cost, expense, or claim of any kind or character, including but not limited to attorney's fees, arising out of or in connection with any use or possession by you of the Product (including the Data).

**Canadian Map Data**

The Map Data for Canada may include or reflect data of licensors, including Her Majesty and Canada Post. Such data is licensed on an 'as is' basis. The licensors, including Her Majesty and Canada Post, make no guarantees, representations or warranties respecting such data, either express or implied, arising by law or otherwise, including but not limited to, effectiveness, completeness, accuracy or fitness for a particular purpose.

The licensors, including Her Majesty and Canada Post, shall not be liable in respect of any claim, demand or action, irrespective of the nature of the cause of the claim, demand or action alleging any loss, injury or damages, direct or indirect, which may result from the use or possession of the data or the Map Data.

The licensors, including Her Majesty and Canada Post, shall not be liable in any way for loss of revenues or contracts, or any other consequential loss of any kind resulting from any defect in the data or the Map Data.

You shall indemnify and save harmless the licensors, including Her Majesty the Queen, the Minister of Natural Resources of Canada and Canada Post, and their officers, employees and agents from and against any claim, demand or action, irrespective of the nature of the cause of the claim, demand or action, alleging loss, costs, expenses, damages or injuries (including injuries resulting in death) arising out of the use or possession of the data or the Map Data.

**Term**

This Agreement is effective until such time as (I) if applicable, your subscription term is either terminated (by you or by Garmin) or expires, or (ii) Garmin terminates this Agreement for any reason, including, but not limited to, if Garmin finds that you have violated any of the terms of this Agreement. In addition, this Agreement shall terminate immediately upon the termination of an agreement between Garmin and any third party from whom Garmin licenses the Data.

**Entire Agreement**

These terms and conditions constitute the entire agreement between Garmin (and its licensors, including their licensors and suppliers) and you pertaining to the subject matter hereof, and supersedes in their entirety any and all written or oral agreements previously existing between us with respect to such subject matter.

**Governing Law**

**(a) For European Union NAVTEQ Data**

The above terms and conditions shall be governed by the laws of the Netherlands, without giving effect to (I) its conflict of laws provisions, or (ii) the United Nations Convention for Contracts for the International Sale of Goods, which is explicitly excluded. You agree to submit to the jurisdiction of the Netherlands for any and all disputes, claims and actions arising from or in connection with the NAVTEQ Data provided to you hereunder.

**(b) For North American NAVTEQ Data and other non-European Union NAVTEQ Data**

The above terms and conditions shall be governed by the laws of Illinois, without giving effect to (I) its conflict of laws provisions, or (ii) the United Nations Convention for Contracts for the International Sale of Goods, which is explicitly excluded. You agree to submit to the jurisdiction of Illinois for any and all disputes, claims and actions arising from or in connection with the NAVTEQ Data provided to you hereunder.

**(c) For disputes, claims and actions not related to the NAVTEQ Data**

The above terms and conditions shall be governed by the laws of Kansas, without giving effect to (I) its conflict of laws provisions, or (ii) the United Nations Convention for Contracts for the International Sale of Goods, which is explicitly excluded. You agree to submit to the jurisdiction of Kansas for any and all disputes, claims and actions arising from or in connection with the Data provided to you hereunder.

**Government End Users**

If End User is an agency, department, or other entity of the United States Government, or funded in whole or in part by the U.S. Government, then use, duplication, reproduction, release, modification, disclosure or transfer of the Product and accompanying documentation is subject to restrictions as set forth in

DFARS 252.227-7014(a)(1) (JUN 1995) (DOD commercial computer software definition),

DFARS 27.7202-1 (DOD policy on commercial computer software),

FAR 52.227-19 (JUN 1987) (commercial computer software clause for civilian agencies),

DFARS 252.227-7015 (NOV 1995) (DOD technical data – commercial items clause);

FAR 52.227-14 Alternates I, II, and III (JUN 1987) (civilian agency technical data and noncommercial computer software clause);

and/or FAR 12.211 and FAR 12.212 (commercial item acquisitions), as applicable. In case of conflict between any of the FAR and DFARS provisions listed herein and this License, the construction that provides greater limitations on the Government's rights shall control.

# Maintenance


Introduction ..... 10.2
Vehicle Jacking ..... 10.3
Servicing Precautions ..... 10.3
Dangerous Substances ..... 10.4
Emergency Items ..... 10.4
Owner Maintenance ..... 10.5
Bonnet Release ..... 10.6
Fluid Levels ..... 10.7
Windscreen Blade Replacement ..... 10.10
Brake Pad Bedding-in ..... 10.11
Clutch Bedding-in ..... 10.11
Tyres ..... 10.11
Tyre Sealant Kit ..... 10.13
Vehicle Recovery ..... 10.15
Vehicle Battery ..... 10.17
Vehicle Battery Charge ..... 10.18
Battery Protection Mode ..... 10.20
Fuse Boxes ..... 10.21
Headlamp ..... 10.25
Other External Lamps ..... 10.26
Boot Lamps ..... 10.27
Internal Lamps ..... 10.27
Door Window Reset ..... 10.28
Front Seat Reset ..... 10.28
Bodywork Maintenance ..... 10.29
Vehicle Cleaning ..... 10.29
Vehicle Storage ..... 10.33

Each item in the service schedules must be performed on time as failure to do so may void the new vehicle warranty or other warranties. It is the owner's responsibility to see that the vehicle is maintained correctly and in accordance with the manufacturer's service schedules.

Due to the sophistication of the various systems and the specialised equipment required to maintain this vehicle, owner maintenance should be restricted to the routine procedures described in this owner's guide.

If you think that this vehicle is not functioning correctly, please return it to an Aston Martin Dealer to be checked professionally.

## Restraint Systems

Aston Martin recommend that the inflatable (airbags) restraint systems and seat belt components installed to this vehicle are replaced at 10 year intervals from the date of manufacture on the certification label.

## Electronic Fuel Injection

***⚠ Warning: If the fuel system is allowed to run dry irreparable damage to the fuel pumps may occur.***

***⚠ Warning: Any modifications or additions to the fuel system not specifically designed by Aston Martin are prohibited. If carried out, they may cause damage to the fuel system which in some circumstances could result in fire. All Service Action Campaigns must be undertaken by an Aston Martin Dealer.***

The electronic fuel injection system requires special equipment and test facilities to set up and maintain so that the vehicle gives maximum performance coupled with economy, reliability and safe vehicle emissions. You are, therefore, strongly advised to entrust all service work to an Aston Martin Dealer.

## Parts and Lubricants

When undertaking a servicing task only parts, materials, lubricants, etc. that are specifically recommended by Aston Martin should be used. Failure to do so can result in damage to your vehicle and may invalidate your new vehicle warranty or other warranties (Refer to 'Aston Martin Warranty', page B.1).

***! Your vehicle's warranty may be invalidated if damage is caused by the use of incorrect engine oil. Low quality or obsolete oils do NOT provide the protection required by modern, high performance engines. Failure to use engine oil that meets the required specification could cause excessive engine wear, a build up of sludge and deposits, and increased pollution. It could also lead to engine failure.***


## Vehicle Jacking

***⚠ Warning: Make sure that no persons are in the vehicle before jacking commences.***

***⚠ Warning: Make sure that the vehicle is parked on firm and level ground to give a secure base for the jack.***

***! Do not raise the vehicle by placing a vehicle jack under the suspension arms.***

If this vehicle is to be raised using a vehicle jack make sure that the following jacking points are used.



## Servicing Precautions

To avoid personal injury, the following safety precautions must be observed when the bonnet is open and the engine is operating or the ignition is ON.

***⚠ Warning: Protect yourself against dangerous substances (Refer to 'Dangerous Substances', page 10.4).***

***⚠ Warning: Keep hands, hair, tools, items of clothing and jewellery clear of all drive belts, pulleys and operating mechanisms. The cooling fans may operate even though the engine is not operating.***

***⚠ Warning: Avoid skin contact with all exhaust system and engine components, engine fluids and escaping steam. They may be hot and will burn you.***

***⚠ Warning: Do not breathe exhaust fumes. Exhaust fumes contain carbon monoxide. Carbon monoxide is a dangerous gas, which is colourless and odourless and can cause unconsciousness and may be fatal. Never start or leave the engine running in an enclosed, unventilated area.***

***⚠ Warning: Do not work beneath the vehicle with a vehicle lifting jack as the only support. Place suitable stands under the vehicle.***

***⚠ Warning: Keep children and pets clear of the vehicle. Do not let anyone inside the vehicle unless specifically working to your instructions.***

***⚠ Warning: Whenever possible work in the engine compartment with the engine cool, the ignition OFF and the vehicle battery disconnected.***

***⚠ Warning: Petrol is highly flammable and, in confined spaces, is also explosive and toxic. In the event of spillage, set the engine to OFF, use no naked flame or light. Do not smoke. Do not inhale fumes.***

## Dangerous Substances

***⚠ Warning: Dangerous substances should be kept out of reach of children.***

***⚠ Warning: Many liquids and other substances used in motor vehicles are poisonous and should under no circumstances be consumed and should, so far as possible, be kept from contact with the skin. These substances include battery electrolyte, antifreeze, oil, brake and clutch fluid, petrol, windscreen washer additives, lubricants, refrigerant and various adhesives.***

***⚠ Warning: Particular care should be taken to avoid unnecessary contact with used engine oil. Always read carefully the instructions printed on labels or stamped on components and follow them carefully. Such instructions are included for reasons of your health and personal safety. Never disregard them.***

### Engine Oils

***⚠ Warning: Prolonged and repeated contact with used engine oils can cause serious skin disorders, including dermatitis and cancer. Avoid excessive contact, wash thoroughly after contact. Keep out of reach of children. When your oil is changed, be sure that it is done by an experienced person. In addition, observe all laws regarding the disposal of waste oil and toxic fluids.***

### Protect The Environment

***⚠ Warning: It is illegal to pollute drains, water courses, or soil. Use authorised waste disposal facilities, including civic amenity sites and garages providing facilities for receipt of used oil. If in doubt, contact your local authority for advice.***

## Emergency Items


***[1] :*** Tyre Sealant Kit, located in the boot (not shown). (Refer to 'Tyre Sealant Kit', page 10.13).

***[2] :*** First Aid Kit (optional).

***[3] :*** Warning Triangle, located in the boot.

***! Always follow local regulations when placing a warning triangle.***

***[4] :*** Towing eye, located in the vehicle tool kit.






In the interests of safety and reliability, it is advisable to carry out the following checks at the intervals suggested (more frequently if your vehicle is heavily used or operating in adverse conditions), and always before starting on a long journey. Refer to the following pages for advice and check procedures.

### Before Use Check:

- Operation of lamps, horn, indicators, wipers, washers and warning symbols
- Check there is sufficient fuel for the intended journey, particularly at night and before entering motorways
- Operation of the seat belts
- Operation of the brakes
- Check for fluid deposits underneath the vehicle.

### Weekly Checks

(daily if covering high mileage or touring)

- Tyres
- Coolant level
- Brake fluid level
- Power steering level
- Operate air conditioning
- Windscreen washer fluid level
- Check operation of windscreen washers.

### Fuel Filler Bowl

During fuel filling check that the fuel filler bowl drain pipe is free from debris which may block the pipe. If the pipe is blocked water can not drain from the bowl and can overflow into the fuel tank.


### Engine Oil Level

***! It is important to check the engine oil level regularly. Running the engine with engine oil below the lower mark or above the upper mark can cause serious engine damage.***

Check the engine oil level every fourth fuel tank fill or weekly - which ever is the sooner.

## Tool Kit

A vehicle tool kit is located in the interior rear left stowage compartment.






The tool kit consists of:

- Towing eye (Refer to 'Vehicle Recovery', page 10.15)
- Screwdriver
- Road wheel lock nut socket (optional).


## Battery Conditioner

A battery conditioner is located in boot storage area. This is an optional item.

(Refer to 'Battery Conditioner', page 10.19)

# Bonnet Release

***⚠ Warning: Do not pull on the bonnet secondary catch to assist in closing the bonnet. This may displace the bonnet secondary catch. If the catch is displaced it may not work correctly.***



***! Do not press down hard on the bonnet if it has not closed correctly. This may damage the bonnet.***

***! Take care to not unintentionally pull on or catch the bonnet release lever.***


*If the windscreen wipers are operating, they will temporarily rest in the park position while the bonnet is unlatched.*

*Before closing the bonnet, remove any tools, cleaning cloths, etc. from the engine compartment. Make sure that no one is obstructing the 'closing' area and that hands, clothing etc. are clear.*

*If the bonnet does not fully close or it opens during driving the message centre will show BONNET OPEN.*

To open the bonnet pull the lever (A) located in the left front footwell to release the bonnet latch. The bonnet will rise but stay secured by the bonnet secondary catch.




Lift slightly on the bonnet front edge whilst pulling upward on the bonnet secondary catch (B) to release it. Lift the bonnet until fully open. The bonnet is held open by two gas struts.




To close the bonnet lower the bonnet until it starts to fall under its own weight. At that point let the bonnet fall to close.

If the bonnet does not shut, open the bonnet again and repeat the closure procedure, this time assist using light hand pressure as the bonnet falls.

***⚠ Warning: Engine components may be hot and could cause severe burns.***




***[1] :*** Washer fluid reservoir.

***[2] :*** Engine oil filler cap.

***[3] :*** Brake fluid reservoir[1].

***[4] :*** Engine oil dipstick.

***[5] :*** Engine coolant reservoir.

***[6] :*** Power steering fluid reservoir.

1. Changes sides for left and right hand drive.

## Windscreen Wash Fluid Level



Top up as required. In winter, to prevent the windscreen wash fluid freezing, increase the fluid concentration (refer to the manufacturers recommendations on the windscreen wash fluid container). When the level of windscreen wash fluid is low an information message will show in the message centre (right) and the amber warning symbol will come ON.

**Local or state regulations may restrict the use of volatile organic compounds (VOCs), which are commonly used as antifreeze agents in windscreen washer fluid. A windscreen washer fluid with limited VOC content should be used only if it provides adequate freeze resistance for all regions and climates in which the vehicle will be operated.**

### Windscreen Washer Jets

The washer jet housings are located on the rear edge of the bonnet. Each housing contains two washer jets.

Windscreen washer jets are set during manufacture and should not need adjustment. However, if adjustment is required, adjust up or down so that the fluid strikes between a third and half way up the windscreen.

## Brake Fluid Level

***⚠ Warning: Do not drive the vehicle if the brake fluid level is below the minimum mark.***

***! Make sure that the brake fluid does not contact the paint work during the topping up operation. Serious paint work damage can result. If a spillage does occur, immediately flush any brake fluid from the paint work with clean, fresh water and then wipe with a clean damp cloth.***

The brake fluid level should read between the Min. and Max. marks.

1. Remove the reservoir cap. Top up to the Max. level.
2. Install the reservoir cap securely.



## Engine Coolant Level

***⚠ Warning: Do not remove the filler cap until the coolant system has cooled. Scalding can be caused by escaping steam or coolant.***

*Use a cloth or glove to protect hands and protect face and arms adequately.*

1. Remove the pressure cap to check the coolant level. The correct coolant level is to the top of the reservoir tank. Top up with the correct antifreeze mix, if required (Refer to 'Fluids and Capacities', page 11.8).
2. Make sure that the filler cap is secure after topping up.




***! Do not over tighten.***

If required to remove the pressure cap before the engine is cold, **use gloves or a protective cloth** and slowly loosen the pressure cap. Allow residual pressure to slowly drop. Continue to turn the pressure cap until it is released.

## Power Steering Fluid Level

***Make sure that the power steering fluid does not contact the paint work during topping up. Serious paint work damage can result. If a spillage does occur, immediately flush any power steering fluid from the paint work with clean fresh water, then wipe with a clean damp cloth.***

Always check the reservoir level when the engine is cold and with the front road wheels in the straight ahead position.

Wipe the reservoir cap clean before removing to prevent an ingress of contaminants.



1. Remove the reservoir cap and wipe the dipstick clean with a lint free cloth. Replace and remove again. The fluid level should read between the Min. and Max. marks.
2. If required, top up fluid level. **Do not overfill**.

## Engine Oil Level

***Warning: Engine oil or components may be hot and could cause severe burns.***

***Running the engine with engine oil below the lower mark or above the upper mark can cause serious engine damage.***

***This vehicle's warranty may be invalidated if damage is caused by the use of incorrect engine oil. Low quality or obsolete oils do NOT give the protection required by modern, high performance engines.***

***Failure to use engine oil that meets the required specification could cause excessive engine wear, a build up of sludge and deposits, and increased pollution. It could also lead to engine failure (Refer to 'Fluids and Capacities', page 11.8).***

- The vehicle should be on level ground.
- Check the oil level when the engine completely cold.
- Check the engine oil level every fourth fuel tank fill or weekly - which ever is the sooner.

***Oil Level Check:***





1. Withdraw and wipe the dipstick clean, using a lint free cloth.
2. Fully insert the dipstick with the Min. and Max. marking on the blade upwards (facing towards the engine). Withdraw again.



*Approximately one litre (two pints) is required to bring the level from Min. to Max.*

3. The oil level should read between the Min. and Max. marks.





4. If required remove the filler, top up to the Max. mark with the recommended engine oil.





5. Wait for approximately two minutes for the oil to settle, then check the level again. Add oil if required. **Do not overfill**.
6. Replace the filler cap securely, replace the dipstick and press it home.

## Windscreen Blade Replacement

To replace the windscreen wiper blades the wiper arms must be set at 90° to the vehicle (A). Press and hold in buttons 2 and 6 on the Infotainment keypad. Insert the vehicle key in the ignition control and move to position 'II' (ignition ON). This will manoeuvre the wiper blade arms to the 90° position. Return the vehicle key to position '0'.




Lift the wiper arm(s) up, press at point B and remove the worn wiper blade(s). Install the new wiper blade(s) and lower the wiper arm(s).




After replacing the wiper blade either:

- Move the vehicle key back through to position 'II' to lower the wiper arms. Return the vehicle key to position '0' or remove.
- Operate the wiper stalk - the wiper arms will complete the request and then park.

## Brake Pad Bedding-in

***⚠Warning: Track day use and high speed driving: For track use or high speed driving new brake pads must be subject to specific conditioning. Failure to correctly condition the pads may result in greatly reduced brake performance. Contact your Aston Martin Dealer.***

***Failure to bed-in new brake pads will result in reduced brake performance and possible brake judder or squeal.***

After the installation of new brake pads, brake performance will be reduced, as the brake discs and pads need to be 'bedded-in'. For the first few hundred kilometres of new brake pad use, avoid excessive braking (hard stops from high speed, alpine descents, etc.).

## Clutch Bedding-in

The vehicle needs to be driven carefully for the first 1000 miles/1600 km before the clutch is fully bedded in. If the vehicle is not driven carefully during this time, early failure of the clutch can occur. This is not covered by warranty as it is incorrect use of the clutch and is considered 'wear'.

***Failure to bed-in a new clutch will result in reduced performance, and possible clutch damage.***

## Tyres

Tyres of the correct type, manufacturer and dimensions, with correct cold inflation pressures are an integral part of every vehicle's design. Regular maintenance of tyres contributes not only to safety, but to the designed function of the vehicle.

Road holding, steering and braking are especially vulnerable to incorrectly pressurised, badly installed or worn tyres.

Tyres of the correct size and type, but of different make have widely varying characteristics.

Only install tyres approved by Aston Martin.

### Tyre Pressures

Make sure that correct tyre pressures are carefully maintained. Road holding, steering, braking and tyre wear are especially vulnerable to incorrect tyre pressures.

Check tyre pressures regularly and before starting any journey. Re-inflate any tyre with a low pressure at the earliest opportunity.

Pressures increase slightly when the tyres are hot. For an accurate reading, pressures should be checked when the tyres are cold. After adjusting the tyre pressures, make sure that the valve caps are securely replaced to provide an additional air seal and to prevent the ingress of dirt.

## Tyre Service

### Front Tyres

The recommended front tyres for this vehicle are symmetrical and directional (when installed on the wheel, the front wheels can not be swapped on the same axle). Make sure that the direction of rotation arrow (on the tyre sidewall) shows the direction of tyre rotation is forwards.

### Rear Tyres

The recommended rear tyres are asymmetrical and directional (the rear tyres can not be swapped on the same axle). The tyres are marked for left or right side, direction of rotation and outside and inside (on the tyre sidewall).

When being installed make sure that the tyre marked right installs on the right side wheel (left tyre on left wheel), the word outside is facing outwards and that the direction of rotation arrow shows the direction of tyre rotation is forwards.

The front and rear tyres are also of different sizes on the front and rear axles, therefore complete wheels cannot be swapped between axles.

## Damage

Tyres should be examined at regular intervals for wear and damage. Inspect the tyre treads and sidewalls for damage, i.e. bulges in the tread or the sidewalls, cracks in the tread groove and separation in the tread or the sidewalls. If damage is observed or suspected have the tyre inspected by a tyre professional.

Stones or other objects which have become lodged in the tyre treads should be carefully removed.

### Flat Spots

It is a characteristic of high performance tyres that temporary 'flat spots' may develop if the vehicle is left standing in high or low ambient temperatures for any length of time.

These 'flat spots' will manifest themselves as minor vibrations when the vehicle is first driven from cold. As the tyres warm up to operating temperature, normal tyre shape should be restored and the vibrations cease. If vibrations persist, consult your Aston Martin Dealer.

### Age

*Local regulations on tyre life may apply.*

Tyres degrade over time, even when they are not being used. It is recommended that tyres generally be replaced after six years of normal service. Heat caused by hot climates or frequent high loading conditions can accelerate the aging process.

### New Tyres

New tyres should not be installed to the front wheels in combination with worn rear tyres, as rear end stability will be affected. When new tyres are required consult your Aston Martin Dealer for advice if the rear tyres are also worn. Each wheel and tyre unit must be balanced dynamically and measured for Radial Force Variation (RFV) to make sure of efficient steering, optimum tyre wear and maximum ride comfort. Because of the potentially high speeds, it is essential that wheel balancing is carried out when new tyres are installed. Contact your Aston Martin Dealer for more information.

### Running-In New Tyres

When new tyres have been installed, speed should be limited, particularly during the first 80 km or so of driving. Fast cornering, hard braking, and harsh acceleration should also be avoided during this period.

### Tread Wear Marks




Tread wear marks (A) are incorporated into the construction of all tyres. These marks are integral moulded ribs spaced at regular intervals around the circumference of the tyre and extend across the full width of the tread, in all primary grooves.

When a tyre has worn causing one or more of the marks to be flush with the outer face of the tread the tyre has reached its wear limit. It then becomes illegal in certain countries and must be replaced.

***⚠ Warning: Do not use the system to seal a tyre that was damaged while driving with insufficient air pressure (e.g. tyre cuts, cracks, bumps or similar damage). Do not use the system to seal tyres with side wall damage. Only punctures in the tread area of tyres may be sealed.***

***⚠ Warning: Do not stand directly beside the tyre while the compressor is pumping. Watch the side wall of the tyre. If there are any cracks, bumps or similar damage set the compressor to OFF. The journey should not be continued. Contact your nearest Aston Martin Dealer.***

***⚠ Warning: If a tyre pressure of 1.8 bar cannot be reached then the tyre can not be sealed. Do not attempt to re-inflate the tyre. Contact your Aston Martin Dealer.***


***⚠ Warning: If the pressure in the tyre after driving for 3 km is below 1.3 bar the tyre has not been effectively sealed. The journey should not be continued. Contact your nearest Aston Martin Dealer.***

***⚠ Warning: After a longer period of rest, the tyre pressure should be rechecked.***

***! The tyre sealant kit only provides temporary mobility. Always refer to local laws and regulations on the use and repair of tyres that have been treated with any form of temporary mobility aid. Consult a tyre specialist for advice.***

*Inform the tyre specialist that the tyre contains sealant.*

### Location



## Operation

Remove the tyre sealant kit from its location in the boot. Follow the instructions detailed on the lid.

Read the following instructions and warnings carefully before using the tyre sealant kit. Compliance with these instructions is vital to make sure of vehicle and user safety. Noncompliance with these instructions means risking severe tyre damage and hazardous vehicle behaviour which can lead to a road accident involving damage to property or injury to persons.

- Make sure that the vehicle is parked far enough from traffic so that there is no danger from passing vehicles and so that you do not disrupt the traffic. Warn other vehicles using the warning triangle.
- The system should only be used between temperatures of – 40°C and 70°C.
- A maximum speed of 80 km/h may not be exceeded at any time after sealing the tyre with the system.
- The system provides only a **temporary emergency repair** for continuing the journey up to 200 km or to the nearest Aston Martin Dealer.
- If the nearest Aston Martin Dealer is over a 200 km away arrange for collection under the Aston Martin Emergency Service scheme.
- The system will effectively seal a tyre that was punctured by an object with a diameter of up to 6 mm. It is possible that a tyre, especially with greater damage, will not be sealed. Do not remove objects that punctured the tyre if they are still lodged in the tyre.
- The sealant bottle needs to be exchanged before it expires. **Do not** use the system after the expiry date on the sealant bottle or casing has been reached. Contact your nearest Aston Martin Dealer.
- Do not attempt to inflate other objects without using a system adapter and do not inflate objects with a volume greater than 50 litre (air mattresses, rubber boats, etc.). Do not let the system pump air for more than 10 minutes without stopping it and allowing it to cool down.

Both the hose and the bottle of sealant need to be replaced after using the system. Sealant deposits in a used hose may cause the system to operate incorrectly. New bottles of sealant can be purchased from your Aston Martin Dealer.

Dispose of empty sealant bottles together with normal household waste.

Remains of liquid sealant must be handed over to your dealer or disposed of in compliance with local waste disposal regulations.

# Vehicle Recovery

***When moving the vehicle by transporter make sure that the vehicle is not strapped down to the transporter by the suspension control arms.***


***Power braking and power steering are not available with the engine OFF. Substantially higher brake pedal pressures and steering effort are required.***

***If there is a transmission fault, this vehicle must be transported.***

Your vehicle should always be recovered on a vehicle transporter[1] and should only be towed for **short distances**, for example, if it is causing an obstruction or if it requires winching onto a transporter.

If moving the vehicle in such a situation:

1. Remove the towing eye from its storage location in the vehicle tool kit and install it to the exposed female threads (A) front, (B) rear, until fully engaged against the vehicle body.




*The towing eye has a left hand thread.*

*Protect vehicle paint work when installing the towing eye.*

2. Put the transmission into neutral. Move the vehicle key to position 'II' (ignition ON) to release the steering lock.
   If the transmission is in neutral then first gear will be selected at ignition OFF. If the transmission is in first or reverse gear, the transmission will stay in the selected gear at ignition OFF. To enable neutral to be selected at ignition OFF, set the ignition to ON then press and release the neutral button twice, or pull back and release the gear shift paddles twice, before the ignition is set to OFF. An audible warning will sound three times while the message centre will show GEARBOX IN NEUTRAL and APPLY PARK BRAKE.
3. When being towed use the footbrake very gently as required to prevent excessive slack in the tow rope.

1. The recommended method for a recovering vehicle is to have it transported in a purpose built, covered, vehicle transporter.

## Jump Start From Another Vehicle

***⚠ Warning: The donor vehicle must have a 12 volt battery and a negative (-), black earth terminal to make sure that the correct battery polarity is maintained.***

***! Apart from vehicle recovery, this vehicle must not be driven if the vehicle battery is incapable of starting the engine. In this case the vehicle battery must be replaced.***

***! If the voltage or earth of the donor vehicle is different or not known, do not attempt starting in the way described.***

If this vehicle will not start due to a discharged battery, it may be started, **for vehicle recovery**, by connecting the battery from another vehicle (donor) to this vehicle (recipient).


### Jump Start Procedure

***! Remove rings, metal watch bands and any other jewellery.***

***! Set all electrical motors and ancillaries in both vehicles to OFF.***

***! Set all lamps to OFF except those needed to protect vehicles or illuminate the work area.***

1. Position the donor vehicle so that the connecting cables will reach into the recipient engine bay. Apply the park brake and set the ignition to OFF.
2. Access the jump start terminal in the recipient engine bay.
3. Connect the positive (red) cable between the positive (red) terminal of the donor battery and the jump start terminal of the recipient vehicle (A).




4. Connect the negative (black) cable between the negative (black) terminal of the donor battery and a good earth (negative) point in the recipient engine bay (B).
5. Start the donor vehicle engine and run at about 1500 – 2000 rpm.

6. Start the engine of the recipient vehicle.
7. Once both vehicles are running remove the jump start cables, first the negative (black) cable from both vehicles and then the positive (red) cable from both vehicles.

   Allow the recipient engine to run until the discharged battery is sufficiently recharged (15 to 20 minutes) to start the engine without assistance. Set the engine to OFF and restart the engine. Take the vehicle on a long run to fully charge the battery.

   Contact your Aston Martin Dealer to have the battery checked or replaced.

📖 *Recharge time will depend on the initial 'state of health' of discharged battery.*

📖 *If this vehicle will not start consult your Aston Martin Dealer.*

***⚠ Warning: Battery posts, terminals and related accessories contain lead and lead compounds. Wash hands after handling.***

***⚠ Warning: Do not allow flames, sparks or lighted substances to come near the battery. Batteries normally produce explosive gases which can cause personal injury. When working near the battery, always shield your face and protect your eyes. Always have sufficient ventilation.***

***⚠ Warning: When lifting a plastic cased battery, excessive pressure on the end walls could cause acid to flow through the vent caps, resulting in personal injury, damage to the vehicle or battery. Lift the battery with a battery carrier or with your hands on opposite corners.***


***⚠ Warning: Keep batteries out of reach of children.***

***⚠ Warning: Batteries contain sulphuric acid. Avoid contact with skin, eyes or clothing. Shield your eyes when working near the battery to protect against possible splashing of acid solution. In case of acid contact with skin or eyes, flush immediately with water for a minimum of 15 minutes and get prompt medical attention. If acid is swallowed, get medical help immediately.***

***! The engine must never be run with the vehicle battery disconnected.***

***! Apart from vehicle recovery, this vehicle must not be driven if the vehicle battery is incapable of starting the engine. In this case the vehicle battery must be replaced. Contact your Aston Martin Dealer.***

The vehicle battery is maintenance free and should only require checking by your Aston Martin Dealer during regular vehicle services. To access the vehicle battery (A) remove the trim panel located in the right rear environment.



## Vehicle Battery Disposal

It is the responsibility of the vehicle owner when disposing of automotive batteries to do it in an environmentally correct manner.

The incorrect disposal of a vehicle (lead-acid) battery can be extremely hazardous to health and the environment. Most batteries contain heavy metals and when disposed of incorrectly, these heavy metals may leak into the ground. This can contribute to soil and water pollution and endanger wildlife.


Follow your local authorised standards for disposal. Call your local authorised recycling centre to find out more about recycling automotive batteries.

Do not dispose of your vehicle battery in the household waste.



## Warnings

The following warnings are located on the vehicle battery.




## Vehicle Battery Charge

Various systems, for example, the clock, security systems and Infotainment centre system continue to drain battery power even with the ignition OFF.

A **new fully charged** battery has the ability to start this vehicle, if left unused, for up to 45 days without a battery conditioner being used.

*In cold climates this time may be reduced.*

*Aston Martin recommend that if this vehicle is to be left unused for 10 days or more a battery conditioner (mains power available) should be used.*

Battery charge can be drained excessively in a number of ways:

- If the vehicle is unused for long periods of time.
- If the vehicle is used regularly but only for short journeys, e.g. less than 48 km a journey.
- If electrical systems are in use without the vehicle engine running.
- If the vehicle key is left in the ignition control for long periods of time without the engine operating.

Excessive battery drain would ultimately mean that the battery would not be able to start the engine.

## Battery Conditioner

Optional

***⚠ Warning: Do not attempt to start the vehicle with a battery conditioner connected to the mains supply.***


***⚠ Warning: Do not smoke. Prevent flames and sparks. Explosive gasses are given off by batteries during charging.***

***! A battery conditioner is designed for conditioning of partially or fully charged batteries. It will not effectively charge a discharged battery.***

***! For indoor use only. Disconnect mains supply before making or breaking battery connections.***

*The Aston Martin battery conditioner (option) is suitable for use on all types of 12 volt lead acid batteries.*

If this vehicle is not going to be used for a period of time, and **mains power is available**, use a battery conditioner to maintain the battery charge level.




When connected the battery conditioner will maintain a small trickle charge to keep the battery in a fully charged state. The battery conditioner may be left in this state indefinitely.

### To Connect a Battery Conditioner

1. Insert the accessory socket plug (B) into the accessory socket (A) located in the boot right side.
2. Insert the mains plug (C) into the mains supply.
3. Gently close, but do not latch, the boot lid. This avoids possible damage to the boot lid water seal from the battery conditioner power cable.

*With the boot lid left open the vehicle doors can be locked and armed.*




To remove the battery conditioner first disconnect from the mains supply, then from the vehicle socket.

# Battery Protection Mode

***Replace the battery as soon as possible, if the battery is not capable of starting the engine.***

Using the vehicle electrical systems, i.e. the infotainment system, with the vehicle key at position 'I' (ignition OFF) will drain the battery charge. Eventually the battery will drain to such a low level that it will not start the engine.

To avoid this happening, a series of safety mechanisms shut down nonessential electrical systems before excessive battery drain takes place.


## Frequently Asked Questions

**What is the first sign of battery protection mode?**

Two messages will show:

***[A] :*** **WARNING - LOW BATTERY** (For 10 seconds).

***[B] :*** **LOW BATTERY**




**What should I do next?**

Set all unnecessary electrical systems to OFF to reduce battery drain. Start the engine to recharge the battery. Run the engine for a reasonable length of time.

**What happens if I ignore the warning messages?**

After approximately two to ten minutes (dependent on the rate of battery charge drain) the following messages will show:

***[A] :*** **INFOTAINMENT WILL BE SHUT DOWN 2 MINUTES** (For 10 seconds).

***[B] :*** **LOW BATTERY POWER SAVE**.

If the audio system is ON the sound will mute for 10 seconds and a short 'Beep' will be heard when the message is first shown.

**What should I do if these messages are shown?**

Set all unnecessary electrical systems to OFF. Start the engine to recharge the battery. Run the engine for a reasonable length of time.

**What happens if I ignore second warning messages?**

The infotainment system will shut down in two minutes. No other electrical system will be shut down. This significantly reduces the rate of battery drain. The following functionality will be lost:

- CD Player
- Navigation System
- Radio Tuner

**What should I do if the infotainment system shuts down?**

Start the engine to recharge the battery. Run the engine for a reasonable length of time.

The infotainment system will not operate without the engine running until the battery has regained its charge. With the engine running the infotainment system will start up.

**What is a reasonable length of time to run the engine?**


The vehicle battery normally requires a journey of approximately 48 km to recharge. Additionally, use the battery conditioner to restore the vehicle battery charge.

**What if I cannot restart the engine?**

If the battery has been run down to a point where it will not start the engine then an external battery charger[1] will be required or your vehicle will require a 'jump start' (Refer to 'Jump Start From Another Vehicle', page 10.16).

1. A battery conditioner is designed for conditioning of partially or fully charged batteries. It will not effectively charge a discharged battery.


## Fuse Boxes



The electrical system is protected by fuses. If any lamps, accessories, or controls don't work, inspect the appropriate circuit protector.

If a fuse has blown, the inside element will be melted. If the same fuse blows again, avoid using that system and consult your Aston Martin Dealer as soon as possible.

## Fuse Box Location




***[1] :*** Engine bay fuse box (passenger side).
***[2] :*** Boot fuse box.

## Engine Bay Fuse Box

| Fuse | Rating | Function |
|---|---|---|
| F1 | 10A | Engine Management System ECU B Permanent Power Feed |
| F2 | 10A | Enhanced Flooded Battery (EFB) Relays |
| F3 | 10A | Valved Airboxes, Crank Relay, Electric Vapour Management Value (EVMV) |
| F4 | 20A | Engine Management System ECU A Powerhold |
| F5 | 20A | Engine Management System ECU B Powerhold |
| F6 | 15A | Universal Exhaust Gas Oxygen (UEGO) and Catalyst Monitor Sensor (CMS) Bank B |
| F7 | 15A | Ignition Coils Bank B |
| F8 | 10A | Variable Value Timing Bank B |
| F9 | 20A | Injectors Bank B |
| F10 | 10A | Air Conditioner Compressor Clutch |

| Fuse | Rating | Function |
|---|---|---|
| F11 | 15A | Dual Horn |
| F12 | 10A | Engine Management System ECU A 'Keep Alive' |
| F13 | 20A | Injectors Bank A |
| F14 | 10A | Variable Valve Timing Bank A |
| F15 | 25A | Starter Motor |
| F16 | 15A | Ignition Coils Bank A |
| F17 | 5A | Not Available |
| F18 | 15A | Universal Exhaust Gas Oxygen (UEGO) and Catalyst Monitor Sensor (CMS) Bank A |
| F19 | 30A | Not Available |
| F20 | 30A | Not Available |
| F21 | | Not Available |

| Fuse | Rating | Function |
|---|---|---|
| F22 | 5A | Mass Air Flow (MAF) Sensor A, Oil Sensor |
| F23 | | Not Available |
| F24 | 5A | Alternator (I-Line) |
| F25 | 5A | Mass Air Flow (MAF) Sensor B, Electronic Control Lock (ECL) |
| F26 | 20A | Headlamp Wash Pump |
| F27 | 40A | Anti-lock Braking System (ABS) Module |
| F28 | 10A | Vehicle Key Reader, Steering Angle Sensor, Fuel Tank Leakage Diagnostic Pump, Anti-lock Braking System (ABS) Module, Electronic Steering Column Lock (ESCL), Brake Switch |
| F29 | 20A | Anti-lock Braking System (ABS) Module |
| F30 | 5A | Anti-lock Braking System (ABS) Module |
| F31 | 40A | EFB Relays |
| F32 | 30A | Wiper Motor (Slow) |
| F33 | 30A | Wiper Motor (Fast) |
| F34 | | Not Available |
| F35 | 80A | Fan Control Module (x2) |

## Boot Fuse Box

| Fuse | Rating | Function |
|---|---|---|
| F1 | 5A | Not Available |
| F2 | 20A | Power Outlet Boot |
| F3 | 30A | Heated Rear Windscreen |
| F4 | 20A | Track Pack Oil Cooler |
| F5 | 30A | Alpine Amplifier/B&O ICE Amplifier |
| F6 | 20A | Not available |
| F7 | 5A | High Intensity Discharge (HID) Module |
| F8 | 30A | Auto Shift Mode (ASM) Pump |
| F9 | 30A | Fuel Pump Diagnostic Monitor (FPDM) |
| F10 | 30A | Not Available |
| F11 | 10A | Satellite Navigation, Digital Tuner |
| F12 | 20A | Auto Shift Mode (ASM) Electronic Control Unit (ECU) |
| F13 | 10A | Auto Shift Mode (ASM) Electronic Control Unit (ECU) |
| F14 | 5A | PDC ECU, ADS ECU |
| F15 | 5A | Exhaust Bypass (Pump and Valve) |
| F16 | 30A | Not Available |
| F17 | 5A | Not Available |
| F18 | 30A | Alpine Subwoofer/B&O DSP Amplifier |
| F19 | 5A | Not Available |
| F20 | 20A | Power Outlet Cubbybox |
| F21 | 30A | Not Available |
| F22 | 20A | Not Available |

# Headlamp

*Continental Driving (UK Only): UK owners wishing to take this vehicle to the continent should contact their Aston Martin Dealer for headlamp and dipped beam alignment checks and adjustments.*

*Headlamp Units: Condensation: The headlamp units will generate condensation under certain conditions. However, this should clear after approximately 10 minutes after the headlamps have been set to ON.*

## Dipped Beam Bulb


***⚠ Warning: High Intensity Discharge (HID) bulbs produce a very high voltage. They should only be serviced by an Aston Martin Dealership.***

High Intensity Discharge (HID) bulbs are used for the dipped beam. HID systems produce a brilliant white light by establishing a high voltage electrical arc between two electrodes within a sealed glass tube. Once the arc is established, the voltage lowers to normal operating conditions.


**HID bulbs are not renewable.** Contact your Aston Martin Dealer if a HID bulb fails to operate.

## Main Beam Bulb

Access to the headlamp bulbs is through a panel in each wheel arch liner. Turn the steering to the opposite lock from the headlamp unit with the defective bulb. Using a flat blade, i.e. a screwdriver or a small coin, release the screw on the access panel and remove the panel.




Using a screwdriver release the two knurled screws and remove the headlamp unit cover.



***[A] :*** Dipped beam

***[B] :*** Main beam




*The main beam bulb (B) is inboard on both the left and right headlamp units.*

Remove the access cover and turn the bulb unit a quarter turn counterclockwise. Withdraw the unit and disconnect the wiring harness plug.

Connect a new bulb unit (Refer to 'Bulbs', page 11.6), insert the bulb unit and turn a quarter turn clockwise to lock. Install the headlamp access cover and wheel arch liner access panel.

# Other External Lamps

## High Level Stop Lamp

The high level mounted stop lamp unit consists of LEDs and is not repairable. If a high level mounted stop lamp LED fails contact your Aston Martin Dealer.

## Front Indicator and Parking Lamps

If a front indicator or parking bulb fails to operate, contact your Aston Martin Dealer. These lamps consist of LEDs and are not repairable.

## Side Indicators

The side indicators comprise of LEDs and are not repairable. If a side indicator lamp bulb fails, contact your Aston Martin Dealer.

## Registration Plate Lamps

To change a registration plate bulb:

Take care not to damage the vehicle trim.

Use a small flat blade screwdriver to lever out, from the right side, the lens unit. Twist, counterclockwise, and withdraw the bulb holder, remove the defective bulb and replace with a new one (Rating: 5W Type: C5W).



Twist the bulb holder back into in position. Replace the boot trim panel.

## Rear Lamp Clusters

The rear indicators, stop and tail, reversing lamps and rear fog LEDs are contained in a sealed lamp cluster unit, one either side of the vehicle. The lamp cluster is not repairable, if a rear lamp fails contact your Aston Martin Dealer.

## Boot Lamps


Take care not to damage the vehicle trim.


Lever out the lens unit. Replace the defective bulb (C10W 10W) and clip the lens unit back into its housing.



## Internal Lamps




***[1] :*** Front footwell lamps: Type: W5W (Blue). Rating: 5W.

***[2] :*** Door puddle lamps: Type: C5W (Festoon). Rating: 5W.

***[3] :*** Reading lamps: LED

LEDs are not repairable. If an LED lamp fails to operate, contact your Aston Martin Dealer.

To renew a bulb:

1) Take care not to damage the vehicle trim.

2) Lever out the lens unit and replace the faulty bulb.

3) **Door puddle lamps only:** Open the access flap and replace the faulty bulb.

4) Press the lens unit into its housing until it clips into position.

## Door Window Reset

If power to the electric windows has been interrupted for any reason, they will fail to operate correctly until reset.


1. Sit in the driver's seat with all doors closed, insert the vehicle key into the ignition control and move to position 'II' (ignition ON).
2. Press firmly and hold the window switch until the window is at the maximum down position. Continue to hold the button for five seconds then release.
3. Pull back and hold the window switch until the window is in the maximum up position. Continue to hold the switch for a further five seconds, then release.
4. The window is now reset. Repeat for the other door windows.

## Front Seat Reset

Should a front seat fail to move or the seat memory position fails to work this may show a loss of seat position in the vehicle's memory. If so, complete the seat reset procedure detailed below:

***⚠ Warning: Do not sit in the seat while you do the seat reset procedure. Seat movement will restrict the occupancy area.***

***⚠ Warning: Make sure that there is nothing in front of, behind, or under the seat during the seat reset procedure.***




***[1] :*** Raise or lower the **front** of the seat.

***[2] :*** Move the seat **forwards** or **rearwards**.

***[3] :*** Raise or lower the **rear** of the seat.

***[4] :*** Raise or lower the **front** of the seat.

Use the seat switch to move the seat base to the most rearward and lowest position and tilt the seat back to the most forward position.

*Early vehicle models may need to move the seat base to the most forward and lowest position.*

Press and hold the seat switch, for each movement, until all seat movement has stopped, then release.

The seat movement and position memory should now work correctly, if not contact your Aston Martin Dealer.

## Door Drain Holes

Check the drain holes in the bottom face of each door periodically and clear if necessary with, for example, a short length of wire or a pipe cleaner.

# Vehicle Cleaning

## Paint Work

Modern water based paints are much safer and more environmentally friendly than solvent based paints. Water based paints are however more susceptible to contamination and marking by corrosive substances. The following list is not exhaustive but does show the most common contaminants which may adversely affect your paint work:

- Bird Droppings,
- Antifreeze,
- Tree Sap,
- Oils and Greases,
- Insect Remains.

Wash such substances from the vehicle using clean warm water with vehicle shampoo, at the earliest opportunity, especially in sunny weather which can accelerate contamination.

*Other groups of contaminants may be added to this list as experience of water based paints and finishes increases.*

## Washing

***Warning: Washing and polishing agents containing silicone should not be applied to glass. This will reduce the efficiency of the windscreen wipers, causing smears which will reduce visibility, particularly during darkness and in the rain.***

***Commercially operated automatic vehicle washes, jet washes and power operated mops are not recommended. The detergents used can contain certain chemicals which may, over time, be detrimental to some exterior parts of the vehicle. Prolonged usage of automatic vehicle washes and power operated mops will also cause fine scratches in the paint surface.***

Aston Martin recommends the use of AUTOGLYM vehicle care products or preparations of similar reputable manufacture for adding to the washing water. Make sure that the manufacturer's instructions are followed.

During the winter months, it is advisable to wash the vehicle more frequently, paying particular attention to the underside to combat the detrimental effects of any salt and sand contamination picked up from treated roads.

To delay the onset of corrosion developing on the brake components Aston Martin recommend that after washing this vehicle, the vehicle should be driven a short distance to make sure that all the water and washing product has dried off.

For best results:

Do not wash the vehicle in strong sunlight. Let the vehicle cool before washing.

Do not use household soaps or detergents.

Do not direct water hoses at full force around the door and boot lid seals.

Do not use a brush on the car body as this will leave little scratches.

Suggested washing method:

1. Fill two buckets with water. To one bucket add a mild neutral detergent, as directed by the detergent manufacturer.
2. Hose the vehicle to remove all dust and mud residue. Don't use a strong jet, as this can rub grit over the paint and scratch it.
3. Soak a large wash mitt or a soft sponge in the soapy water, make sure to wash out any dirt in it, and begin applying it to the vehicle. Wash the vehicle section by section, starting at the top. Circle around the car several times, washing lower areas with each round.
4. Rinse the dirt out of the wash mitt or soft sponge in the bucket with plain water frequently.
5. After one section is washed, rinse it with the hose before moving on, don't let the soap dry on the paint and stain it. Always keep the vehicle wet, this will prevent droplets from drying on the paint and leaving water-spots.
6. Dry the car with a chamois leather before it air-dries.

**Front Grille**

Wash and clean the vehicle's front grille in the same way as the paint work, but make sure that the front grille is dried off completely leaving no water droplets on the grille (wipe the front grille last using a chamois leather): Chrome polish or other abrasive cleaners must not be used.

**Road Wheels**

To avoid possible damage to the alloy road wheels, wheel nuts and wheel centre trims, from a build up of brake dust wash and clean the alloy road wheels frequently, using a mild soapy water solution only. Do not use chemical alloy road wheel cleaners, as they can often have a high acid or alkaline content and could cause discolouration. Always clean one wheel at a time and do not allow the cleaning solution to dry on the wheel. Fully flush off with clean water.

**Satin Black Road Wheels**

Option

***The Aston Martin new car warranty covers defects in materials or workmanship of the paint work. The warranty does NOT cover repairs to your Satin Black paint work caused by negligence, lack of or improper maintenance such as waxing or polishing the finish, environmental influences, or improper repairs or damage that causes the Satin Black finish to become glossy.***

In comparison to conventional wheel colours with a gloss or metallic surface, the Satin Black paint work must be cared for slightly differently. In order to avoid damage to the Satin Black paint work, make sure that the cleaning and care points below are followed:

1. Only use cleaning products recommended by Aston Martin. Abrasive cleaning products will change the satin appearance of the wheel and must not be used.
2. Do not polish or wax the wheel. Polishing or waxing can lead to glossing of the Satin Black paintwork.
3. Do not wash the car in an automatic car wash. This will avoid particles, for example: sand and dust, from damaging the Satin Black painted surface.
4. Only use a soft sponge to clean the wheel. Do not use abrasive cleaning tools.
5. Remove insect remains, bird droppings, resins, tar spots, fuels and oil immediately. Avoid strong rubbing while cleaning the wheel.
6. Any stickers applied to the paint work will leave a mark when removed.
7. Repairs to the wheel paint work must be completed by an Aston Martin category A or B body shop.

**Ceramic Brake Discs**

To avoid possible damage to the ceramic brake discs, when washing the road wheels with products or materials other than a mild soapy water solution always remove the wheels from the vehicle.

**Headlamp Lenses**

Only use a mild soapy water solution when washing the Headlamp Lenses. Do not use cleaning materials which contain solvents.

Cleaning materials which contain solvents, i.e. tar remover, petrol, waxes or polishes, may damage the headlamp lens.

**Polishing**

Approximately twice a year, a good quality polish should be applied to the body work and then buffed, using a soft lint free cloth.

The alloy wheel rims should be treated with a cleaner which is specifically manufactured for this purpose.

**Upholstery, Trim, Carpets and Seats**

***Warning: Fumes from cleaning solvents may be dangerous in confined spaces. Make sure that the vehicle is well ventilated and follow the manufacturer's printed instructions when using these products.***

***Certain types of clothing, such as denim and vegetable tanned leather, are prone to 'dye transfer'. This can cause discolouration in the leather. Make sure that the affected areas are cleaned and re-protected as soon as possible.***

The seats and soft trimmed components of this vehicle are covered in hand crafted leather. In order to maintain the beauty of leather it will require regular cleaning, which, if neglected, may cause deterioration.

Where dust and dirt are allowed to accumulate and become ingrained in the surface the leather may become permanently damaged. Leather faced features should be cleaned with a damp cloth moistened with an undiluted leather cleaner.

**Do not** use detergents, quick cleansers or furniture polishes. These products may give an initially impressive result, but their use will lead to rapid deterioration of the leather and will invalidate the warranty.

Several times a year, a leather conditioner or preservative should be used. Appropriate care materials are obtainable from your Aston Martin Dealer.

Alcantara roof linings and other soft trimmed areas may be brushed with a soft brush. Stains from water based substances such as coffee, tea or soft drinks should be cleaned as soon as possible with mild soap and water.

The brushed and anodised aluminium trim should be cleaned using a dry clean lint free cloth.

Consult your Aston Martin Dealer for instructions on the removal of more difficult stains such as oil, grease or ballpoint ink.

Carpets should be cleaned regularly with a vacuum cleaner. Any stains or grease marks should be removed with a good quality solvent suitable for use on carpets.

**Care and Maintenance of Seat Belts**

***Do not allow seat belts to be retracted until they are completely dry.***

To make sure that the restraint webbings are in correct working order, regularly check the seat belts. Look for fraying, cuts, burns and similar problems. Make sure that the latches and buckles operate correctly. If a seat belt is not in good condition or is not working correctly, consult your Aston Martin Dealer.

Any seat belt that has been worn during a serious collision should be replaced by an Aston Martin Dealer.

To clean the seat belts, use mild soap and water; do not use bleach, solvents or dyes as they can weaken the material. Allow the seat belts to dry thoroughly before use.

**Under Bonnet Cleaning**

Under bonnet cleaning using high pressure hoses or steam cleaners should not be carried out. The electronic control module connections and fuse boxes can be damaged by indiscriminate use of high pressure cleaning equipment.

## Recommendations

*These recommendations apply to new and pre-owned vehicles either in dealer or customer ownership.*

If your vehicle is not to be used for periods in excess of three months it should be stored in a dry, well ventilated building.

1. Drive the vehicle for a sufficient distance to warm the oil in the engine and the transaxle; make sure that the internal components of the engine are lubricated.
2. Check the engine coolant level. Top up if necessary with the correct antifreeze and water solution.
3. In order to take the weight off the tyres, raise the vehicle with a jack and place supports under the front and rear suspension. If the vehicle is not raised from the ground, increase the tyre pressures to 3.4 bar. Cover the tyres to exclude any light. Turn the wheels ¼ turn every month to avoid tyre flat spots.
4. If mains power is available, use a battery conditioner to maintain the battery in a fully charged state.
5. Once a month:
   - 5.1 Disconnect the battery conditioner (if installed).
   - 5.2 Start and operate the engine until it is fully warmed up.
   - 5.3 Check there are no fluid leaks.
   - 5.4 Set the ignition to OFF.
   - 5.5 Connect a battery conditioner.
   - 5.6 Check and correct tyre pressures if necessary. When returning the vehicle to normal service, set the tyre pressures to normal specification before driving on the road.

*Excessive sunlight and humidity can increase the vehicle temperature, which can cause damage to the vehicle interior and trim. If storing the vehicle in these conditions, Aston Martin recommend using a solar reflecting car cover to prevent any potential damage due to high temperatures.*

## Extended Storage

For storage periods exceeding six months the following measures are recommended:

*Do not drain the fuel system.*

1. Operate the engine until there is as small a quantity of fuel in the tank as is practical for storage purposes.
2. Add engine oil to the remaining fuel in the tank to make a concentration of 2% (i.e. 20 ml per one ltr of fuel), then operate engine for not less than ten minutes to circulate the mixture thoroughly through all of the fuel system.
3. Inspect rubber connections of coolant system and have them renewed if necessary.
4. Wash the vehicle bodywork thoroughly and repair any paint blisters or patches of corrosion in order to prevent any further deterioration. Apply a suitable polish.
5. Clean the carpets and upholstery thoroughly. Treat all leather upholstery with an application of a leather conditioner or preservative.
6. If the storage building is dry leave vehicle windows slightly open. If there is any tendency towards dampness close vehicle doors and windows and place an anti-moisture compound such as silica desiccant bags in an open metal container inside vehicle.
7. Cover vehicle with a cotton or fabric cover.

## Recommissioning after Storage

Provided that the vehicle has been stored in accordance with the recommended procedure, only the following points should need attention before using your vehicle on the road.

***Starting the engine without sufficient lubrication can cause serious engine damage. Make sure that the engine oil pressure is established before the engine starts.***

1. Check the tyre pressures, inflate if necessary, lower the vehicle to ground.
2. Drain the engine oil and install a new engine oil filter element. Fill the engine to its maximum level (as shown on the dip stick) with approved oil.
3. Drain the final drive unit. Fill the final drive unit to its maximum level (oil will dribble out of the fill hole), with approved oil.
4. Check the coolant level and, if necessary, top up with the correct antifreeze to water solution.
5. Check all fluid levels and top up as necessary.
6. Fill the fuel tank.

***Starting the engine without sufficient lubrication can cause serious engine damage. Make sure that the engine oil pressure is established before allowing the engine to start.***


7. Obtain engine oil pressure:
   - 7.1 Press and hold the accelerator pedal hard to the floor (this temporarily stops fuel injection during cranking).
   - 7.2 Fully press the clutch pedal down. Insert the vehicle key into the ignition control and move through to engine start. Allow the engine to crank until the oil pressure symbol in the instrument cluster goes OFF (showing oil pressure in the engine).
   - 7.3 Set the ignition to OFF. Release the vehicle key and accelerator pedal.
8. Start the engine normally and check that the oil pressure and ignition warning symbols go OFF as the engine starts (correct oil pressure and battery charging).
9. Raise the bonnet and check for leaks of fuel, oil and coolant.
10. Carefully test drive your vehicle and check the operation of all functions.

Braking performance can be impaired, initially, due to a fine film of corrosion on the brake disc surface. Drive conservatively and, when safe to do so, frequently apply the brakes until disc surfaces have been cleaned. Full braking performance should then be restored.

If in any doubt about the condition of your vehicle, have it checked by your Aston Martin Dealer.

# Specifications


Engine....11.2
Performance....11.2
Power and Torque....11.2
Transmission....11.3
Electrics....11.3
Steering....11.3
Suspension....11.4
Brakes....11.4
Wheels....11.4
Tyres....11.5
Bulbs....11.6
Vehicle Specification....11.6
Vehicle Weights....11.6
Interior Dimensions....11.7
Exterior Dimensions....11.7
Fluids and Capacities....11.8

## Engine

All alloy, quad overhead cam 48 valve V12.

***Fuel:*** Recommended 98 RON Super Unleaded for optimum performance. 95 RON minimum.

Use of fuels containing more than 10% Ethanol are not recommended.

***Fuel Delivery System:*** Multi point sequential fuel injection.

***Capacity:*** 5935 cc

***Firing Order:*** 1 - 7 - 5 - 11 - 3 - 9 - 6 - 12 - 2 - 8 - 4 - 10

***Idle Speed:*** 750 rpm

***Bore:*** 89.0 mm (3.504 in)

***Stroke:*** 79.5 mm (3.13 in)

***Spark Plugs:*** NGK: SITR7A11G

***Spark Plug Gap:*** 1.1 mm (0.043 in) +0.0/-0.1 mm (0.004 in)

***Compression Ratio:*** 11:1

***Ignition:*** 'Coil on Plug' ignition system.

***Emission Control:*** Eight oxygen sensors (four per exhaust branch). Two three-way catalytic convertors (one per exhaust branch). Evaporative loss purge.

***Lubrication:*** Wet sump pressurised lubrication.

## Performance

***Maximum Power:*** 565 bhp @ 6750 rpm

***Maximum Torque:*** 457 lb.ft @ 5750 rpm


***Maximum Speed:*** Where permitted.

205 mph

***0-62 mph:*** 3.7 seconds

***Maximum Engine Speed:*** 7000 rpm

## Power and Torque




***[1] :*** Torque (Nm / lb/ft)

***[2] :*** Power (kw / bhp)

***[3] :*** Engine speed (rpm)

## Transmission

### SportShift Transaxle

Graziano seven speed transaxle with integrated, electronically-controlled hydraulic shifting system.

| Gear Ratios | |
|---|---|
| 1st | 3.286:1 |
| 2nd | 2.158:1 |
| 3rd | 1.609:1 |
| 4th | 1.269:1 |
| 5th | 1.034:1 |
| 6th | 0.848:1 |
| 7th | 0.675:1 |
| Reverse | 3.286:1 |

### Final Drive

Ratio: 3.727:1. Multi plate limited slip differential

### Clutch

Twin plate / 215 mm diameter

## Electrics

***Alternator:*** Denso SC2 150 Amps

***Voltage Regulation:*** 14.4V ±0.5V @ 20°C

***Battery:*** Varta 90 AH

## Steering

Rack and pinion, power assisted steering. Column tilt and reach adjustments.

***Turns Lock to Lock:*** 2.5

***Turning Circle:*** 11.8 m (Kerb to Kerb)

***Total Toe:*** Refer to your Aston Martin Dealer for the correct data.

## Suspension

***Front:*** Aluminium independent double wishbone. Coil over aluminium monotube dampers and anti-roll bar.

***Rear:*** Aluminium independent double wishbone. Coil over aluminium monotube dampers and anti-roll bar.

### Features

- Dynamic Stability Control (DSC)

## Brakes

### Footbrake

#### Ventilated Carbon Ceramic Discs

| | Front | Rear |
|---|---|---|
| Diameter | 398 mm | 360 mm |
| Calipers | Six piston | Four piston |

### Park Brake

Lever and cable operated independent park brake calipers on each rear brake disc.

### Brake System Features

- Anti Lock Braking System (ABS)
- Hydraulic Brake Assist (HBA)
- Electronic Brake force Distribution (EBD)
- Traction Control (TCS)

## Wheels

### Aston Martin Aluminium Alloy

| | Front | Rear |
|---|---|---|
| Factory Install | 9J x 19 | 11J x 19 |
| Winter Wheels | 8.5J x 19 | 10J x 19 |

### Wheel Nut Torque

Tighten all wheel nuts in two stages.

1. Tighten every second nut (as shown in the diagram) to 80 Nm (60 lb/ft) until all five nuts are tightened.
2. Tighten every second nut (as shown in the diagram) to 180 Nm (133 lb/ft) until all five nuts are tightened.



# Tyres

## Tyre Loading

Tyres installed to this vehicle shall have a maximum load rating not less than 710 kg (front) and 800 kg (rear).

## Summer Tyres

***⚠ Warning: Pirelli Corsa tyres are biased towards dry road handling conditions. There is an increased risk of aquaplaning when driving on wet road surfaces and tyre grip performance is reduced when the outside temperature is below 7°C.***

*📖 The original equipment tyres installed to this vehicle are an approved specification, designated by: 'AM8' (summer tyre) and 'AM9' (winter tyre) on the sidewall.*

**Aston Martin and Pirelli recommend that Pirelli Corsa tyres are not used when using this vehicle in sustained low temperatures.**

| | Front | Rear |
|---|---|---|
| Pirelli Corsa | 255/35 ZR19 (96Y) XL | 295/30 ZR19 (100Y) XL |

## Winter Tyres

| | Front | Rear |
|---|---|---|
| Pirelli Sotto Zero | 235/40 R19 (96W) XL | 275/35 R19 (100W) XL |

***⚠ Warning: When winter tyres are fitted, the maximum speed limit of the vehicle could be reduced. Winter tyre speed limits and information should be provided upon installation of the winter tyres. Please consult your Aston Martin Dealer for more information.***

## Tyre Air Pressures

**Cold Inflation[1]**

| Front | Rear |
|---|---|
| 2.5 bar | 2.5 bar |

1. All Tyres

## Bulbs

| | Rating | Type |
|---|---|---|
| Headlamp dipped beam (HID) | 35W | D1S |
| Headlamp main beam | 65W | H9 |
| Registration plate, footwell (blue) lamps | 5W | W5W |
| Door lamps | 5W | C5W |
| Boot lamps | 10W | C10W |
| Front indicator lamps | | LED |
| Side repeater | | LED |
| Reading lamps | | LED |
| High mounted stop lamp | | LED |

The rear lamp cluster is a sealed unit. If any rear cluster lamp fails to operate contact your Aston Martin Dealer.

## Vehicle Specification

### Body

Two door coupe with tailgate and 2+0 seating

Extruded aluminium bonded body structure with aluminium, magnesium alloy, composite and steel body panels.

### Towing

This vehicle is not engineered to tow any form of caravan, boat or trailer.

No towing devices are approved to install to this vehicle, other than a front towing eye to aid recovery or loading of this vehicle onto a transporter.

## Vehicle Weights

| | |
|---|---|
| **Kerb Weight**: | 1665 kg |
| **Gross Vehicle Weight (GVW)**: | 1960 kg |
| **Boot Load**: | 40 kg |


(Maximum load, evenly distributed.)


## Interior Dimensions


| | |
|---|---|
| **Effective Headroom:** | 933 mm |
| **Effective Legroom**: | 1086 mm |
| **Boot Volume**: | 239 ltr |

## Exterior Dimensions

*Ride height is measured at Gross Vehicle Weight (GVW). Dimensions shown in millimetres and inches.*



# Fluids and Capacities

## Recommended Fluids

***To achieve the required high performance of synthetic lubricants, do not mix with mineral oils.***

***Engine Oil:*** Mobil 1 0W-40. However, if this oil is not available a fully synthetic 0W-40 oil meeting the specifications detailed below can be used. No other viscosity grades or specifications are acceptable.

| Authority | Standard |
|---|---|
| API | SL / SJ / EC / CF |
| ACEA | A3 / B3 / B4 |
| ILSAC | GF3 |

***Do not mix OAT antifreeze with glycol based antifreeze.***

***Engine Coolant:*** 50% water, 50% Havoline OAT

***Gearbox and Final Drive Oil:*** Castrol BOT270A (Only available from Aston Martin Dealers.)

***Brake and Clutch Fluid:*** React Performance DOT 4

***Power Steering Fluid:*** Pentosin CHF-11S

***Air Conditioner Refrigerant:*** HFC134A

## Capacities

***Engine Sump (including filter):*** 13.1 ltr

***Engine Cooling System:*** 14 ltr


***Transaxle:*** 3.2 ltr

***Screen Washer Reservoir:*** 5.9 ltr

***Fuel Tank:*** 80.0 ltr[1]

1. Approximately 78.0 ltr usable.

ASTON MARTIN



# Service


Pre-delivery Inspection ..... A.2
Servicing ..... A.4
Service Record ..... A.7
Brake Disc Check ..... A.11
Anti Corrosion Inspection ..... A.13
Replacement of Airbag Units ..... A.14
Replacement of Seat Belt Pre-tensioners ..... A.15
Field Service Actions ..... A.15
Service Action Recalls ..... A.16

# Pre-delivery Inspection

This free series of checks is carried out on the vehicle by the Selling Dealer before delivery. The checks make sure that you receive a vehicle which matches the high quality standards set by Aston Martin Limited.

The list below applies to all Aston Martin vehicles. Your Aston Martin may or may not have all or some of the functionality listed.

Make sure that the entry is stamped and signed as completed. The following checks will be made:

## Levels and Leaks

- Engine oil
- Power steering oil
- Brake fluid
- Clutch fluid
- Engine coolant level
- Engine coolant specific gravity
- Windscreen washer fluid
- Fuel system
- Transaxle leak check
- Lift glass
- Battery.

## Mechanical Functions

- Gear selection
- Clutch operation
- Throttle pedal operation
- Park brake operation
- Steering column adjustment and lock operation
- Seat adjuster rails
- Bonnet release and catch
- Door operation and locks
- Storage compartments
- Rear view mirror
- Boot release and catch
- Lift glass release and catch
- Seat belt operation.

## Electrical Checks

- Battery condition
- Gear selection
- Heated rear window
- Windscreen and headlamp washers
- Windscreen wipers
- Climate control
- Infotainment centre operation
- All speakers
- Reversing, registration plate and brake lamps
- Side and headlamps
- Rear fog lamps
- Hazard warning lamps
- Instrument illumination and dimmer
- Gauges and warning symbols
- Centre stack controls
- Horns
- Reset clock
- Blower motor
- Seat belt warning system
- Security system and vehicle key
- Interior lamps
- Cigar lighter (Option)
- All seat functions
- Door window mechanisms
- Door and boot lamps
- Central locking system
- Filler flap lock operation
- Clutch pedal start inhibit

- Door mirror adjustments
- Interrogate fault codes
- Record battery open-circuit voltage
- Tyre pressure sensing
- Centre console controls.

### Wheels and Tyres

- Install locking road wheel nuts (option)
- Check road wheel nuts torque
- Tyre pressures
- Tyre orientation.

### Road Test

- Engine
- Clutch
- Transaxle
- Steering
- Brakes
- Wheel balance
- Adaptive dampers
- Dampers
- Exhaust by-pass system
- Gear shift operation
- Noise, vibration or harshness
- Climate control performance
- Instruments operation
- Seat belt and buckle operation
- Steering wheel alignment
- Dynamic stability control, traction control, adaptive damping and anti-lock braking system operation
- Transmission oil cooler.

### Final Checks

- Drive belt tensioner operation
- Fuel and brake pipe security
- Fuel and fluid leaks
- Security of cooling hoses
- Exhaust catalyst security.

### Hand-over Preparation

- Check function of locks and vehicle keys
- Clean bodywork and road wheel arch liners.
- Clean off all transit labels
- Valet vehicle
- De-grease windscreen
- Install carpets
- Remove interior protection
- Check owner's guidebook
- Check tools
- Install registration plates
- Tyre sealant kit
- Towing eye
- Battery conditioner (option)
- Field service actions and recall status.

**Free Pre-delivery Inspection**

| | |
|---|---|
| Service Actions Checked: | Yes/No |
| Open Service Actions Completed: | Yes/No |
| Date: | |
| Signature: | |

## Service Periods

Vehicle servicing is every 10,000 miles or 12 months, which ever occurs first.

- 10,000 mile or 12 months
- 20,000 mile or 24 months
- 30,000 mile or 36 months.

## Service Tables

The following service schedules are recommended for this vehicle. The schedules may be modified if necessary. Please consult your Aston Martin Dealer for details of any service schedule updates.

| 10,000 miles / 12 months | 20,000 miles / 24 months | Item |
|---|---|---|
| **Pre Maintenance Work** | | |
| | | Install the vehicle protection kit. |
| | | Check the diagnostic codes. |
| **Under Body** | | |
| x | x | Examine the condition, operation and attachment of the engine, transmission mounting system and check for leaks. |
| x | x | Examine the condition, operation and attachment of the exhaust system, heat shields, bypass valve operation and check for leaks. |
| x | x | Examine the condition, operation and attachment of the suspension and steering system for wear, and check for leaks. |
| x | x | Examine the condition, operation and attachment of the braking system for wear and adjustment, and check for leaks. |
| x | x | Examine the condition, operation and attachment of the park brake system for wear and adjustment. |
| x | x | Examine the condition, operation and attachment of the drive shafts. |
| x | x | Examine the condition, operation and attachment of the wheel arch liners and under body protection. |
| x | x | Examine the condition, operation and attachment of the cooling pack assembly, and check for leaks. |

| 10,000 miles / 12 months | 20,000 miles / 24 months | Item |
|---|---|---|
| x | x | Examine the condition, operation and attachment of all under body fluid lines and check for leaks. |
| 5 Years | | Replace engine coolant. |
| | x | Check and adjust the oil level in the manual transaxle. |
| 40,000 mls/64,000 km | | Replace the oil and clean the filter in the manual transaxle. |
| | x | Check and adjust the oil level in the automatic differential. |
| 40,000 mls/64,000 km | | Replace the oil and clean the filter in the automatic differential. |
| x | x | Replace the brake fluid. |
| **Upper Body** | | |
| x | x | Replace the engine oil. |
| x | x | Replace the engine oil filter. |
| 20,000 mls/32,000 km | | Replace the pollen filter and air filter (optional). |
| 32,000 mls/48,000 km | | Replace the pollen filter and air filter (optional). |
| x | x | Examine the condition, operation and attachment of the accessory drive belt. |
| x | x | Examine the condition, operation and attachment of the power steering system, and check for leaks. |

| 10,000 miles / 12 months | 20,000 miles / 24 months | Item |
|---|---|---|
| x | x | Examine the condition, operation and attachment of the brake system, and check for leaks. |
| x | x | Examine the condition, operation and attachment of the fuel system, and check for leaks. |
| x | x | Examine the condition, operation and attachment of the air conditioning system, and check for leaks. |
| x | x | Check all power steering system fluid levels and adjust accordingly. Check for leaks. |
| x | x | Check all braking system fluid levels and adjust accordingly. Check for leaks. |
| x | x | Check all cooling system fluid levels and adjust accordingly. Check for leaks. |
| x | x | Check all screen and headlight wash system fluid levels and adjust accordingly. Check for leaks. |
| 70,000 mls/112,000 km | | Replace the spark plugs. |

| 10,000 miles / 12 months | 20,000 miles / 24 months | Item |
|---|---|---|
| **General** | | |
| x | x | Examine the condition, operation and attachment of all the occupant restraint systems. |
| x | x | Examine the condition, operation and attachment of all the door locks, latches, hinges, bonnet catches and lubricate them. |
| x | x | Examine the condition, operation and attachment of the wiper blades and wash system including headlights. |
| x | x | Examine the condition, operation and attachment of all the light units and the horn. |
| x | x | Examine the condition of the road wheels and check the wheel nut torque. |
| x | x | Complete a tyre report and adjust the tyre pressures as required. |
| x | x | Complete the tyre pressure sensor system functional test. |
| x | x | Reset the service interval indicator. |

| 10,000 miles / 12 months | 20,000 miles / 24 months | Item |
|---|---|---|
| **Road Test** | | |
| x | x | Check the powertrain system for excessive noise, vibration and harshness. |
| x | x | Check the braking system for excessive noise, vibration and harshness. |
| x | x | Check the suspension system for excessive noise, vibration and harshness. |
| x | x | Check the steering system for excessive noise, vibration and harshness. |
| x | x | Check the wheels and tyres for excessive noise, vibration and harshness. |
| x | x | Check the cabin environment for excessive noise, vibration and harshness. |
| x | x | Check the driver information and warning system operation. |

## Service Record

The following service records cover the regular services at 10,000 miles or 12 months intervals, which ever occurs first. Make sure that at each service the appropriate entry is stamped and signed as completed.

***Vehicle Identification Number (VIN):***

_____

***Date of Delivery:***

_____

| 10,000 Miles or 12 Months | | |
|---|---|---|
| Odometer: | | |
| Service Actions Checked: | | Yes / No |
| Open Service Actions Completed: | | Yes / No |
| Air Filter Changed: | | Yes / No |
| Pollen Filter Changed: | | Yes / No |
| Manual Transmission Oil Changed: | | Yes / No |
| Auto Differential Oil Changed: | | Yes / No |
| Coolant Changed: | | Yes / No |
| Spark Plugs Changed: | | Yes / No |
| Signature: | Date: | |

| 20,000 Miles or 2nd Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: Date: | |

| 30,000 Miles or 3rd Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: Date: | |

| 40,000 Miles or 4th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: Date: | |

| 50,000 Miles or 5th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: Date: | |

| 60,000 Miles or 6th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: Date: | |

| 70,000 Miles or 7th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: Date: | |

| 80,000 Miles or 8th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: | Date: |

| 90,000 Miles or 9th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: | Date: |

| 100,000 Miles or 10th Year | |
|---|---|
| Odometer: | |
| Service Actions Checked: | Yes / No |
| Open Service Actions Completed: | Yes / No |
| Air Filter Changed: | Yes / No |
| Pollen Filter Changed: | Yes / No |
| Manual Transmission Oil Changed: | Yes / No |
| Auto Differential Oil Changed: | Yes / No |
| Coolant Changed: | Yes / No |
| Spark Plugs Changed: | Yes / No |
| Signature: | Date: |

## Brake Disc Check

At each brake pad change (per axle), the ceramic brake discs are required to be cleaned, dried and weighed. Record the date of each brake pad change and disc weight.

**Brake Pads Changed - Brake Discs Checked**

| | | |
|---|---|---|
| Disc Weight (Front Axle): | kg | kg |
| Disc Weight (Rear Axle): | kg | kg |
| Odometer: | | |
| Signature: | Date: | |

**Brake Pads Changed - Brake Discs Checked**

| | | |
|---|---|---|
| Disc Weight (Front Axle): | kg | kg |
| Disc Weight (Rear Axle): | kg | kg |
| Odometer: | | |
| Signature: | Date: | |

**Brake Pads Changed - Brake Discs Checked**

| | | |
|---|---|---|
| Disc Weight (Front Axle): | kg | kg |
| Disc Weight (Rear Axle): | kg | kg |
| Odometer: | | |
| Signature: | Date: | |

**Brake Pads Changed - Brake Discs Checked**

| | | |
|---|---|---|
| Disc Weight (Front Axle): | kg | kg |
| Disc Weight (Rear Axle): | kg | kg |
| Odometer: | | |
| Signature: | Date: | |

**Brake Pads Changed - Brake Discs Checked**

Disc Weight (Front Axle): kg kg

Disc Weight (Rear Axle): kg kg

Odometer:

Signature: Date:

**Brake Pads Changed - Brake Discs Checked**

Disc Weight (Front Axle): kg kg

Disc Weight (Rear Axle): kg kg

Odometer:

Signature: Date:

**Brake Pads Changed - Brake Discs Checked**

Disc Weight (Front Axle): kg kg

Disc Weight (Rear Axle): kg kg

Odometer:

Signature: Date:

**Brake Pads Changed - Brake Discs Checked**

Disc Weight (Front Axle): kg kg

Disc Weight (Rear Axle): kg kg

Odometer:

Signature: Date:

**Brake Pads Changed - Brake Discs Checked**

Disc Weight (Front Axle): kg kg

Disc Weight (Rear Axle): kg kg

Odometer:

Signature: Date:

**Brake Pads Changed - Brake Discs Checked**

Disc Weight (Front Axle): kg kg

Disc Weight (Rear Axle): kg kg

Odometer:

Signature: Date:

## Anti Corrosion Inspection

**Anti Corrosion Inspection 1st Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 2nd Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 3rd Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 4th Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 5th Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 6th Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 7th Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 8th Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 9th Year**

Odometer:

Date:

Signature:

**Anti Corrosion Inspection 10th Year**

Odometer:

Date:

Signature:

## Replacement of Airbag Units

Every 10 years from the date of vehicle registration, all airbag units must be replaced. To make sure this is completed correctly and safely, this work should be carried out by your Aston Martin Dealership.

**Airbag Replacement 10th Year**

Odometer:

Date:

Signature:

## Replacement of Seat Belt Pre-tensioners

Every 10 years from the date of vehicle registration, all seat belt pre-tensioners must be replaced. To make sure this is completed correctly and safely, this work should be carried out by your Aston Martin Dealership.

**Seat Belt Pre-Tensioners Replacement 10th Year**

Odometer:

Date:

Signature:

## Field Service Actions

| Action No. | Date | Dealer | Action No. | Date | Dealer |
|---|---|---|---|---|---|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

## Service Action Recalls

| Action No. | Date | Dealer |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| Recall No. | Date | Dealer |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| Recall No. | Date | Dealer |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

# Additional Service Notes

| Recall No. | Date | Dealer | Additional Notes | Additional Notes |
|---|---|---|---|---|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

**Additional Notes**

# Aston Martin Warranty


Vehicle Warranties ..... B.2
Warranty Period ..... B.2
Who May Repair the Vehicle ..... B.3
Wear and Tear Items ..... B.3
What is Not Covered ..... B.4
Customer Responsibility ..... B.5
Warranty Coverage when Touring ..... B.6
Aston Martin Extended Warranty ..... B.6
Consumer Law ..... B.6
Owner Details ..... B.7
Vehicle Details ..... B.7
Owner Warranty Transfer (3) ..... B.9
Owner Warranty Transfer (2) ..... B.9
Owner Warranty Transfer (1) ..... B.9
Owner Warranty Transfer (6) ..... B.11
Owner Warranty Transfer (5) ..... B.11
Owner Warranty Transfer (4) ..... B.11




## Vehicle Warranties

Aston Martin gives a Warranty for each new Aston Martin vehicle and each replacement vehicle or assembly manufactured or supplied by the Company to be free from defects in material and workmanship under normal use and service for the applicable Warranty period.

The warranties provided herein are for the benefit of the original purchaser and any subsequent owner during the relevant Warranty Period (defined below) in the Serviced Countries (defined below).

An Aston Martin vehicle is built and homologated to support the Region for which it is manufactured and is compliant with the local regulatory requirements of that Region. As a result, the warranties cover Aston Martin vehicles that are built for and supplied to the Region.

For the purposes of this Owner's Guide, Region means one of the following territories:

- the Americas, including the United States, Canada, and South America; or
- the United Kingdom, Europe, Russia and South Africa; or
- the Middle East, North Africa and India; or
- Asia Pacific, including China, Japan, Taiwan, Hong Kong, Singapore, Australia and New Zealand.

**'Serviced Countries'** means either: (a) any country in the Region from which your Aston Martin vehicle was purchased, where there is an Aston Martin authorised dealer or repairer; or (b) any country agreed in writing with Aston Martin.

*Tyres are covered separately by the tyre manufacturer. Dealers are expected to offer assistance to the customer in pursuing a claim against the tyre manufacturer.*

### Exchange Parts Under Warranty

New parts will only be used for repairs at PDI and during the first three months or 5000 km/3000 miles (which ever occurs first) from the date the vehicle is handed over to the first retail customer. Thereafter exchange parts must be used where available under Aston Martin's exchange plan.

### Anti Perforation Corrosion Protection Warranty

The vehicles bodywork is protected by an Anti Perforation Corrosion Warranty. Should any part of the bodywork of the Aston Martin vehicle be perforated, the panel(s) affected by the perforation will be repaired or replaced.

The term 'perforation' means a hole that penetrates through a body panel from the inside.

## Warranty Period

The period of cover for all types of warranty commences on the day the vehicle is handed over to the first registered keeper of the car (first registered keeper shall mean the Dealer in the context of demonstration vehicles).

The Vehicle Warranty period of cover is three years with unlimited mileage.

The Anti Perforation Corrosion Warranty period of cover is ten years with unlimited mileage.

## Who May Repair the Vehicle

Franchise holders or Approved Repairers, who are appointed and receive full technical support from Aston Martin, provide facilities for the servicing and repair of Aston Martin motorcars. Only such Franchise Holders or Approved Repairs will under the terms of this warranty, repair replace or readjust, free of charge to the owner, any part or assemble proved to Aston Martins satisfaction to show a defect in materials or workmanship within the applicable period.

## Wear and Tear Items

Items that are subject to wear and tear are generally divided into two categories, namely those specified for replacement or adjustment during scheduled maintenance and those that require replacement or adjustment dependent upon conditions of use.

### Scheduled Maintenance Items

The items listed below are covered by the Vehicle Warranty up to the first scheduled change point that replacement or adjustment is required during scheduled maintenance operations. The customer literature supplied with the new Vehicle includes a service book setting out such scheduled maintenance operations.

- Drive belts
- Spark plugs
- Oil, air, pollen and fuel filters.

*The period of warranty cover for any item may not exceed the time and distance limitation of the vehicle warranty.*

### Wear and Tear Items

The items listed below are recognised as having a limited service life or are subject to wear or damage. However, these items are covered by the vehicle warranty for up to one year or the first service, which ever occurs first.

- Wiper blades.
- All light bulbs.
  HID headlamp bulbs and instrumentation illumination bulbs are covered by the full vehicle warranty.
- Wheel alignment and balancing.
- Adjustments, including but not limited to: headlamp and hinged panel adjustments, suspension tightening, steering geometry adjustments, emission and fuel systems checks and park brake cable adjustments.
- Remote handset batteries.

*Brake pads, brake discs, clutches and other friction related components are not covered when replacement is due to wear and tear, but they are covered against manufacturing defects (whether in material or workmanship) for the duration of the Vehicle Warranty.*

# What is Not Covered

## Consumables

Replacement or top up of consumable fluids, e.g. oils, antifreeze, brake fluid, windscreen wash solution and refrigerant, will only be covered when they are used as part of a warranty repair.

## Vehicle Warranty

Aston Martin is **not** responsible for any repair or replacement that is required as a direct result of:

- Normal wear and tear.
- Friction related components, e.g. clutch, brake pads and brake discs.
- Failure to properly maintain the vehicle in accordance with Aston Martin's maintenance schedules and service instructions.
- Failure to use Aston Martin specified parts or fluids during a warranty repair (or parts of equivalent quality during a retail repair).
- Damage resulting from neglect, accident, flooding or improper use.
- Any modification of the vehicle or parts which is not authorised by Aston Martin, including any engine performance enhancement modifications.
- Refilling or topping up with incorrect fuel, e.g. diesel instead of petrol.
- Use of bio ethanol alternative fuels.
- Use of a fuel not approved or recommended by Aston Martin in the Owner's Guide is considered misfuelling, and that any damage resulting from misfuelling is not covered by the vehicle warranty.
- Defects caused as a result of the vehicle being used in motor sport or track events or for any other purpose other than normal private or commercial use.
- Any vehicle that has had its vehicle identification number altered or removed, or on which the odometer reading has been unlawfully altered.

# Customer Responsibility

## Paint Surface and Corrosion Protection

Aston Martin is not responsible for any repair or replacement that is required as a direct result of the following:

- Failure to properly maintain paint and bodywork by regular cleaning in accordance with Aston Martin instructions.
- Factors beyond Aston Martin's control, such as environmental hazards (including industrial fallout, storm damage, acid rain) and damage (including stone chips, scratches and use of unsuitable cleaning agents).
- Accident repairs using materials or methods of repair that have not been approved by Aston Martin.
- Alterations of the vehicle from Aston Martin's original specification.
- Failure to rectify on a timely basis any paint or corrosion damage as recorded in the vehicle documentation by a dealer at the time of the annual inspection.

## Other Exclusions

The Aston Martin warranty excludes liability for any lost time, inconvenience, loss of transportation, or any other incidental or consequential damage you (or anyone else) may incur as a result of a defect covered by this warranty.

The customer literature will describe the proper care and use of the vehicle. Proper maintenance and use guard against major repair expenses resulting from misuse, neglect or inadequate maintenance, and may help increase the value that the customer may receive when selling the vehicle.

The Customer is responsible to:

- Make sure that the vehicle is maintained in accordance with the vehicle service and maintenance guide published in the customer literature.
  Failure to perform maintenance promptly and in accordance with Aston Martin's specified service intervals will invalidate warranty coverage on the parts affected.
- The customer is required to take the vehicle to a dealer for any warranty repairs as soon as practicable after a defect is detected.
- Make sure that the Service and Maintenance schedule has been stamped by the servicing dealer after the completion of a scheduled service operation.
- Make sure that paint and bodywork is maintained by regular cleaning in accordance with the vehicle manufacturer's instructions.
- Make sure that the body panels are examined annually by an authorised Aston Martin Dealer and that this inspection is recorded in the Owners Guide.

## Warranty Coverage when Touring

Aston Martin has a comprehensive service network in most parts of the world. Any authorised Aston Martin dealer can carry out repairs under the terms of the vehicle warranty. Under normal circumstances, the customer should not be required to pay for any warranty work performed by an Aston Martin dealer.

It is the customer's responsibility to produce the warranty documentation issued with the new vehicle. This establishes the customers right to warranty coverage and the relevant maintenance and service records. If the customer is unable do so, the dealer should seek advice from Aston Martin.

## Aston Martin Extended Warranty

Aston Martin Extended Warranty is specifically designed to provide the customer with first class after-sales protection from unexpected repair costs when the vehicle warranty has expired, and the knowledge that your Aston Martin will be repaired by trained technicians using only genuine Aston Martin parts.

Contact your Aston Martin Dealer for more information on the benefits and protection provided by the Aston Martin Extended Warranty.

## Consumer Law

The Warranty is a manufacturer's warranty that supplements and does not affect the Owner's legal rights under the vehicle purchase agreement or under applicable national legislation governing the sale of consumer goods.

## Owner Details

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

Signature:

Date:

Dealer Stamp

## Vehicle Details

**Registration Plate No.:**

**VIN No.:**

**Engine No.:**

**Warranty Start Date:**

If the vehicle is sold, the benefits of any un-expired portion of the warranties can be transferred to the new owner.

The new owner should complete a 'tear off' sheet (next page) and send the new details to:

Aston Martin Warranty Department,
Aston Martin Lagonda Limited,
Banbury Road,
Gaydon,
Warwick,
CV35 0DB,
England

ASTON MARTIN


ASTON MARTIN


ASTON MARTIN

## Owner Warranty Transfer (3)

**Registration Plate No.:**

**VIN No.:**

**Odometer:**

**Date of Purchase:**

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

**Telephone No.:**

**Signature:**

**Date:**

## Owner Warranty Transfer (2)

**Registration Plate No.:**

**VIN No.:**

**Odometer:**

**Date of Purchase:**

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

**Telephone No.:**

**Signature:**

**Date:**

## Owner Warranty Transfer (1)

**Registration Plate No.:**

**VIN No.:**

**Odometer:**

**Date of Purchase:**

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

**Telephone No.:**

**Signature:**

**Date:**

ASTON MARTIN


ASTON MARTIN


ASTON MARTIN

## Owner Warranty Transfer (6)

**Registration Plate No.:**

**VIN No.:**

**Odometer:**

**Date of Purchase:**

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

**Telephone No.:**

**Signature:**

**Date:**

## Owner Warranty Transfer (5)

**Registration Plate No.:**

**VIN No.:**

**Recorded Mileage (mile):**

**Date of Purchase:**

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

**Telephone No.:**

**Signature:**

**Date:**

## Owner Warranty Transfer (4)

**Registration Plate No.:**

**VIN No.:**

**Odometer:**

**Date of Purchase:**

**Name:**

**Address:**

**:**

**:**

**:**

**Post Code:**

**Telephone No.:**

**Signature:**

**Date:**

ASTON MARTIN


ASTON MARTIN


ASTON MARTIN

# Aston Martin Assistance


Emergency Assistance ..... C.2
Benefits ..... C.3
Alternative Travel Arrangements ..... C.4
What To Do In An Emergency ..... C.6
European Autoroute Restrictions ..... C.7
What is not Covered ..... C.7
Schedule - Eligible Vehicles ..... C.10

# Emergency Assistance

As the owner of an Aston Martin vehicle you should enjoy a high standard of trouble free motoring. However, should the unexpected occur, our worldwide Dealer network is there to help you. Details and contact telephone numbers are shown in the Dealer Directory. In the UK and specific countries within Europe, a special additional emergency service, known as '**Aston Martin Emergency Assistance**', has been designed to provide you and your passengers with the help you need quickly and efficiently should your vehicle suffer a Breakdown Incident [1].

## Vehicles Covered

The benefits of Aston Martin Emergency Assistance are applicable to new and / or used Aston Martin vehicles purchased from an authorised Aston Martin Dealer. Refer to www.astonmartin.com for a list of all authorised Aston Martin Dealers.

1. A **Breakdown Incident** means an event where an eligible Vehicle is immobilised due to a breakdown in circumstances where it qualifies for Aston Martin Emergency Assistance, including home-starts or broken glass. Furthermore, Aston Martin Emergency Assistance covers you in the event of safety-related defects, which render the Vehicle illegal to drive. These defects relate to, for example, failure of the seat belts, windscreen wipers, direction indicators, front and rear lamps.

At completion of your purchase, your Aston Martin Dealer will register your vehicle for Aston Martin Emergency Assistance. From registration, your vehicle will be entitled to Aston Martin Emergency Assistance (the '**Vehicle**'). For more details of what constitutes an eligible Vehicle, please refer to the Schedule.

An eligible Vehicle is entitled to receive Aston Martin Emergency Assistance for a period of 36 months from the date of registration with the service provider. Owners of eligible Vehicles can also obtain Aston Martin Emergency Assistance when travelling temporarily outside their Country [2], within Europe.

## Europe is defined as:

Andorra, Austria, Belgium, Bosnia-Herzegovina, Bulgaria, Crete, Croatia, Czech Republic, Denmark, Estonia, Finland, France, Germany, Gibraltar, Greece, Hungary, Italy, Latvia, Liechtenstein, Lithuania, Luxembourg, Monaco, Netherlands, Norway, Poland, Portugal (not Madeira), Republic of Ireland, Romania, Russia, San Marino, Slovakia, Slovenia, Spain (including the Balearic Islands and Canary Islands), Sweden, Switzerland, Turkey (European Part), Ukraine, and Vatican City.

2. '**Country**' means the country in which your Vehicle is registered.

## United Kingdom (UK) is defined as:

England, Scotland, Wales, Northern Ireland, Channel Islands and Isle of Man.

## Benefits

The service provider, appointed by Aston Martin to provide the Aston Martin Emergency Assistance services (the 'Service Provider') will provide the following benefits dependent on requirements to entitled Vehicles in both the home Country and Europe as defined.

### Roadside Assistance

The Service Provider's Agent vehicle should promptly arrive with you after your call has been placed. You may also book an appointment for a convenient time.

Aston Martin Emergency Assistance shall provide you with updates on its estimated time of arrival via your preferred communication method.

If following a Breakdown Incident in an area of coverage, your journey cannot be completed, and where the Vehicle cannot be repaired at the roadside, Aston Martin Emergency Assistance shall organise recovery of the Vehicle, including any luggage contained in the Vehicle at the time. Your Vehicle and luggage shall be transported to the nearest Aston Martin Dealer, without distance or financial limitation.

If the Vehicle cannot be repaired at the roadside or at your home address within a reasonable time period (45 minutes), the Service Provider will take you, the Vehicle and your passengers to the nearest Aston Martin Dealer. In the event that you (or your passengers) need to keep an important appointment, you will be taken there before the disabled Vehicle is transported to its required destination.

Should the Breakdown Incident occur outside of workshop hours, Aston Martin Emergency Assistance shall arrange for secure storage of the Vehicle until the next working day. The Vehicle shall arrive at the Dealer by midday on the next day.

If the nearest Dealer, to where the eligible Vehicle has been towed, is able to carry out the repairs at its premises, then the Vehicle will be repaired there.

Once the Vehicle is at a Dealership for repair, Aston Martin Emergency Assistance will keep in contact with the Dealer to follow the progress of the repair, and if necessary, arrange any extension of a replacement vehicle with Aston Martin Customer Service.

### Home Start

Aston Martin Emergency Assistance will provide all the benefits of Roadside Assistance at the Vehicle's registered address.

### Recovery

If Aston Martin Emergency Assistance cannot repair your Vehicle at the roadside, the Service Provider will arrange recovery of you and your Vehicle to the nearest Aston Martin Dealer.

If your Vehicle has been involved in an accident or has gone off the road and needs to be salvaged before towing, Aston Martin Emergency Assistance will charge you for services on a 'Pay for Use' basis and you may be able to claim these back from your insurance company.

You will be covered for costs of recovery and towing (including any handling fee) but you may be charged for any costs incurred if the Vehicle is, for example, disabled by floods or snow-affected roads, is embedded in sand or mud, or is not easily accessible.

If your Vehicle cannot be repaired and / or recovery is initiated to an Aston Martin Dealer, the Service Provider will provide alternative travel options for you. You will be entitled to receive one of the following additional services:

a) A replacement vehicle for up to two working days in your Country, or 14 days if the Breakdown Incident occurs outside your Country (a collection and delivery service, or equivalent, is available from chosen suppliers subject to availability and supplier's terms and conditions);

b) Onward transportation; or

c) Overnight accommodation.

### Vehicle Collection Following Repair

Following repairs organised by Aston Martin Emergency Assistance, the cost of a first class rail ticket or (if rail transport would normally exceed six hours) a business class air ticket will be met to permit you or a person you designate to collect the repaired Vehicle. Alternatively, arrangements can be made for your Vehicle to be returned to your home or business address, whichever is the nearest to the repairing Dealer. Alternative addresses closer to the repairing Dealer may also be considered.

If the Service Provider estimates that the repairs to your Vehicle will take more than eight hours, the Aston Martin Emergency Assistance will cover your reasonable costs for alternative necessary travel, including for members of your party.

Reasonable additional expenses shall be covered for one or a combination of the following:

- Replacement vehicle costs to a maximum of two working days in your Country and up to 14 days outside your Country.
- Air fares (business class ticket).
- Rail fares (first class ticket).
- Local taxi fares.
- Any other transport equivalent to first class rail fares.

### Replacement Vehicle

If following a Breakdown Incident:

- Your Vehicle is immobilised.
- Roadside repairs are unsuccessful.
- If repair of the Vehicle is not possible within the same day after towing to the Dealer.

Aston Martin Emergency Assistance will organise free of charge, a replacement vehicle for you until completion of the repairs. The replacement vehicle will include fully comprehensive insurance [1], with an option to upgrade to include collision damage waiver.

The loan of this replacement vehicle will not exceed two working days (in your Country) or, if the Breakdown Incident occurred outside your Country, 14 days plus two working days after your return to your home country.

Aston Martin Emergency Assistance aim to make sure that the replacement vehicle is a suitable vehicle for you. A priority for the choice of the replacement vehicle is a hire car of category G or equivalent, where available. Specially adapted replacement vehicles will not be provided.

The replacement vehicle will be delivered to you, where possible, but if you prefer, taxi costs for collecting the replacement vehicle, will be met by Aston Martin Emergency Assistance.

1. Unless the driver is under 21 years of age, where there may be an additional charge incurred.

You will be responsible for fuelling and basic maintenance of the replacement vehicle, while under your care. You will also be responsible for paying any deposit required by the vehicle Hire Company.

Once the repair on your Vehicle is complete, the replacement vehicle will then either be returned to the vehicle Hire Company or collection will be arranged where possible, at your request.

If the replacement vehicle has been kept beyond the term of the permitted loan period (as noted above), you will be responsible for any additional charges incurred for the extended period. If you cannot fulfil the nominated vehicle Hire terms and conditions, or circumstances prevent you from qualifying to hire the vehicle, and alternative mobility arrangements are more appropriate, then onward travel arrangements or hotel accommodation will be provided instead. The vehicle hire agreement will be between you and the relevant supplier and will be subject to that supplier's Terms and Conditions. These will usually require or include (amongst other things):

- Production of a full driving licence valid at the time of issue of the hire vehicle.
- Limits on acceptable endorsements.
- Limitations on the availability and, or engine capacity of the replacement vehicle.
- A deposit, e.g. for fuel.
- Drivers to be aged at least 21 years depending on Country, and to have held a full driving licence for at least 12 months.

## Onward or Home Journey

If following a Breakdown Incident that occurs more than 80 km (50 miles) from your place of residence, your Vehicle cannot be repaired at the roadside on the same day of the Breakdown Incident, Aston Martin Emergency Assistance will cover:

- The costs of the journey from the place of the Breakdown Incident to the nearest Dealer.
- The costs of a replacement vehicle as outlined above.
- Where necessary, taxi costs for one journey to the nearest accessible train station or airport, for you and your passenger(s).
- Where necessary, the costs of a first class train journey for you and your passenger(s). If the train journey exceeds six hours, the cost of a scheduled flight (Business Class) for you and your passenger(s).

Aston Martin Emergency Assistance will reimburse you for reasonable costs incurred relating to the above, upon receipt of a claim letter from you, detailing the circumstances of the claim, along with receipts for all transport costs claimed. All claim letters must be directed to Aston Martin Emergency Assistance at Aston Martin Customer Service, Aston Martin Lagonda Limited, Banbury Road, Gaydon, Warwick, CV35 0DB. Only costs directly connected with the Breakdown Incident will be covered.

The refund process to you shall be managed by Aston Martin Emergency Assistance.

## Repaired Vehicle Re-delivery

Aston Martin Emergency Assistance will attempt to contact you within 24 hours of successful repair at the Dealer in order to arrange re-delivery of the repaired Vehicle to either your home or place of work, as you request. Alternative addresses closer to the Repairing Dealer may also be considered.

## Hotel

If following a Breakdown Incident that occurs more than 80 km/50 miles from your place of residence, and your Vehicle cannot be repaired at the roadside on the day of the Breakdown Incident, accommodation costs for you and your passenger(s) shall be covered for the duration of the repair, for up to a maximum of two nights if the Breakdown Incident occurs in your Country, or seven nights if the Breakdown Incident occurs outside your Country. You shall be responsible for any excess costs.

## Repatriation of Un-repaired Vehicle from Abroad

If the Vehicle cannot be repaired by Aston Martin Emergency Assistance within an agreed time schedule (three working days), the costs for transporting the Vehicle and its contents from the Dealer to the home Country Dealer, will be covered by Aston Martin Emergency Assistance.

Aston Martin Emergency Assistance shall arrange the safe repatriation of the Vehicle at the least cost, while respecting the need to deliver the Vehicle to the home Dealer within 14 consecutive days.

Aston Martin Emergency Assistance will cover the costs for parking the Vehicle, pending repatriation or import.

Should assistance be required in the unlikely event of a Breakdown Incident, simply contact Aston Martin Emergency Assistance using the relevant telephone number listed below.

*It may be helpful to have the relevant telephone numbers entered into your mobile phone 'phone book'.*

00 800 28 86 28 86 [1]

+44 208 603 9875

When connected, enter the 2 digit number as prompted for your home country. Please do not make your own arrangements as Aston Martin Emergency Assistance will be not be able to reimburse you. If you are in a remote location and need assistance, the time taken to receive the assistance may be longer because of distance and local restrictions.

1. Calls from landlines shall be free. Calls from mobile phones will be charged at standard mobile network rates.

## Vehicle Identification and Location

To minimise delay, please have the following information available:

- Your name.
- Aston Martin model.
- The Vehicle Identification Number (VIN). The last six digits from the VIN label in the corner of the windscreen.
- The location of the vehicle.
- Vehicle registration number and colour.
- Telephone number where you can be contacted.
- Description of the concern experienced.

## European Autoroute Restrictions

If assistance is required on a French Autoroute or on certain Autoroutes in other European countries, you must use the official SOS boxes at the side of the road in order to arrange initial assistance or recovery. You will be connected to the authorised Autoroute Assistance Service because these roads are privatised. Neither Aston Martin Emergency Assistance nor any other assistance organisations are allowed to assist on these roads.

Once your Aston Martin has been recovered from the Autoroute, you should contact Aston Martin Emergency Assistance at the earliest opportunity to make sure that any further assistance arrangements you require can be made on your behalf.

Aston Martin Emergency Assistance will advise you how to reclaim costs incurred for recovery from the Autoroute.

## What is not Covered

Aston Martin Emergency Assistance is thorough and comprehensive; however, claims cannot be met as a result of any of the following:

1. Where you, or anyone else acting on your behalf, make repair or service arrangements without authorisation (and a file number) from Aston Martin Emergency Assistance.
2. Where any loss, theft, damage, death, bodily injury, cost or expense that is not directly associated with the incident that caused you to claim, unless expressly stated in this policy.
3. If the Breakdown Incident is due to fire, theft, accident or vandalism, your costs will not be covered by Aston Martin Emergency Assistance but should be met by third party insurance covering the incident.
4. Damage or injury intentionally caused by you or resulting from your participation in a criminal offence.
5. If your Vehicle is kept in an un-roadworthy condition or has not been serviced in accordance with the Manufacturer's recommendations.
6. Any costs that would have been payable by you, such as petrol, toll charges, parking fees, cost of meals, drinks, telephone calls and/ or newspapers or any other costs not specifically stated as being covered by Aston Martin Emergency Assistance, which may be incurred by you and/ or the other member(s) of your party as a result of and/ or in connection with the Breakdown Incident.
7. Release fees: Should your Vehicle be stolen and subsequently recovered by the police, you may be asked to pay a release fee before we can remove your Vehicle to an authorised Aston Martin Dealer.
8. Specialist charges: In the event that the use of specialist equipment is required to give assistance when your Vehicle has, for example, gone off the road, is in a ditch, is standing on soft ground, sand, shingle, stuck in water or snow or has been immobilised by the removal of its wheels, we will arrange recovery but you will be responsible for the costs of any specialist equipment required. The costs may be refundable under the terms of your motor insurance policy.

9. Adverse weather conditions: On those occasions when we experience adverse weather conditions, such as high winds, snow, floods, etc., external resources may be stretched and some operations become physically impossible until the weather improves. At such times, our priority is to make sure that you and your passengers are taken to a place of safety and so the recovery of your Vehicle may not be possible until weather conditions permit.
10. Customer induced breakdown incidents are not covered under Aston Martin Emergency Assistance. However, Aston Martin and the Service Provider will, at their sole discretion, assist you if you request it. However we are not obligated to provide assistance and you shall be responsible for any charges resulting from any assistance given caused by a customer induced fault. In such circumstances, a swipe card deposit maybe taken by the Service Provider. Assistance in such circumstances will not include additional benefits (replacement vehicle, onward journey, hotel accommodation). Customer– induced faults may include, for example, the following:
    - Lock-outs / lost keys
    - Broken keys
    - Discharged battery
    - Running out or loss of fuel
    - Use of wrong fuel (no replacement at the location of breakdown, only towing)
    - Tyre damage
    - Road traffic accidents.
11. Lockout / lost keys: Whilst we will always try to provide assistance by the most practical method, should you be unable to gain entry to your Vehicle, modern security systems make it extremely difficult for this to be done should spare keys not be available. If a forced entry is required, you will be asked to sign a declaration stating that you have given permission for this to take place and that any costs for resultant damage will be your sole responsibility.
12. Aston Martin Emergency Assistance shall not be required to provide services in the following circumstances:

    a) in respect of Vehicles not displaying a valid road fund licence.

    b) in respect of eligible Vehicles situated on private property (for example garage premises) unless you can establish to the reasonable satisfaction of Aston Martin Emergency Assistance that permission has been given by the relevant owner or occupier.

    c) Vehicle servicing or re-assembly where this is required as a result of neglect or unsuccessful work on the Vehicle other than on the part of the Service Provider or its agents.

    d) the recovery of any Vehicles bearing trade plates or which Aston Martin Emergency Assistance has reason to believe have just been imported or purchased at auction.

    e) the transportation of immobilised Vehicles where Aston Martin Emergency Assistance considers this to be part of a commercial activity.

f) assistance for Vehicles broken down as a result of taking part in any 'Motor Sport Event', including, without limitation, motor racing, rallying, speed or duration tests or practice thereof, trials or time-trials, auto test (other than auto tests performed by the Client using roadworthy, road legal cars on public roads), but excluding 'Concours d'elegance' events, track test days for road-legal Vehicles or rallies held exclusively on open public roads where participants are required to comply with the normal rules of the road (save for Aston Martin organised and controlled track day events).

g) where the police, highways agency and / or other emergency service require that your Vehicle be recovered by a third party.

h) where your entitlement to Aston Martin Emergency Assistance lapses or if your Vehicle is no longer considered eligible for Aston Martin Roadside Assistance, the Service Provider may charge you directly for the Services provided. Any such charges will be charged on a 'pay for use' basis and will constitute a direct contract between you and the Service Provider. If it is determined that Aston Martin is at fault for the Vehicle not being recorded as an eligible Vehicle, then Aston Martin shall pay the relevant charges.

I) assistance for routine maintenance and running repairs of the Vehicle such as fixing faulty radios, interior light bulbs and heated rear windows.

j) for transit risk insurance, which Aston Martin Emergency Assistance recommends you take out where a Vehicle is to be repatriated.

k) where locksmiths, body-glass or tyre specialists are required. Aston Martin Emergency Assistance will endeavour to arrange for their assistance on your behalf, however, you will be responsible for the costs of their services. Further, if use of a locksmith or other specialist would, in Aston Martin Emergency Assistance's opinion, mobilise the vehicle, no further service will be given for the breakdown in question.

l) the transportation of any animal or pets shall be at the sole discretion of the Service Provider.

13. The Service Provider may charge you directly for:

a) any replacement component, lubricant and / or fuel (the 'Parts') or consumable items supplied (except where Aston Martin has provided or paid for such Parts)

b) any extension of the Services which you are entitled to receive in connection with this Agreement (which shall be performed by the Service Provider (in its absolute discretion) at your request.

c) the use of any specialist lifting or towing assistance needed to recover your Vehicle if your Vehicle has gone off the road, is in a ditch, sunk in soft ground, sand or shingle or when it is stuck in snow or flood water.

d)any additional charges resulting from the failure to carry legal and serviceable spare wheel(s) or tyre(s) in the Vehicle. Aston Martin Emergency Assistance will endeavour to arrange assistance from a third party on your behalf but you will be responsible for the costs of the call out and/ or for any repair.

e) the cost of garage or other labour required to repair the Vehicle, other than that provided by Aston Martin Emergency Assistance at the scene of the Breakdown Incident.

f) any costs of draining or removing fuel, lubricants or other fluids as a result of the introduction of an inappropriate substance.

g) transportation of personal effects, goods, vehicles, boats or other waterborne craft on or in the Vehicle and any trailer or caravan. Aston Martin Emergency Assistance will not consider any claim for loss resulting from damage to / loss of use of these items. Such items remain your responsibility at all times.

14. If following a Breakdown Incident, the Service Provider, its third party garage agent or subcontractor makes a temporary repair to your Vehicle (for these purposes, a temporary repair shall mean temporary repairs of the Vehicle where the underlying cause of the Vehicle's failure is not resolved), then the Service Provider, its third party garage agent or subcontractor shall recommend you to have such temporary repair made good by a Dealer.

## Schedule - Eligible Vehicles

**New Vehicles**

Any Aston Martin vehicle which is sold directly by Aston Martin or a Dealer in the UK or European Territories and which is first registered in the UK or European Territories (as appropriate, (Refer ro page C.2)).

**Used Vehicles**

Those used vehicles registered in the UK or the European Territories in respect of which an Extended Warranty has been started.

**In All Cases**

- Maximum Gross Vehicle Weight (including any caravans or trailers being towed at the time of the Breakdown Incident): 3500 Kg
- Maximum Vehicle Length: 5.5 m
- Maximum Vehicle Width (including any caravans or trailers being towed at the time of the Breakdown Incident): 2.3 m
- Maximum Vehicle Height: 3 m

The dimensions detailed above will be calculated taking into account anything attached to the relevant eligible Vehicle at the time of the relevant Breakdown Incident and any trailer or caravan, including but not limited to towing equipment, any carriers or racks (e.g. bike or luggage), or anything else attached to the Vehicle or the carriers / racks.

Vehicles must be built to manufacturer's specifications, display a road fund licence, and where applicable, hold a certificate of roadworthiness.

ASTON MARTIN
ASTON MARTIN
ASTON MARTIN
ASTON MARTIN

ASTON MARTIN
ASTON MARTIN


ASTON MARTIN
ASTON MARTIN


ASTON MARTIN
ASTON MARTIN

# Alphabetical Index


**A**

Accessory Power Sockets ..... 3.29
Adaptive Damping ..... 5.13
Airbags ..... 3.14
  Passenger Deactivation Switch ..... 3.17
Alarm ..... 2.12
  Movement Sensor ..... 2.12
  Reduced Guard ..... 2.12
  Tilt Sensor ..... 2.12
Ambient Temperature ..... 4.16
Anti Corrosion Inspection ..... A.13
Anti-Lock Braking System ..... 5.10
Approach Light ..... 2.11
Ashtray and Cigar Lighter ..... 3.29
Aston Martin Assistance ..... C.1
Aston Martin Tracking ..... 2.2
Aston Martin Warranty ..... B.1
Audio ..... 7.1
  Battery Protection Mode ..... 7.6
  Essentials ..... 7.2
Automatic Lock ..... 2.10

**B**

Battery
  Maintenance ..... 10.18
  Protection Mode ..... 7.6
Battery Charge ..... 10.18
Battery Conditioner ..... 10.19
Battery Disposal ..... 10.18
Battery Protection Mode ..... 10.20
Bonnet Release ..... 10.6
Boot Cover ..... 3.28
Boot Lamps ..... 10.27
Boot Lid ..... 2.8
Brake Disc Check ..... A.11
Brake Pad Bedding-in ..... 10.11
Brakes
  Anti-Lock Braking System ..... 5.10
  Park Brake ..... 5.11

**C**

Cabin Storage ..... 3.26
Catalytic Converters ..... 5.15
Child Safety ..... 3.15
Child Seats ..... 3.21
  Passenger Airbag Deactivation ..... 3.17
Climate Control
  Automatic Operation ..... 6.6
  Controls ..... 6.2
  Manual Operation ..... 6.7
  Operating Tips ..... 6.2
Coat Hooks ..... 3.31
Component Location ..... 1.3
Condensation, Headlamp Units ..... 10.25
Controls
  Centre ..... 4.7
  Information and Warning Symbols ..... 4.5
  Instrument Cluster ..... 4.3
  Stalk ..... 4.11
Controls Overview ..... 4.2
Cruise Control ..... 4.15

**D**

Dangerous Substances ..... 10.4
Data Recording ..... 1.4

Day Time Running ....4.13
Deadlocking ....2.10
Defrosting and Demisting
Automatic ....6.6
Manual ....6.7
Driving Techniques ....5.2
Dynamic Stability Control ....5.11

**E**

Electric Windows ....3.30
Emergency Items ....10.4
Emotion Control Unit ....2.5
External Lamps ....10.26

**F**

Fluid Levels ....10.7
Footbrake ....5.9
Front Seat Reset ....10.28
Fuel
Catalytic Converters ....5.15
Fuel Filling ....5.14
Fuse Boxes ....10.21

**G**

Garage Door Opener ....2.14
Garage Door Opener (Option)
Operation ....2.15
Programming ....2.14
Reprogramming ....2.16
Rolling Code Synchronisation ....2.15

**H**

Hands-Free Phone ....8.1
Connecting a Phone ....8.4
Removing a Phone ....8.7
Using a Phone ....8.8
Headlamp ....10.25
Headlamp Condensation ....10.25
Homesafe ....2.11

**I**

Ignition Control ....4.9
Interior Mirrors ....3.8
Internal Lamps ....10.27

**J**

Jump Start From Another Vehicle ....10.16

**L**

Lamps ....4.13
Boot ....10.27
External ....10.26
Headlamp ....10.25
Internal ....10.27
Locking the Vehicle ....2.7
Low Outside Temperature Warning ....4.7

**M**

Maintenance ....10.1, 10.5
Vehicle Jacking ....10.3
Maintenance Items
Battery Conditioner ....10.6
Tool Kit ....10.6
Master Lamp ....4.12
Master Vehicle Lock ....2.8
Memory Seats ....3.6
Mirrors
Auto Fold Function (Door Mirrors) ....3.9
Door ....3.9
Interior ....3.8
Power Fold Function (Door Mirrors) ....3.9
Reverse Dip Function (Door Mirrors) ....3.9

**P**

Park Brake .....5.11
Parking Assist .....5.16
Passenger Airbag Deactivation .....3.16
Passive Anti-Theft System .....2.13
Personalisation
  Security .....2.16

**R**

Reading Lamps .....3.31
Replacement of Airbag Units Record ..... A.14
Replacement of Seat Belt Pre-tensioners Record ..... A.15
Restraints System .....3.10
  Determining if the System is Operational .....3.10

**S**

Safety Defects - Reporting .....1.5
Satellite Navigation .....9.1
  Find a Location .....9.7
  Navigation Map .....9.10
  Navigation System ON and OFF .....9.5
Seat Adjustment .....3.2
  Sport Seat .....3.4
Seat Adjustment - Lightweight Seat .....3.3
Seat Belts .....3.11
  Care and Maintenance .....10.32
  Child .....3.13
Seats
  Memory Function .....3.6
Security
  Personalisation .....2.16
Service Record ..... A.7
Servicing ..... A.4
Servicing Precautions .....10.3
Specifications .....11.1
  Brakes .....11.4
  Bulbs .....11.6
  Electrics .....11.3
  Engine .....11.2
  Exterior Dimensions .....11.7
  Fluids and Capacities .....11.8
  Interior Dimensions .....11.7
  Steering .....11.3
  Suspension .....11.4
  Transmission .....11.3
  Tyres .....11.5
  Vehicle Type .....11.6
  Wheels .....11.4
SportShift Transmission .....5.5
  Paddle Shift Mode .....5.6
Starting the Engine .....5.3
Steering Wheel .....3.8
Storage .....3.26
Supplemental Restraints System .....3.14

**T**

Track Days .....5.2
Traction Control .....5.13
Trip .....4.13
Tyre .....4.17
Tyre Sealant Kit ..... 10.13
Tyres ..... 10.11

**U**

Unlocking the Vehicle .....2.6

**V**

Vehicle Battery ..... 10.17
Vehicle Cleaning ..... 10.29
Vehicle Horn .....4.12
Vehicle Identification .....1.4
Vehicle Key .....2.5
Vehicle Recovery ..... 10.15

Vehicle Storage .....10.33

**W**

Wheel Nut Torque .....11.4
Window Reset .....10.28
Windscreen Blade Replacement .....10.10
Wipers
Wiper .....4.11

ASTON MARTIN
ASTON MARTIN
ASTON MARTIN
ASTON MARTIN