

1967 Cadillac

Data Book

Downloaded from www.Manualslib.com manuals search engine

Combining features of the Cadillac Optional Specifications Manual, Salesman's Color and Trim Book and Cadillac Data Book into a single sales manual, under one cover, provides a concise and more convenient source of all of the information the Cadillac salesman requires to properly present the 1967 Cadillac to his customers. Once you have fully acquainted yourself with the contents of each section, as outlined on the facing page, you will find any information you desire, whether on product or optional equipment features, prices, special orders and procedures . . . quickly and readily available. The sales opportunities presented to you by the magnificent 1967 Cadillac, including the World's Finest Personal Car—the new Fleetwood Eldorado—are limitless.
Your new Cadillac Data Book is designed to help make 1967 the most productive of years, for you and for Cadillac.

Downloaded from www.Manualslib.com manuals search engine

Section Contents

Colors and Equipment ..... **A**
Names and code numbers of each body style, exterior color and interior trim with recommended color combinations. Also a listing of standard and optional equipment, and equipment groups, for 1967.

Optional Equipment Features ..... **B**
Features of Cadillac Optional Equipment are explained to help the owner tailor his Cadillac to his personal requirements for maximum motoring satisfaction and increased pride of ownership.

Body Styles and Interiors ..... **C**
Illustrations of the exterior and interior of each body style plus details of interior upholstery and trim.

Special Orders ..... **D**
Availability and explanations of special interiors and/or exterior colors plus General Information on all ordering procedures.

Prices ..... **E**
This section contains Manufacturer's Suggested Retail Prices for each Cadillac Body Style, each Group and individual Optional Equipment item and for Special Order colors, upholstery or equipment.

New Features ..... **F**
Highlights of 1967 Cadillac new features are illustrated and explained.

Engine-Chassis-Body Features ..... **G**
Cadillac's dedication to quality in the engineering of its engine, chassis and body is the base upon which the highest owner loyalty in the industry has been built. Special engineering features of the new Fleetwood Eldorado are explained and illustrated separately in this section.

General Specifications ..... **H**
Here is a page of General Specifications followed by the Detailed Specifications of the 1967 Cadillac. Though perhaps referred to but occasionally, they provide a source for information not otherwise readily available.

Milestones ..... **I**
Listed in this section are "milestones" which point up the development of and increased demand for the Cadillac motor car as it won recognition, more firmly year-by-year, as the Standard of the World.

Index ..... **J**
A comprehensive and cross-reference index to help you locate individual subjects throughout the book. Where practical, introductory page to each section also contains an abbreviated index to that section.

Downloaded from www.Manualslib.com manuals search engine

Cadillac 1967 Body Styles

STYLE NO.	CODE	NAME	WHEELBASE	OVERALL LENGTH	WEIGHT
Calais					
68247	G	Calais Coupe	129.5″	224″	
68249	N	Calais Hardtop Sedan	129.5″	224″	
68269	K	Calais Sedan	129.5″	224″	
DeVille					
68367	F	De Ville Convertible	129.5″	224″	
68347	J	Coupe de Ville	129.5″	224″	
68349	B	Hardtop Sedan de Ville	129.5″	224″	
68369	L	Sedan de Ville	129.5″	224″	
Fleetwood					
69347	H	Fleetwood Eldorado	120″	221″	
68069	M	Fleetwood Sixty Special Sedan	133″	227.5″	
68169	P	Fleetwood Brougham	133″	227.5″	
69723	R	Fleetwood Seventy-Five Sedan	149.8″	244.5″	
69733	S	Fleetwood Seventy-Five Limousine	149.8″	244.5″	
COMMERCIAL					
69890	Z	Commercial Chassis	156″	249.5″	

Downloaded from www.Manualslib.com manuals search engine

Cadillac 1967 Exterior Recommendations

COLOR	BROUGHAM PADDED ROOFS	ELDORADO PADDED ROOFS	DE VILLE PADDED ROOFS	CONVERTIBLE TOPS
10 Sable Black	2 1	2 1	2 1	2 1 6
12 Grecian White	2 1 3	2 1 3	2 3 1	1 2 3
16 Regal Silver	2	2 1	2 1	2 1
18 Summit Gray	2	2	2	2 1
20 Venetian Blue	1 3 2	1 2 3	1 2 3	1 3 2
24 Marina Blue	2 3 1	2 1 3	2 3 1	1 3 2
26 Admiralty Blue	2 3 1	2 1 3	2 1 3	1 3 2 6
28 Capri Aqua	2 1	2 1	2 1	1 2
30 Pinecrest Green	2 1 6	2 1 6	2 1 6	1 2 6
36 Sherwood Green	2 6	2 6 1	2 6	2 6 1
40 Persian Ivory	2 1 5	2 1 5	2 1 5	2 1 5
42 Sudan Beige	5 6 2	5 2 6	5 2 6	5 6 2 1
43 Baroque Gold	2 1	2 1	2 1	2 1
44 Doeskin	5 2 6 1	5 6 2 1	5 6 2 1	5 6 2 1
48 Flamenco Red	2 1	1 2	1 2	1 2
49 Regent Maroon	2 6 1	2 6 1	2 1 6	2 1 6
Firemist Colors at Extra Charge				
90 Atlantis Blue	2 3 1	2 1 3	2 1 3	1 3 2
92 Crystal	2 1	2 1	2 1	2 1
96 Tropic Green	2 1	2 1	2 1	1 2
97 Olympic Bronze	5 2 6 1	5 2 6 1	5 2 6 1	5 6 2 1
98 Ember	2 1 6	2 1 6	2 1 6	1 2 6

Padded Roofs and Convertible Tops

1	White
2	Black
3	Medium Blue
5	Dark Brown
6	Sandalwood

Downloaded from www.Manualslib.com manuals search engine

Cadillac 1967 Color-Trim Recommendations

Cloth with Vinyl/Leather

COLOR	CALAIS SERIES Coupe G Hardtop N Sedan K	DE VILLE SERIES Coupe J Hardtop B Sedan L	FLEETWOOD SERIES Sixty Special M Brougham P	Eldorado H
10 Sable Black	211 220 240 228 244 251 282	311 326 320 340 328 344 349	010 or 011 016 025 or 026 040 043 or 044 049	410 411 426 440 429 444 431
12 Grecian White	211 220 228 240 251 282	311 320 326 349 328 340	010 or 011 021 025 or 026 049 028 or 029 040	410 411 426 429 431 440
16 Regal Silver	211 220 251	311 320 326 349	010 or 011 016 021 025 or 026 049	410 411 426
18 Summit Gray	211 220 251	311 326 349	016 010 or 011 025 or 026 049	410 411 426
20 Venetian Blue	220 211 251	320 326 311	021 025 or 026	426 410 411
24 Marina Blue	220 211 251	320 326 311	021 025 or 026 010 or 011	426 410 411
26 Admiralty Blue	220 211 251	326 320 311	025 or 026 021 010 or 011	426 410 411
28 Capri Aqua	228 211 251	328 311	028 or 029 010 or 011	429 410 411
30 Pinecrest Green	230 211 251	330 311	030 010 or 011	431 410 411
36 Sherwood Green	230 211 240 244 251 282	330 311 340 344	030 010 or 011 040 043 or 044	431 410 411 440 444
40 Persian Ivory	211 240 251 282	311 340	010 or 011 040	410 411 440 431
42 Sudan Beige	244 211 282 251	344 311 349	043 or 044 010 or 011 049	444 410 411
43 Baroque Gold	240 211 251	340 311	040 010 or 011	440 410 411
44 Doeskin	244 211 282 251	344 311	043 or 044 010 or 011	444 410 411
48 Flamenco Red	211 251 282	311 344	010 or 011 043 or 044	410 411 444
49 Regent Maroon	211 244 251 282	349 311 344	049 010 or 011 043 or 044	410 411 444

Firemist Colors at Extra Charge

90 Atlantis Blue	220 211 251	326 320 311	021 025 or 026 010 or 011	426 410 411
92 Crystal	230 211 251 282	330 311	030 010 or 011	431 410 411
96 Tropic Green	230 211 240 244 251 282	330 311 340 344	030 010 or 011 040 043 or 044	431 410 411 440 444
97 Olympic Bronze	244 211 282 251	344 311	043 or 044 010 or 011	444 410 411
98 Ember	211 244 251 282	311 344	010 or 011 043 or 044	410 411 444

Downloaded from www.ManualsLib.com manuals search engine

Cadillac 1967 Color-Trim Recommendations

Leather

COLOR	DE VILLE SERIES			FLEETWOOD SERIES	
	Convertible **F**	Coupe **J** Hardtop **B** Sedan **L**		Sixty Special **M** Brougham **P**	Eldorado **H**
10 Sable Black	351 388 352 385 382 389 380	351 388 352 385 382		051 088 052 085 082 089	451 488 452 482 485 489
12 Grecian White	388 351 352 360 389 368 371	351 388 352 360		051 088 052 060 071 089	488 451 452 466 469 471 489
16 Regal Silver	351 388 389	351 388		051 088 089	451 488 489
18 Summit Gray	351 388 352 389	351 388 352		051 088 089 052	451 488 489 452
20 Venetian Blue	360 353 351	360 353 351		060 052 051	466 452 451
24 Marina Blue	360 353 351	360 351 353		060 051 052	466 452 451
26 Admiralty Blue	360 353 351 388	360 351 353		060 051 052	466 452 451
28 Capri Aqua	368 355 351	351 355		051 052	469 451 452
30 Pinecrest Green	371 351 382 352	351 382 352		071 051 082 052	471 451 482 452
36 Sherwood Green	371 351 382 385 352	351 382 385 352		071 051 082 085 052	471 451 482 485 452
40 Persian Ivory	351 380 371 352	351 352		051 071 052	451 471 452
42 Sudan Beige	382 385 351 389	382 385 351		082 085 051 089	482 485 451 489
43 Baroque Gold	380 351 385 352	351 385 352		051 085 052	451 485 452
44 Doeskin	385 382 351 352	385 382 351 352		085 082 051 052	485 482 451 452
48 Flamenco Red	354 388 351	354 351 388 352		088 051 052	488 451 452
49 Regent Maroon	389 351 352 382	351 382 352		089 051 082 052	489 451 452 482

Firemist Colors at Extra Charge

90 Atlantis Blue	360 353 351	360 353 351		060 052 051	466 452 451
92 Crystal	371 351 352	351 352		071 051 052	471 451 452
96 Tropic Green	371 352 351 382 385	351 352 382 385		071 051 052 082 085	471 452 451 482 485
97 Olympic Bronze	385 382 351	385 382 351		085 082 051	485 482 451
98 Ember	351 352 385 382	351 385 352 382		051 052 085 082	451 452 485 482

Downloaded from www.Manualslib.com manuals search engine

Color-Trim Recommendations

(See charts on pages A-3 and A-4)

Cadillac interior colors are selected and toned to harmonize with their counterpart exterior colors. Therefore, the first upholstery recommendations on the color and trim charts are designed to result in fully color-coordinated interior and exterior combinations with every assurance of complete color harmony.

The upholstery selection involves the complete interior decor of the car and, if not harmonized with the exterior color, becomes uncomplimentary to the automobile.

Most customers respect and adhere to the Cadillac color and upholstery recommendations as they are based upon professional standards of esthetic principles and experience. They are a part of Cadillac quality standards.

Other Combinations

Although the recommended combinations are the most harmonious and will appeal to the majority, almost any combination of colors may be regarded as compatible by some customers and they may order such choices.

Acceptable options in this fringe area, however, are unlisted since they would not only complicate the tables but make them less effective in the selection of preferred combinations.

When a customer selects a combination not among those recommended, even though apprised of the risk of potential disappointment, the order should be marked "color trim sure." This will confirm the accuracy of the colors as ordered and prevent production of an undesirable color scheme not wanted by the customer or dealer.

Exterior Colors

Exclusive Shades

For 1967 Cadillac offers a total of 21 exterior colors of which 19 are exclusive to Cadillac.

This includes five Firemist colors, optional at extra charge on all body styles.

"Fire-Frost" Colors

The high lustre beauty and radiance of "Fire-Frost" colors are available on special order (See Special Order and Price sections). Light reflections from many faceted bright metallic flakes produce the unusual depth and brilliance of "Fire-Frost." The additional cost, about three times that of regular paint, will be understood by the select group of buyers to whom the distinction and exclusiveness of these outstanding colors will appeal.

Two-Tone Not Available

Since 1967 body styling does not provide a designed separation point for colors between upper and lower panels, two-tone paint treatment is not available. A two-tone appearance is obtainable in selection of the Padded Roof color on certain body styles.

Color Samples

The samples of exterior colors in Cadillac's color selection book are faithful reproductions of master metal panels. In making these samples, acetate, which is more costly than paper, is used to add depth and lustre to simulate the color as applied to the car's metal surface. Most accurate viewing of the color is achieved by looking straight down at the sample. Viewed at an angle, there is an increased amount of acetate through which the eye sees the color resulting in a slight change of values. This explanation is presented to help avoid any misunderstanding by a customer, who selects his car color from the sample book, that the larger expanse of color as seen on his delivered car is not exactly the same color as the small sample.

Special Colors (See Special Order Section)

Any past model or non-standard shade can be supplied on a special order basis. To order, Type OO in COLOR space which denotes that color is not a current option and indicate color name and reference in special feature section of the order form, e.g., 1964 Lime; 1959 Seminole Red.

Allow 4 to 5 weeks for shipment since a qualified chemist must defer his regular duties to formulate, obtain and blend the paint to the requirements of such special order colors.

Downloaded from www.Manualslib.com manuals search engine

Cadillac 1967 Upholstery Options

LEATHER

Leather—Extra Charge Except Convertibles	DEVILLE SERIES Convertible F	Coupe J Hardtop B	Sedan L	FLEETWOOD SERIES 60 Special M Brougham P	Eldorado H	
Black	351-351B	351-351B	351	051	451-451B	Black
White—Black Carpet	352-352B	352	352	052	452	White—Black Carpet
White—Blue Carpet	353	353	353			
White—Red Carpet	354	354	354			
White—Aqua Carpet	355	355	355			
Med. Blue	360	360	360	060	466	Dk. Blue
Med. Aqua	368				469	Dk. Aqua
Dk. Green	371			071	471	Dk. Green
Covert	380					
Sandalwood	382-382B	382	382	082	482-482B	Sandalwood
Antique Saddle	385	385	385	085	485	Antique Saddle
Med. Red	388-388B	388-388B	388	088	488	Med. Red
Maroon	389			089	489	Maroon

CALAIS SERIES — Coupe G, Hardtop N, Sedan K

	INSERTS DUET CLOTH	BOLSTERS VINYL
211	Black	Black
220	Dk. Blue	Med. Blue
228	Dk. Aqua	Med. Aqua
230	Dk. Green	Med. Green
240	Dk. Covert	Med. Covert
244	Dk. Beige	Med. Beige
	All Vinyl—Extra Charge	
251	Black	282 Sandalwood

DEVILLE SERIES — Coupe J, Hardtop B, Sedan L

	INSERTS CLOTH		BOLSTERS LEATHER
311	Black	Duchess	Black
320	Med. Blue	Duchess	Med. Blue
326	Dk. Blue	Darien	Dk. Blue
328	Med. Aqua	Darien	Med. Aqua
330	Med. Green	Duchess	Med. Green
340	Covert	Darien	Covert
344	Med. Beige	Duchess	Med. Beige
349	Maroon	Darien	Maroon

CONVERTIBLE TOPS AND PADDED ROOFS — Styles F-J-B-L-H-P-R-S

1	White
2	Black
3	Med. Blue
5	Dk. Brown
6	Sandalwood

On Limousine style S, front compartment will be standard Black leather. Gray, Dark Blue or Beige leather is optional and may be ordered by adding code G for Gray, M for Dark Blue or F for Beige. e.g., 716G, 719G would have Gray leather front; 721M and 726M Dark Blue; and 743F Beige. Leather is non-perforated.

FLEETWOOD SERIES — Eldorado H

	INSERTS CLOTH		BOLSTERS VINYL
410	Black/White	Dalmatian	Black
411	Black	Darien	Black
426	Dk. Blue	Darien	Dk. Blue
429	Dk. Aqua	Darien	Dk. Aqua
431	Dk. Green	Darien	Dk. Green
440	Covert	Darien	Covert
444	Med. Beige	Darien	Med. Beige

Sixty Special M — Brougham P

	INSERTS CLOTH		BOLSTERS LEATHER
010	Black	Damascus	Black
011	Black	Diplomat	Black
025	Dk. Blue	Diplomat	Dk. Blue
026	Dk. Blue	Damascus	Dk. Blue
028	Med. Aqua	Damascus	Med. Aqua
029	Dk. Aqua	Diplomat	Dk. Aqua
040	Covert	Damascus	Covert
044	Med. Beige	Diplomat	Med. Beige
049	Maroon	Diplomat	Maroon
	ALL DEVONSHIRE CLOTH Embroidered Back Rests		
016	Lt. Gray	030	Med. Green
021	Med. Blue	043	Med. Beige

"75" Sedan R — "75" Limousine S

Devonshire Cloth Has Embroidered Design
Damascus Cloth Has Leather Bolster

716	Lt. Gray	Devonshire
719	Med. Gray	Decordo
721	Med. Blue	Devonshire
726	Dk. Blue	Damascus
743	Med. Beige	Devonshire

Downloaded from www.Manualslib.com manuals search engine

Options
The equipment options listed on the following page are available for factory installation on new cars at an extra charge. (Filler Plate and 3.21 Gear Ratio are at no charge.)

New Groups 8 and 9
In addition to the basic 1, 2, 3 and 4 combinations, two new equipment groups have been created—numbers 8 and 9.

Both contain the same five popular items, but group 9 also includes a Headlamp Control—code U.

Separate Code for Recliner
A passenger seat Recliner, which includes a pair of Head Rests, is an extra-charge option on the standard Eldorado bench seat as well as *all* bucket seats.

When Bucket Seats are ordered on any car and a Recliner is wanted, both codes B and R must be specified on the order.

This differs from last year when R included Bucket Seats and is due to the availability of a Recliner on Eldorado bench seats.

License Frames
License Frames are *not* a part of any group. Order separately by their new code letters.

L — One License Frame

O — Two License Frames

Group Restrictions
One of the options in groups 1, 2 and 3 is Power Windows which are standard in all cars except the Calais series. Nevertheless, these groups may be ordered in all other cars except the following:

Group 1. Stereo Radio is not available for the "75"; therefore, group 1 should not be ordered in "75" cars.

Group 4. A Rear Control AM Radio is included in this group, which is only available for the "75"; therefore, it cannot be ordered in any other series.

Why Groups?
Using groups simplifies the ordering of optional equipment. It may also serve as a selling tool by offering the whole group as a desirable comfort and convenience package, instead of a more time consuming effort if sold on an individual item basis.

If All Equipment Not Ordered
When full equipment is not ordered, it is suggested that the customer be appraised of the options that were *not* specified.

This reversal of ordinary habit will have a more positive effect by calling attention to desired items that may have been overlooked. It will prevent the possibility of inadvertently failing to bring to the customer's attention an option he may later wish he had ordered.

Why Groups Change?
The suggestion to maintain the same groups from year to year is sometimes advocated. It would have the advantage of familiarity. However, the introduction of new features and changes in popularity of some options make revisions necessary.

Special Horn
A special Cadillac four-note horn combination producing a harmoniously blended distinctive sound is available at extra charge, on all cars.

Standard equipment consists of three seashell type horns which combine F, A and high C notes.

When the Special Horn option is ordered, a fourth low D note seashell horn is added, resulting in a more vibrant, deep-toned, authoritative signal.

Disc Brakes
Front Disc Brakes (Code F) are an extra-charge option on the Eldorado only. They are not available on any of the other body styles.

Air Injection Reactor System
On cars to be registered in the State of California, this Closed Positive Crankcase Ventilator-Air Injection Reactor System is a mandatory option required by California law. Code V should, therefore, be specified on all new Cadillac car orders destined for original California registration.

Downloaded from www.Manualslib.com manuals search engine

Cadillac 1967 Factory Installed Options

	BASIC GROUPS	*Group 1*	*Group 2*	*Group 3*	*Group 4* ("75" Only)
1	RADIO, AM-FM STEREO (Not on "75")	1			
2	RADIO, AM-FM		2		
3	RADIO, AM			3	
4	RADIO, AM REAR CONTROL ("75" Only)				4
W	TIRES, WHITE WALL	W	W	W	W
X	WINDOWS, POWER	X	X	X	STD
E	GLASS, SOFT RAY	E	E	E	E
Y	SEAT ADJUSTERS 6-Way Front or 4-Way Driver's Bucket	Y	Y	Y	Y (Except Style S)
D	DOOR EDGE GUARDS	D	D	D	D
K	AUTOMATIC CLIMATE CONTROL	K	K	K	STD

EQUIPMENT GROUPS

Group 8

Q	STEERING WHEEL, TILT & TELESCOPE
M	DOOR LOCKS, POWER
J	TWILIGHT SENTINEL
S	TRUNK LOCK, REMOTE CONTROL
C	CRUISE CONTROL

Group 9

U	HEADLAMP CONTROL, GUIDE-MATIC
Q	STEERING WHEEL, TILT & TELESCOPE
M	DOOR LOCKS, POWER
J	TWILIGHT SENTINEL
S	TRUNK LOCK, REMOTE CONTROL
C	CRUISE CONTROL

Heater-Defroster is standard equipment and included in the basic price of the car. However, a delete option—Code H—is available at reduced cost on all except Fleetwood "75" cars. The Heater-Defroster is an integral component of Automatic Climate Control and cannot be deleted when the car is equipped with this feature.

ORDER INDIVIDUALLY

B	BUCKET SEATS
R	RECLINER & HEAD RESTS (Available on all bucket seats also Eldorado Bench seat)
H	HEAD RESTS (Available on all seats)
A	SEAT WARMER
Z	SHOULDER STRAPS
J	SEAT BELTS, REAR CENTER
L	LICENSE FRAME—ONE
O	LICENSE FRAMES—TWO
F	FILLER PLATE
G	CONTROLLED DIFFERENTIAL (Not on Eldorado)
B	DE-FOGGER, REAR WINDOW (Not on Convertible or "75")
N	VENT WINDOWS, POWER (Rear quarters on Eldorado)
L	LEVEL CONTROL, AUTOMATIC
P	SPECIAL HORN
F	DISC BRAKES—FRONT (Eldorado Only)
V	CLOSED POSITIVE CRANKCASE VENTILATOR-AIR INJECTION REACTOR SYSTEM (Available only on cars destined for initial registration in the State of California)
R	3.21 OPTIONAL GEAR RATIO (Available on cars without Automatic Climate Control)

Downloaded from www.Manualslib.com manuals search engine

1967 Cadillac Standard and Optional Equipment

S—Standard O—Optional N—Not Available A—Available on Special Order

	CALAIS				DE VILLE				FLEETWOOD			
	Coupe	Hardtop Sedan	Sedan	Convertible	Coupe	Hardtop Sedan	Sedan	Eldorado	60 Special	Brougham	9-Pass. Sedan	Limousine
Air Cleaner, dry-pack	S	S	S	S	S	S	S	S	S	S	S	S
Armrests, sides, front and rear	S	S	S	S	S	S	S	S	S	S	S	S
Armrest, center, front	S	S	S	S	S	S	S	S	S	S	S	N
Armrest, center, rear	N	N	N	N	S	S	S	N	S	S	S	S
Assist Handles (two)	N	S	S	N	N	S	S	N	S	S	S	S
Assist Straps (two)	N	N	N	N	N	N	N	N	N	N	S	S
Automatic Climate Control	O	O	O	O	O	O	O	O	O	O	S	S
Automatic Level Control	O	O	O	O	O	O	O	S	S	S	S	S
Bench Seats, leather	N	N	N	S	O	O	O	O	O	O	A	A
Bucket Seats, front	N	N	N	O	O	O	A	O	A	A	N	N
Cigarette Lighter, front	S	S	S	S	S	S	S	S	S	S	S	S
Cigarette Lighters, rear (2) (Eldorado) (1)	N	S	S	S	S	S	S	S	S	S	S	S
Clock, electric, front	S	S	S	S	S	S	S	S	S	S	S	S
Controlled Differential	O	O	O	O	O	O	O	N	O	O	O	O
Cruise Control	O	O	O	O	O	O	O	O	O	O	O	O
De-fogger, rear window	O	O	O	N	O	O	O	O	O	O	N	N
Door Edge Guards	O	O	O	O	O	O	O	O	O	O	O	O
Door Locks, power	O	O	O	O	O	O	O	O	O	O	O	O
Folding Seat Back Latch (coupe and bucket)	S	N	N	S	S	N	N	S	N	N	N	N
Front Seat Adjustment, power, 2-way	N	N	N	S	S	S	S	S	S	S	S	S
Front Seat Adjustment, power, 6-way	O	O	O	O	O	O	O	O	O	O	O	N
Hazard Warning Flasher	S	S	S	S	S	S	S	S	S	S	S	S
Headlamp Control (Guide-Matic)	O	O	O	O	O	O	O	O	O	O	O	O
Head Rests, front seats	O	O	O	O	O	O	O	O	O	O	O	O
License Frames	O	O	O	O	O	O	O	O	O	O	O	O
Light, front ash receiver	S	S	S	S	S	S	S	S	S	S	S	S
Light, glove compartment	S	S	S	S	S	S	S	S	S	S	S	S
Light, luggage compartment	S	S	S	S	S	S	S	S	S	S	S	S
Light, map	S	S	S	S	S	S	S	S	S	S	S	S
Lights, backup (dual)	S	S	S	S	S	S	S	S	S	S	S	S
Lights, cornering	S	S	S	S	S	S	S	S	S	S	S	S
Lights, courtesy	S	S	S	S	S	S	S	S	S	S	S	S
Lights, directional signal	S	S	S	S	S	S	S	S	S	S	S	S
Lights, directional indicator	S	S	S	S	S	S	S	S	S	S	S	S
Lights, reading	S	S	S	N	S	S	S	S	S	S	S	S
Oil Filter, Full-Flow	S	S	S	S	S	S	S	S	S	S	S	S
Outside Mirror, left side, remote-control	S	S	S	S	S	S	S	S	S	S	S	S
Power Brakes (dual system)	S	S	S	S	S	S	S	S	S	S	S	S
Power Brakes (dual system), disc front	N	N	N	N	N	N	N	O	N	N	N	N
Power Steering (variable ratio except 75's)	S	S	S	S	S	S	S	S	S	S	S	S
Radio, AM	O	O	O	O	O	O	O	O	O	O	O	O
Radio, AM-FM	O	O	O	O	O	O	O	O	O	O	O	O
Radio, AM-FM Stereo	O	O	O	O	O	O	O	O	O	O	N	N
Radio, AM, rear controls	N	N	N	N	N	N	N	N	N	N	O	O
Recliner, passenger bucket seat	N	N	N	O	O	O	A	O	A	A	N	N
Recliner, passenger bench seat	N	N	N	N	N	N	N	O	N	N	N	N
Red Lens, reflector, door panels	S	S	S	N	N	N	N	N	N	N	S	S

Downloaded from www.Manualslib.com manuals search engine

continued

	CALAIS				DE VILLE			FLEETWOOD				
	Coupe	Hardtop Sedan	Sedan	Convertible	Coupe	Hardtop Sedan	Sedan	Eldorado	60 Special	Brougham	9-Pass. Sedan	Limousine
Red Lens, illuminated, door panels	N	N	N	S	S	S	S	S	S	S	N	N
Seat Belts, front and rear	S	S	S	S	S	S	S	S	S	S	S	S
Seat Belts, rear center	O	O	O	O	O	O	O	O	O	O	O	O
Seat Warmer, front (rear only on 75's)	O	O	O	O	O	O	O	O	O	O	O	O
Shoulder Straps, front (2)	O	O	O	O	O	O	O	O	O	O	O	O
Soft Ray Glass	O	O	O	O	O	O	O	O	O	O	O	O
Tilt and Telescope Steering Wheel	O	O	O	O	O	O	O	O	O	O	O	O
Trunk Lock, remote-control	O	O	O	O	O	O	O	O	O	O	O	O
Turbo Hydra-Matic Transmission	S	S	S	S	S	S	S	S	S	S	S	S
Twilight Sentinel (automatic headlamp timer)	O	O	O	O	O	O	O	O	O	O	O	O
Vent Windows, power, front	O	O	O	O	O	O	O	N	S	S	O	O
Vent Windows, power, rear	N	N	N	N	N	N	N	O	S	S	N	N
Visor Vanity Mirror, shatterproof	S	S	S	S	S	S	S	S	S	S	S	S
Visors, dual sun, padded	S	S	S	S	S	S	S	S	S	S	S	S
Wheel Discs (set of four)	S	S	S	S	S	S	S	S	S	S	S	S
Whitewall Tires, 9.00 x 15 (5), 8.20 x 15 on 75's	O	O	O	O	O	O	O	O	O	O	O	O
Windows, power	O	O	O	S	S	S	S	S	S	S	S	S
Windshield Washer and Coordinator	S	S	S	S	S	S	S	S	S	S	S	S

Fleetwood Body Styles (Special Features)

	Eldorado	60 Special	Brougham	9-Pass. Sedan	Limousine
Additional Room in Rear Compartment		X	X	X	X
Ash Receivers (2) on back of Division				X	X
Auxiliary Seats (2)				X	X
Body Styling, exclusive	X	X	X	X	X
FLEETWOOD nameplate on fender and trunk lid		X	X		
Coil Seat Springs		X	X	X	X
Courtesy Lights, rear door armrests		X	X	X	X
Decorative grille, base of rear deck	X	X	X	X	X
Division Glass					X
Foot Rests, rear			X	X	X
Multi-purpose Trays on Front Seat Back			X		
Padded Roof with perimeter molding			X		
Reading Lamps, adjustable			X		
Reading Lamps, overhead on A/C outlets				X	X
Reading Spotlight, front compartment header					X
Rear-View Mirror, 3-way, Soft Ray Glass		X	X		
Spare Tire Cover		X	X		
Stainless Steel Rocker Panel Molding	X	X	X		
Trunk Compartment, completely fabric lined		X	X		
Vent Windows, power, rear		X	X		
Wheelbase, exclusive length	X	X	X	X	X
Wreath and Crest insignia on Hood, Deck Lid and Rear Quarter Panels	X	X	X	X	X
Wreath and Crest insignia on Steering Wheel	X	X	X	X	X

Downloaded from www.Manualslib.com manuals search engine

Packaged Accessories
Available for Dealer Installation

CODE		CODE	
	Antenna, Electric		Mat, Floor—Front One-Piece Full
L	Automatic Level Control, except styles H-M-P-R-S		Mats, Floor—Front RH and LH (Pair)
	Basket, Litter		Mat, Floor—Rear One-Piece Full except R-S
K	Automatic Climate Control (Air Conditioner) except R-S		Mats, Floor—Rear RH and LH (Pair) except R-S
	Compass, Auto		Mat, Luggage Compartment
	Cover, Spare Tire	2	Radio, AM-FM
C	Cruise Control	3	Radio, AM
	Cushion Cover, Front or Rear (Each) except Bucket Seats and styles R-S	4	Radio, Rear Control (AM) styles R-S
B	De-Fogger, Rear Window except styles F-R-S		Seat Belts, Front Center except Bucket Seats
D	Door Edge Guards, 2 Doors	J	Seat Belts, Rear Center
D	Door Edge Guards, 4 Doors	Z	Shoulder Straps, Front (2)
	Foot Selector Control, AM Radio		Speaker, Radio—Rear Auxiliary except style F
U	Headlamp Control, Guide-Matic	S	Trunk Lock, Remote Control Cars with Vacuum Door Locks Cars without Vacuum Door Locks
P	Horn, Special "D" Note		Tissue Dispenser
L	License Frame (one)	J	Twilight Sentinel (Automatic Headlamp Timer)
O	License Frames (two)		

Downloaded from www.Manualslib.com manuals search engine

Code and Acrylic Numbers for 1967 Cadillac Colors

		Manufacturer's Identification*			
Code	**Name**	**Du Pont**	**Forbes**	**Rinshed-Mason**	**% Used in 1966**
10	Sable Black	942-96459	**850-360**	L 61 K 011	8.0
12	Grecian White	868-93774	850-178	**L 61 W 004**	17.5
16	Regal Silver	867-97593	**855-425**	L 62 A 028	5.8
18	Summit Gray	867-97685	855-443	**L 62 A 032**	3.0
20	Venetian Blue	868-98371	850-550	**L 61 B 004**	4.6
24	Marina Blue	867-98144	855-479	**L 62 B 017**	9.0
26	Admiralty Blue	943-97220	855-391	**L 62 B 009**	3.0
28	Capri Aqua	867-98146	855-481	**L 62 B 018**	6.8
30	Pinecrest Green	867-98147	855-482	**L 62 G 007**	5.1
36	Sherwood Green	867-97224	855-394	**L 62 G 018**	3.6
40	Persian Ivory	868-98148	850-483	**L 61 Y 007**	5.1
42	Sudan Beige	868-96809	**850-362**	L 61 N 004	6.4
43	Baroque Gold	**867-98457**	855-551	L 62 N 015	14.9
44	Doeskin	**867-98150**	855-484	L 62 N 005	2.4
48	Flamenco Red	942-97540	**850-395**	L 61 R 020	2.4
49	Regent Maroon	**943-98151**	855-485	L 62 M 003	2.4
Firemist Colors					
90	Atlantis Blue	867-98372		**L 62 B 020**	22.3
92	Crystal	867-98743		**L 62 G 026**	16.7
96	Tropic Green	867-97895		**L 62 G 049**	14.2
97	Olympic Bronze	867-98152		**L 62 N 011**	30.7
98	Ember	**867-97898**		L 62 R 018	16.1

*Bold face indicates source of original factory finish.


Downloaded from www.Manualslib.com manuals search engine

1967 Cadillac

Optional Equipment Features

	Page
Automatic Climate Control	B-2
Automatic Level Control	B-2
Cruise Control	B-3
Twilight Sentinel	B-3
Guide-Matic (headlamp control)	B-3
Windows, Power	B-4
Vent Windows, Power	B-4
Door Locks, Power	B-4
Seat Adjusters, Power	B-4
Radio, AM	B-5
Radio, AM-FM	B-5
Radio, AM-FM Stereo	B-5
Radio, AM (Rear compartment controls. For Fleetwood Seventy-Five models only)	B-5
Tilt and Telescope Steering Wheel	B-6
Head Rests	B-6
Reclining Bucket Seat, passenger side only	B-6
Seat Warmer, Electric	B-6
Controlled Differential	B-7
De-Fogger, Rear Window	B-7
Trunk Lock, Remote-control	B-7
Soft Ray Glass	B-7
Disc Brakes, Front (Fleetwood Eldorado only)	B-8
Whitewall Tires	B-8
Seat Belts, Center	B-8
Shoulder Straps	B-8


Downloaded from www.Manualslib.com manuals search engine




Automatic Climate Control (Air Conditioner-Heating System)
A single setting of the thermostat dial brings and maintains the interior temperature of the car to the degree selected by the driver. Without further adjustment, heated or cooled air is supplied automatically to maintain the selected temperature, year around, whether the car is driven in desert heat or the cold of mountain altitudes. When outside air is above approximately 35°, incoming air is first cooled to control humidity, then reheated thus assuring maximum comfort and minimizing window fogging.

Control lever provides the following positions: OFF, VENT, for ventilation with outside air not under temperature control, AUTO, Lo for normal automatic operation, Hi for fast cool down when car has been standing in the sun, FOG for defogging and ICE for deicing the windshield. Five air outlets are adjustable for direction of air or may be turned off individually. For dual system Automatic Climate Control, standard on Fleetwood Seventy-Five body styles, see page G-14.


Automatic Level Control
Even with up to five hundred pounds of luggage compartment loading, a full complement of passengers or when trailer traveling, the Automatic Level Control keeps the car level with the roadway. Pressurized air is directed into or exhausted from the rear shock absorbers as required to level the car. The result is best appearance, handling ease and headlamp beam direction, regardless of load. Automatic Level Control is standard on all Fleetwood series cars.




Downloaded from www.Manualslib.com manuals search engine



Cruise Control
The benefits of automatically maintained cruising speeds and a warning against exceeding any pre-selected speed are provided by the Cadillac Cruise Control. Set in AUTO position, it maintains the speed selected on the dial without foot pressure on the accelerator. A touch of the brake disengages Cruise Control until car is re-accelerated to speed setting. It is also disengaged by moving control switch to OFF or turning ignition off. At any dial setting, a gentle resistance by the accelerator pedal warns the driver whenever he is about to exceed his dial-selected speed. Green light reminds driver when Cruise Control is on AUTO (automatic).





Twilight Sentinel
Set the Twilight Sentinel control lever, integral with headlamp switch, to automatic and, whenever the ignition is ON, the headlamps and taillamps of the car will automatically turn on when lighting is required as at dusk or whenever daylight is otherwise reduced. Lights are automatically turned off when sufficient daylight returns. Twilight Sentinel also permits leaving car lamps, including either cornering lamp (as selected by directional signal lever), lighted for up to a minute and a half after the ignition is turned OFF, thus providing a pathway of light away from the car, then automatically turning lamps off. Control lever may be set on manual when driver prefers for normal headlamp pull switch operation.



Guide-Matic (headlamp control)
An appreciated nighttime driving aid, Guide-Matic automatically dims the headlamps of the car when another car approaches from the opposite direction or when the Cadillac driver draws closer to the taillights of a car ahead. An overriding foot switch permits signalling drivers who neglect to dim their car's bright lights in return. Guide-Matic is adjustable for sensitivity or may be turned OFF with control integral with headlamp switch.

Downloaded from www.Manualslib.com manuals search engine







Power Window Regulators
Driver may raise or lower windows from a four-switch panel on the driver's door while single switches are provided for passenger operation of individual windows. Forward on the panel is an additional control switch providing three positions: NORMAL—for operation as above, whenever ignition or accessories circuit is on; LOCK—restricting window operation to driver's switches only; EMERG (emergency)—permitting window operation when ignition or accessories circuits are off. Switch returns to NORMAL when released from EMERG. On the Fleetwood Limousine, chauffeur's armrest has switches for front windows (and to close rear windows only) while rear quarter trim panel has switches for passenger operation of rear windows and division glass. Lock-out switch is not provided.

Power Vent Window Regulators
Available on models equipped with power windows. Two switches (four with front and rear ventipanes) are provided for driver. Single door panel switches for passenger use. Standard front and rear on Fleetwood Sixty Special and Brougham. Rear option only available for Eldorado.

Power Door Locks
A master switch on each door panel (front doors on sedans) permits locking all doors by pushing down on the switch. Pushing up on switch unlocks all doors. Individual doors may be unlocked by pulling up the door lock button. All inside door handles freewheel when doors are locked thus preventing accidental opening. On Fleetwood Limousine, master control switch is on right rear door panel and left front door. Front door switch will lock all doors but unlock front only. Rear door switch locks or unlocks all doors.


Power Seat Adjustment (six-way)
Controls on driver's side of front seat permit horizontal, vertical and angle adjustment of seat for maximum comfort. Vertical and angle provisions only need be ordered on models with horizontal power adjustment standard. Fleetwood Seventy-Five Sedan and Limousine have horizontal power adjustment standard with six-way adjustment optional on sedan only.








Power Seat Adjustment (four-way, bucket seats only)
Permits horizontal and angle adjustment of driver's seat only on bucket seat equipped models. Horizontal adjustment only is standard with bucket seats.

Downloaded from www.Manualslib.com manuals search engine










Cadillac AM Radio (Signal Seeking)
In addition to pushbutton selection of five favorite stations, a More Stations selector bar permits tuning in each successive station across the dial. Selector bar may be set for only strongest stations or, moving bar to right, weaker and more distant stations as well. Adjustments are provided for base or treble tones, for balancing sound as desired between front and rear speakers and for raising and lowering antenna. Cadillac radios are transistorized for instant operation and have printed circuits for maximum dependability.


Cadillac AM-FM Radio
FM radio offers the added enjoyment of the more sophisticated FM programs. FM radio rejects outside electrical interference. When a station is slightly mistuned, manually, the Cadillac FM radio with its Automatic Frequency Control tends to lock directly on to the station wanted without interference from adjacent stations. Best reception with FM is up to twenty miles from the transmitting station. Beyond this distance another FM station or AM may be selected. Tilt bar switch over the radio dial has designations for AM or FM and lighted initials on dial tell which position bar is in.

Cadillac AM-FM Stereo Radio
The added enjoyment of stereo sound with its full richness and dramatic presence is available with the Cadillac AM-FM Stereo Radio. Four speakers, one located at each end of the instrument panel and the rear package shelf, are linked in a criss-cross system. The left front and right rear speakers serving one channel of the dual-channel amplifier; the right front and left rear speakers serving the other. Thus the driver and passengers, front or rear, enjoy equally the concert hall realism of stereo. A control ring permits balancing sound level between front and rear speakers as desired. The word STEREO appears in amber color when stereo programming is being received. Available on all but Seventy-Five models.

Rear Compartment Radio Controls
The Cadillac Radio available for the Fleetwood Seventy-Five Sedan and Limousine is provided with rear compartment controls located on the right-hand rear armrest for operation by rear compartment passengers. This radio has AM reception only.


Downloaded from www.Manualslib.com manuals search engine





Tilt and Telescope Steering Wheel
The benefits of the Tilt and Telescope Steering Wheel are many. It permits adjustment of the steering wheel to fit the exact requirements of any driver, permits changing positions on long trips, thus relieving tension and minimizing fatigue, and aids entry and exit since lifting the tilt lever automatically tilts the wheel to its uppermost position.


Telescoping the wheel over a three inch range of adjustment is achieved by moving the small lever atop the steering column to the right. After adjustment, moving lever to left locks wheel in position. Tilt adjustment is accomplished by lifting short lever at left of steering column, tilting wheel to desired position and releasing lever.



Reclining Bucket Seat
(Passenger side only)
Permits adjusting the seat back angle to various reclining positions up to 30° for maximum rest and relaxation. Head Rests are included with this option. Reclining Strato-bench seat (passenger side only) is also available for Eldorado.




Head Rests
Available for all bench and bucket front seats, removable head rests are adjustable for height, provide added support and comfort.




Seat Warmers
For added cold weather comfort Seat Warmers are available for the front seat cushion and seat back (rear seat and seat back only on Seventy-Five body styles). Heating elements located beneath the seat surface may be turned on or off by a switch on the instrument panel. Switch turns off automatically when car heater provides adequate interior warmth.

Downloaded from www.Manualslib.com manuals search engine


Controlled Differential
By always directing driving force to the rear wheel having the better traction, Cadillac's Controlled Differential assures maximum mobility on such skid-inducing surfaces as ice, snow, sand, mud, gravel and wet or oily pavement. This feature also reduces swerving on high crowned roads, provides greater resistance to skidding, adds stability on washboard roads, and contributes to tire life. (Available for all body styles except Fleetwood Eldorado.)





Rear Window De-Fogger
Designed to keep the rear window free of fog or mist, the Cadillac Rear Window De-Fogger directs fan blown air from a rectangular, centrally located grille on the rear package shelf across the rear window glass. It operates at either of two speed settings selected on an instrument panel switch. Not available for convertible or Seventy-Five body styles.



Soft Ray Glass
Cadillac Soft Ray Glass shields the interior of the car from the heat and glare of the sun for greater comfort and better visibility. A natural complement to air conditioned cars, Soft Ray Glass installation includes tinted glass on all windows with additional shading on the upper portion of the windshield.









Remote-Control Trunk Lock
The touch of a button located on the left side within the glove compartment permits the driver to automatically release and slightly raises the deck lid providing access for service station or shopping attendants. When deck lid is brought down to a nearly closed position, the power trunk lock takes over and closes and latches it securely. Red warning light on instrument cluster indicates when deck lid is unlocked.

Downloaded from www.Manualslib.com manuals search engine






Disc Brakes (front, Eldorado only)
In keeping with the advanced styling and engineering of the Fleetwood Eldorado, owners are offered the option of front wheel disc brakes as an added engineering distinction for this body style only.

Whitewall Tires
Newly styled with two narrow white rings, optional whitewall tires are available in 2-ply, size 9.00 x 15 except, on the Seventy-Five, an 8.20 x 15, 4-ply tire is provided. Special high speed nylon tires are available at extra charge in 9.00 x 15 size.





Shoulder Straps
Considered an added security precaution for certain types of sudden stops, the Cadillac Shoulder Straps are available for the outboard front seat occupants. Straps are designed to the same high quality standards as Cadillac seat belts and also have pushbutton buckles.

Center Seat Belts
In addition to the two pair of seat belts, front and rear, provided as standard by Cadillac, rear center seat belts are available (front for dealer installation only) to provide added security when more than four passengers are carried. Not available with bucket front seats.

Downloaded from www.Manualslib.com manuals search engine

1967 Cadillac


Body Styles and Interiors

Here are exterior and interior illustrations of each Cadillac body style, including the world's finest personal car, the new Fleetwood Eldorado.


Beneath each interior illustration is a brief explanation of the seat styling available plus other information pertinent to that particular body style. The facing page lists the upholstery choices available and color decor for the entire interior. Fold-out pages provide interior drawings showing details of cloth, leather and vinyl usage as well as seat styling.

	PAGE NUMBER Exterior	Interior
CALAIS COUPE	C-2	C-9
CALAIS HARDTOP SEDAN	C-2	C-11
CALAIS SEDAN	C-2	C-13
DE VILLE CONVERTIBLE	C-3	C-15
COUPE DE VILLE	C-4	C-17
HARDTOP SEDAN DE VILLE	C-4	C-19
SEDAN DE VILLE	C-4	C-21
FLEETWOOD ELDORADO	C-5	C-23
FLEETWOOD SIXTY SPECIAL SEDAN	C-6	C-25
FLEETWOOD BROUGHAM	C-6	C-27
FLEETWOOD SEVENTY-FIVE SEDAN	C-7	C-29
FLEETWOOD SEVENTY-FIVE LIMOUSINE	C-7	C-31
FLEETWOOD SEVENTY-FIVE WITH LANDAU ROOF	C-7, C-33	


Downloaded from www.Manualslib.com manuals search engine



Downloaded from www.Manualslib.com manuals search engine



Downloaded from www.Manualslib.com manuals search engine



Downloaded from www.Manualslib.com manuals search engine



Downloaded from www.Manualslib.com manuals search engine

Chart Study Recommended

To gain a more comprehensive understanding of the interior options, it is suggested that as each subject here is read, a reference be made to the applicable chart on the right-hand pages of this section.

Expanded Vinyl in Calais Cars

In addition to a Duet cloth option in six colors, two all-vinyl interiors—Black and Sandalwood—are offered in the three Calais body styles.

Expanded Vinyl is an extra-thick vinyl-coated fabric upholstery material of superior quality, luxuriant to the touch, with an appealing Mill grain surface texture.

The soft resilient feel of Expanded Vinyl is attained by sandwiching a sponge-like cellular structure between the backing fabric and plastic top coating.

De Ville Convertible Leather Interiors

Thirteen bench seat perforated leather options are offered at no extra charge in the Convertible. Four combinations are available with Bucket Seats. There is a charge for the Bucket Seats, but the leather is without extra charge on this body style only.

Leather Interiors in De Ville Closed Cars

In De Ville closed cars, nine bench seat perforated leather combinations are offered at an extra charge. In the Coupe and Hardtop Sedan styles, Black and Red leathers are available with Bucket Seats at an extra charge.

Leather in Brougham & Sixty Special is Non-Perforated

Eight color options of non-perforated leather are offered in the Brougham and Sixty Special Sedans at an extra charge. The trim style is pillow and button.

Eldorado Leather Upholstery Available at Extra Charge

Nine perforated leather upholstery selections are offered *at an extra charge*. Two of these—Black and Sandalwood—are available with Bucket Seats. There is also an extra charge for the Bucket Seats.

Bucket Seats

Eight leather upholstery code numbers suffixed with B are available with Bucket Seats as a production option at extra charge.

Large Upholstery Book Has Complete Duet Pattern

All six Calais Duet cloth colors have alternating light and dark tone stripes of approximately 1″ and 2″ widths.

In the limited size of the Data Book samples, some pieces of material may only show one of the colors. Therefore, to view the entire pattern, it may be necessary to refer to the large upholstery book. Also, the Calais trim style of wide pleats with a deep sew line reduces the actual visible width of the small stripe by half.

Covert and Maroon Cloths in De Ville

Two cloth patterns—Duchess and Darien—in eight color options are offered in three De Ville closed cars.

Covert and Maroon are two new colors which are available in the Darien cloth pattern.

Eldorado Cloth Options

Two patterns in seven color combinations of cloth and vinyl are optional in the Eldorado.

One of the cloths is a dramatic black and white Dalmatian houndstooth pattern which is used on the seat inserts and is surrounded by black vinyl.


Fleetwood Brougham & Sixty Special Interiors Include Two Trim Styles

Cloth upholstery is available in two trim styles. (See pages C-25 through C-29 for illustrations.)

The cloth upholstery options in the Brougham and Sixty Special. include three patterns—Diplomat, Damascus, Devonshire—in ten colors.

To provide a choice of cloth patterns in the two most popular Fleetwood interior colors—Black and Dk. Blue—two cloth selections in each of these colors are offered.

Downloaded from www.Manualslib.com manuals search engine



CALAIS COUPE

Upholstery Styling

Calais fabric selections listed on the facing page are tailored in 2.625-inch piping with bolsters of supple expanded vinyl at seat cushion sides and at the sides and top of seat back inserts.

New all vinyl upholstery, optional at extra cost, is also styled in 2.625-inch piping except for the plain bolster areas mentioned above. Six additional vinyl colors are available on special order. See Special Order and Price sections.

Seat Styling

Coupe (Notch-back) front seat with folding seat backs divided by a center armrest. Seat backs latch securely in place until released individually by pushbuttons located (one) at outboard side of each front seat backrest.


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.


INTERIOR DIMENSIONS		
	Front	Rear
Head room	37.9"	37.4"
Shoulder room	60.0"	60.7"
Hip room	63.6"	55.2"
Leg room	41.0"	38.1"
Seat height	12.4"	14.5"

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends and rear quarter	X	Headlamp
Map, on inst. cluster		Integral
Glove Box and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine







Calais Coupe

CLOTH

VINYL

Downloaded from www.Manualslib.com manuals search engine

CALAIS COUPE

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANELS	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Expanded Vinyl • Cushion Facings • Headlining—Boucle Pattern Coated Fabric	Front Seat Wings • Laces • Head Rests	Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Trenton & Travana Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
211	Black Duet	Black		Black		Black	Black	Black
220	Dk. Blue Duet	Med. Blue		Med. Blue		Dk. Blue	Med. Blue	Med. Blue
228	Dk. Aqua Duet	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
230	Dk. Green Duet	Med. Green		Med. Green[1]		Dk. Green	Med. Green	Med. Green
240	Dk. Covert Duet	Med. Covert		Med. Covert[2]		Dk. Covert	Med. Covert	Med. Covert
244	Dk. Beige Duet	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige


Expanded Vinyl at Extra Charge

	Expanded Vinyl					
251	Black	Black	Black	Black	Black	Black
282	Sandalwood	Sandalwood	Sandalwood[3]	Dk. Beige	Sandalwood	Med. Beige

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs; Window Regulator Handle Knobs.

1. Dark Green Moulded Vinyl Parts
2. Med. Fawn Moulded Vinyl Parts
3. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



CALAIS HARDTOP SEDAN

Upholstery Styling

Fabric selections listed on the facing page are tailored in 2.625-inch piping with vinyl bolsters at sides of the seat cushion and at sides and top of the seat back inserts.

Vinyl upholstery, optional at extra cost, also has 2.625-inch piping except for plain bolster areas. Six additional vinyl colors are available on special order. See Special Order and Price sections.

Seat Styling

Bench seat with conventional, straight-across, stationary seat back and folding front seat center armrest.


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.


INTERIOR DIMENSIONS		
	Front	Rear
Head room	37.9″	37.2″
Shoulder room	60.9″	60.4″
Hip room	63.6″	62.7″
Leg room	41.0″	39.7″
Seat height	12.4″	14.5″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends and rear quarter	X	Headlamp
Map, on inst. cluster		Integral
Glove Box and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine







Calais Hardtop Sedan

CLOTH

VINYL

Downloaded from www.Manualslib.com manuals search engine

CALAIS HARDTOP SEDAN

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Expanded Vinyl • Cushion Facings • Headlining—Boucle Pattern Coated Fabric	Front Seat Wings • Laces • Head Rests	Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Trenton & Travana Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
211	Black Duet	Black		Black		Black	Black	Black
220	Dk. Blue Duet	Med. Blue		Med. Blue		Dk. Blue	Med. Blue	Med. Blue
228	Dk. Aqua Duet	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
230	Dk. Green Duet	Med. Green		Med. Green[1]		Dk. Green	Med. Green	Med. Green
240	Dk. Covert Duet	Med. Covert		Med. Covert[2]		Dk. Covert	Med. Covert	Med. Covert
244	Dk. Beige Duet	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige


Expanded Vinyl at Extra Charge

	Expanded Vinyl					
251	Black	Black	Black	Black	Black	Black
282	Sandalwood	Sandalwood	Sandalwood[3]	Dk. Beige	Sandalwood	Med. Beige

*Moulded Soft Vinyl Parts Include: Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs; Window Regulator Handle Knobs.

1. Dark Green Moulded Vinyl Parts
2. Med. Fawn Moulded Vinyl Parts
3. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



CALAIS SEDAN

Upholstery Styling

Fabric upholstery listed on the facing page is tailored in 2.625-inch pipes with expanded vinyl bolsters at sides of seat cushion and at sides and top of seat back inserts.

Vinyl upholstery, now available as an extra-cost option, is also fashioned in 2.625-inch piping except for plain bolster areas. Six additional vinyl colors are available on special order. See Special Order and Price sections.

Seat Styling

Bench seat with conventional, straight-across, stationary seat back and folding front seat center armrest.


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.


INTERIOR DIMENSIONS		
	Front	Rear
Head room	39.1"	38.2"
Shoulder room	60.9"	60.4"
Hip room	63.6"	62.5"
Leg room	41.0"	41.9"
Seat height	12.4"	14.9"

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends and rear quarter	X	Headlamp
Map, on inst. cluster		Integral
Glove Box and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine







Calais Sedan

CLOTH

VINYL

Downloaded from www.Manualslib.com manuals search engine

CALAIS SEDAN

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Expanded Vinyl • Cushion Facings • Headlining—Boucle Pattern Coated Fabric	Front Seat Wings • Laces • Head Rests	Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Trenton & Travana Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
211	Black Duet	Black		Black		Black	Black	Black
220	Dk. Blue Duet	Med. Blue		Med. Blue		Dk. Blue	Med. Blue	Med. Blue
228	Dk. Aqua Duet	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
230	Dk. Green Duet	Med. Green		Med. Green[1]		Dk. Green	Med. Green	Med. Green
240	Dk. Covert Duet	Med. Covert		Med. Covert[2]		Dk. Covert	Med. Covert	Med. Covert
244	Dk. Beige Duet	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige


Expanded Vinyl at Extra Charge

	Expanded Vinyl					
251	Black	Black	Black	Black	Black	Black
282	Sandalwood	Sandalwood	Sandalwood[3]	Dk. Beige	Sandalwood	Med. Beige

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs; Window Regulator Handle Knobs.

1. Dark Green Moulded Vinyl Parts
2. Med. Fawn Moulded Vinyl Parts
3. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



DE VILLE CONVERTIBLE

Upholstery Styling
Smartly tailored of luxurious leathers in four section pinch seam, biscuit styling with a recessed button centered in each section.

Seat Styling
Available in Coupe (Notch-back) seat styling with front seat center armrest or, optional at extra cost, Bucket Seats with dividing console and without center armrest. In either style, front seat backs latch securely in place until released individually by pushbuttons located (one) at outboard side of each front seat backrest.

Recliner passenger bucket seat which permits passenger to tilt the seat back to various reclining positions may be ordered. This option, which automatically includes headrests on both bucket seats, is denoted by adding Code R to Code B (for bucket).

Additional Leather Colors and Two-Tone Colors
Should an owner inquire about a color not listed on the facing page, or want two-tone leather, refer to the Special Order and Price sections for availability and price.

Top Materials
The convertible top is available in the colors indicated below. Liner colors cannot be changed since the top material is a fusion of four layers of vinyl, fabric, rubber and drill cloth liner bonded into a single sheet at the fabricating mill.

Top Colors
Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood


Top Boot
The top boot, a two-way-stretch, coated fabric, is provided in colors keyed to the upholstery, NOT TO THE TOP MATERIAL.


Equipment, Standard and Optional
Refer to Equipment Chart on Pages A-9 and -10.

INTERIOR DIMENSIONS		
	Front	Rear
Head room	38.4″	37.9″
Shoulder room	60.9″	53.4″
Hip room	63.5″	55.2″
Leg room	40.5″	37.4″
Seat height	12.4″	14.5″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. Panel Ends	X	Headlamp
Courtesy rear quarter (and rear of console with bucket seats)	X	L.H. Rear Quarter Trim Panel
Door, red warning	X	
Map, on inst. cluster		Integral
Glove Box, inner console and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine





PERFORATED LEATHER

VINYL

NON-PERFORATED LEATHER

De Ville Convertible

Downloaded from www.Manualslib.com manuals search engine


DE VILLE CONVERTIBLE

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	LEATHER		FORMED FRONT SEAT BACK PANELS	INSERTS	ARMREST	TOP	LOWER	
	INSERTS	BOLSTERS						
	Kashmir Perforated Grain	Center Section—Non-perforated Leather • Cushion Facings—Expanded Vinyl • Top Boot	Front Seat Wings • Laces • Console Case • Head Rests	Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
351 351B	Black		Black	Black		Black	Black	Black
352 352B	White		White	White[1]		Black	Black	Black
353	White		White	White[1]		Dk. Blue	Med. Blue	Med. Blue
354	White		White	White[2]		Dk. Red	Red	Dk. Red
355	White		White	White[1]		Dk. Aqua	Med. Aqua	Med. Aqua
360	Med. Blue		Med. Blue	Med. Blue		Dk. Blue	Med. Blue	Med. Blue
368	Med. Aqua		Med. Aqua	Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
371	Dk. Green		Dk. Green	Dk. Green		Dk. Green	Dk. Green	Dk. Green
380	Covert		Covert	Covert[3]		Dk. Covert	Covert	Covert
382 382B	Sandalwood		Sandalwood	Sandalwood[4]		Dk. Beige	Sandalwood	Med. Beige
385	Antique Saddle		Ant. Saddle	Antique Saddle		Dk. Beige	Ant. Saddle	Med. Saddle
388 388B	Red		Red	Red		Dk. Red	Red	Dk. Red
389	Maroon		Maroon	Maroon		Maroon	Maroon	Maroon

**Moulded Soft Vinyl Parts include:* Rearview Mirror Support Cover; I.C.V. Regulator Knobs.

1. Seat Belts Same as Carpet
2. Red Seat Belts
3. Med. Fawn Moulded Vinyl Parts
4. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



COUPE DE VILLE

Upholstery Styling

Fabric or, optional at extra cost, leather selections listed on the facing page are fashioned in four-section pinch seam, biscuit styling with a recessed button centered in each section.

Seat Styling

Coupe (Notch-back) front seat with folding seat backs divided by a center armrest. Rear seat center armrest is also provided. Front seat backs latch in place until released individually by pushbuttons located (one) at outboard side of each front seat backrest. Bucket seats, an extra-cost option, are also available with a console between the seats and no center armrest in front. Recliner, available for passenger bucket seat, permits passenger to tilt seat back to various reclining positions. Head rests are included for both bucket seats with this extra-cost option. Recliner may be ordered by adding Code R to Code B when ordering bucket seats.

Additional Leather Choices

When an owner desires a leather color not listed on the facing page, refer to the Special Order and Price sections for availability and price.

Padded Vinyl Roof

Available at extra cost, the Padded Vinyl Roof adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.

INTERIOR DIMENSIONS		
	Front	Rear
Head room	38.2"	37.3"
Shoulder room	60.9"	60.6"
Hip room	63.6"	55.0"
Leg room	41.0"	38.1"
Seat height	12.4"	14.5"

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. Panel Ends	X	Headlamp
Courtesy rear quarter (and rear of console with bucket seats)	X	L.H. Rear Quarter Trim Panel
Door, red warning	X	
Map, on inst. cluster		Integral
Glove Box, inner console and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine





Coupe de Ville

PERFORATED LEATHER

VINYL

NON-PERFORATED LEATHER

Downloaded from www.Manualslib.com manuals search engine

COUPE DE VILLE

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANELS	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Center Section—Non-perforated Leather • Headlining—Corded Coated Fabric	Front Seat Wings • Laces • Console Case • Cushion Facings—Expanded Vinyl • Head Rests	Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
311	Black Duchess	Black		Black		Black	Black	Black
320	Med. Blue Duchess	Med. Blue		Med. Blue		Dk. Blue	Med. Blue	Med. Blue
326	Dk. Blue Darien	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
328	Med. Aqua Darien	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
330	Med. Green Duchess	Med. Green		Med. Green[1]		Dk. Green	Med. Green	Med. Green
340	Covert Darien	Covert		Covert[2]		Dk. Covert	Covert	Covert
344	Med. Beige Duchess	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige
349	Maroon Darien	Maroon		Maroon		Maroon	Maroon	Maroon


Leather Options at Extra Charge

	INSERTS Kashmir Perforated Leather	CENTER SECTION Non-perforated Leather				
351 351B	Black	Black	Black	Black	Black	Black
352	White	White	White[3]	Black	Black	Black
353	White	White	White[3]	Dk. Blue	Med. Blue	Med. Blue
354	White	White	White[4]	Dk. Red	Red	Dk. Red
355	White	White	White[3]	Dk. Aqua	Med. Aqua	Med. Aqua
360	Med. Blue	Med. Blue	Med. Blue	Dk. Blue	Med. Blue	Med. Blue
382	Sandalwood	Sandalwood	Sandalwood[5]	Dk. Beige	Sandalwood	Med. Beige
385	Antique Saddle	Ant. Saddle	Antique Saddle	Dk. Beige	Ant. Saddle	Med. Saddle
388 388B	Red	Red	Red	Dk. Red	Red	Dk. Red

**Moulded Soft Vinyl Parts Include:* Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs.

1. Dark Green Moulded Vinyl Parts
2. Med. Fawn Moulded Vinyl Parts
3. Seat Belt Color Same as Carpets
4. Red Seat Belts
5. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



HARDTOP SEDAN DE VILLE

Upholstery Styling

Fabric and leather upholstery or, optional at extra cost, leather selections are tailored in four-section pinch seam, biscuit styling with a recessed button centered in each section.

Seat Styling

With combined fabric and leather upholstery, seats are the conventional, bench type with straight-across, stationary seat backs and a folding center armrest front and rear. With leather upholstery selections, coupe (Notch-back) seat styling is provided, but with stationary front seat backs.

Bucket seats, optional at extra cost with two leather upholstery selections, have a console between the front seats, no front seat center armrest and stationary seat backs. They may be ordered also with a reclining passenger seat, optional at extra cost, which includes head rests for both bucket seats. Add Code R to B when ordering the recliner bucket seat feature.

Assist handles on the rear of the front seat back are provided *only* with the conventional, straight-across, bench type seat.

Additional Leather Choices

When a leather not listed on the facing page is requested by the customer, refer to the Special Order and Price sections for availability and price.

Padded Vinyl Roof

Available at extra cost, the Padded Vinyl Roof adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood

Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.


INTERIOR DIMENSIONS		
	Front	Rear
Head room	37.8"	37.2"
Shoulder room	60.8"	60.0"
Hip room	63.6"	62.7"
Leg room	41.0"	39.7"
Seat height	12.4"	14.5"


INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
*Courtesy-Inst. panel ends, rear quarter (and rear of console with bucket seats)	X	Headlamp
Door, red warning	X	
Map, on inst. panel		Integral
Glove Box, inner console and Trunk		Automatic


*With bench seat styling (cloth and leather combinations) rear courtesy lamps operate from rear door jambs and manual switch on rear of front seat back. Headlamp switch and front door jambs operate Inst. panel courtesy lamps only.

Downloaded from www.Manualslib.com manuals search engine









CLOTH

PERFORATED LEATHER

VINYL

NON-PERFORATED LEATHER

Hardtop Sedan de Ville

Downloaded from www.Manualslib.com manuals search engine

HARDTOP SEDAN DE VILLE

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Center Section—Non-perforated Leather • Headlining—Corded Coated Fabric	Front Seat Wings • Laces • Console Case • Cushion Facings—Expanded Vinyl • Head Rests	Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
311	Black Duchess	Black		Black		Black	Black	Black
320	Med. Blue Duchess	Med. Blue		Med. Blue		Dk. Blue	Med. Blue	Med. Blue
326	Dk. Blue Darien	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
328	Med. Aqua Darien	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
330	Med. Green Duchess	Med. Green		Med. Green[1]		Dk. Green	Med. Green	Med. Green
340	Covert Darien	Covert		Covert[2]		Dk. Covert	Covert	Covert
344	Med. Beige Duchess	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige
349	Maroon Darien	Maroon		Maroon		Maroon	Maroon	Maroon


Leather Options at Extra Charge

	INSERTS Kashmir Perforated Leather	CENTER SECTION Non-perforated Leather				
351 351B	Black	Black	Black	Black	Black	Black
352	White	White	White[3]	Black	Black	Black
353	White	White	White[3]	Dk. Blue	Med. Blue	Med. Blue
354	White	White	White[4]	Dk. Red	Red	Dk. Red
355	White	White	White[3]	Dk. Aqua	Med. Aqua	Med. Aqua
360	Med. Blue	Med. Blue	Med. Blue	Dk. Blue	Med. Blue	Med. Blue
382	Sandalwood	Sandalwood	Sandalwood[5]	Dk. Beige	Sandalwood	Med. Beige
385	Antique Saddle	Ant. Saddle	Antique Saddle	Dk. Beige	Ant. Saddle	Med. Saddle
388 388B	Red	Red	Red	Dk. Red	Red	Dk. Red

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs.

1. Dark Green Moulded Vinyl Parts
2. Med. Fawn Moulded Vinyl Parts
3. Seat Belt Color Same as Carpets
4. Red Seat Belts
5. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



SEDAN DE VILLE

Upholstery Styling

Fabric and leather upholstery or, optional at extra cost, leather selections are tailored in four-section pinch seam, biscuit styling with a recessed button centered in each section.

Seat Styling

With combined fabric and leather upholstery, seats are the conventional, bench type with straight-across, stationary seat backs and a folding center armrest front and rear. With leather upholstery selections, coupe (Notch-back) seat styling is provided but with stationary front seat backs.

Assist handles on the rear of the front seat back are provided *only* with the conventional, straight-across, bench type seat.

Additional Leather Choices

When a leather not listed on the facing page is requested by the customer, refer to the Special Order and Price sections for availability and price.

Padded Vinyl Roof

Available at extra cost, the Padded Vinyl Roof adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood

Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.

INTERIOR DIMENSIONS		
	Front	Rear
Head room	39.0"	38.2"
Shoulder room	60.8"	60.0"
Hip room	63.6"	62.5"
Leg room	41.0"	41.9"
Seat height	12.4"	14.6"

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
*Courtesy-Inst. panel ends and rear quarter	X	Headlamp
Door, red warning	X	
Map, on inst. panel		Integral
Glove Box and Trunk		Automatic

*With bench seat styling (cloth and leather combinations) rear courtesy lamps operate from rear door jambs and manual switch on rear of front seat back. Headlamp switch and front door jambs operate inst. panel courtesy lamps only.

Downloaded from www.Manualslib.com manuals search engine



Sedan de Ville

Downloaded from www.Manualslib.com manuals search engine

SEDAN DE VILLE

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS Nylon-Viscose Cloth	BOLSTERS Center Section—Non-perforated Leather • Headlining—Corded Coated Fabric	FORMED FRONT SEAT BACK PANELS Front Seat Wings • Laces • Console Case • Cushion Facings—Expanded Vinyl • Head Rests	INSERTS Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	ARMREST Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	TOP Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	LOWER Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
311	Black Duchess	Black		Black		Black	Black	Black
320	Med. Blue Duchess	Med. Blue		Med. Blue		Dk. Blue	Med. Blue	Med. Blue
326	Dk. Blue Darien	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
328	Med. Aqua Darien	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
330	Med. Green Duchess	Med. Green		Med. Green[1]		Dk. Green	Med. Green	Med. Green
340	Covert Darien	Covert		Covert[2]		Dk. Covert	Covert	Covert
344	Med. Beige Duchess	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige
349	Maroon Darien	Maroon		Maroon		Maroon	Maroon	Maroon


Leather Options at Extra Charge


	INSERTS Kashmir Perforated Leather	CENTER SECTION Non-perforated Leather				
351	Black	Black	Black	Black	Black	Black
352	White	White	White[3]	Black	Black	Black
353	White	White	White[3]	Dk. Blue	Med. Blue	Med. Blue
354	White	White	White[4]	Dk. Red	Red	Dk. Red
355	White	White	White[3]	Dk. Aqua	Med. Aqua	Med. Aqua
360	Med. Blue	Med. Blue	Med. Blue	Dk. Blue	Med. Blue	Med. Blue
382	Sandalwood	Sandalwood	Sandalwood[5]	Dk. Beige	Sandalwood	Med. Beige
385	Antique Saddle	Ant. Saddle	Antique Saddle	Dk. Beige	Ant. Saddle	Med. Saddle
388	Red	Red	Red	Dk. Red	Red	Dk. Red

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs.

1. Dark Green Moulded Vinyl Parts
2. Med. Fawn Moulded Vinyl Parts
3. Seat Belt Color Same as Carpets
4. Red Seat Belts
5. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine





FLEETWOOD ELDORADO

Upholstery Styling

Fleetwood Eldorado upholstery in leather, or cloth with coated fabric bolsters, has distinctively tailored three-panel seat and seat back inserts extending from the forward edge of the seat cushion up to the smartly stitch-paneled seat back bolster.

Seat Styling

Available in Strato-bench styling with wide center armrest, front, and folding front seat backs which latch in place until released individually by push-buttons located (one) at outboard side of each front seat backrest.

Strato-bucket seats, available at extra cost, have a console between the two front seats and no front seat center armrest. Recliner, available at extra cost for passenger bucket seat, permits tilting the seat back to various reclining positions. Head rests are included for both bucket seats with this option. Recliner may be ordered by adding Code R to Code B when ordering bucket seats. Recliner also available for Strato-bench passenger seat on Eldorado only.

Additional Leather Choices

In addition to the leather selections on the opposite page, certain colors are available on special order at extra cost (see Special Order and Price sections).

Padded Vinyl Roof

Available at extra cost, the Padded Vinyl Roof adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood

Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.

NOTE: Rear ash receiver and lighter are centered on rear of front seat back on Strato-bench seats. On Strato-bucket seats, lighter is on rear of console, ash receivers on rear of door armrests.

INTERIOR DIMENSIONS		
	Front	Rear
Head room	37.7″	37.6″
Shoulder room	59.6″	55.7″
Hip room	62.2″	54.2″
Leg room	40.9″	36.2″
Seat height	10.8″	12.0″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends	X	Headlamp
Courtesy-rear quarter (and rear of console with bucket seats)	X	L.H. Rear quarter trim panel
Door, red warning	X	
Map, on inst. cluster		Integral
Glove Box, inner console and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine



Fleetwood Eldorado

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD ELDORADO

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANELS	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Expanded Vinyl • Cushion Facings • Headlining—Perforated Taffeta Vinyl	Front Seat Wings • Laces • Console Case • Head Rests	Vacuum Formed Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Vacuum Formed Vinyl	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
410	Black & White Dalmatian	Black		Black		Black	Black	Black
411	Black Darien	Black		Black		Black	Black	Black
426	Dk. Blue Darien	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
429	Dk. Aqua Darien	Dk. Aqua		Dk. Aqua		Dk. Aqua	Dk. Aqua	Dk. Aqua
431	Dk. Green Darien	Dk. Green		Dk. Green		Dk. Green	Dk. Green	Dk. Green
440	Covert Darien	Covert		Covert[1]		Dk. Covert	Covert	Covert
444	Med. Beige Darien	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige


Leather Options at Extra Charge

	INSERTS Kashmir Perforated Leather	CENTER SECTION Non-perforated Leather				
451 451B	Black	Black	Black	Black	Black	Black
452	White	White	White[2]	Black	Black	Black
466	Dk. Blue	Dk. Blue	Dk. Blue	Dk. Blue	Dk. Blue	Dk. Blue
469	Dk. Aqua	Dk. Aqua	Dk. Aqua	Dk. Aqua	Dk. Aqua	Dk. Aqua
471	Dk. Green	Dk. Green	Dk. Green	Dk. Green	Dk. Green	Dk. Green
482 482B	Sandalwood	Sandalwood	Sandalwood[3]	Dk. Beige	Sandalwood	Med. Beige
485	Antique Saddle	Ant. Saddle	Antique Saddle	Dk. Beige	Ant. Saddle	Med. Saddle
488	Red	Red	Red	Dk. Red	Red	Dk. Red
489	Maroon	Maroon	Maroon	Maroon	Maroon	Maroon

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; Coat Hooks; I.C.V. Regulator Knobs.

1. Med. Fawn Moulded Vinyl Parts
2. Black Seat Belts
3. Parchment Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



FLEETWOOD SIXTY SPECIAL SEDAN

Upholstery Styling

Shown above is the horizontal pillow and button style tailoring used with the fabric and leather or leather selections on the facing page. With fabric selections (Devonshire cloth) upholstery is tailored in wide piping with the vertical panels of the upper seat back elegantly embroidered and the lower seat back comfort-contoured with two rows of deeply recessed buttons (see Page C-29).

Seat Styling

Bench type with straight-across, stationary back rests and a folding center armrest, front and rear.

Additional Leather Choices

In addition to the leather selections on the opposite page, certain colors are available on special order at extra cost. Refer to the Special Order and Price sections for availability and price.


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.

INTERIOR DIMENSIONS		
	Front	Rear
Head room	39.1″	38.0″
Shoulder room	61.3″	59.7″
Hip room	63.6″	62.4″
Leg room	41.0″	45.4″
Seat height	12.0″	14.2″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-inst. panel ends	X	Headlamp
Courtesy-rear quarter* and rear door	X	*Manual on rear of front seat back
Doors, red warning	X	
Map, on inst. panel		Integral
Glove Box and Trunk		Automatic

Downloaded from www.Manualslib.com manuals search engine





Fleetwood Sixty Special Sedan

CLOTH

VINYL

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SIXTY SPECIAL—FLEETWOOD BROUGHAM. Cloth with Leather Selections.

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Center Section Non-perforated Leather • Cushion Facings Expanded Vinyl	Front Seat Wings • Laces • Headlining* • Head Rests • Assist Handles	Nylon-Viscose Cloth Same as Seat Inserts • Upper Doors Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Trays & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
010	Black Damascus	Black		Black		Black	Black	Black
011	Black Diplomat	Black		Black		Black	Black	Black
025	Dk. Blue Diplomat	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
026	Dk. Blue Damascus	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
028	Med. Aqua Damascus	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med. Aqua
029	Dk. Aqua Diplomat	Dk. Aqua		Dk. Aqua		Dk. Aqua	Dk. Aqua	Dk. Aqua
040	Covert Damascus	Covert		Covert[1]		Dk. Covert	Covert	Covert
044	Med. Beige Diplomat	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige
049	Maroon Diplomat	Maroon		Maroon		Maroon	Maroon	Maroon

**Moulded Soft Vinyl Parts include:* Rearview Mirror Support Cover; Coat Hooks.

**Headlining:* Early Production—Taffeta Vinyl; Later Cars—Ascot Cloth.

1. Med. Fawn Moulded Vinyl Parts.

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SIXTY SPECIAL—FLEETWOOD BROUGHAM. All Cloth Selections with Embroidered Back Rests.

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Devonshire Cloth	Nylon-Viscose Devonshire Cloth • Also—Cushion Facings	Front Seat Wings • Laces • Headlining* • Head Rests • Assist Handles	Nylon-Viscose Devonshire Cloth Same as Seat Inserts • Upper Doors Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Trays & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
016	Lt. Gray		Lt. Gray	Lt. Gray		Dk. Gray	Lt. Gray	Med. Gray
021	Med. Blue		Med. Blue	Med. Blue		Dk. Blue	Med. Blue	Med. Blue
030	Med. Green		Med. Green	Med. Green[1]		Dk. Green	Med. Green	Med. Green
043	Med. Beige		Med. Beige	Med. Beige		Dk. Beige	Med. Beige	Med. Beige

**Moulded Soft Vinyl Parts include:* Rearview Mirror Support Cover; Coat Hooks.

**Headlining:* Early Production—Taffeta Vinyl; Later Cars—Ascot Cloth.

1. Dk. Green Moulded Vinyl Parts.

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SIXTY SPECIAL—FLEETWOOD BROUGHAM. Leather Options at Extra Charge.


CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	LEATHER		FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	INSERTS	BOLSTERS						
	Non-perforated Leather	Center Section Non-perforated Leather • Cushion Facings Expanded Vinyl	Front Seat Wings • Laces • Headlining* • Head Rests • Assist Handles	Non-perforated Leather • Upper Doors—Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
051	Black		Black	Black		Black	Black	Black
052	White		White	White[1]		Black	Black[3]	Black
060	Med. Blue		Med. Blue	Med. Blue		Dk. Blue	Med. Blue	Med. Blue
071	Dk. Green		Dk. Green	Dk. Green		Dk. Green	Dk. Green	Dk. Green
082	Sandalwood		Sandalwood	Sandalwood[2]		Dk. Beige	Sandalwood	Med. Beige
085	Antique Saddle		Antique Saddle	Antique Saddle		Dk. Beige	Antique Saddle	Med. Saddle
088	Red		Red	Red		Dk. Red	Red	Dk. Red
089	Maroon		Maroon	Maroon		Maroon	Maroon	Maroon

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; Coat Hooks.

*Headlining: Early Production—Corded Vinyl; Later Cars —Taffetta Vinyl.

1. Black Seat Belts.
2. Parchment Moulded Vinyl Parts.
3. Garnish Moldings White.

Downloaded from www.Manualslib.com manuals search engine



FLEETWOOD BROUGHAM

Upholstery Styling

Fabric and leather, as shown above, or leather are fashioned in horizontal pillow and button styling. Fabric selections (Devonshire cloth) are tailored in wide piping with finely embroidered vertical panels on the upper seat backs and a comfort-contoured lower seat back formed by two rows of recessed buttons (see Page C-29).

Seat Styling

Bench type seats with straight-across, stationary backrests and a folding center armrest, front and rear.

Additional Leather Choices

In addition to the leather selections on the opposite page, certain colors are available on special order at extra cost. Refer to the Special Order and Price sections for availability and price.

Padded Vinyl Roof

Provided as standard on the Brougham, the Padded Vinyl Roof with Brougham name on upper quarter panels adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10.


INTERIOR DIMENSIONS		
	Front	Rear
Head room	39.1″	38.0″
Shoulder room	61.3″	59.7″
Hip room	63.6″	62.4″
Leg room	40.0″	45.4″
Seat height	12.0″	14.2″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends	X	Headlamp
Courtesy-rear quarter* and rear door	X	
Doors, red warning	X	
Map, on inst. panel		Integral
Glove Box and Trunk		Automatic
Reading Spots, swivel	X	Rear quarter trim panels
Seat Back Trays		Automatic

Downloaded from www.Manualslib.com manuals search engine







Fleetwood Brougham

VINYL

NON-PERFORATED LEATHER

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SIXTY SPECIAL—FLEETWOOD BROUGHAM. Cloth with Leather Selections.

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Cloth	Center Section Non-perforated Leather • Cushion Facings Expanded Vinyl	Front Seat Wings • Laces • Headlining* • Head Rests • Assist Handles	Nylon-Viscose Cloth Same as Seat Inserts • Upper Doors Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Trays & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
010	Black Damascus	Black		Black		Black	Black	Black
011	Black Diplomat	Black		Black		Black	Black	Black
025	Dk. Blue Diplomat	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
026	Dk. Blue Damascus	Dk. Blue		Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
028	Med. Aqua Damascus	Med. Aqua		Med. Aqua		Dk. Aqua	Med. Aqua	Med Aqua
029	Dk. Aqua Diplomat	Dk. Aqua		Dk. Aqua		Dk. Aqua	Dk. Aqua	Dk. Aqua
040	Covert Damascus	Covert		Covert[1]		Dk. Covert	Covert	Covert
044	Med. Beige Diplomat	Med. Beige		Med. Beige		Dk. Beige	Med. Beige	Med. Beige
049	Maroon Diplomat	Maroon		Maroon		Maroon	Maroon	Maroon

**Moulded Soft Vinyl Parts Include:* Rearview Mirror Support Cover; Coat Hooks.

**Headlining:* Early Production—Taffeta Vinyl; Later Cars—Ascot Cloth.

1. Med. Fawn Moulded Vinyl Parts.

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SIXTY SPECIAL—FLEETWOOD BROUGHAM. All Cloth Selections with Embroidered Back Rests.

CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	BOLSTERS	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	Nylon-Viscose Devonshire Cloth	Nylon-Viscose Devonshire Cloth • Also—Cushion Facings	Front Seat Wings • Laces • Headlining* • Head Rests • Assist Handles	Nylon-Viscose Devonshire Cloth Same as Seat Inserts • Upper Doors Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Trays & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
016	Lt. Gray		Lt. Gray	Lt. Gray		Dk. Gray	Lt. Gray	Med. Gray
021	Med. Blue		Med. Blue	Med. Blue		Dk. Blue	Med. Blue	Med. Blue
030	Med. Green		Med. Green	Med. Green[1]		Dk. Green	Med. Green	Med. Green
043	Med. Beige		Med. Beige	Med. Beige		Dk. Beige	Med. Beige	Med. Beige

**Moulded Soft Vinyl Parts include:* Rearview Mirror Support Cover; Coat Hooks.

**Headlining:* Early Production—Taffeta Vinyl; Later Cars—Ascot Cloth.

1. Dk. Green Moulded Vinyl Parts.

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SIXTY SPECIAL—FLEETWOOD BROUGHAM. Leather Options at Extra Charge.


CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	LEATHER		FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
	INSERTS	BOLSTERS						
	Non-perforated Leather	Center Section Non-perforated Leather • Cushion Facings Expanded Vinyl	Front Seat Wings • Laces • Headlining* • Head Rests • Assist Handles	Non-perforated Leather • Upper Doors: Expanded Vinyl • Seat Belt Webbing • Moulded Vinyl Parts*	Top: Padded Vinyl • Side: Vinyl Covered • Door Pull	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf • De-Fogger Grille	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Cowl Quarter Grille • Retractor Housing • Anchor Cover Retainer Button
051	Black		Black	Black		Black	Black	Black
052	White		White	White[1]		Black	Black[3]	Black
060	Med. Blue		Med. Blue	Med. Blue		Dk. Blue	Med. Blue	Med. Blue
071	Dk. Green		Dk. Green	Dk. Green		Dk. Green	Dk. Green	Dk. Green
082	Sandalwood		Sandalwood	Sandalwood[2]		Dk. Beige	Sandalwood	Med. Beige
085	Antique Saddle		Antique Saddle	Antique Saddle		Dk. Beige	Antique Saddle	Med. Saddle
088	Red		Red	Red		Dk. Red	Red	Dk. Red
089	Maroon		Maroon	Maroon		Maroon	Maroon	Maroon

**Moulded Soft Vinyl Parts include:* Rearview Mirror Support Cover; Coat Hooks.

**Headlining:* Early Production—Corded Vinyl; Later Cars —Taffetta Vinyl.

1. Black Seat Belts.
2. Parchment Moulded Vinyl Parts.
3. Garnish Moldings White.

Downloaded from www.Manualslib.com manuals search engine



FLEETWOOD SEVENTY-FIVE SEDAN

Upholstery Styling

Devonshire cloth selections as shown above, are fashioned in wide piping with the upper area of the seat backs elegantly embroidered and the lower seat back area comfort-contoured with two rows of deeply recessed buttons. Fabric and leather combinations and Decordo cloth are tailored in horizontal pillow and button style as shown on previous Page C-27. Front compartment of the Limousine has leather upholstery in 2-inch piped styling (see Page C-31).

Seat Styling

Bench type with straight-across, stationary seat backs and folding center armrests front and rear on 9-passenger sedan.

Limousine (see next page), has bench seat styling but without front seat center armrest and has a power-operated division glass between the front and rear compartments.

Auxiliary Seats

Two auxiliary seats are provided in the rear compartment. They fold into a recess in the rear of the front seat back when not in use.

Padded Vinyl Roof

Available at extra cost, the Padded Vinyl Roof adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood


Equipment, Standard and Optional


Refer to Equipment Chart on Pages A-9 and -10. See Landau Roof illustration on Page C-7 and Page C-33.


INTERIOR DIMENSIONS		
	Front	Rear
Head room	40.5″	38.4″
Shoulder room	61.9″	59.4″
Hip room	63.6″	57.7″
Leg room	40.4″	—
Seat height	11.5″	12.8″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends	X	Headlamp
Courtesy rear door	X	
Reading Spot, on A/C roof grilles	X	Rear quarter trim panels
Doors, red warning	X	
Map, on inst. panel		Integral

Downloaded from www.Manualslib.com manuals search engine







Fleetwood Seventy-Five Sedan

CLOTH

VINYL

NON-PERFORATED LEATHER

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SEVENTY-FIVE SEDAN


	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	INSERTS	CENTER SECTION	FORMED FRONT SEAT BACK PANEL	INSERTS	ARMREST	TOP	LOWER	
CODES	Nylon-Viscose Cloth	Nylon-Viscose Cloth or Non-perforated Leather • Cushion Facings—Expanded Vinyl or Cloth • Seaming Laces	Rear Side Arm Rests—Top & Side: Expanded Vinyl • Headlining* • Head Rests • Assist Handles • A/C Outlets in Headlining	Nylon-Viscose Cloth—Same as Seat Inserts • Seat Belt Webbing • Moulded Vinyl Parts* • Windlace • Door Header Lace	Front—Coated Fabric	Radio Speaker Grilles • Climate Control Sensor Grilles • Rear Shelf	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors • Garnish Mouldings	Tropicana & Tamara Quality • Retractor Housing • Anchor Cover Retainer Button • Foot Rests • Carpet Binding
716	Lt. Gray Devonshire	Lt. Gray Devonshire	Lt. Gray	Lt. Gray		Dk. Gray	Lt. Gray	Med. Gray
719	Med. Gray Decordo	Med. Gray Decordo	Med. Gray[1]	Med. Gray[2]		Dk. Gray	Med. Gray	Med. Gray
721	Med. Blue Devonshire	Med. Blue Devonshire	Med. Blue	Med. Blue		Dk. Blue	Med. Blue	Med. Blue
726	Dk. Blue Damascus	Dk. Blue Leather	Dk. Blue	Dk. Blue		Dk. Blue	Dk. Blue	Dk. Blue
743	Med. Beige Devonshire	Med. Beige Devonshire	Med. Beige	Med. Beige		Dk. Beige	Med. Beige	Med. Beige

**Moulded Soft Vinyl Parts include:* Rearview Mirror Support Cover; I.C.V. Regulator Knobs.

**Headlining:* Code 719 Early Production Lt. Gray Corded Vinyl; Later Cars Taffeta Vinyl.
All Others—Early Production Taffeta Vinyl; Later Cars—Ascot Cloth.

1. Lt. Gray Headlining
2. Lt. Gray Seat Belts & Moulded Vinyl Parts

Downloaded from www.Manualslib.com manuals search engine



FLEETWOOD SEVENTY-FIVE LIMOUSINE

Upholstery Styling

Chauffeur compartment is fashioned in 2-inch piping of leather selections listed on opposite page. The rear compartment with fabric and leather or Decordo cloth is styled in horizontal pillow and button style. Devonshire fabric selections are tailored in wide piping with upper seat backs finely embroidered and the lower seat back area contoured for maximum comfort with two rows of deeply recessed buttons.

Seat Styling

Bench type with straight-across, stationary seat backs with a folding center armrest in the rear compartment.

Division Glass

Dividing the front and rear compartments is a division glass, power operated, which may be raised or lowered by controls on the right rear quarter trim panel.

Auxiliary Seats

Two auxiliary seats in the rear compartment may be folded forward into recesses in the rear of the front seat back.

Padded Vinyl Roof

Available at extra cost, the Padded Vinyl Roof adds individual distinction, can provide two-tone exterior appearance and further isolates sound from the car interior.

Padded Roof Colors

Code: 1. White 2. Black 3. Medium Blue 5. Dark Brown 6. Sandalwood


Equipment, Standard and Optional


See Landau Roof illustration on Page C-7 and information on next page. Refer to complete Equipment Chart on Pages A-9 and -10.

INTERIOR DIMENSIONS		
	Front	Rear
Head room	40.5″	38.4″
Shoulder room	61.9″	59.4″
Hip room	63.6″	57.7″
Leg room	40.4″	—
Seat height	11.8″	12.8″

INTERIOR LAMPS		
	SWITCHES	
LAMPS	Door Jambs	Other
Courtesy-Inst. panel ends	X	Headlamp
Courtesy-rear door	X (Rear)	
Reading Spot, on A/C roof grilles	X (Rear)	Rear quarter trim panels
Door, Front, red warning	X	
Map, on inst. panel		Integral
Map, Spot, on header		Integral

Downloaded from www.Manualslib.com manuals search engine





Fleetwood Seventy-Five Limousine

CLOTH

VINYL

NON-PERFORATED LEATHER

Downloaded from www.Manualslib.com manuals search engine

FLEETWOOD SEVENTY-FIVE LIMOUSINE


CODES	SEATS			DOORS		INSTRUMENT PANELS		CARPETS
	FRONT	REAR	FORMED FRONT SEAT BACK PANEL	FRONT	REAR	TOP	LOWER	
	Non-perforated Leather—2" Pleats • Cushion Facing—Expanded Vinyl • Wings & Side Panels—Coated Fabric • Head Rests	Nylon-Viscose Cloth Inserts • Nylon-Viscose Cloth or Leather Center Section • Cushion Facings Expanded Vinyl or Cloth	Nylon-Viscose Cloth Inserts Same as Rear Seat Inserts • Rear Quarter Side Arm Rest • Headlining* • Garnish Mouldings	Upper Doors—Expanded Vinyl • Arm Rests—Top & Side Coated Fabric • Seat Belt Webbing • Moulded Vinyl Parts*	Upper Doors—Expanded Vinyl • Nylon-Viscose Cloth Inserts Same as Rear Seat Inserts • Arm Rests Top & Side—Expanded Vinyl	Radio Speaker Grilles • Climate Control Sensor Grilles	Steering Wheel • Control Lever Caps • Steering Column & Cover • Ash Tray & Glove Box Doors	Tropicana & Tamara Quality • Retractor Housing
716	Black	Lt. Gray Devonshire	Lt. Gray	Black	Lt. Gray	Black	Black	Med. Gray[4]
719	Black	Med. Gray Decordo	Med. Gray[3]	Black	Med. Gray	Black	Black	Med. Gray[4]
721	Black	Med. Blue Devonshire	Med. Blue	Black	Med. Blue	Black	Black	Med. Blue[4]
726	Black	Dk. Blue[2] Damascus	Dk. Blue	Black	Dk. Blue	Black	Black	Dk. Blue[4]
743	Black	Med. Beige Devonshire	Med. Beige	Black	Med. Beige	Black	Black	Med. Beige[4]
716G	Lt. Gray	Lt. Gray Devonshire	Lt. Gray	Lt. Gray	Lt. Gray	Dk. Gray	Lt. Gray	Med. Gray
719G	Lt. Gray	Med. Gray Decordo	Med. Gray[3]	Lt. Gray	Med. Gray	Dk. Gray	Lt. Gray	Med. Gray
721M	Dk. Blue	Med. Blue Devonshire	Med. Blue	Dk. Blue[1]	Med. Blue	Dk. Blue	Dk. Blue	Dk. Blue—Frt. Med. Blue—Rr.
726M	Dk. Blue	Dk. Blue[2] Damascus	Dk. Blue	Dk. Blue	Dk. Blue	Dk. Blue	Dk. Blue	Dk. Blue
743F	Med. Beige	Med. Beige Devonshire	Med. Beige	Med. Beige	Med. Beige	Dk. Beige	Med. Beige	Med. Beige

*Moulded Soft Vinyl Parts include: Rearview Mirror Support Cover; I.C.V. Regulator Knobs.

*Headlining: Codes 719 & 719G—Early Production Lt. Gray Corded Vinyl; Later Cars Taffeta Vinyl. All Others—Early Production Taffeta Vinyl; Later Cars—Ascot Cloth.

1. Med. Blue Moulded Vinyl Parts
2. Dark Blue Leather Center Section
3. Lt. Gray Headlining
4. Black Carpet in Front Compartment

Downloaded from www.Manualslib.com manuals search engine



LANDAU ROOF OPTION
FLEETWOOD SEVENTY-FIVE SEDAN AND LIMOUSINE

Landau Roof

The distinctive Fleetwood styling attains an ultimate elegance when a Landau Roof is added to either of the Seventy-Five body styles.

New Landau Bows

An attractive slim Landau Bow fully chrome finished has been newly designed for the padded, vinyl-covered Landau Roof for 1967. The arms are in bright metal and a circular brushed finish is on the center pivot section and the two end studs.

New Rear Window

A departure from convention is the reduction of the rear window size which adds to rear compartment privacy. This window has a new rectangular or trapezoid shape instead of rounded four corners.

Options

The following options are also available:

1. Omit the Landau Bows.
2. Shape the small rear window with rounded corners.
3. Retain the regular rear window size.

Exterior Ornamentation

A Fleetwood plaque on the upper rear quarters of the vinyl covered, padded roof and the wreath and crest on the lower rear quarter panels are included with the Landau option.

Padded Roof Only

A padded roof with standard rear and quarter windows is also available.

Downloaded from www.Manualslib.com manuals search engine



Special Orders

SUBJECT	PAGE
ADVANCE PROCUREMENT REQUESTS	D-11
INTERIOR NOMENCLATURE AND TERMINOLOGY	D-13 & 14
LIMOUSINE-TYPE DIVISION GLASS IN BROUGHAM	D-10
SPECIAL CARPETS	D-8
SPECIAL CLOTHS	
All Cloth Upholstery	D-6
Bucket Seats in Cloth	D-9
Cloth Front Compartment in Limousine	D-9
Decordo Cloth in Brougham and Sixty Special	D-8
Eldorado Cloth in DeVilles	D-6
For Eldorado (from other body styles)	D-6
Non-standard Upholstery in Seventy-Fives	D-11
Two-tone Combinations	D-7
Wool Broadcloth (available in all body styles)	D-10
Contrasting Seaming Laces	D-7
SPECIAL COLORS (EXTERIOR)	
"Fire-Frost" Colors	D-12
Past Model Exterior Colors	D-12
SPECIAL LEATHER	
Available Colors	D-3
Bucket Seats	D-9
Bucket Seats, in Brougham and Sixty Special	D-9
Front Compartment on Brougham and Sixty Special	D-10
General Information	D-2
In the Brougham and Sixty Special	D-5
In the DeVilles	D-4
In the Eldorado	D-5
Maximum Leather	D-5
Non-perforated Leather	D-4
Seats Only in White Leather	D-7
Two-tone Combinations	D-7
With Cloth Seat Inserts on Eldorado	D-5
SPECIAL TOP BOOTS (CONVERTIBLE)	D-4
SPECIAL VINYL COLORS (CALAIS SERIES)	D-6

Downloaded from www.Manualslib.com manuals search engine

Special Leather

15 Leather Options
Leather upholstery is available as a production option or on special order for all body styles except the Calais series on which it is not available.

Please refer to chart on the next page for a list of the fifteen standard and special leather colors.

Price Schedule for Special Orders
On the leather chart the shaded spaces represent colors that may be special ordered. Manufacturer's Suggested Retail Prices, which will be furnished later, may be filled in these spaces.

Standard Leather
The colors that are marked STD indicate they are a regular production option and the M.S.R. Price will be nominal.

Perforated Leather
A Kashmir pattern perforated leather is used in the insert sections of the seats in De Ville and Eldorado cars. The center or bolster areas will be in plain Mill grain leather.

Non-Perforated Leather
On a special order any leather may be specified to be non-perforated in a De Ville or Eldorado body style.

Leather in Sixty Special and Brougham
The leather is non-perforated on the entire seat in the Fleetwood Sixty Special or Brougham. Although perforated leather is not recommended on these two styles, it can be supplied on a special order.

Maximum Leather
In upholstery classified as leather, some components such as cushion skirt, sides of back, front seat back panel, etc., are vinyl. Leather may be substituted in these areas by marking MAXIMUM LEATHER on the order. An M.S.R. Price Schedule which is higher than the special leather prices applies to such "Maximum Leather" orders.

Code Numbers
The first digit of upholstery code numbers designates the car series.

0 Sixty Special and Brougham
2 Calais
3 De Ville
4 Eldorado

The last two numbers represent the color. For example, 351 is Black leather in a De Ville, 051, in a Sixty Special or Brougham.

To conserve space, chart on the next page lists only De Ville or Eldorado leather upholstery code numbers.

Trim Styles in De Ville and Eldorado
Leather upholstery style is the same as the cloth combination in De Ville and Eldorado cars.

Sixty Special and Brougham
The Fleetwood Sixty Special and Brougham have two trim styles. (See pages C-25, -27, -29.) When leather is ordered, pillow and button style will be used as shown on page C-27.

Trim Styles Are Not Interchangeable
The styles of upholstery are not interchangeable between series.

When an upholstery material of one series is ordered for another series, the trim style will remain that of the body style into which it is being installed and not that from which it is taken. e.g., Fleetwood upholstery material ordered in a style 68349 will be in the De Ville four biscuit and button method and not in the pillow and button styling of the Sixty Special.

Where to Find Non-Standard Leather Samples
Leather code numbers 356, 370 and 384 are not in the regular leather section of the upholstery book. They may be found with the cloth samples.

Downloaded from www.Manualslib.com manuals search engine

Leather

		DE VILLE		FLEETWOOD	
COLORS	**CODES***	Convertible **F**	Coupe **J** Hardtop **B** Sedan **L**	Eldorado **H**	60 Special **M** Brougham **P**
Black	**351**	N/C	STD	STD	STD
White—Black Carpet	**352**	N/C	STD	STD	STD
White—Blue Carpet	**353**	N/C	STD		
White—Red Carpet	**354**	N/C	STD		
White—Aqua Carpet	**355**	N/C	STD		
Lt. Gray	**356**			N/A	
Med. Blue	**360**	N/C	STD	N/A	STD
Dk. Blue	**466**			STD	
Med. Aqua	**368**	N/C		N/A	
Dk. Aqua	**469**			STD	
Med. Green	**370**			N/A	
Dk. Green	**371**	N/C		STD	STD
Covert	**380**	N/C			
Sandalwood	**382**	N/C	STD	STD	STD
Med. Beige	**384**				
Antique Saddle	**385**	N/C	STD	STD	STD
Red	**388**	N/C	STD	STD	STD
Maroon	**389**	N/C		STD	STD

Legend

N/C	No Charge	STD	Standard Option—Extra Charge
N/A	Not Available		Special Order—Extra Charge

TRIM CODES: De Ville start with 3, Eldorado 4, Sixty Special and Brougham 0.

Downloaded from www.Manualslib.com manuals search engine

Special Leather in De Ville

Coupe Seats with Leather on Sedans
Coupe type front seats are used in both De Ville four-door styles B and L when upholstered in leather.

This Coupe type seat does not include assist handles on the back side and Coupe seat back latches are omitted since the backrests are anchored and do not tilt forward in four-door types as they do in two-door styles.

Note 000C in Trim Space
The 000C code in the TRIM space indicates that although the car is a four-door Sedan, the front seat will be a "Coupe Type" which has individual backrests.

Omit "C" on Coupe Orders
On Coupe orders omit the letter C from the 000 in the TRIM space. This is because a Coupe seat is standard in all two-door cars.

Sedan Seat Backrest Optional
On special leather upholstery orders, a Sedan bench type seat with a "straight-across" backrest may be specified on blank space in Special Features section of the wholesale order form if assist handles on the back side are desired.

Extra Copy Needed
A copy of all special orders is needed at the Central Office.

Dealers should, therefore, send two copies of non-standard orders to their Zone Office who will in turn forward the extra copy to Central Office.

The extra copy will be used by the Custom Order Department to procure and manufacture the special features.

When Ordering Dark Green Leather (Code 371) Note:

Carpets and Headlining Will Be Medium Green on De Ville Sedan Body Styles
Medium tone green color is used for the ceiling and floor covering with Dark Green leather in De Ville four-door body styles B and L.

On Coupe and with Bucket Seats, Carpets Will Be Dark Green
The Coupe de Ville and any Bucket Seat car (Coupe or Sedan) will have Dk. Green carpets and Med. Green headlining when Dk. Green leather is ordered.

Non-Perforated Leather Available
On De Ville special upholstery orders, non-perforated leather is optional.

To order, indicate N in box captioned NON-PERFORATED LEATHER. Otherwise, the leather will be perforated.

Special Non-perforated Leather

Standard leather grain in De Ville and Eldorado is perforated. In the Brougham and Sixty Special it is non-perforated.

For customers who prefer non-perforated leather in a De Ville or Eldorado, mark on the order form the regular leather code number in TRIM space under SPECIAL FEATURES.

Then type N in square next to caption NON-PERFORATED LEATHER.

Mill Grain
A Mill Grain embossing is applied to non-perforated leather, resulting in a natural hair cell texture.

Mill Grain finish is standard in the center sections of all De Ville and Eldorado leather seats, and in both insert and center sections of the Brougham and Sixty Special.

When non-perforated leather is ordered in a De Ville or Eldorado, the Mill grain finish will be used on the entire seat cushion and backrest.

Convertible Top Boots

Top boot colors match the seats and not the color of the top material.

However, on special orders the top boot color is optional and may be ordered to customer's preference. This choice could harmonize with the exterior body color if it is similar to one of the available coated fabric materials.

All colors are made of two-way stretch materials except Lt. Gray, Dk. Blue, Dk. Aqua, Med. Green and Med. Beige.

Downloaded from www.Manualslib.com manuals search engine

Maximum Leather

Regular leather upholstery implies the use of vinyl for certain interior components.

For those who prefer the use of leather wherever possible, maximum leather may be specified.

When maximum leather is ordered, it will be applied in place of vinyl on the seat cushion skirt, sides of back rests, sides of center armrests, front seat back insert and on De Ville Sedans (styles B and L) the section above rear center armrest and top face of rear seat backrest.

The extra charge for maximum leather is higher than the schedule of M.S.R. Prices for regular special leather.

Maximum leather may be ordered on De Ville, Eldorado, Brougham or Sixty Special cars.

Leather with Cloth Seat Inserts on Eldorado

With cloth upholstered Eldorado seat inserts, the adjoining sections are vinyl. Instead of vinyl, this surrounding area may be ordered in leather by specifying a leather code number in the bolster space of the order form.

Special Leather in Eldorado

Seats Only Available in Special Color
The seats in an Eldorado may be ordered in any color leather or cloth from the other series Cadillac cars (except Calais cloth cannot be used).

However, the other interior parts must be restricted to the eleven standard Eldorado interior colors.

Two-Tone Combination
This means that if a seat upholstery color is selected that is not one of the eleven Eldorado colors, the doors, instrument panels, steering wheel, carpets, headlining and flat seat laces must be in a standard Eldorado color which will result in a two-tone combination.

For example, if Medium Blue is ordered for the seats, such areas as referred to above would be in Dark Blue.

Decorative Laces
On Eldorado seats—either bench or bucket, cloth or leather—there are four ribbon-like, flat, vinyl belts or laces about 3/8" wide. These are decorative and available in the eleven standard Eldorado interior colors. They are referred to as "flat seat laces."

Special Leather in the Brougham and Sixty Special

Leather is Non-Perforated
Non-perforated Mill grain leather is used on the entire seat—inserts and center section—in Brougham and Sixty Special body styles.

This applies to both regular production or special order options and no special markings to this effect are necessary on the order.

Perforated Leather May Be Ordered
Leather upholstery in the Brougham and Sixty Special is fashioned in a pillow and button style with form-fitting concave backrests.

The overall appearance of non-perforated leather is regarded as more appropriate for this trim style. However, perforated leather may be ordered by indicating "Perforated Leather" in the blank lower right section of the order form.

Coupe Seat Not Available
The front seat will be a regular Sedan bench type with undivided straight-across backrest.

A Coupe type seat is not available in the Brougham and Sixty Special.

Downloaded from www.Manualslib.com manuals search engine

Special Color Vinyl Upholstery

For Calais Series
The six special vinyl colors listed below are available in Calais series cars on special order.

These are in addition to Black and Sandalwood, which are offered as regular vinyl interior options at extra charge.

Colors	Codes
White	252
Med. Blue	260
Med. Aqua	268
Med. Green	270
Med. Covert	280
Med. Beige	284

White Vinyl
In a White vinyl interior, the following parts will be Black:

Instrument Panels—Top & Lower
Steering Wheel and Control Knobs
Carpets
Door Pulls
Window Crank Knobs
Seat Belts

Color Substitution Possible
However, instead of Black, these parts can be ordered in any of the other six Calais interior colors.

If Black components are not wanted, specify the following in desired color: 1) Top Instrument Panel 2) Lower Instrument Panel 3) Steering Wheel 4) Carpets 5) Seat Belts.

The white headlining will be De Ville corded material and the garnish moldings will be bright metal.

Other Vinyl Colors
The basic expanded vinyl is available in other colors such as Red, Dk. Blue, Maroon, etc.

However, with such non-standard colors the door pulls and the crank knobs on manual window regulator cars would have to be in one of the seven standard Calais interior colors.

The carpets would be cut pile Tropicana quality as used in De Ville cars. The garnish moldings would be bright metal.

Eldorado Cloth in De Ville

Fleetwood Patterns Available in De Ville
Fleetwood upholstery fabrics with their exclusive, unique patterns may be substituted in De Ville closed cars.

For example, the use of Eldorado Dalmatian cloth in the seat inserts.

Trim Style Will Remain De Ville
The trim will remain De Ville style, which is four biscuit and button on each side of the seat, separated by a leather center section.

All Cloth Upholstery

To Omit Leather or Vinyl Body Contact
Leather and vinyl may be eliminated from the seat cushions and back rests by ordering an "All Cloth" interior.

When all cloth is specified in De Ville and Fleetwood, the center leather-vinyl strip will be cloth. In a Calais, the vinyl end sections will be cloth. The cushion skirts ordinarily in vinyl will be cloth.

The doors will have a standard combination of vinyl and/or cloth.

Patterns May Mis-Match
If a cloth with a large design such as Damascus is involved, a discrepancy of patterns may result between the inserts and center or end sections. The latter replacing leather or vinyl are cut separately and when joined, the patterns may not match exactly.

All cloth upholstery is at extra charge.

Downloaded from www.Manualslib.com manuals search engine

Seats Only in White Leather
Balance of Interior in Darker Colors

Contrasting Colors on Seats and Doors
A special order treatment favored by some is a combination of White seats with the remaining or surrounding areas in Black or some other dark shade.

This means that the doors and rear quarters, top and lower instrument panels, steering wheel and carpets will be in a medium or dark monotone.

The headlining may be ordered in White; however, this can also be ordered in the dark shade if so desired.

Laces in Dark Color
An additional custom touch may be had by ordering the seaming laces in a dark shade.

Laces are the welts used to join two pieces of material. In a contrasting color, a piped effect on the seats is produced.

Other suggested SEATS ONLY combinations are White with Blue, Aqua, Red or Maroon; Red and Black.

Two-Tone Combination

Select All Components
For a two-tone interior combination, each of the 11 interior components should be specified on the order form.

This allows the purchaser a choice of light or dark tone on certain parts of the interior. For example, in a Black and White combination the door side arm rests may be ordered in White or Black. A similar option is available on other parts.

Seats Only
If the side arm rests are ordered in Black, the two-tone effect would be on the seats only.

On Fleetwood Sixty Special and Brougham
There are two trim styles in the Brougham and Sixty Special, but a two-tone combination is only available in the pillow and button style.

Light Tone Components
Customer preference specified on the order may prevent misunderstanding. Orders that are not specified in detail will be produced with a light tone on bolsters, front seat back panel, cushion skirt, seat wings, side arm rests and headlining.

Two-Tone Suggestions
Warm colors such as Maroon, Beige or Saddle may be combined with a lighter tone, providing an accent and relief from the overall monotone effect of a standard interior.

Contrasting Seaming Laces

Piped Effect
Contrasting seaming laces, which create a piped appearance, may be ordered.

Laces to match the carpet color produce attractive combinations with White or Sandalwood upholstery. With Black upholstery, added interior interest is created if White, Red or other contrasting laces are specified.

Why Laces and Buttons?
In seat upholstery, seaming laces and, in some styles, buttons are both decorative and functional.

Primary purpose of the laces is to join materials. They also serve to locate and properly position the upholstery fabric, contributing to a retention of the original seat shape.

Similar reasons apply to the use of buttons. In addition to being decorative by producing a tufted effect, they tie down and help preserve the original trim design.

Downloaded from www.Manualslib.com manuals search engine

Special Carpets

Determine Components to be Changed
Depending upon the exterior color, greater harmony may be created if, in addition to the carpet, the instrument panels and steering wheel colors are also changed. Following are examples:

Avoid Hood and Top of Instrument Panel Color Contrast
A White leather upholstery when combined with such exterior colors as Green or Maroon results in a sharp contrast of hood and the Black top of instrument panel color.

This may be avoided by ordering the top of instrument panel in Green or Maroon.

When this is done the lower instrument panel and steering wheel should also be specified in color to match the exterior. Otherwise, they would remain Black, resulting in a three-tone interior.

Option of Two-Tone Instrument Panels
In a combination such as: 1) Flamenco Red exterior 2) Black interior and 3) Red carpets, a single or two-tone combination of instrument panels is optional.

The top of instrument panel should be Red but the lower panel and steering wheel may remain in Black matching the seats and creating a two-tone effect; or both panels may be specified in Red, making a single tone combination. The above would also apply to Sandalwood upholstery.

Floor Covering Plush Cut Pile or Loop Pile
Tropicana Quality is a 100% nylon cut pile carpeting and is used for the floor covering of all cars except the Calais series.

Trenton Quality, 80% rayon, 20% nylon loop pile is used for the floor covering in Calais series cars only.

Other Areas
In addition to floor covering, carpeting is applied on such other parts of the interior as: lower doors, cowl quarters, lower front seat back and on two-door cars, the lower rear quarters.

Tamara Quality—a nylon cut pile—carpeting is used on "other areas" of all cars except the Calais series.

Travana Quality—a rayon-nylon loop pile—carpeting is used in "other areas" of Calais series cars.

Codes
Code numbers in the 200 series (those starting with 2) will be in Trenton loop pile quality. All others will be in Tropicana cut pile.

Medium Gray Cord Upholstery—Code 719 Decordo Cloth
On Brougham or Sixty Special

Trim Style
When a Brougham or Sixty Special is ordered in Decordo cloth upholstery, it will be in pillow and button style similar to leather or Damascus cloth, except the center section of the seat will also be in cloth instead of leather.

Light Gray Except on Seats
Medium Gray Decordo cloth is used on the entire seat for both inserts and bolsters.

When ordered in other than a "75" body style, the remainder of the interior components will be light Gray.

Such parts include the front seat back panel, assist grips, door pulls, door armrests, headlining, lower instrument panel, steering wheel, plastic parts, garnish moldings, front seat wings, windhose and seat belts.

These components cannot be changed, as they are prefabricated and available only in the light tone.

In summary, with code 719 Gray Decordo cloth a two-tone effect is created between the medium Gray upholstery color on the seats only and the other interior components which are in light Gray.

Downloaded from www.Manualslib.com manuals search engine

Cloth Front Compartment in "75" Limousine

Substitute Cloth for Leather Front
Instead of leather, the Limousine front compartment may be upholstered in the same cloth material as the rear by specifying "Cloth Front and Rear" on the order form.

Trim Style
The trim style will be the same as when upholstered in leather—2" pleats.

Bucket Seats

000B Denotes Bucket Seats
To special order Bucket Seats specify letter B in the Bucket Seat column on the order form, in addition to the 000 in the regular TRIM space.

This is important, as it is the only indication on the order that the front seats are to be Bucket type.

If order is not correctly marked, the car will have a standard bench type seat.

Special Leather Bucket Seats
To order Bucket Seats in non-standard leather, follow the procedure for ordering special leather on standard bench type seats *except be sure to add letter B in Bucket Seat column and 000 in the* TRIM *space.*

Bucket Seats (Cloth Upholstered)
Bucket Seats may be ordered upholstered in cloth.

The trim style will be the four biscuit De Ville type similar to standard bench seats.

This means the entire top surface or cover of the cushions and back rests will be in cloth. The skirt of the cushion and sides of the back rests will be in matching vinyl.

The rear bench seat will be a standard cloth type which includes a leather center section.

Head Rests
Head Rests are included when a Recliner is ordered. Code H, therefore, should not be specified with code R.

However, if the passenger seat recliner is not wanted but head rests are, be sure to specify H.

Bucket Seats in Brougham

De Ville Type Seats
Bucket Seats were not designed for the Brougham or Sixty Special.

However, on a special order De Ville Bucket Seats can be adapted with the following provisions:

Front Trim Style
The Bucket Seat trim styling will be the four biscuit De Ville type.

Rear Seat Trim Style
The rear seat trim style will depend upon the upholstery selection.

If Damascus, Diplomat or leather is ordered, the rear seat will be in pillow and button style.

With Devonshire cloth, the rear seat will be pleated and include embroidery.

Trays and Foot Rests Omitted in Brougham
When Bucket Seats are installed in a Brougham, the utility trays and foot rests are omitted.

The rear quarter reading lamps are retained.

Rear Quarter Lights Switch
When Bucket Seats are substituted in a Sixty Special, the rear quarter lights will operate from the instrument panel headlamp switch instead of front seat back panel switch which necessarily must be omitted.

Downloaded from www.Manualslib.com manuals search engine

Wool Broadcloth

Special Option in Any Body Style
A choice of Beige or Gray wool broadcloth is available in all body styles.

Trim Style
When ordered in a Fleetwood Brougham, Sixty Special or Seventy-Five, the upholstery style will be pleated similar to the Devonshire cloth method. (See page C-29 for illustration.) However, the embroidery will be omitted on both back rests and door panels.

If wanted, embroidery can be applied upon request.

Optional Trim Style
In the Fleetwood body styles mentioned above, a pillow and button trim style—as used with Damascus cloth—can be furnished upon request.

The center section of the seats will, however, be cloth instead of leather.

Limousine Front Compartment
The front compartment in the Limousine (style S) will be in standard black leather unless otherwise requested. The front compartment options are Gray, Beige or Dk. Blue leather or cloth as used in the rear.

All Cloths Not Interchangeable
In addition to the special wool broadcloth, any Fleetwood or De Ville cloth may be ordered in Calais, De Ville or Fleetwood cars except that Diplomat cloth should not be ordered in an all cloth method, such as the Fleetwood pleated style with embroidery, since Diplomat cloth has stripes which would result in a cross pattern effect.

Also, the Calais Duet cloth is not recommended for use in De Ville or Fleetwood because of a visible basting thread on each of its narrow stripes that would be exposed and could fray if upholstered in a style other than the Calais pleated method.

Leather Front Compartment

Available in Brougham or Sixty Special
A front compartment upholstered in leather with the rear compartment in cloth is available at extra charge.

Trim Styles
Both front and rear compartments will be in horizontal pillow and button style.

If a contrast in appearance between the front and rear compartments should be wanted, the rear may be ordered in "all cloth" style.

This method will have vertical pleats and, if the material is plain such as Devonshire, it will also be embroidered. However, this is optional.

Front and Rear in Different Colors
If the front compartment leather is ordered in a different color from the rear, the color distribution will be as follows:

FRONT COLOR:
Front Seat • Front Carpet • Front Doors • Front Seat Wings • Top and Lower Instrument Panels • Steering Wheel

REAR COLOR:
Rear Seat • Front Seat Back Panel and Assist Grips • Front Seat Back Inserts • Lower Front Seat Carpet Area • Rear Carpet • Center Pillar • Rear Doors and Quarters • Windhose • Headlining • Rear Shelf • Garnish Moldings

Limousine Type Glass Partition is Available
A glass division between the front and rear compartments may be ordered in the Brougham.

A Padded Roof and small rear window will be included. Utility trays and foot rests are omitted. The front seat is not adjustable and will be leather (pleated style) similar to the "75" Limousine.

To order, specify "Glass Division."

Downloaded from www.Manualslib.com manuals search engine

Special Interior Colors in Fleetwood "75" Cars

Five Standard Interior Colors
There are five optional rear compartment colors in the Fleetwood "75" body styles: Lt. Gray, Med. Gray, Med. Blue, Dk. Blue, Med. Beige.

Upholstery materials from the other four lines of cars can also be furnished. However, if a non-standard color such as Black, Red, etc., is selected, all of the other interior components must be made on a special individual order in small quantities for only a single car.

Examples of Special Parts Needed
Parts that must be specially color matched range from thread to carpets. For example, there are two rubber, adjustable air conditioning outlets in the ceiling which are molded in color to match the headlining. The machine for producing these parts is set up to make them in the five standard colors. *If ordered in Black or any other non-standard color,* the regular production cycle of the machine must be stopped, cleaned and set up to produce two Black rubber parts.

Understanding of Time and Cost Factors
This explanation of the intricacies in fabricating non-standard interior colors is presented in order to provide the customer with a better understanding of the time and cost factors involved in what may seem to be a simple request, inasmuch as the basic upholstery fabric is available.

Special orders are not too frequent, but their complexity can sometimes be time-consuming. Having ready answers reduces the interval needed to complete the specifications, thereby releasing each person's time for the pursuit of selling and handling standard option cars.

Advance Procurement
As soon as any information of a pending special order is available—especially the type described above—please alert your zone office so that the Central Office may be notified to start procurement of the necessary special materials.

Extra Charge
Prices for special upholstery will be furnished upon request.

Advance Procurement

When to Order
Special cars or their non-standard features should be ordered immediately upon finalization of the basic specifications.

Send such orders in duplicate to the zone office ahead of the regular mailing period.

A Preliminary Notice Will Expedite Delivery
If the car order must be deferred due to unavailable allotments, etc., send a "preliminary notification" listing the special upholstery and/or exterior color specifications. This may be in any form, such as a letter or a copy of the order.

The minimum information required on this type of advance notice is:

1. A description of the special interior features and/or special exterior color.
2. If the order is to be for a special interior, will any of the following equipment be specified?
   K —Automatic Climate Control
   R —Recliner
   H —Head Rests
   A —Seat Warmer
   Z —Shoulder Straps
   1 —Stereo Radio
   M—Power Door Locks
   B —De-Fogger
   N —Power Vent Windows
3. If a special exterior is involved, advise if a padded roof will be specified.
4. State when the regular order may be forthcoming—30, 60 or 90 days.
5. Advance procurement requests should be forwarded to the "Custom Order Department" at the Central Office via your zone office. They may be identified by: a) customer's name b) order number or any other means that will permit the association of preliminary requests with the eventual order.

Downloaded from www.Manualslib.com manuals search engine

"Fire-Frost" Colors

A high lustre "Fire-Frost" finish of remarkable beauty and radiance is available on special order. Light reflections from many facets of bright mirror-like metallic flakes produce the extraordinary depth and brilliance of "Fire-Frost."

The additional cost—about three times that of regular special paint—will be understood by the select group of buyers to whom the distinctive exclusiveness of this exterior color will appeal.

Any translucent color such as Silver, Gray, Aqua, Gold, Red, etc., may be ordered. Opaque colors such as White, Black, Yellow, Light Beige cannot be furnished as they will not reflect the metallic ingredient.


However, in the case of Black a good subsistute is an attractive charcoal color which, although classified as dark gray, is actually jet in appearance with an iridescent effect.

Past Model Cadillac Exterior Colors

(Available at extra charge)

1966	1965	1964	1963	1962
10 Sable Black	10 Sable Black	10 Ebony	10 Ebony	10 Ebony
12 Strathmore White	12 Aspen White	12 Aspen White	12 Aspen White	12 Olympic White
16 Starlight Silver	16 Starlight Silver	14 Nevada Silver	14 Nevada Silver	14 Nevada Silver
18 Summit Gray	18 Ascot Gray	16 Cardiff Gray	16 Cardiff Gray	16 Aleutian Gray
20 Mist Blue	20 Hampton Blue	22 Beacon Blue	22 Benton Blue	22 Newport Blue
24 Marlin Blue	24 Tahoe Blue	24 Spruce Blue	24 Basque Blue	24 Avalon Blue
26 Nocturne Blue	26 Ensign Blue	26 Somerset Blue	26 Somerset Blue	26 York Blue
28 Caribbean Aqua	28 Alpine Turquoise	29 Turino Turquoise	29 Turino Turquoise	29 Turquoise
30 Cascade Green	30 Cascade Green	32 Seacrest Green	32 Basildon Green	32 Sage
36 Inverness Green	36 Inverness Green	34 Lime	36 Brewster Green	36 Granada Green
40 Cape Ivory	40 Cape Ivory	36 Nile Green	44 Bahama Sand	44 Sandalwood
42 Sandalwood	42 Sandalwood	44 Bahama Sand	46 Fawn	45 Maize
44 Antique Gold	44 Sierra Gold	46 Sierra Gold	47 Palomino	46 Driftwood Beige
46 Autumn Rust	46 Samoan Bronze	47 Palomino	48 Briar Rose	48 Laurel
48 Flamenco Red	48 Matador Red	50 Matador Red	50 Matador Red	50 Pompeian Red
49 Claret Maroon	49 Claret Maroon	52 Royal Maroon	52 Royal Maroon	52 Burgundy
90 Cobalt Firemist	90 Peacock Firemist	92 Firemist Blue	92 Frost Silver	94 Neptune Blue
92 Crystal Firemist	92 Sheffield Firemist	94 Firemist Aquamarine	94 Frost Aquamarine	96 Pinehurst Green
96 Tropic Green Firemist	96 Jade Firemist	96 Firemist Green	96 Frost Green	97 Victorian Gold
97 Florentine Gold Firemist	97 Saddle Firemist	97 Firemist Saddle	97 Frost Gold	98 Bronze
98 Ember Firemist	98 Crimson Firemist	98 Firemist Red	98 Frost Red	99 Heather

Downloaded from www.Manualslib.com manuals search engine



Downloaded from www.Manualslib.com manuals search engine

Glossary of Interior Styling Terminology

Back of Front Seat Back
The back of front seat that is visible to the rear seat passengers. Also called division. Also called frame.

Back rest
The upright cushion against which passengers rest.

Backlight
Rear window.

Belt Line
The uppermost part of doors and rear quarters, extending from windshield base to rear shelf.

Bench Type Seat
A regular seat with straight-across bench type cushion and backrest as contrasted with bucket seats.

Bezel
A sloping rim around an object such as headlamp lens, brake pedal, etc.

Biscuits
Style of upholstering when material is formed into square or oblong sections by seams or pressed indentations.

Body Cloth
The basic trim material used on seat inserts—usually the heaviest weight.

Bolsters
The front, side or center part of a seat cushion, separated from the back or center by a welt, lace or seam. The top, side or center part of a backrest sometimes extending along the sides in a U or H shape.

Buttons
Used to produce a tufted or biscuit effect in the upholstery design; to retain trim covers and as an appearance item.

Coated Fabric
A synthetic material with a leather-like appearance, also called expanded vinyl and elascofab. (Elastic-coated-fabric)

Center Pillar
A rear door hinge support structure between front and rear doors terminating at belt line on hardtop sedans.

Combination
When referred to interior upholstery, it is the complete interior that includes a combination of colors and materials such as cloth, leather, vinyl, etc.

Coupe Type Seat
Individual back rests, creating a notched appearance. On 4-door styles the backrests are anchored and do not fold as they do in 2-door models.

Cowl Quarters
The section forward of the front door on inside of front compartment.

Cushion
The lower seat cushion or section upon which passengers sit.

Cushion Face
Vertical surface forming front and sides of seat cushion.

Cut and Sew
Cutting material to pattern; sewing and molding to form a set of "trim stock."

Dielectric
A heat and pressure process to unite, form and make designs on fabrics.

Division
The back part of front seat. Separation between front and rear compartments.

Door Pull
A grip handle on upper door panel.

Door Pad
The upholstered part of a door or section below window.

Dust Boot
Convertible top cover when lowered. Also called top boot.

Embossed
A dielectrically formed design on coated fabric.

Expanded Vinyl
An extra thick vinyl coated fabric. The soft resilient feel is attained by sandwiching a sponge-like cellular structure between the backing fabric and plastic top-coating.

Front Seat Back Panel
A machine-formed vinyl panel that covers top and sides of front seat back.

Garnish Molding
The frame next to the glass on the inside of windshield, door, rear window and along side of headlining.

Inserts
When used with reference to upholstery, it is the center section back of bolster on the cushion and below the bolster or in the center of the back rest.

Leather Upholstery
This term means that a combination of genuine leather and coated fabric is used throughout.

Lower Instrument Panel
The instrument panel, glove compartment door and ash receiver doors.

Luxury Coil Springs
A coil seat spring, wrapped in sheeting or muslin, wider in diameter than marshall type.

Marshall Type Springs
Narrow diameter, individually wrapped in burlap, coil seat springs.

Molded Plastic
A formed plastic, such as front seat back panel.

Natural Grain
Leather with a natural hair cell without any additional design.

Notched Back
A separation at top between individual back rests. Usually in a Coupe type seat.

Nylon Cloths
Nylon warp fibers with Viscose filler. Any reference to a Nylon cloth means that the material is a Nylon-Viscose blend.

OO
When used on new car order, it refers to a special exterior color.

OOO
Refers to special upholstery, on new car order.

Pipes or Pleats
Style of upholstering when material is folded or separated by seams, visible or invisible.

Rear Quarters
When applied to interior it may refer to rear upper area below headlining; on 2-door cars, the section back of doors. For exterior reference it may mean rear section above belt line; lower section back of door extending to rear end of car.

Rear Shelf
The area between rear seat back and rear window. Package shelf.

Risers
A section raised above its surrounding area.

Seaming Laces
Also called welts. A fabric covered cord or piping used to join by sewing two sections of material. This also has the benefit of locating and properly positioning the upholstery material to form and preserve the required shape.

Sedan Type Seat
A straight-across type seat without individual back rest separation. Has assist handles on back side.

Seat
Combination of back rest and seat cushion which comprises entire seat assembly.

Seat Cover
The top of cushion or face of back rest which has body contact.

Seat Side Panels
A section along side of front seat back rest.

Seat Wings
Lower front seat side panel.

Set of Trim Stock
The various components that comprise a complete interior upholstery.

Skirt
See Cushion face.

Strato Backrest
Thin, tapered backrest.

Top Boot
Convertible top cover when lowered.

Top of Instrument Panel
The padded vinyl top or instrument panel cover in back of windshield.


Trim
The interior upholstery combination.

Trim Style
The design into which the upholstery fabrics are shaped, such as pipe, biscuits, plain, etc.


Vacuum Formed
Vinyl or plastic molded by vacuum instead of pressure.

Windlace
The fabric or leather covered windhose applied around doors as an air seal.

Downloaded from www.Manualslib.com manuals search engine





Viewed from the rear, the 1967 Cadillac presents a simplicity of form and detail marked by strong horizontal lines. New taillight housings, tapering rearward from top and bottom, serve also as vertical extensions of the rear bumper. New deck sill has a new heavier license plate housing concealing the gasoline filler tube and new grille design with a grid pattern on Calais and De Ville series, vertical lines on Fleetwood.




Clean integral styling of taillight housings with rear quarter panels emphasizes the solidity and strength which mark the new Cadillac. Impressively wide deck lid has a single center contour line, angles sharply downward to meet the deck sill in a flush, unbroken line. Again, unity of design is apparent in the similar rearward angles of license plate housing and taillights.

Downloaded from www.Manualslib.com manuals search engine






Contributing to the impressively longer look of the 1967 Cadillac is the gracefully sweeping side contour extending from the front fender top to just above midpoint of the taillight housing and the forward extension of the rear quarter panel profile. Calais and De Ville series and the Fleetwood Seventy-Five have a single fine chrome molding extending the length of the body, starting at the front wheel opening. Just above the rear of the molding the Calais and De Ville have their series designations in chrome script, the Fleetwood Seventy-Five has the wreath and crest. Fleetwood Sixty Special and Brougham have a bright and brushed-chrome rocker sill molding, wreath and crest on the lower and upper rear quarter panel, respectively, and "Fleetwood" on front fenders.




The Coupe de Ville, shown here, and Calais Coupe are further distinguished for 1967 with an exclusive new roof and upper rear quarter or sail panel. It provides an appearance of custom coachwork, affords greater privacy and, especially with the Padded Roof option on the De Ville, offers a rare distinction, even for the world's most popular luxury coupes. Hardtop sedans in these series also have the exclusive roofline without as wide a sail panel.



Wheel discs retain the elegant beauty of bright and brushed-chrome concentric rings. Raised hub bearing the Cadillac crest has a ribbed perimeter which provides reflective highlights when the car is in motion. New dual-ringed whitewalls provide a perfect complement to wheel disc design.

Downloaded from www.Manualslib.com manuals search engine


Fleetwood Eldorado Special Features




The dramatically new and exclusive Eldorado styling is detailed here by the bold headlamp-concealing grille, extended front fender profile and low, bumper mounted parking lamps.


Smartly contoured, chrome-framed full wheel openings on the Eldorado set off to maximum advantage the exclusive wheel discs of bright and brushed chrome. Rectangular openings on seven-section outer ring add distinctiveness and contribute to brake cooling.

Fleetwood Eldorado headlamps are concealed behind the outer grille sections (upper left picture) which rotate to reveal headlamps whenever headlamp switch is pulled out. Turning headlamps off automatically rotates the outer sections to again conceal headlamps behind the grille.






Rear detail emphasizes the crisply tapered, chrome-framed rear quarter panels with distinctive louvered taillights recessed into the sloped upper portion of the panel sides.




Another exclusive styling feature of the Eldorado is the classic "V" or wedge design of the rear window and upper roofline contour.




Downloaded from www.Manualslib.com manuals search engine

New Instrument Panel


The Cadillac instrument panel looks and is entirely new for 1967. It has a padded, vinyl-covered upper section and a new vinyl-covered lower section. Instrument cluster is designed for maximum legibility and minimum reflection. Instrument cluster control panel is located for convenience and accessibility, yet recessed out of the impact area. New glove compartment designed with increased holding capacity has been relocated higher and to the right on the instrument panel. Distinction between series is denoted by the nameplate over the left side of the glove compartment door, also by the lower background panel of the instrument cluster which is brushed aluminum on the De Ville, shown here, black on the Calais and light and dark vertical stripes on the Fleetwoods.




Downloaded from www.Manualslib.com manuals search engine



New energy absorbing steering wheel for 1967 is a thickly padded three spoke design with a Cadillac crest or, on Fleetwoods, the wreath and crest insignia. Smaller diameter, now 15½" (permitted by Cadillac Power Steering efficiency) gives increased clearance to seat cushion for added comfort.



New door panels are designed with padded upper portions, padded armrests and with soft door pull handles. Door latch handles are in a recessed position. Eldorado, shown, has dual door latch handles for added convenience in the world's finest personal car, and recessed, soft-lined door pull grips.





Newly designed knobs on the Turbo Hydra-Matic selector lever, as well as on the turn indicator and steering wheel tilt adjustment lever, shown here, are a soft plastic with a cushioned feel. Turn indicator lever has new halfway position for manual lane change signaling.


Downloaded from www.Manualslib.com manuals search engine


New folding front seat back latches for 1967 are designed to lock the seat backs in their upright position until released by pushing in on the release buttons. Each folding seat back has its individual release button located on the outboard side of the seat back.

Added convenience and increased capacity is provided by the new larger glove compartment. Newly located to a higher position on the right side of the instrument panel, it is designed for improved retention of contents when opened.











New door latch handles for 1967 are designed in a recessed position flush with the padded door armrests. New passenger-guard door locks permit handles to disengage or free wheel when door lock buttons are pushed down . . . reengage when buttons are pulled up.

New Turbo Hydra-Matic selector lever has a larger soft plastic knob for improved feel and cushioning. Selector lever has been designed for easier travel and at the same time to provide an improved, more positive positioning "feel".

Downloaded from www.Manualslib.com manuals search engine






New manual window regulators have large, soft plastic knobs for softer feel and added cushioning. In addition, power window and vent window regulators are available as an option at extra cost for any body style not already so equipped.

New inside rearview mirror for 1967, in addition to its day-night positions, has shatter-resistant, vinyl-edged glass and a new mounting support designed to break away in event of major impact. Fleetwood Sixty Special and Brougham have their own 3-position, Soft Ray glass mirror.

New standard Hazard Warning Flasher will flash all four turn indicator lights when activated by pushing in the padded, FLASHER identified knob on the steering column. Pulling out on control knob or a sufficient turn of the steering wheel cancels flasher.

New telltale lights on the instrument cluster include a brake malfunction warning indicated by the word BRAKE in red and a new Cruise Control (optional at extra cost) light which indicates by the word CRUISE and a green light when Cruise Control is on automatic position.





Downloaded from www.Manualslib.com manuals search engine



Engine • Chassis • Body Features

	PAGES
ENGINE (including engine, transmission and drive-line)..	G-1 thru G-6
CHASSIS (frame, suspension, steering and brakes).....	G-7 thru G-10
BODY (construction features).....	G-11 thru G-15
FLEETWOOD ELDORADO SPECIAL FEATURES.....	G-16 thru G-21

The features of Cadillac's famous 340-horsepower V-8 engine are applicable to all series. However, the exhaust system which is different on the Fleetwood Eldorado is covered separately for this new body style. In addition, transmission and drive-line, chassis and body construction features unique to the Fleetwood Eldorado are explained, as indicated above, on Pages G-16 through G-21 of this section.


Downloaded from www.Manualslib.com manuals search engine

Cadillac Engine with Turbo Hydra-Matic Transmission

The remarkable quietness, efficiency and dependability of the Cadillac engine (it develops more horsepower per weight than any competitive engine) has been brought to even greater heights of refinement for 1967.

Among the many advancements are a new quadrajet carburetor for improved performance, reliability and economy; new rocker arms and camshaft contour which combine for both a dynamically and acoustically quieter valve operation; and smoother cylinder bores to further reduce friction, minimize oil consumption and extend engine life.


These latter two accomplishments were achieved through such advanced engineering methods as the use of a new research device which can track, by a light beam, any vibration of the valves and display the result on an oscilloscope and a special electronic recorder capable of measuring machined surface finishes and contours to within 3-millionths of an inch.




Basic Engine Specifications

Type	90° V-8
Horsepower @ 4600 r.p.m.	340
Torque @ 3000 r.p.m.	480
Compression ratio	10.5 to 1
Piston displacement	429 cu. in.
Valve arrangement	Overhead
Bore and stroke	4.13″ x 4.0″

Downloaded from www.Manualslib.com manuals search engine






New Quadrajet Carburetor
Cadillac's new four-barrel carburetor has the two primary (smaller) barrels designed to increase the velocity of incoming air; this permits more precise metering of the fuel-to-air ratio for maximum smoothness and economy. The secondary barrels are now larger for increased air capacity with a resulting gain in performance under initial full throttle conditions. New choke mounting on intake manifold permits better matching of the richness of the fuel mixture to requirements of the engine for efficient warmup. New float bowl now centered between carburetor primary barrels provides added assurance against engine cut-out on abrupt turns.


Pistons and Crankshaft
Contributing to the smooth and instant response of the Cadillac engine are the short, rigid crankshaft and lightweight aluminum pistons designed to minimize friction and starting inertia. New precision in cylinder bore finish and piston ring design further reduces friction and contributes to oil economy.

New Valve Train and Camshaft
For increased quietness and lower inertia the rocker arms for 1967 are of a stamped metal design, of lighter weight and mounted on a strong but light, sintered iron "tee" support. New cam contours are also designed for quieter valve operation.


Exhaust System
Cadillac's Coaxial Resonator exhaust system is scientifically designed to produce resonances or impulses of sound which oppose and cancel out sound impulses from the engine. Refinements for 1967 include a new stainless steel mesh for expansion control in the resonator for even greater quietness.




Downloaded from www.Manualslib.com manuals search engine




Engine Cooling
The computer-designed profile and blade spacing of the radiator fan coupled with a cross-flow radiator without top and bottom tanks to disturb the air flow provides high cooling efficiency. On air-conditioned cars, a thermally activated fan clutch disengages the (6-blade aluminum) fan at higher car speeds (where ram air is sufficient for engine cooling) thus lightening the engine accessory load.



Battery
The Cadillac battery has cell connectors passing through rather than around cell partitions providing a short, less restricted electrical path. The result is high ignition voltage and engine cranking speed. Delco Eye inspection window shows amber when fluid is low, encouraging attention by service attendants.




Generator
Cadillac's high output generator with lubricated-for-life bearings has a 42 amp. rating (55 amp. on air conditioned cars). Generator regulator has hard gold contact points for long, dependable life.





Starting Motor
With gear teeth especially designed for strength, quietness and long life, the starting motor and coil have been further refined, including improved sealing of lubricant on starting motor shaft for even greater reliability. Solenoid lever is enclosed within housing for maximum wet weather protection.

Crankcase Ventilation
The Cadillac positive crankcase ventilation system directs unburned air-fuel mixture from the crankcase back to the intake manifold for reburning. On Cadillac cars for California delivery, the Cadillac Air Injection Reactor system is factory installed. It employs an air pump, protective check valves and carburetor modifications to further reduce hydrocarbons in the exhaust.

Downloaded from www.Manualslib.com manuals search engine








Turbo Hydra-Matic Transmission

The Cadillac Turbo Hydra-Matic transmission gives the Cadillac owner the greatest smoothness, flexibility and responsiveness ever achieved in a motor car. For 1967, drive away smoothness has been further increased by raising the torque ratio of the torque converter unit. A major advantage of Turbo Hydra-Matic is the use of a variable stator in the torque converter. When the accelerator is depressed about halfway the pitch of the stator vanes is designed to deliver maximum torque (and acceleration). Less depression of the accelerator pedal reduces the pitch of the stator vanes with a corresponding reduction in torque. This latter condition is desirable for precise maneuvering in parking, to prevent creeping at idle and for less urgent acceleration. Engine braking, provided in either of the two Drive Ranges and in Low Range, offers three choices to meet varying grades of descent. (Fixed-stator on Seventy-Five body styles).

Left-hand DRIVE position gives maximum cruising economy, quietness and slower engine speeds. At the same time, acceleration as desired is available from the fluid-smooth thrust of the torque converter alone, or, by depressing the accelerator pedal further, by engaging a lower gear.


Right-hand DRIVE position locks out high gear and utilizes the Intermediate gear for maximum responsiveness. This position is often preferred in mountain driving for climbing steep slopes and for increased engine braking on the down grades.

Downloaded from www.Manualslib.com manuals search engine




Cadillac Drive Line

The use of a one-piece propeller shaft (two-piece with center support on 75 series), precisely aligned with the rear axle pinion gear through machined mountings, transmits power from the transmission to the rear axle with utmost quietness and resistance to vibration.




Constant Velocity Joints

Further contributing to smooth, quiet transmission of power to the driving wheels is the use of CV (constant velocity) joints at the ends of each propeller shaft. In effect, the CV joint is like combining two U-joints with the advantage that each serves to offset any vibration-setting tendencies of the other.



Rear Axle

The rear axle housing is of exceptionally strong, rigid construction with a minimum number of sections and welds. Rear axle pinion seal has a two-lip design, outer lip sealing out dirt, inner lip sealing in lubricant. Bearings are prestressed for long lasting smoothness and durability.




Tires and Wheels

Cadillac wheels have safety rims which tend to hold the bead of the tire to the rim even in event of sudden deflation. Tires have tread design extending onto shoulders for smooth cornering. Improvements in tread design and compounds, cord material and bonding assure even greater durability for 1967.

Downloaded from www.Manualslib.com manuals search engine

Cadillac Chassis—1967



Cadillac Variable-Ratio Steering for minimum parking effort, added responsiveness in straight-ahead steering.

New energy absorbing steering wheel for added security.

New all-rubber flexible coupling between steering gear and column isolates road noise or vibration.

New energy absorbing steering column for added security.

Turbo Hydra-Matic transmission for maximum smoothness, flexibility and performance.

Cadillac Triple Braking System with independent front and rear systems plus true auxiliary emergency braking.

Box section perimeter frame has hidden bulkheads for torsional rigidity and strength (Eldorado frame on Page G-18).

Engine mountings precisely tuned to frame characteristics for smooth, quiet, stable idling.

New larger (9½") booster unit on power brakes for improved high speed and high altitude braking.


Cadillac shock absorbers prevent mixing of air with fluid for consistent quality of ride.

Cadillac Four-Link rear suspension minimizes fore and aft or sideways motion; resists downward deflection during acceleration.

New corrosion-resistant brake lines for increased durability.

Body mount compounds and locations tested and proved on road simulator for maximum isolation of road noise and vibration.


Downloaded from www.Manualslib.com manuals search engine





New Energy Absorbing Steering Column
The new Energy Absorbing Steering Column on all 1967 Cadillac body styles is designed to compress on impact. Thus, should the car become involved in a frontal collision and the primary force (forward movement of the car) be suddenly halted, the steering column compresses reducing its tendency to move rearward toward the driver's compartment. The secondary force, that of the driver continuing to move forward against the steering wheel, is also partially absorbed by compression of the steering column and additionally by the new padded steering wheel itself.

Cadillac Variable-Ratio Power Steering
(Except Seventy-Five Models.)
This feature gradually increases the ratio of turn of the front wheels the further the steering wheel is turned right or left from the straight-ahead position. Thus while there is some reduction in amount of steering wheel movement required for all maneuvering, there is a major reduction, up to one-third, in the number of steering wheel turns required to make a full swing of the front wheels from right to left or left to right, as may be required on hairpin turns or for parking in restricted space.

Rubber Cushioned Coupling and Bushings
Contributing to Cadillac's smooth, effortless, fatigue-free steering is the use of a flexible rubber coupling in the steering shaft and the use of rubber bushings at steering gear-to-frame mountings thus isolating road shocks or vibration from the steering wheel.








Downloaded from www.Manualslib.com manuals search engine

Cadillac Triple Braking System



A. The Cadillac pioneered independent front and rear braking systems incorporates a separate fluid reservoir, master cylinder piston and hydraulic lines for each system. Thus a malfunction (indicated by red telltale light on instrument cluster) to either front or rear system leaves the other still operative.

B. The Cadillac parking or emergency brake provides an auxiliary braking system since, with the ignition ON, and the car in gear, it may be applied and released without locking in applied position.


C. New larger power brake vacuum booster for 1967 assures improved high speed and high altitude braking performance.

D. New corrosion-resistant brake lines and rayon cord brake hoses assure increased durability and long life.

E. Long life pistons in wheel brake cylinders are made of a super-hard, self-lubricating alloy for maximum durability.


F. Finned brake drums, front and rear, offer maximum area to cooling flow of air for fast heat dissipation. Flange on front brake backing plates shields interior of drums from splashing water.


G. Self-adjusting brake shoes automatically bring linings back to proper clearance with drums when brakes are applied while car is in rearward motion.



DUAL MASTER CYLINDER

Downloaded from www.Manualslib.com manuals search engine





Front Suspension


Cadillac's front suspension not only cushions the ride but contributes to stability and handling. Strut rods, mounted to the lower control arms and, through thick rubber bushings, to the front frame crossmember hold the wheels in firm fore and aft alignment during normal driving yet permit a momentary rearward deflection of the wheel when it encounters a bump or depression in the road surface thus cushioning the impact. Other front suspension members, too, are mounted to the frame with rubber bushings further insulating against road noise or shock. Rubber limit bumpers cushion impact should bottoming ever occur.

Shock Absorbers

Cadillac shock absorbers are of an exclusive design with a gas-filled nylon envelope replacing the air space in conventional shock absorbers. Since there is no mixing of air with the fluid, efficiency is maintained even on roughest roads.


Rear Suspension

Cadillac Four-Link rear suspension has two lower control arms to hold the wheels in fore and aft alignment and two upper control arms angle-mounted high on the rear axle housing, thus resisting both sideways motion and roll on curves. Deflection of the rear of the car downward on quick acceleration is also minimized. Thick rubber insulation at control arm-to-frame mountings and at top and bottom of springs absorb and isolate road noise.





Downloaded from www.Manualslib.com manuals search engine


Cadillac Body Construction



Downloaded from www.Manualslib.com manuals search engine







Ease of Entry and Exit

Cadillac attention to the safety, comfort and convenience of the driver and passengers is exemplified in many details which contribute to ease of entry and exit. For example, wide-opening, forward hinged doors, low door sills, rounded cushion corners, no extending dogleg at windshield pillars and a padded, small diameter steering wheel which, with the Tilt and Telescope provision, can be swung up out of the way at the touch of a lever. *Interior roominess is best exemplified by the interior dimensions shown in* Section C of this book beneath each interior illustration.


Door Locks and Latches


Passenger-guard door locks on all doors for 1967 provide disengagement or free-wheeling of the inside door handles when the door lock buttons are pushed down. Door lock buttons must be returned to up position manually, by Power Door Lock switch or by outside key lock to re-engage inside door handles. Latches themselves are designed to resist opening under impacts. Rugged hinges, securely anchored, are designed to resist severe stress.


Hood Latches

The smartly styled expanse of hood, reaching from centerline to centerline of the front fenders, is designed as an actual functional part of the front end structure. It is firmly secured with dual hood latches released by a fingertip lever just below and to the right of the hood center.

Downloaded from www.Manualslib.com manuals search engine










Luggage Compartment
With a capacity designed to accommodate all of the luggage normally carried on a trip, including golf clubs, the Cadillac luggage compartment features a new soft-textured, felt-finish lining, non-protruding hinges which recess into a housing for protection of fine luggage, spare tire mounted out of the way at the rear of the compartment (except on convertibles and Seventy-Five models) and a protective spare tire cover, standard on the Fleetwood Sixty Special and Brougham, optional on all other body styles. Rubber seal entirely around deck lid protects against entrance of dust, rain or snow.

Windshield Washer-Wipers (3-speed)
Designed to provide a large cleared area in front of the driver and passenger, Cadillac Windshield Washer-Wipers also feature: three-speed operation to cope with varied weather demands; reduced glare wiper arms and blades for minimum reflection; illuminated switch and washer-wiper button for night-time convenience.






Downloaded from www.Manualslib.com manuals search engine




Dual Compartment Automatic Climate Control
Standard on the Fleetwood Seventy-Five Sedan and Limousine, dual compartment Automatic Climate Control provides separate controls, blowers, sensors and evaporator for automatically supplying the proper mixture of heated and cooled air to both front and rear compartments. Thus, driver and rear compartment passengers can dial and maintain separate interior temperatures. (There is no vent position on this dual system).

Heated or cooled air, as required, is supplied year-round without the need for further adjustment. (See page B-2.)





Separate Rear Compartment Air Intakes
Outside air for the rear is drawn in through newly styled air inlets located high on the rear of the body.



Separate Rear Controls
A separate on-off switch and a temperature dial are mounted beneath a hinged cover on the right rear armrest, conveniently accessible to the rear compartment passenger.

Downloaded from www.Manualslib.com manuals search engine





Floor Insulation
A four-layer barrier of selected materials protects the front compartment against heat, cold, noise and drafts.

1. Jute
2. Rubber Compound
3. Jute
4. Carpeting


Scientific Soundproofing
The quietness of Cadillac interiors, a matter of pride and pleasure for Cadillac owners, is achieved through selected soundproofing. There is a molded one-piece sound barrier between engine and passenger compartments and sound deadening material at designated areas to absorb noise of thrown gravel. Added quietness is assured by insulation in rear quarter panels to reduce tire noise and rubber door seals which greatly reduce wind noise. A highly efficient rubber compound sound barrier is used at each side of the cowl. A thicker sound barrier insulates front compartment floor. Rear compartments have two layers of jute topped by deep carpeting. There is a layer of felt deadener and a layer of tuflex insulation between the steel top and headlining of Calais, De Ville, Fleetwood Eldorado, Sixty Special and Brougham models. The underside of the hood is insulated by 1½" thick fiberglass.

Ignition Switch Helps Protect Battery
The Cadillac ignition switch provides a stop which requires pressing the key inward slightly before turning it to ACCESSORY position. This reduces the likelihood that the key will be inadvertently turned past OFF to ACCESSORY position and thus reduces the possibility of running down the battery.

Downloaded from www.Manualslib.com manuals search engine


Fleetwood Eldorado (Special Features)

Created as the World's finest personal car, the Fleetwood Eldorado provides many distinctive engineering features exclusive to this body style. These features, described on the following pages, are as important to the personal character of this elegant motor car as its individualistic styling shown in Sections C and F of this book.



Downloaded from www.Manualslib.com manuals search engine

Fleetwood Eldorado Special Features



Front Wheel Drive

Among the attractions of a personal car are distinctive attributes which make it outstanding even among other motor cars produced by the same manufacturer.


The Fleetwood Eldorado fulfills this measurement not only in its exclusive styling but in its mechanical characteristics as well. Front wheel drive, for example, with the attendant steering and suspension it requires, provides exceptional directional stability combined with a quick and precise steering. The result is a feeling of participation and control certain to be appreciated by the personal car enthusiast.


Yet, because of the wide front tread, medium-weight springs and Cadillac's exclusive shock absorber design, the riding quality is traditionally Cadillac, comfortable, stable and controlled, with minimum roll.


Diagramed above is the flow of power through front wheel drive with arrows denoting the directional changes from engine to torque converter, (via silent chain) to transmission, to differential, to axles and wheels.

Downloaded from www.Manualslib.com manuals search engine

Fleetwood Eldorado Special Features







Special Frame

The Fleetwood Eldorado frame is designed to fit the structural requirements of its front wheel drive. Major elements are forward while lighter components are at the rear. Space at the rear, normally taken up by the differential and rear axle housing, permits mounting the spare tire directly behind the rear seat to provide adequate luggage space even with the Eldorado's close-coupled rear deck design.

Front Suspension


The use of individual torsion bars instead of coil springs on the front suspension is in keeping with the space requirements of the front wheel drive axles. At the same time, this suspension method contributes to the handling characteristics, the feeling of road control and stability so much appreciated by personal car owners.


Rear Suspension


Rear suspension in the Eldorado is provided by single leaf springs, that are rubber mounted, and the use of four exclusive Cadillac shock absorbers, two mounted horizontally and two angled vertically. Positioned thus, the shock absorbers provide positive control of fore and aft wheel deflection as well as vertical and sideways motion of the car for maximum stability.


Downloaded from www.Manualslib.com manuals search engine

Fleetwood Eldorado Special Features










Ventilation System

The Fleetwood Eldorado ventilation system takes in air at the cowl air intake grille on the hood just forward of the windshield. Some air is directed to the floor through the cowl vent outlets. The five air conditioner outlets (which are provided on the Eldorado whether it has the air conditioning system or not) direct the balance of the air flow so that it passes over the front and rear seat passengers, then under the rear seat and into the trunk. It then exits from the car through four outlet grilles, one on each rear fender and one on each door lock pillar. The efficiency of this ventilation eliminates any requirement for front ventipanes on the Fleetwood Eldorado. Individual pull knobs are also provided (except with air conditioning system) underneath each end of the instrument panel to open the cowl air vents if desired.



Operating Controls

With air conditioning, Eldorado controls are the same as described in OPTIONAL EQUIPMENT FEATURES Section B. Standard heater-defroster controls on the Eldorado have an added VENT position as shown in illustration at left, to operate the ventilation system described above.

Downloaded from www.Manualslib.com manuals search engine

1967 Cadillac

GENERAL SPECIFICATIONS

All Series and Body Styles

Horsepower	340
Compression Ratio	10.5 to 1
Piston Displacement	429 cu. in.
Valve Arrangement	Overhead
Carburetor	4-barrel
Transmission	Turbo Hydra-Matic
Steering**	Variable Ratio Power
Brakes	Dual System plus true auxiliary parking brake
Frame	Perimeter
Springs***	Helical Coil, front and rear
Axle Ratios	2.94 to 1*

*3.21 optional; standard on Eldorado and air conditioned cars.
**Fixed ratio on Seventy-Five models.
***Torsion bar, front; leaf rear, on Eldorado.

	Calais Sedans and Sedans de Ville	De Ville Convertible, Coupe de Ville and Calais Coupe	Fleetwood Eldorado	Fleetwood 60 Special Sedan and Brougham	Fleetwood 75 9-Passenger Sedan and Limousine
Wheelbase	129.5"	129.5"	120"	133"	149.8"
Overall Length	224"	224"	221"	227.5"	244.5"
Overall Width	80"	80"	80"	80"	80"
Overall Height	55.6"†	54.6"**	53.3"	56.7"*	57.4"
Minimum Road Clearance	5.2"	5.2"	5.7"	5.4"	5.8"
Steering Ratio—Overall	16.2	16.2	16.3	16.2	18.2
Turning Radius (Wall-to-Wall)	23'9"	23'9"	22'3"	24'4"	28'7"
Tread—Front	62½"	62½"	63½"	62½"	62½"
Tread—Rear	62½"	62½"	63"	62½"	62½"
Tires, Tubeless—Size	9.00 x 15	9.00 x 15	9.00 x 15	9.00 x 15	8.20 x 15
Tires	2-ply	2-ply	2-ply	2-ply	4-ply

*Brougham 56.8". **54.3 on De Ville Convertible. †54.5" on hardtop sedans.

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

engine

Number of cylinders	8
Cylinder arrangement	90° V-type
Valve arrangement	Overhead
Bore and stroke	4.13″ x 4.0″
Block and cylinder head material	Cast iron
Piston displacement	429 cu. in.
Taxable horsepower	54.6
Max. brake horsepower	340 @ 4600 r.p.m.
Max. engine torque—lbs.-ft.	480 @ 3000 r.p.m.
Compression ratio	10.5:1
Engine mounts	Vulcanized rubber
Number of points of suspension	3

pistons and rings

Make	Bohn Aluminum—Central Foundry—Zollner-sterling
Material	Aluminum alloy
Type	Slipper type, cam ground, control expansion
Clearance	.0006-.0010″
Number of oil rings per piston	1
Number of comp. rings per piston	2
Top compression ring	Molybdenum filled

rods and pins

Wristpin length	3.090″
Wristpin material	Steel
Type	Pressed in rod
Connecting rod length	6.500″
Material—connecting rod	Forged steel
Weight—connecting rod	19.36 oz.
Lower bearing material	Steel-back Moraine
Connecting rod bearing clearance	.0005″-.0021″
Connecting rod bearing end play	.008″-.014″ (total two rods)

crankshaft

Material	Pearlitic malleable iron
Weight	59 pounds
Main bearing thrust	Center main
Crankshaft end play	.001″-.007″
Main bearing removable	Yes
Main bearing material	Steel-back Moraine
Main bearing clearance—rear	.0006″ to .003″
Main bearing journal— Diameter x Length:	
Number 1	3.000″ x 1.120″
Number 2	3.000″ x 1.062″
Number 3	3.000″ x 1.338″
Number 4	3.000″ x 1.062″
Number 5	3.000″ x 1.120″

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

camshaft

Drive	Chain
Camshaft sprocket material	Aluminum with nylon teeth
Timing chain—make	Link Belt
Timing chain—no. of links	46
Timing chain—width	.750″
Timing chain—pitch	.500″

valves

Valve arrangement	Overhead
Intake opens	39° B.T.C. at .001 lift
Intake closes	109° A.B.C. at .001 lift
Exhaust opens	86° B.B.C. at .001 lift
Exhaust closes	62° A.T.C. at .001 lift

intake

Material	Alloy steel
Overall length	4.794″
Diameter of head	1.875″
Angle of seat	44°
Lift	.440″

exhaust

Material	Alloy steel
Overall length	4.815″
Diameter of head	1.500″
Angle of seat	44°
Lift	.440″
Hydraulic valve lifters	Yes
Valve inserts	None
Valve seats cooled by	Direct water circulation

lubrication

Type	Full pressure
Oil under pressure to:	
Main bearings	Yes
Connecting rods	Yes
Wristpins	Splash
Camshaft bearings	Yes
Tappets	Yes
Oil pump type	Gear
Normal oil pressure	30 to 35 lbs. @ 30 m.p.h.
Capacity of oil reservoir	5 qts. with filter. Refill, 4 qts.
Type of oil level gauge	Dip stick
Make of pressure gauge	AC—Tell-Tale Lite
Oil filter	Standard
Type	Full-Flow

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

fuel

Gasoline tank capacity	Approx. 26 gallons*
Type of fuel feed	Camshaft pump
Carburetor—make	Rochester & Carter
Carburetor—type	Four-barrel downdraft
Manifold heat control	Automatic
Type of air cleaner	Dry-pack

*Eldorado, approx. 24 gallons.

cooling

Water pump type	Centrifugal—dual outlet
Pressure relief valve	Yes
Choke for recirculation	Yes
Radiator core	Cross-flow
Full length cylinder water jacket	Yes
Water all around cylinders	Yes

		Fleetwood 75
Fan belt length:		
Generator	38.08″	53.10″
Steering pump	49.94″	50.62″
Fan belt width	⅜″	
Fan blade material	Steel*	
Fan—no. of blades	7*	
Cooling system capacity**	18.1 qts.	19.5 qts.
		Add 1 qt. for A/C

*6-blade, aluminum on Eldorado and A/C cars.
**17 qts. (17.5 with A/C) on Eldorado.

generator

Make	Delco-Remy
Minimum charging speed	At idle
Generator ventilation	Forced air

generator regulator

Make	Delco-Remy
Voltage regulator setting	13.8-14.8 @ 100° (adjust to 14.2)
Generator max. charging rate*	42 amp.
(Fleetwood 75 and air-conditioned cars)	55 amp.

*63 amp., optional.

starting motor

Make	Delco-Remy
Flywheel teeth, integral or ring	Steel integral

ignition

Spark advance	Centrifugal and vacuum
Ignition unit—make	Delco-Remy
Manual advance	None
Maximum centrifugal advance	Crankshaft (12°-16°) at 4000 rpm.
Vacuum advance, maximum	Crankshaft (25.5° at 18.25 in. of Hg.)
Distributor breaker gap	.016″

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

ignition—continued

Initial spark advance	5° B.T.C. (Nominal)
Firing order	1-8-7-2-6-5-4-3
Ignition coil—make	Delco-Remy
Spark Plugs:	
Make	AC
Model	44.0
Thread	14 mm.
Gap	.035″

battery

Make	Delco-Energizer
Number of plates	13
Capacity (amp. hrs.)	73
Terminal grounded	Negative
Location of battery	Under hood on tray at front right-hand side of radiator cradle

lights and horn

Headlight—make	Guide sealed-beam (Dual)
Headlight cover glass, dia.	5¾″
Parking light—make	Guide
Taillight—make	Guide
Lighting switch—make	Delco-Remy
How are headlights dimmed?	Depressed beam—foot switch
Cornering light	Guide-activated by directionals & light switch
Horn:	
Make	Delco-Remy
Type	Vibrator, seashell electric F, A and high C notes (3)*

*Additional low D horn optional extra cost.

turbo hydra-matic transmission

Type	Fully automatic stepped gear transmission with variable stator torque converter*
Gearing	Planetary
No. of forward speeds in left DRIVE position	3
No. of forward speeds in right DRIVE position	2
No. of forward speeds in (L) low position	1
Transmission ratio	
Low gear	2.48 plus torque converter
Intermediate gear	1.48 plus torque converter
High gear	1.00 plus torque converter
Reverse	2.09 plus torque converter
Torque converter maximum torque multiplication at stall	2.00

*Fixed stator on Fleetwood 75 models.

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

turbo hydra-matic transmission—continued

Oil capacity	
Completely dry transmission	11 qts. 6 oz.
Pan drained by filler tube only	4 qts. 20 oz.
Pan and strainer removed	5 qts.

frame

		Eldorado
Frame—make	A. O. Smith	Dana
Frame—type	Perimeter	Boxed perimeter

front suspension

		Eldorado
Front suspension—type	Forked arms, upper. Single arms with tension strut rods, lower.	Forked arms, upper. A-frame lower.
Control arm pivots	Rubber bushings	
Knuckle support bearing	Spherical	
Front wheel inner bearing	Tapered roller	Double-row
Front wheel outer bearing	Tapered roller	ball bearing.
Front spring—type	Helical coil	Torsion bar
Front spring, material	Spring steel	
Shock absorber—type	Hydraulic direct-acting type	
Front stabilizer	Torsion rod	

rear suspension

		Eldorado
Type	Cadillac four-link	See below
Yoke and control arm pivots	Rubber bushings	
Springs	Helical coil	Single leaf
Material	Spring steel	
Shock absorbers	Hydraulic direct-acting, inverted "V" mounting	Also two horizontal mounted in fore and aft direction

propeller shaft*

		Fleetwood 75
Type	1-piece	2-piece
Make	Saginaw	
Drive and torque taken through	Four-link rear suspension	

universal joints

Number used	2	3
Type	Constant Velocity	
Universal joints, lubricated	Permanently	

*Eldorado has front wheel drive with 4-CV (constant velocity) joints. Drive and torque taken through engine mounts.

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

rear axle

		Fleetwood 75 and Eldorado
Rear axle—make	Own	
Rear axle—type	Semifloating	
Differential gear—make	Own	
Rear axle:		
Oil capacity	5 pints	
Grade recommended:		
S.A.E. viscosity	90 hypoid	
Type of final gearing	Hypoid	
Gear ratio:		
Standard	2.94	3.21
Optional	3.21*	
Rear wheel bearing—type	Ball, grease-packed (permanent)	

*Standard on air-conditioned models.

tires and wheels

		Fleetwood 75
Tires:		
Make	U. S. Royal, Firestone, Goodrich and Goodyear	
Type	Tubeless	
Size	9.00 x 15	8.20 x 15
Ply	2-ply	4-ply
Inflation pressure:		
Front	24 lbs.*	28 lbs.
Rear	24 lbs.*	28 lbs.**
Wheels:		
Type	Slotted disc	
Make	Kelsey-Hayes	
Rim, diameter	15″	

		Eldorado
Tread:		
Front	62½″	63½″
Rear	62½″	63″

*Sixty Special and Brougham, 25 lbs. Eldorado, 24 lbs. front; 22 lbs. rear.
**38 lbs. with 9 passengers and 200 lb. trunk load.

steering

		Fleetwood 75
Steering	Variable ratio Hydraulic Power	Non-variable
Type	Concentric gear	
Make	Saginaw	
Overall steering ratio	16.2 to 1*	18.2
Car turning radius:		
(wall-to-wall)	23′9″**	28′7″
60 Special and Brougham	24′4″	

*Eldorado 16.3 to 1.
**Eldorado 22′3″

Downloaded from www.Manualslib.com manuals search engine

Detailed Specifications

brakes

		***Eldorado
Front	Independent hydraulic	
Rear	Independent hydraulic	
Type	Duo-servo, self-adjusting	
Brake drum diameter	12″	
Brake drum, internal or external	Internal	
Brake lining, length per wheel:		
Forward shoe	11.00″	12.00″
Reverse shoe	12.36″	12.00″
Total	23.36″	24.00″
Brake lining width	2½″	2.75″ front; 2.00″ rear
Brake shoe clearance**	.010″—.030″	
Foot Parking brake location	Left side below dash	
Release	Automatic vacuum* plus manual	
Operates on	Rear service brakes	
Power brakes	Standard, all models	

*With engine running and car in any drive gear.
**Controlled by self-adjusting linkage.
***Disc brakes, front, optional extra cost on Eldorado.

miscellaneous specifications

Car lifting device, jack	Bumper type
Engine lubrication—type	Pressure
Chassis lubrication—type	No lube fittings
Axle lubrication—type	Splash

lubricants

Engine crankcase capacity	4 qts.
With oil filter (Std.)	5 qts.
Recommended viscosity	Anticipated temperature: 32°F or higher, SAE-10W-30, SAE 20, SAE 20W 0°F to +32°F, SAE 10W, SAE 5W-20 0°F or lower, SAE 5W, SAE 5W-20
Drain	6000 miles

CAUTION: Drain more frequently in accordance with Owner's Manual under varying operating conditions.

Rear axle oil	5 pints
Recommended viscosity	90 hypoid
Transmission fluid	Type "A" (Suffix "A")
Turbo Hydra-Matic refill	11 qts. 6 ozs. (completely dry) 4 qts. 20 ozs. (pan drained by filler tube only) 5 qts. (with pan and strainer removed)
Gasoline tank capacity	Approx. 26 gallons*

*Approx. 24 gallons on Eldorado.

Downloaded from www.Manualslib.com manuals search engine



1902-1966 Cadillac Milestones

Cadillac has pioneered in the development of many motoring achievements . . . advancements in engineering and design which have set the trend for other motorcar makers in the course of the ensuing years. The "milestones" listed in this section of your Data Book point up the dramatic year-by-year development of and increased demand for the Cadillac automobile, recognized and respected everywhere as the "Standard of the World."

Downloaded from www.Manualslib.com manuals search engine

1902/1966 Cadillac milestones

Model Year	Total Production	Type of Cars Produced	List Price (Typical Car)	Wheelbase	Milestones
1902 1903	2,500	1 cyl. "A"	$ 850	76"	Detroit Automobile Co., established 1899, reorganized as "Cadillac Automobile Co."
1904	2,318	1 cyl. "B"	950	76"	Cadillac Automobile Co. and Leland & Faulconer consolidate as "Cadillac Motor Car Company" with Henry M. Leland, grand old man of the industry, as General Manager.
1905	4,182	1 cyl. "F" 4 cyl. "D"	950 2,800	76" 100"	**First** four-cylinder establishes Cadillac as the pioneer of multi-cylinder motor cars.
1906	4,307	1 cyl. "M" 4 cyl. "H"	950 2,500	76" 102"	
1907	2,696	1 cyl. "M" 4 cyl. "G" 4 cyl. "H"	950 2,000 2,500	76" 100" 102"	Famous Johansson gauges, **First** imported into United States by Cadillac, enable Cadillac to become the following year the—
1908	2,012	1 cyl. "T" 4 cyl. "H"	1,000 2,500	82" 102"	**First** American car to be awarded the Dewar Trophy by Royal Automobile Club of London for being **First** to achieve interchangeability through standardization of parts.
1909	5,902	4 cyl. "30"	1,400	106"	Cadillac purchased by General Motors Corporation. Four-cylinder production increases six times over 1908 production.
1910	8,006	4 cyl. "30"	1,600	106"	**First** to offer Closed Bodies as standard equipment. Less than 10% of cars then produced had closed bodies.
1911	10,018	4 cyl. "30"	1,800	116"	Custom Coachcraft by Fleetwood Body Company begins.
1912	13,994	4 cyl. "1912"	3,250	116"	**First** to equip cars with Electric Starting, Lighting, Ignition, for which Cadillac again was awarded the Dewar Trophy. **First and only** car in the world to win this award twice.
1913	15,017	4 cyl. "1913"	3,250	120"	
1914	14,002	4 cyl. "1914"	2,800	120"	October—**First** in this country to offer a production car (1915 Cadillac) with a V-type, water cooled, eight-cylinder engine, the prototype of engines later used throughout the industry. **First** to use thermostatic control of cooling system.
1915	13,001	V-8 "51"	2,800	120"	**First** to use Tilt-Beam Headlights for night driving safety.
1916	18,003	V-8 "53"	2,950	122"	Cadillac becomes "Division of General Motors."
1917	18,002	V-8 "55"	3,110	125"	Cadillac adopted as **Standard** Officers' car by U. S. Army after grueling tests at Marfa, Texas.
1918	20,285	V-8 "57"	3,535	125"	Cadillac supplied 2,350 cars and 1,157 V-8 artillery tractor engines to U. S. Army.
1919	20,678	V-8 "57"	4,090	125"	
1920	19,628	V-8 "59"	4,750	125"	Cadillac completes new Clark Ave., Detroit, plant, most modern in the industry.
1921	5,250	V-8 "59"	4,950	132"	
1922	26,296	V-8 "61"	4,100	132"	**First** to use Thermostatic Carburetor Control.
1923	14,707	V-8 "61"	4,150	138"	**First** to build the inherently balanced 90° V-type eight-cylinder engine. **First** to use the Compensated Crankshaft. Four-wheel brakes featured.
1924	18,827	V-8 "63"	3,835	132"	**First** to provide wide choice of Duco Exterior Finishes as standard equipment.
1925	16,673	V-8 "63"	3,195	132"	**First** to use Crankcase Ventilation. $5,000,000 expansion program started. Cadillac contracts for entire output of Fleetwood Custom Body Co.
1926	20,419	V-8 "314"	3,250	132"	**First** to develop a comprehensive Service Policy and place it on a nationwide basis.
1927	47,420	V-8 "303" V-8 "314"	2,685 3,250	125" 132"	

Downloaded from www.Manualslib.com manuals search engine

1902/1966 Cadillac milestones

Model Year	Total Production	Type of Cars Produced	List Price (Typical Car)	Wheelbase	Milestones
1928	29,572	V-8 "303"	$2,685	125"	**First** to develop and use the Clashless Synchro-Mesh Transmission. **First** to install Security Plate Glass as standard equipment.
		V-8 "341-A"	3,250	140"	
1929	40,965	V-8 "328"	2,495	125"	**First** to adopt Chrome Plating as standard.
		V-8 "341-B"	3,595	140"	
1930	25,991	V-8 "340"	2,565	134"	**First** to build a Sixteen-Cylinder Automobile Engine. Later in the year, the V-12 Cadillac was introduced. **First** to offer a complete line of multi-cylinder cars—all of V-type design. **First** to use Hydraulic Valve Silencers.
		V-8 "353"	3,695	140"	
1931	29,781	V-8 "345-A"	2,295	134"	
		V-8 "355-A"	2,795	134"	
		V-12 "370-A"	3,895	140"	
		V-16 "452-A"	5,950	148"	
1932	8,085	V-8 "345-B"	2,495	136"	**First** to introduce Super-Safe Headlights, Air-Cooled Generator, Completely Silent Transmission and Full-Range Ride Regulator.
		V-8 "355-B"	3,095	140"	
		V-12 "370-B"	3,795	140"	
		V-16 "452-B"	5,095	149"	
1933	6,654	V-8 "345-C"	2,245	136"	**First** to provide fine cars with No-Draft Ventilation.
		V-8 "355-C"	2,895	140"	
		V-12 "370-C"	3,595	140"	
		V-16 "452-C"	6,250	149"	
1934	11,856	Str.-8 "50"	1,595	119"	**First** to introduce today's mode of streamlining. **First** American car with spare tire concealed within body. **First** to develop and use Knee-Action Wheels.
		V-8 "10"	2,495	128"	
		V-8 "20"	2,695	136"	
		V-8 "30"	3,295	146"	
		V-12 "40"	3,995	146"	
		V-16 "60"	6,650	154"	
1935	13,449	Str.-8 "50"	1,545	119"	**First** and **Only** fine car equipped with one-piece solid steel Turret Top. For five years, more Cadillacs purchased than any other make of fine car.
		V-8 "10"	2,445	128"	
		V-8 "20"	2,645	136"	
		V-8 "30"	3,295	146"	
		V-12 "40"	3,995	146"	
		V-16 "60"	6,750	154"	
1936	25,905	Str.-8 "50"	1,225	120"	48.1% of all cars sold above $1,500 were Cadillacs.
		V-8 "60"	1,695	121"	
		V-8 "70"	2,445	131"	
		V-8 "75"	2,645	138"	
		V-12 "80"	3,195	131"	
		V-12 "85"	3,345	138"	
		V-16 "90"	7,570	154"	
1937	46,153	V-8 "37-50"	1,260*	124"	Cadillac-built V-8 proves stamina, dependability and speed of present day stock car by breaking all previous stock car records at Indianapolis Speedway. Deliveries at retail hit all-time peak in previous Cadillac history.
		V-8 "37-60"	1,660*	124"	
		V-8 "37-65"	2,090*	131"	
		V-8 "37-70"	2,595*	131"	
		V-8 "37-75"	2,815*	138"	
		V-12 "37-85"	3,535*	138"	
		V-16 "37-90"	7,750*	154"	
1938	24,950	V-8 "38-50"	1,385*	124"	**First** to create and introduce a practical motor car of advanced styling. **First** to engineer and build the 135° V-type sixteen-cylinder engine. A majority public recognition of **Cadillac Merit** and **Advanced Progress** is definitely established.
		V-8 "38-60"	1,775*	124"	
		V-8 "38-60S"	2,085*	126"	
		V-8 "38-65"	2,285*	132"	
		V-8 "38-75"	3,075*	141"	
		V-16 "38-90"	5,265*	141"	
1939	36,611	V-8 "39-50"	1,320*	120"	**First** to develop and introduce Controlled-Action, greatest advancement in riding comfort and safety since Knee-Action. More than half of all fine cars sold above $2,000 are Cadillacs.
		V-8 "39-61"	1,680*	126"	
		V-8 "39-60"	2,090*	127"	
		V-8 "39-75"	2,995*	141"	
		V-16 "39-90"	5,140*	141"	

Downloaded from www.Manualslib.com manuals search engine

1902/1966 Cadillac milestones

Model Year	Total Production	Type of Cars Produced	List Price (Typical Car)	Wheelbase	Milestones
1940	37,162	V-8 "40-50"	$1,320*	123"	**First to offer** custom car interiors at medium price. **First** to equip passenger cars with Ball Bearing Steering. **First** to introduce an **ultramodern,** large, luxurious motor car—the Cadillac Fleetwood 72. During first six months, 1939, Cadillac outsold all makes combined with series having 5 touring sedans priced at or above $1,300.
		V-8 "40-52"	1,440*	123"	
		V-8 "40-62"	1,745*	129"	
		V-8 "40-60S"	2,090*	127"	
		V-8 "40-72"	2,670*	138"	
		V-8 "40-75"	2,995*	141"	
		V-16 "40-90"	5,140*	141"	
1941	66,130	V-8 "41-61"	1,445*	126"	**First** to introduce to the medium price field a motor car of unquestioned prestige without a compromise in quality. **First** high price car to offer Hydra-Matic, the completely automatic transmission that eliminates the clutch pedal and all gear shifting. Cadillac outsold all makes of cars in both the medium and high price groups.
		V-8 "41-62"	1,495*	126"	
		V-8 "41-63"	1,695*	126"	
		V-8 "41-60S"	2,195*	126"	
		V-8 "41-67"	2,595*	139"	
		V-8 "41-75"	2,995*	136"	
1942	16,511	V-8 "42-61"	1,647*	126"	**Presentation** of the Fortieth Anniversary Cadillacs. Introduction of sealed, ribbed Super-Safe Brakes and All-Weather Ventilation System.
		V-8 "42-62"	1,754*	129"	
		V-8 "42-63"	1,882*	126"	
	(Production halted February, 1942)	V-8 "42-60S"	2,435*	133"	
		V-8 "42-67"	2,896*	139"	
		V-8 "42-75"	3,306*	136"	
1943	—	—	—	—	Cadillac-built light tanks and motor carriages contributed immeasurably to the struggle for victory and peace. Precision aircraft engine parts made by Cadillac helped power America's leading combat planes. Army-Navy "E" award to Cadillac for excellence in production of war equipment.
1944	—	—	—	—	Cadillac produced the M-24, one of the world's fastest and most maneuverable combat vehicles of its kind. This famous light tank, which served on all battlefronts, was powered by Cadillac V-type engines and Cadillac Hydra-Matic transmissions.
1945	—	—	—	—	Continued production of the world-famous M-24 light tank for distinguished use in European and Pacific theaters. Introduction of the M-19, a potent anti-aircraft gun motor carriage.
1946	29,194	V-8 "46-61"	2,176*	126"	**Presentation** of the 1946 Cadillacs, using the battle-proved Cadillac V-type engine and Hydra-Matic transmission, the only automotive units of this kind to be produced and improved without interruption during the war.
		V-8 "46-62"	2,359*	129"	
		V-8 "46-60S"	3,099*	133"	
		V-8 "46-75"	4,298*	136"	
1947	61,926	V-8 "47-61"	2,324*	126"	**Postwar** production reaches over 90% of prewar peak. Cadillac increases fine-car leadership with over 96,000 unfilled orders.
		V-8 "47-62"	2,523*	129"	
		V-8 "47-60S"	3,195*	133"	
		V-8 "47-75"	4,471*	136"	
1948	52,706 (9 months)	V-8 "48-61"	2,647*	126"	Cadillac presented its greatest engineering achievement in 45 years—the new, compact, better performing, more economical, valve-overhead, V-type, eight-cylinder engine for all 1949 Cadillacs.
		V-8 "48-62"	2,781*	126"	
		V-8 "46-60S"	3,506*	133"	
		V-8 "48-75"	4,471*	136"	
1949	92,554	V-8 "49-61"	2,893*	126"	Cadillac's 1 millionth car produced November 25, 1949.
		V-8 "49-62"	3,050*	126"	
		V-8 "49-60S"	3,828*	133"	
		V-8 "49-75"	4,750*	136"	
1950	103,857	V-8 "50-61"	2,866*	122"	Cadillac production exceeds 100,000 cars for the first time in its history.
		V-8 "50-62"	3,234*	126"	
		V-8 "50-60"	3,797*	130"	
		V-8 "50-75"	4,770*	147"	
1951	110,340	V-8 "51-62"	3,315*	126"	Cadillac moves into defense production of tanks in Cleveland without interruption of automobile production.
		V-8 "51-60"	3,892*	130"	
		V-8 "51-75"	4,887*	147"	
1952	90,715 (11 months)	V-8 "52-62"	3,636*	126"	Cadillac celebrates its Golden Anniversary.
		V-8 "52-60"	4,270*	130"	
		V-8 "52-75"	5,361*	147"	

Downloaded from www.Manualslib.com manuals search engine

1902/1966 Cadillac milestones

Model Year	Total Production	Type of Cars Produced	List Price (Typical Car)	Wheelbase	Milestones
1953	109,657	V-8 "53-62" V-8 "53-60" V-8 "53-75"	$ 3,666.26* 4,304.88* 5,604.34*	126 130 147	Cadillac offers highest horsepower engine ever used in an American production motor car.
1954	96,680 (9 months)	V-8 "54-62" V-8 "54-60" V-8 "54-75"	3,932.70* 4,683.32* 5,874.78*	129 133" 149¾	Cadillac is **First** to provide Power Steering as standard equipment on its entire line of cars.
1955	140,778 (11 months)	V-8 "55-62" V-8 "55-60" V-8 "55-75"	3,976.70* 4,728.32* 6,186.78*	129" 133" 149¾"	Cadillac establishes new production and sales records by building and selling over 140,000 motor cars in 11 months.
1956	154,631	V-8 "56-62" V-8 "56-60" V-8 "56-75"	4,291* 5,042* 6,608*	129" 133" 149¾"	Cadillac becomes the only car in its price class ever to be rewarded with an owner demand for over 150,000 cars in one year.
1957	146,840	V-8 "57-62" V-8 "57-60" V-8 "57-75"	4,780.96* 5,614.32* 7,439.88*	129½" 133" 149¾"	Cadillac introduces the fabulous Eldorado Brougham, a limited production luxury motor car with air suspension as standard equipment. All Cadillac models feature the revolutionary new Cadillac tubular-center X frame.
1958	121,786	V-8 "58-62" V-8 "58-60" V-8 "58-75"	4,891* 6,232* 8,460*	129½" 133" 149¾"	Cadillac pioneered Four-Link Rear Suspension adopted as standard equipment with coil springs or (optional at extra cost) air suspension throughout entire line.
1959	142,272	V-8 "59-62" V-8 "59-60" V-8 "59-75"	5,080* 6,233* 9,533*	130" 130" 149¾"	Cadillac becomes the only luxury motor car with an owner demand for well over 1,000,000 cars in a single decade.
1960	142,184	V-8 "60-62" V-8 "60-60" V-8 "60-75"	5,080* 6,233* 9,533*	130" 130" 149¾"	Cadillac introduces to luxury car owners front-fender mounted directional signal indicator lights and an automatically releasing vacuum operated parking brake.
1961	138,379	V-8 "61-62" V-8 "61-60" V-8 "61-75"	5,080* 6,233* 9,533*	129½" 129½" 149¾"	Pre-packed suspension and steering connections minimize maintenance; increase quietness and durability. Over 50% of all 1961 Cadillac motor cars equipped with factory-installed Air Conditioning.
1962	160,840	V-8 "62-62" V-8 "62-60" V-8 "62-75"	5,213* 6,366* 9,722*	129½" 129½" 149¾"	Cadillac sets new luxury car records with production of over 160,000 cars with 60% Air Conditioned. Cadillac is **First** to provide Triple Braking system and Cornering Lights.
1963	163,174	V-8 "63-62" V-8 "63-60" V-8 "63-75"	5,214* 6,366* 9,724*	129½" 129½" 149¾"	Cadillac **First** to provide two C-V (constant velocity) joints on propellor shaft for maximum quietness and stability.
1964	165,959	V-8 "64-62" V-8 "64-60" V-8 "64-75"	5,236* 6,388* 9,746*	129½" 129½" 149¾"	Cadillac introduces Comfort Control—**First** fully automatic year 'round air conditioning-heating system. Cadillac completes multi-million dollar expansion program which includes new Engineering Center, enlarged Manufacturing and Assembly space, multi-level parking facility, complete rebuilding of Administration Building, and conversion of previous Engineering facility to Manufacturing space.

Model Year	Total Production	Types of Engines	Models or Series	List Price (Typical Car)	Wheelbase	Milestones
1965	181,435	V-8	Calais	5,247*	129½"	Cadillac introduces new coaxial resonator exhaust system, new one-piece propeller shaft with two CV (constant velocity) joints, new perimeter frame with pheasant tail, rear engine mount and new Tilt and Telescope Steering Wheel. Cadillac production tops 180,000 reflecting highest owner loyalty in the industry.
		V-8	De Ville	5,666*	129½"	
		V-8	Fleetwood 60S	6,479*	133"	
		V-8	Fleetwood 75	9,746*	149¾"	
1966	196,675	V-8	Calais	5,171*	129.5"	**First** to introduce variable ratio steering on American cars.
		V-8	De Ville	5,581*	129.5"	
		V-8	Fleetwood Brougham	6,695*	133.0"	
		V-8	Fleetwood 75	10,312*	149.8"	

*Manufacturer's suggested retail price at Detroit, does not include optional equipment or state and local taxes.

Downloaded from www.Manualslib.com manuals search engine



Alphabetical index

A

Accessory Groups....A-7, 8
Accessories, Packaged....A-11
Acrylic Numbers....A-12
Advance Procurement Request....D-11
"A-I-R" Air Injection Reactor System....G-4
Air Cleaner....H-4
Air Conditioner-Heater System....B-2, G-14
Arm Rests, Center....A-9, Section C
Arm Rests, Door....Section C, F-7
Ash Receivers....A-9, 10, F-6, C-23
Assist Handles....A-9, C-19, 21
Assist Straps....A-9
Automatic Choke Control....G-3
Automatic Climate Control....B-2, G-14
Automatic Level Control....B-2
Axle Ratios....H-1, 7

B

Backup Lights....F-3
Battery....G-4, H-5
Body Construction....G-11 thru 15
Body Insulation....G-15
Body Sealing....G-15
Body Styles....A-1, C-1
Boot, Top, Convertible....C-15
Brake Drums....G-9
Brake Lining....H-8
Brakes....G-9, 21
Brakes, Disc....B-8, G-21
Brakes, Parking....G-9

B continued

Brakes, Power....G-9, 21
Bucket Seat, Recliner....B-6, Section C
Bucket Seats....Section C
Bucket Seats, Cloth (Special)....D-9
Bucket Seats, Leather (Special)....D-9
Bucket Seats, Power....B-4
Bumpers....F-2, 3

C

Camshaft....G-3, H-3
Carburetor....G-3, H-4
Carpets....Section C
Carpets, Special Order....Section D
Chassis Features....G-7 thru 10
Chassis, Fleetwood Eldorado....G-16
Chassis, Overall View....G-7
Chauffeur Compartment....C-31
Choke Control....G-3
Cigarette Lighters....A-9, C-23
Climate Control, Automatic....B-2, G-14
Closed Positive Crankcase Ventilator—Air Injection Reactor....G-4
Cloth, Special Orders....Section D
Coaxial Resonator Exhaust....G-3
Colors, Exterior....A-2, 12
Colors, Exterior, Special Order....D-12
Color-Trim Recommendations....A-3, 4, 5
Compression Ratio....G-2, H-1
Concealed Headlamps....F-5
Connecting Rods....H-2

Downloaded from www.Manualslib.com manuals search engine

C continued

Console, Bucket Seat....Section C
Constant Velocity (CV) Joints....G-6
Controlled Differential....B-7
Control Knobs and Levers....F-7, 8, 9
Convertible Top Boot....C-15
Convertible Tops....A-1, C-15
Cooling....G-4, H-4
Cornering Lights....F-4
Crankcase, Ventilation....G-4
Crankshaft....G-3, H-2
Cruise Control....B-3

D

Deck Lid....F-3
Deck Lid Lock, Power....B-7
De-Fogger, Rear Window....B-7
Differential, Controlled....B-7
Dimensions, Exterior....A-1, H-1
Dimensions, Interior....Section C
Directional Signals....F-2, 5, 7
Disc Brakes....B-8, G-21
Displacement, Engine....G-2, H-1
Distributor....H-4
Division Glass in Brougham....D-10
Division Glass in Limousine....C-31
Doors....G-20
Door Latch Handles....F-7, 8, G-12, 20
Door Locks, Passenger-guard....F-8, G-12
Door Locks, Power....B-4
Door Pulls....F-7, G-20
Drive Line....G-6

E

Eldorado, Exterior....C-5
Eldorado, Interior....C-23
Eldorado, Special Features....F-5, G-16 thru 21
Energy Absorbing Steering Column....G-8
Energy Absorbing Steering Wheel....F-7
Engine Cooling....G-4, H-4
Engine Features....G-1 thru 4
Engine Lubrication....H-3
Engine Specifications....G-2, Section H
Engine Warm-Up....G-3
Equipment, Fleetwood—Extra Features....A-10
Equipment Groups....A-7, 8
Equipment, Optional....A-9, 10, B-1
Equipment, Standard....A-9, 10
Exhaust System....G-3, 21, H-1
Exhaust Valves....H-3
Exterior Color Recommendations....A-2
Exterior Colors, "Fire-Frost"....D-12
Exterior Colors, Past Model....D-12
Exterior Dimensions....A-1, H-1
Exterior, Illustrations....Section C

F

Fan, Radiator....G-4, H-4
Fenders, Front....F-4
Fenders, Rear....F-4
Field Installed Accessories....A-11
"Fire-Frost" Colors....D-12

F continued

Firemist Colors....A-2
Folding Front Seat Back Latches....F-8
Footrests....A-10
Four-Barrel Carburetor....G-3, H-4
Frame....G-7, 18, H-6
Front End Design....F-2
Front Suspension....G-10, 18, H-6
Front Wheel Drive....G-17
Fuel System....H-4
Full-Flow Oil Filter....H-3

G

General Engine Specifications....G-2, H-2
General Specifications....H-1
Generator....G-4, H-4
Generator Regulator....G-4, H-4
Glass, Soft Ray....B-7
Glove Compartment....F-6, 8
Grille, Front....F-2
Grille, Deck Sill....F-3
Groups, Accessory....A-7, 8
Guide-Matic....B-3

H

Handles, Assist....A-9, C-19, 21
Hazard Warning Flasher....F-9
Headlamp Control, Power....B-3
Headlights....F-2, 5
Headrests, Front....B-6
Heater-Defroster Controls (Eldorado)....G-19
Hood Insulation....G-15
Hood Latches....G-12
Hood Styling....F-2
Horn....H-5

I

Ignition Switch....G-15
Ignition System....H-4, 5
Instrument Cluster....F-6
Instrument Panel....F-6
Intake Valves....H-3
Interior Charts....Section C
Interior Color Recommendations....A-3, 4, 5
Interior Dimensions....Section C
Interior Lamps....Section C
Interior Nomenclature....D-13, 14
Interior Terminology....D-13, 14
Interiors....C-1
Interiors, Special Order....Section D
Insulation, Body....G-15

L

Landau Roof....C-7, 33
Leather, Special Order....D-1
Level Control, Automatic....B-2
License Plate....F-2, 3
Lights and Horn....H-5
Lights, Backup....F-3
Lights, Cornering....F-4
Lights, Courtesy....Section C

Downloaded from www.Manualslib.com manuals search engine

L continued

Lights, Directional....F-2, 5
Lights, Headlamp....F-2, 5
Lights, Reading....Section C
Lights, Parking....F-2, 5
Lights, Tail and Stop....F-3, 5
Lights, Telltale....F-6, 9
Lock, Deck Lid, Power....B-7
Locks, Door, Passenger-guard....F-8, G-12
Locks, Hood....G-12
Lubricants....H-8
Lubrication....H-3
Luggage Compartment....G-13, 20

M

Milestones....Section I
Mirrors....A-9, 10, F-9

N

New Features....F-1
Nomenclature, Car Interior Trim....D-13, 14

O

Oil Change....H-8
Oil Filter, Full-Flow....H-3
Optional Equipment....A-9, 10, B-1
Order Procedure, Special Orders....D-11

P

Padded Top Recommendations....A-2
Parking Brakes....G-9
Parking Lights....F-2, 5
Pistons....G-3, H-2
Power Brakes....G-9
Power Deck Lid Lock....B-7
Power Door Locks....B-4
Power Headlamp Control....B-3
Power Seats....B-4
Power Steering....G-8, 21, H-7
Power Ventipanes....B-4, G-20
Power Windows....B-4
Prices....Section E
Propeller Shaft....G-6, H-6

Q

Quadrajet Carburetor....G-3, H-4
Quadrant, Turbo Hydra-Matic....G-5

R

Radiator....G-4, H-4
Radiator Fan....G-4, H-4
Radios....B-5
Radio Antenna....B-5
Rear Axle....G-6, H-7
Rear Axle Ratios....H-1, 7
Rear End Styling....F-3, 5
Rear Fender Styling....F-4, 5
Rear Springs....G-10, 18, H-6
Rear Suspension....G-10, 18, H-6
Rear Vertipanes....B-4, G-20

R continued

Rear View Mirrors....A-9, 10, F-9
Rear Window De-Fogger....B-7
Recliner, Passenger Bucket Seat....B-6
Recliner, Passenger Strato-bench Seat....B-6
Reflectors, Door Panel....A-9
Remote-control Trunk Lock....B-7
Rings....G-3, H-2
Rods, Connecting....H-2
Roof, Coupe and Hardtop Sedans....F-4, Section C
Roof Insulation....G-15
Roof, Landau....C-7, 33
Roof, Padded....A-2, Section C

S

Seat Belts....B-8
Seat Styling....Section C
Seat Warmer....B-6
Seats, Auxiliary....C-29, 31
Seats, Bucket....Section C
Seats, Strato-bench....C-23
Seats, Power-operated....B-4
Shipping Weights....A-1
Shock Absorbers....G-10, 18, H-6
Shoulder Straps....B-8
Soft Ray Glass....B-7
Spare Tire....G-13
Spare Tire Cover....G-13
Special Orders, Cloth, Leather, Vinyl, Colors....D-1
Specifications....H-1
Springs, Coil....G-10, H-6
Springs, Leaf....G-18, H-6
Springs, Seat....A-10
Standard Equipment....A-9, 10
Starting System....G-4, H-4, 5
Steering....G-8, 21, H-7
Steering Column, Energy Absorbing....G-8
Steering, Power....G-8, 21, H-7
Steering, Variable Ratio....G-8, 21, H-7
Steering Wheel, Energy Absorbing....F-7
Strato-bench and Bucket Seats....C-23
Styling....F-2 thru 9, Section C
Suspension, Front....G-10, 18, H-6
Suspension, Rear....G-10, 18, H-6

T

Terminology, Interior....D-13, 14
Tilt and Telescope Steering Wheel....B-6
Tires and Wheels....B-8, G-6, H-7
Top Boot....C-15
Top, Convertible....A-1, C-15
Top, Padded....Section C
Torsion Bars....G-18, H-6
Transmission....F-8, G-5, H-5, 6
Trays, Fold-down (Brougham)....A-10, C-27
Tread Width....H-1, 7
Trim Charts....Sections A and C
Trim-Color Recommendations....A-3, 4, 5
Trunk Lock, Remote-control....B-7
Turbo Hydra-Matic Transmission....F-8, G-5, H-5, 6
Twilight Sentinel....B-3
Two-Tone Interiors, Special Order....D-1
Two-Tone Paint, Not Available....A-5

Downloaded from www.Manualslib.com manuals search engine

U

Universal Joints....H-6
Upholstery Options (General Information)....C-8
Upholstery Recommendations....A-3, 4, 5, C-8
Upholstery Selections....A-6, Section C
Upholstery Styling....Section C

V

Valves....G-3, H-3
Variable Ratio Steering....G-8, H-7
Ventilation System....B-2, G-19
Ventipanes, Front, Power....B-4
Ventipanes, Rear....B-4, G-20

V continued

Visors, Padded Sun....A-10

W

Water Pump....H-4
Weights, Car....A-1
Wheelbase....A-1, H-1
Wheel Bearings, Rear....G-6, H-7
Wheel Discs....F-4, 5
Wheels and Tires....B-8, G-6, H-7
Window Regulators, Manual....F-9
Window Regulators, Power....B-4
Windshield Washer-Wipers....G-13


The Cadillac Motor Car Division
of General Motors Corporation
reserves the right
to make changes at any time,
without notice, in prices,
colors, materials, equipment,
specifications and models,
and also to discontinue models.

All information contained herein has been carefully checked with the most reliable sources, but responsibility for the absolute authenticity of this information cannot be assumed. The right is reserved to change any specifications, parts or equipment at any time without incurring any obligation to equip same on cars built prior to date of such change.

The 1967 Cadillac Data Book was compiled as of August, 1966, and was printed in U. S. A. The above reservations apply to all pages unless otherwise noted.

Cadillac Motor Car Division
General Motors Corporation

Downloaded from www.Manualslib.com manuals search engine



IMPORTANT SAFETY TIPS
PAGES 2 & 3

Cadillac

1967 OWNER'S MANUAL

Downloaded from www.Manualslib.com manuals search engine

1967 CADILLAC OWNER'S MANUAL

The information in this manual has been prepared to acquaint you with the operation, care and proper maintenance of your new 1967 Cadillac car. We suggest that you review these instructions carefully so that you can enjoy the many special features engineered into this fine motor car.

If a question should occur that is not answered here, please write to us, giving the Vehicle Identification Number of your car. We will be happy to hear from you at any time.

WARRANTY INFORMATION

on your 1967 Cadillac is given in complete detail in the OWNER PROTECTION PLAN booklet you received from your Cadillac Dealer. Read this booklet carefully so that you will understand your responsibilities and those of the dealer and manufacturer under this warranty.

SERVICE DEPARTMENT
CADILLAC MOTOR CAR DIVISION
GENERAL MOTORS CORPORATION
DETROIT, MICHIGAN 48232

© General Motors Corporation 1966

Important Safety Tips To Help You Enjoy The Maximum In Satisfaction And Safety!

Downloaded from www.Manualslib.com manuals search engine

HIGHWAY SAFETY DEPENDS ON–

1 You, the driver

2 The condition of your vehicle

3 The traffic and highway conditions

...BE SURE YOU UNDERSTAND ALL THREE!

SAFE DRIVER CHECKLIST

- ☐ Make seat belts a habit . . . buckle up for safety.
- ☐ Lock the doors for added safety.
- ☐ Adjust seats and mirrors for clear vision and safe handling.
- ☐ Check tire pressure regularly.
- ☐ Observe weather and road conditions . . . and drive accordingly.
- ☐ Be sure you are physically and mentally alert to drive.
- ☐ Look around before driving away from where you are parked.

SAFE DRIVERS OBSERVE ALL TRAFFIC LAWS . . .

Downloaded from www.Manualslib.com manuals search engine

REMEMBER . . .

Proper operation, periodic maintenance and safety inspections help provide—

- Economical operation of your vehicle
- Safety for you and your passengers
- Dependable transportation

Have this 10-point Safety Inspection Performed Once a Year*

√Brakes
√All Lights
√Turn Signals and Hazard Warning Flasher
√Steering and Wheel Alignment
√Tires
√Exhaust System
√Glass and Mirrors
√Windshield Wipers and Washers
√Windshield De-Icer and De-Fogger
√Horns

For details refer to the 1967 Cadillac Owner Protection Plan Booklet

**Minimum Requirement-Some States Require More Frequent Inspection*


Quick Reference Index

	Page
Door Locks	36, 37
Power Steering	18
Power Brakes	17
Automatic Brake Adjusters	17
Seat and Shoulder Belts	34, 35
Head Restraints	33, 34
Jack Operation	56, 57, 58
Fuel	47, 48
Exhaust Gas Caution	62
Radiator Cap	52
Fabric Cleansing Caution	61
Tires	58, 59
Controlled Differential	62
Battery Gas Caution	54
Trailer Hauling	6
Towing	6

Of Important Safety Information

MAKE SAFE DRIVING A HABIT . . . GET A SAFETY-INSPECTION ONCE A YEAR*

Downloaded from www.Manualslib.com manuals search engine



OPERATING YOUR CADILLAC



Your new Cadillac is ready for all normal driving just as you receive it from your dealer. Precision manufacturing techniques have prepared it for the road and a formal break-in period is not required. From the very start, drive your new Cadillac in a normal manner at varying speeds, as required by different traffic and road situations.

Keys

Two separate keys are provided for your car. Each key has a different keyway to fit the locks. The key with the octagonal head and the letter "A" stamped on the keyway operates the ignition switch and front door locks. The key with the rounded head and the letter "B" is used for the luggage compartment and glove box door locks, as well as the center console lock on cars with bucket seats. These compartments should be locked and the key removed from the car should it be necessary to leave the ignition key with an attendant.

On Limousine styles, a separate key is provided for the lock on the right hand door of the rear passenger compartment. The key is coded differently from the one used for the ignition switch and left front door, and the octagonal head is notched on two sides for easy identification.

The code number of each key is stamped on a "knock-out" plug in the key head. Record the numbers so that you may

Downloaded from www.Manualslib.com manuals search engine


have duplicate keys made in the event the original keys are lost. After recording the number of each key, remove and discard the "knock-out" plug so that your key cannot be easily duplicated by anyone else.

A high percentage of car thefts occur because car doors are left unlocked or key is not removed from ignition switch. Always remove ignition key and lock doors when leaving car unattended.

Ignition Switch

The ignition switch is located below the instrument cluster to the right of the steering column. The key slot is illuminated when instrument panel lights are on. The key can be turned to any one of three positions, but can be inserted or withdrawn only in the straight-up, "OFF" position. First position "right" completes the ignition circuit and activates all instruments and accessories. Full "right" position cranks the engine. All accessories are disconnected while the ignition switch is in the cranking position.

The "left" position is for operation of accessories with ignition off. The key must be pushed in before it can be turned to the "left" position. This feature prevents accidental engagement of the accessories position and subsequent battery discharge if the accessories are operating at the time.



Normal starting

The starter operates when the ignition key is turned to the full "right" position, provided the transmission selector lever is in either "Park" or "Neutral". The starter is inoperative in all driving positions. When the engine is cold, press the accelerator pedal slowly to the toeboard once, then remove your foot, and turn the key to the full "right" position. DO NOT hold the key in full "right" position longer than 15 seconds at

Downloaded from www.Manualslib.com manuals search engine

one time. When the engine starts, releasing the key permits it to return to the first "right" position. If the car has been standing over 48 hours, it is helpful to pump the accelerator three times before starting.

Restarting

If the engine is warm from previous running (within the last two to four hours), hold the accelerator part way down while cranking.

Extreme cold weather starting

The starting procedure for extreme cold weather is basically the same as for normal conditions. Should the engine start, run for a few seconds and then stall, repeat the normal starting procedure. If the engine does not restart within five seconds of cranking, push the accelerator to the floor and hold it (DO NOT PUMP) while continuing to crank until engine starts. Do not crank engine longer than 15 seconds at a time. Proper engine oil viscosity is very important for easy cold weather starting. See page 51.

Emergency starting

The automatic transmission does not permit the engine to be started by pushing the car. To start the car when the battery is discharged, use an auxiliary battery with jumper cables. Be sure to observe correct polarity (positive cable to positive terminal and negative cable to negative terminal) when connecting the auxiliary battery to prevent possible damage to the electrical system.

Starting flooded engine

Hold the accelerator pedal all the way down and crank until engine starts (not over 15 seconds at a time).

Towing

If your Cadillac must be towed, the following precautions must be observed: The car may be towed safely on its rear wheels with the shift lever in neutral "N" position at speeds of 35 miles per hour or less under most conditions.

However, the drive shaft must be disconnected or the car towed on its front wheels if:

- *Tow speeds in excess of 35 MPH are necessary,*
- Car must be towed for extended distances (over 50 miles), or,
- Transmission is not operating properly.

If car is towed on its front wheels, the steering wheel should be secured to keep the front wheels in a straight-ahead position.

Trailer hauling

It should be recognized by trailer users that all makes of passenger cars are designed and intended to be used primarily

Downloaded from www.Manualslib.com manuals search engine

as passenger conveyances. A trailer cannot be towed behind a passenger car without having some effect on safe operation, dependability and economy. Although all Cadillac cars will pull a trailer as satisfactorily as other makes of passenger cars, maximum satisfaction and pleasure will be derived through use of proper equipment and avoiding overloads and other abusive operation.


Since many kinds of trailer hitches are sold, it is not practical for Cadillac to evaluate and test all hitches. We recommend only that the owner satisfy himself as to the strength of the hitch and the method by which it is attached to the car. Generally, trailer tongue loads should be minimized by maintaining good balance of the load in the trailer. General information on trailer hauling is available and can be obtained by writing to Cadillac Motor Car Division, Service Department, Detroit, Michigan.

INSTRUMENTS

NOTE: Fuel and temperature gage needles are of the balanced-type and may not return to the left when ignition is turned "OFF", but may stop at any point on the dial.

Fuel gage

The fuel gage is located on the lower right side of the instrument cluster. It registers only when the ignition key is turned to the right.



Temperature gage

The engine temperature gage is located on the lower left side of the instrument cluster. Normally, the gage pointer will move gradually from the extreme left when the engine is cold, to approximately the one-quarter mark.

Do not be alarmed if the pointer registers above the center range in heavy traffic or on long drives during warm weather. The pressure-controlled radiator overflow will normally prevent coolant losses up to 259° F. If the pointer reaches "H" or if the coolant boils, indicated by a buzzing sound from the radiator cap, stop the car immediately and have the condition causing the overheating corrected. CAUTION: Before removing radiator cap, see page 52.

Low brake pedal warning light

A red warning light for the brake system is located in the row

Downloaded from www.Manualslib.com manuals search engine

of lights on the left side of the instrument cluster. Under normal conditions, this light will glow during engine cranking, but will go out when the engine is running. In the event of a fluid leak in either the front or rear hydraulic system, resulting in excessive brake pedal travel during normal brake application, the light labeled "Brake" will glow. Should this occur, immediate inspection of the brake system should be made by your Authorized Cadillac Dealer.

Oil pressure indicator light

If engine oil pressure is low, a red indicator light labeled "OIL", located in the row of lights on the left side of the instrument cluster, will glow. Under normal conditions this light will glow when the ignition is turned on, but will go out when the engine is running. If it does not go out, the car should not be operated until the cause of the low oil pressure has been corrected by an Authorized Cadillac Dealer.

Generator indicator light

A red indicator light for the charging circuit is located in the row of lights on the left side of the instrument cluster. The light, labeled "GEN", glows whenever the generator is not charging. In normal operation, it will light when the ignition is turned on and will go out when the engine starts. The light will also glow, but not as brightly, when the ignition switch is in the accessory position. If it glows while the engine is running, have your car checked by an Authorized Cadillac Dealer.


Speedometer and odometer

The speedometer indicates car speed. The odometer indicates distance traveled. It is divided into two sections—the left half records accumulated mileage and the right half indicates trip mileage. A reset knob for the trip mileage is located in the instrument cluster just to the right of the odometer. To reset trip mileage, push in on the reset knob and turn it clockwise until all nines appear. Repeat the operation until all nines again reappear, then reverse the knob until all zeros appear.

INSTRUMENT PANEL AND CONTROLS

Your new Cadillac has easy to read dials, instruments and controls that are designed for your convenience. Only a few minutes review is needed to gain an understanding of the proper use of these instruments and controls. Refer to the illustration on page 9 to acquaint yourself with the instruments and controls on the instrument panel.


Downloaded from www.Manualslib.com manuals search engine



Downloaded from www.Manualslib.com manuals search engine


Windshield wipers and washers

The three-speed windshield wipers are controlled by a lever located on the instrument panel to the left of the steering column. To operate the wipers, move the lever to the first triangular mark "LOW", the second triangular mark "MEDIUM", or the "HIGH" position Do not try to move the blades by hand or attempt to run the wipers if the blades are frozen to the glass. Avoid operating the wipers on a dry windshield.



Windshield washers are provided for cleaning the windshield. Pressing down on the WASH button, located just to the left of the wiper control lever, automatically actuates the wipers to operate at low speed and sprays solution on the windshield. When washing action is completed, move the wiper lever to the "OFF" position. NOTE: The washers may not operate effectively at extremely low temperatures or while traveling at high speeds.

Headlight controls



Downloaded from www.Manualslib.com manuals search engine

The control knob for the headlights, parking lights, instrument panel lights, and courtesy lights is located below the instrument cluster to the left of the windshield wiper controls. HEADLIGHTS are operated by pulling the control knob all the way out. PARKING LIGHTS come on as the same knob is pulled halfway out.

Whenever a sealed beam headlight is replaced, headlight aim should be checked and adjusted.

INSTRUMENT PANEL LIGHTS are on in both positions. Instrument panel lights can be increased or decreased in intensity, or turned off, by rotating the control knob. Rotating it completely counterclockwise turns on the courtesy lights.

Headlight dimmer switch

The headlight dimmer switch permits you to select the correct headlight beam for different types of driving. All four lights are on when you use the high beam for highway driving . . . only the upper lights are on for low beam city driving. Select desired beam by depressing the foot switch located on the floor just below the parking brake pedal.

High beam indicator

When the headlights are on high beam, an indicator light below the 60 MPH mark on the speedometer dial glows red. Do not leave the high beam on when approaching oncoming traffic or driving behind another car.

Map light

A map light is located under the top edge of the instrument panel cover to the right of the instrument cluster. The map light is operated manually by a switch located above the clock.

Back-up lights


Your Cadillac is equipped with dual back-up lights that go on automatically when the transmission selector lever is in the reverse "R" position with the ignition switch on.

Courtesy lights

Your Cadillac is equipped with courtesy lights that illuminate the interior of the car when any door is opened. On sedan styles all interior courtesy lights go on when either front or rear door is opened. When all doors are closed, full counterclockwise position of the headlight control knob turns on courtesy lights. A manual switch is centrally located on the back of the front seat on some sedan styles, and on the front of the left rear armrest on some coupe styles, for control of rear courtesy lights and for control of the console light on the Coupe de Ville and De Ville Convertible.

A red warning light (red reflector on some models) is located below the armrest on each door. The red light or reflector serves as a warning to others at night when the door is opened.

Downloaded from www.Manualslib.com manuals search engine




On the Fleetwood Brougham Sedan, adjustable reading lights are located on the upper rear quarter trim panels. These lights can be adjusted individually to direct illumination where desired by rear seat passengers, while reducing glare for the driver. The lights are operated separately by a manual switch located just ahead of each light.

Turn signal

The turn signal lever is located on the left side of the steering column. Move turn signal lever to the "up" position to signal a right turn, and to the "down" position for a left turn. This activitates flashing signals on the right or left, both front and rear of the car, to inform oncoming and following drivers of the direction you intend to turn. Directional signal indicators are located on the top of each front fender to indicate to the the driver the turn being signalled, without requiring him to take his eyes off the road. When the steering wheel returns to the straight ahead position, the flashing signals automatically cancel.

When making a partial turn, such as when changing lanes the driver has the option of moving the turn signal lever part way to a detent stop. The signal will continue as long as the lever is held in this position and will automatically cancel when the lever is released.



Downloaded from www.Manualslib.com manuals search engine

A steady beam from either indicator light means failure of a front or rear signal bulb on that side of the car. Always have burned out bulbs replaced immediately.

Hazard warning flasher

In the event your car is disabled or you stop for any reason on the highway, this Hazard Warning System, which flashes all four turn signal lights, should be used to warn other drivers of your presence. The turn signal indicator lights on the front fenders also flash to assure the driver that the system is operating.

Since the flashing of all turn signal lights universally means "this vehicle is not moving," never drive the car with the Hazard Warning Flasher operating.




The system is operated by a push-pull type switch located on the right side of the steering column just below the steering wheel. Pushing the switch knob inward activates the flasher mechanism regardless of the ignition switch or turn signal lever position. Pulling the knob outward or turning the steering wheel will cancel the Hazard Warning Flasher.

If the brake pedal is applied when the Hazard Warning Flasher is in operation, the lights will not flash, but will glow continuously.

Cornering lights

Your Cadillac is equipped with cornering lights that operate in conjunction with the turn signals. When the turn signal is




Downloaded from www.Manualslib.com manuals search engine

operating in either direction, with the headlights or parking lights on, the corresponding cornering light emits a steady sideward beam to provide additional illumination when turning corners.

Electric clock

A fully automatic electric clock is located in the instrument cluster to the right of the speedometer. To reset, pull out the reset knob, rotating it slightly, and then continue to rotate it in the direction you want to move the minute hand, until the hands register the correct time. Resetting the clock 5 or more minutes in either direction will automatically regulate the clock to run approximately 20 seconds faster or slower per day, depending on which way the reset knob is rotated. If more than a 20-second adjustment is desired, you can again reset it after 12 hours have elapsed and thereby adjust it to run an additional 20 seconds faster or slower.



To assure accurate time-keeping, your clock should be removed for cleaning and oiling every two years by your Cadillac Dealer, who will be pleased to send it to an authorized clock repair station for necessary maintenance at reasonable cost.

Ash trays and lighters

There are two illuminated ash trays and a lighter located in the center of the instrument panel for the convenience of both passenger and driver. The ash tray can be opened by grasping the finger recess and sliding the ash tray straight out.

Rear combination ash trays and lighters are provided on all models except the Calais Coupe, which is equipped with ash trays only.



Downloaded from www.Manualslib.com manuals search engine

TRANSMISSION

Your 1967 Cadillac is equipped with a Turbo Hydra-matic transmission. The transmission shift indicator has six positions marked park "P", reverse "R", neutral "N", drive "DRIVE" (left and right positions), and low "L".

An arrangement of steps in the steering column restricts a straight line movement of the shift lever. It is necessary to pull up on the lever when shifting into and out of park "P", when shifting out of neutral "N" into reverse "R", when shifting from the left hand "DRIVE" position to the right hand "DRIVE" or "LOW" position.

"Drive" range—left hand

In drive range, with the indicator in the left hand "DRIVE" position, three forward speeds are available. The left hand "DRIVE" position is used for all normal driving. This permits the transmission to operate through its complete range of gear ratios and select the proper gear ratio for road and load conditions.


PASSING—for passing at moderate speeds, 30-45 miles per hour—depressing the accelerator pedal only part way will usually provide sufficient acceleration. When additional acceleration is required, such as when passing at higher speeds, press the accelerator all the way down. This downshifts the transmission into second gear.

"Drive" range—right hand

In hilly terrain—the right-hand "DRIVE" position may be used. In this position, only first and second speeds are available, improving acceleration and deceleration. The right-hand "DRIVE" position also reduces shifting on hills, provides more control on slippery pavement, and decreases brake usage when descending medium grades. It may be selected at any car speed.

"L" low range

"L" Low range provides maximum engine braking assist. It should always be used when going down very steep grades and where traffic signs call for first or second gear.



Downloaded from www.Manualslib.com manuals search engine

A shift from either "DRIVE" position to low "L" can be made while traveling at moderate speeds. This shift is not recommended when the pavement is slippery or when in loose gravel, as it may induce rear wheel skip.

"R" Reverse

To back up your car, first bring it to a complete stop, then move shift lever to reverse "R" position. The shift lever cannot be moved to reverse "R" from neutral "N" or any "DRIVE" position without pulling up on the lever. It is also necessary to pull up on the lever when shifting to reverse "R" from park "P" position.

"N" Neutral

PROLONGED IDLING IN HEAVY TRAFFIC—place shift lever in neutral "N" when engine must be idled for long periods in heavy traffic during hot weather. The engine can be started with the shift lever in neutral position.

"P" Park

Place shift lever in the park "P" position to lock rear wheels when parked. When parking on hills or steep inclines, apply parking brake and turn front wheels toward curb. It is necessary to raise the shift lever when moving it from any other position to park "P" position. NEVER move the lever to park "P" with the car in motion. The engine can be started with the shift lever in park position.

Rocking the car

If it becomes necessary to rock the car to free it from sand, mud or snow, move the selector lever from "D" to "R" in a repeat pattern while simultaneously applying moderate pressure to the accelerator. Do not race engine. Avoid spinning wheels when trying to free the car.

BRAKES

Your 1967 Cadillac is equipped with power brakes incorporating a dual reservoir master cylinder. With this type cylinder, the front and rear brakes have separate hydraulic systems. The rear brakes are not affected in the event of fluid leaks from the front hydraulic system. Likewise, the front brakes are not affected by loss of fluid from the rear hydraulic system. In the event of a fluid leak in either the front or rear hydraulic system, resulting in excessive brake pedal travel during normal brake application, a red warning light labeled "Brake", located on the left side of the instrument cluster, will glow. Should this occur, immediate inspection of the brake system should be made by your Authorized Cadillac Dealer. Under normal conditions, this light will glow during engine cranking, but will go out when the engine is running.

Downloaded from www.Manualslib.com manuals search engine

All Cadillacs are equipped with self-adjusting brakes which eliminate periodic brake adjustments. The self-adjusting mechanism is actuated, as needed, whenever the car is moved in reverse and the brakes applied. It is possible, however, for excessive brake pedal travel to develop if the required reverse movement with the brake application does not take place during a prolonged period of stop and go forward driving.

Should this occur, the car should be driven backward and forward with the brakes applied at the end of each directional movement, until the brake pedal travel is back to normal. If this procedure fails to restore normal pedal travel, or if any abnormally rapid increase in pedal travel is experienced, immediate inspection should be made by your Authorized Cadillac Dealer. Care should be exercised to assure that full brake pedal travel cannot be obstructed by improper floor mats or other interfering material under the pedal.

Brake lining should be inspected periodically for wear. The frequency of this inspection depends upon driving conditions such as traffic or terrain and also the driving habits of individual owners. Your Cadillac Dealer is best qualified to advise you as to how often this inspection should be performed. When brakes require relining, use genuine General Motors parts, or an equivalent of the highest quality.

Power Brakes

Cadillac power brakes utilize engine vacuum to reduce the braking effort to much less than is required with regular brakes. A built-in vacuum reserve will supply two or more power assisted brake applications after the engine has stopped. After the vacuum reserve has been exhausted, the vehicle can be stopped utilizing the manual portion of the power brake system although considerably more foot pressure will be needed to stop the vehicle.


Braking on hilly terrain

The transmission is designed to supplement the braking system when driving on hilly terrain. To decrease brake usage, place the transmission selector lever in the right-hand "DRIVE" position when descending medium grades and in the Low "L" range when descending steep grades for maximum engine braking assist.

Parking brake

To apply the parking brake, step on the parking brake pedal suspended from the underside of the instrument panel to the left of the power brake pedal. It will lock into place automatically when the transmission is in "Park" or "Neutral" with

Downloaded from www.Manualslib.com manuals search engine



engine running, or in any position when the engine is not running.

The parking brake will release automatically when the transmission selector lever is moved to any drive range with the engine running. A definite noise should be heard when the pedal releases. Do not drive the car unless the parking brake is completely released. Should it be necessary to release the brake manually, pull on the hand release lever located on the upper right side of the parking brake assembly. When pedal travel of the parking brake exceeds approximately five inches, it should be adjusted by your Authorized Cadillac Dealer.

Since the parking brake will not lock into place when the transmission selector is in "Drive", "Low" or "Reverse" ranges with the engine running, it may be used as a fully controllable brake pedal, providing rear wheel braking only, under emergency conditions.

As a precaution when parking on hills, it is advisable to turn the wheels toward the curb, lock the rear wheels by placing the transmission selector in "Park" position, and place the parking brake in its fully depressed position.

Power Steering


Cadillac's variable ratio power steering provides ease in handling, parking, and getting into or out of tight places. Power assist is provided by a hydraulic pump driven by the engine. When the engine is not running or if the power steering pump drive belt breaks, there is no power assist and much greater steering effort is required.

VENTILATION AND HEATING

Ventilation

On cars not equipped with air conditioning, outside air is drawn into the passenger compartment through the grille located in the cowl directly below, and in front of, the windshield. This location reduces intake of exhaust fumes from other cars. Ventilation controls are located under the top edge of the instrument panel to the right of the instrument cluster.

Downloaded from www.Manualslib.com manuals search engine



Moving the control levers individually, right or left, away from the "OFF" position, opens air doors and admits ventilating air into the passenger compartment through outlets in the cowl kick-pads. The levers can be moved gradually to admit as much air as desired.

Heating


The Cadillac heating system delivers heated air through a unit located on the right-hand side of the cowl. Outside air is delivered through the heating system to the front passenger compartment by means of grilles and openings in front of the dash panel. Heated air is delivered to the rear passenger compartment through ducts that extend rearward under the front carpet and seat. Part of the heated air may be directed to the windshield for removing fog or ice.

Heater control operation

The heater controls are located in the instrument panel to the right of the ignition switch. The controls consist of a switch to control fan speed and two horizontal sliding levers to control the defroster and heater. The controls are illuminated when instrument panel lights are on.

The system can be operated with the fan switch "OFF" or with the fan running at any one of three speeds.

The lower lever controls the temperature. To increase the temperature, move the lever to the right; to decrease the temperature, move it to the left. The upper lever turns the



Downloaded from www.Manualslib.com manuals search engine

heater on and off, and directs defrosting air to the windshield. Moving the upper lever to "HEAT" turns the heater on. If air is desired on the windshield, move the lever to the "DEFROST" position, and move the lower lever to the desired temperature position. For removing ice, move both levers to the extreme right position, and set the fan switch on "HIGH".


Heater control during warm-up

For maximum heat and quickest warm-up in cold weather, place the upper lever at "HEAT", move the lower lever all the way to the right, and set the fan switch on "HIGH". If it is necessary to remove some fog from inside the windshield during this period, move upper lever to the "DEFROST" position to direct air to the windshield. Any snow covering the cowl air intake grille should be removed to facilitate defogging.

MIRRORS


Inside day-night rear view mirror

The rear view mirrors used on all 1967 Cadillac cars have shatter resistant vinyl edged glass and a breakaway support. The inside day-night rear view mirror may be positioned from clear daylight visibility to non-glare visibility at night by rotating the lever on the bottom of the mirror. For daylight driving, move the lever to the left; for night driving, to the right. The mirror can be adjusted to accomodate the driver's




height and seat position by moving it on the ball stud or pivot arm in back of the mirror.

Fleetwood inside rear view mirror



Downloaded from www.Manualslib.com manuals search engine


The three-way, inside rear view mirror used on the Fleetwood Sixty Special Sedan and Brougham can be adjusted for three different types of driving conditions. For daylight driving, the lever at the bottom of the mirror should be in the left hand position. For normal night driving the lever should be positioned at the center of the mirror. Move the lever to the right to counteract intense glare.




Remote-control outside mirror

Your Cadillac is equipped with a remote-control outside rear-view mirror on the driver's side of the car. Movement of the handle inside the car allows you to adjust the mirror to suit your requirements. Rotating the mirror head in its support permits additional adjustment so that the view into the mirror is not obstructed.

Downloaded from www.Manualslib.com manuals search engine





SPECIAL FEATURES

There are some special features that are standard on your Cadillac and others are optional at extra cost. These features are designed for your comfort and convenience and to add further to the enjoyment of your 1967 Cadillac.

Operating instructions for these special features are given in this section. Review them carefully, as a complete understanding of their operation will help you derive the utmost satisfaction from their use.

AUTOMATIC CLIMATE CONTROL HEATING AND AIR CONDITIONING

Automatic Climate Control is standard on the Fleetwood Seventy-Five sedan and limousine and optional at extra cost on all other models. This system controls heating and air conditioning automatically to provide the interior temperature selected on the control panel temperature dial.

Downloaded from www.Manualslib.com manuals search engine

The system, being completely automatic, may be set at a comfortable temperature and left with virtually no adjustments required due to outside weather conditions. In cold weather the system will provide heat automatically when engine coolant is warm enough; and when outside temperatures are high, the system will provide air conditioning automatically.

In warm weather, cooled, dehumidified air is discharged from five adjustable outlets—two at each end and one in the center of the instrument panel. On all models except the Fleetwood Seventy-Five sedan and limousine, a separate ventilation feature is provided to admit outside air directly into the passenger compartment through these outlets.

In cool weather, warm air (as high as 90° F.) may be emitted from the five outlets. Each outlet can be rotated to direct air throughout the car. The vanes in the end outlets can be set to direct air flow in any direction by positioning the knob on each outlet in the direction you wish the air to flow. The end outlets can be closed by moving the knobs toward each other. The center outlet can be closed or set to direct air flow up or down by rotating the vaned outlet. Also, one side of the outlet discharges a concentrated stream of air; the other side, when rotated 180°, spreads the air over a wider area.

In cold weather, heated air enters the front passenger compartment through grilles and openings in front of the dash panel. Heated air is delivered to the rear passenger compartment through ducts that extend rearward under the front carpet and seat. Part of the heated air may be directed to the windshield for removing fog or ice.

Individually controlled front and rear systems are used on the Fleetwood Seventy-Five sedan and limousine. Operating instructions for the front system as explained in this section, with the exception of the ventilation feature, also apply to Fleetwood Seventy-Five cars.

The rear system is a completely separate system with a large heater, blower and evaporator assembly mounted in the trunk. Operating instructions for the rear system are explained in Section 3, beginning on page 44.

CONTROLS


The control panel for Automatic Climate Control is located just below the instrument cluster to the right of the ignition switch.

NORMAL OPERATION

1. Set the temperature dial on the control panel to the interior temperature desired.

2. Position horizontal sliding lever at the white triangle above the word "AUTO". This turns the system on, providing 100% outside air at all times and automatically controls heating, air conditioning and blower speeds.

Downloaded from www.Manualslib.com manuals search engine



After initial settings are made, it is recommended that the system be left "ON" at all times for maximum comfort. The air conditioner-heater system will operate automatically whenever the car is started; it will start almost immediately in warm weather, but heater operation in cold weather will be delayed until heat is available from the engine coolant.


Additional settings

Five additional settings of the control lever are provided for use in those instances when extreme weather conditions call for extra or reduced volumes of heated or cooled air, outside air or for air to be directed to the windshield.

The "LO" setting causes the system to operate as in the "AUTO" setting but at a fixed low blower speed, reducing the volume of air.

The "HI" setting causes the system to operate as in the "AUTO" setting but at maximum blower speed, resulting in quicker cool-down in summer and warm-up in winter. Also, it allows the air conditioner to operate on 80% recirculated air for maximum cooling efficiency.

To achieve quicker cool-down when the car has been parked in the hot sun, the end outlets should be positioned so



Downloaded from www.Manualslib.com manuals search engine

they face outboard and upward on a 45° angle and the center outlet positioned upward on a 20° angle. Also, the windows should be lowered for a few minutes to exhaust the hot air.

The "FOG" position should be used when the windshield is fogged over. This causes the system to operate as in the "AUTO" setting but directs air to the windshield to clear off fog.

The "ICE" position provides maximum heated air at MAXIMUM blower speed for melting snow and ice.


In the "FOG" and "ICE" positions, the system will go on as soon as the engine is started regardless of engine coolant temperature as any air flow across the inside of the windshield is helpful in removing fog or ice.

In the "VENT" position outside air is discharged into the passenger compartment through the air conditioning outlets The blower automatically operates at a fixed low speed to provide positive air circulation. The compressor does not operate in this setting.

The Automatic Climate Control system is designed to minimize window fogging. In most cases windows will remain clear whenever the system is "ON", due to inherent dehumidification with normal system operation.

Should the car be driven in mild weather with the Climate Control set to the "OFF" position, light fog may build up on the windows. To remove this fog, it is recommended that the control be set first to the "AUTO" position to take full advantage of the dehumidification characteristics of the system. If additional defogging is still required, the control may then be set to the "FOG" or "ICE" position. Likewise, when operating under similar conditions and it is desired to move the Climate Control from "OFF" to "VENT", it is recommended that the control be moved first to the "AUTO" position to dehumidify the system.

REAR WINDOW DE-FOGGER



Downloaded from www.Manualslib.com manuals search engine

The Cadillac Rear Window De-Fogger is optional at extra cost on all models except the convertible and Fleetwood Seventy-Five sedan and limousine. In operation, the De-Fogger distributes fan-blown air across the rear window to help clear fog or steam for better visibility in humid weather. During winter driving conditions, it helps prevent accumulation of snow or ice on the rear window glass.

The De-Fogger is controlled by a switch located under the top edge of the instrument panel cover on the left side. For "HIGH" fan speed, move switch to the right. For "LOW" speed, move it to the left. The De-Fogger is "OFF" when the switch is in center position.

Tilt and telescope steering wheel

The Tilt and Telescope Steering Wheel (optional at extra cost) permits two separate adjustments of the wheel position for greater comfort, convenience and driving ease. The steering wheel can be tilted to any one of six different positions, and can be moved closer to or farther from the driver over a three-inch range of adjustment. This permits individual selection of the most natural and comfortable position for all driving conditions. Also, on long trips, the steering wheel position can be changed to minimize tension and fatigue. The adjustments are simple, and independent of each other.

The tilt adjustment is achieved by lifting upward on the small lever located on the left side of the steering column below the



turn signal lever. The steering wheel can then be tilted to the desired angle and locked in place by releasing the lever. Moving the locking lever located on top of the steering column above the steering wheel cover to the left permits telescoping; moving the lever to the right locks the wheel. Both the tilt and telescope mechanisms can be changed while driving, but should not be attempted in heavy traffic.

These features also permit maximum ease in entering and leaving the car. The wheel is spring-loaded, so that lifting upward on the small lever automatically raises the wheel to a higher position. Additional clearance can be obtained by unlocking the steering wheel and moving it all the way in.


Downloaded from www.Manualslib.com manuals search engine

The Tilt and Telescope Steering Wheel can be adjusted in conjunction with the seat to provide maximum driving comfort.

CRUISE CONTROL

Cadillac Cruise Control (optional at extra cost) is a speed reminder and automatic speed regulating device controlled by a speed setting dial and a three-position control switch, marked "AUTO", located on the left side of the instrument panel.

To use as a SPEED REMINDER, rotate the dial until desired speed setting, as indicated by the numerals on the dial rim, is lined up with the triangular mark to the left of the dial. Then rotate tabbed control switch forward to first detent position.



This places the control switch in the "ON" position. The Cruise Control will indicate that the selected speed has been reached when back pressure is felt on the accelerator pedal.

The speed reminder feature may also be used under adverse conditions to prevent the driver from unknowingly exceeding the speed at which he wishes to limit himself.

Cruise Control does not interfere with normal accelerator pedal movement up to the selected speed reminder setting. To obtain further acceleration above that speed for passing slower moving cars, press the accelerator pedal through the warning back pressure.

For AUTOMATIC SPEED CONTROL with ignition on, rotate selector dial to 80 MPH. Then rotate control switch forward momentarily to the end of its travel to engage the "AUTO" position. This activates a green light labeled "CRUISE", located on the upper left side of the instrument cluster. Release the control switch and it will return to the "ON" position. Light will remain "ON" indicating system is set for AUTOMATIC SPEED CONTROL. Rotate dial to desired speed setting, accelerate until the selected speed is reached and back pressure is felt on the accelerator pedal. Cruise Control will lock-in and maintain the car speed selected on the dial without foot pressure within the limits of engine performance.

Downloaded from www.Manualslib.com manuals search engine

CAUTION: Do not use the automatic feature when conditions do not warrant maintaining a constant speed, such as in moderate to heavy traffic, or on winding or slippery roads. Under these conditions, the system should be turned off. The speed reminder feature can be retained if the switch is reset to the "ON" position.

When the unit is in automatic control, car speed can be changed by slowly rotating the dial forward to increase speed, or backward to decrease speed.

CAUTION: When changing speed during automatic control, the dial acts as a hand throttle. Always rotate dial slowly to prevent sudden acceleration.

In automatic control also, car speed can be increased by pressing the accelerator pedal through the warning back pressure. The car will return to set speed when foot is removed from accelerator pedal. The throttle control is disengaged when the brake pedal is depressed. To re-engage, accelerate until back pressure is felt. The unit will again engage automatically. It is not necessary to rotate control switch forward to re-engage automatic control.

To change from automatic control to speed reminder operation, rotate the control switch to "OFF" and reset to "ON".


To disengage automatic control or speed reminder operation, rotate control switch rearward to its stop, which is the "OFF" position. The automatic control is completely disengaged whenever the ignition switch is turned off.

With the unit "OFF", no back pressure will be felt at any speed and the indicator light will not glow. When automatic control is disengaged, it is necessary to move the control switch forward momentarily to the end of its travel to re-engage.

GUIDE-MATIC POWER HEADLIGHT CONTROL

The Guide-Matic Power Headlight Control (optional at extra cost) automatically switches the car's headlights from high to low beam when another vehicle approaches from the opposite direction, and returns them to high beam again when conditions permit. When driving behind another car at night the headlights may switch from high to low beam, as Power Headlight Control is sensitive to the red reflection of the tail lights of the car ahead.

The foot switch is a special dimmer-override type that provides either automatic or lower beam control of the headlights. It also contains an override feature for obtaining an overriding high beam when in automatic position, if desired.



Downloaded from www.Manualslib.com manuals search engine


A slight downward pressure on top of the switch provides high beam, regardless of the amount of outside light. This arrangement permits signaling an approaching driver if he fails to switch to low beam, and also provides a simple check for the automatic position of the foot switch.

A sensitivity control ring located directly behind the headlight control knob permits adjusting the sensitivity of the Power Headlight Control. This ring is identified by the words "AUTO DIMMING" above the ring. Centering the control ring pointer between "OFF" and "FAR" provides normal sensitivity. Rotating the control ring clockwise toward the word "FAR" causes the lights to dim sooner; rotating it counterclockwise delays the dimming action.

For conventional operation of headlight dimming, rotate the sensitivity control ring counterclockwise to the "OFF" position.

TWILIGHT

SENTINEL



Cadillac Twilight Sentinel (optional at extra cost) automatically turns on the car's driving lights as darkness approaches, when the ignition switch is "ON". The unit also turns the lights off as daylight approaches. The unit is designed so that the car's headlights will not turn on when driving short distances under viaducts, trees, etc., or turn off when passing under bright lights.

The Twilight Sentinel control lever is located behind the headlight control knob (on cars equipped with Guide-Matic Power Headlight Control, the control lever is located behind the sensitivity control ring).

For automatic operation, move the control lever counterclockwise away from the "OFF" position. Leave the headlight control knob all the way in. The car's lights will automatically turn "ON" as darkness approaches and "OFF" as daylight approaches. If the driver desires to turn the car's headlights on during daylight hours, which may be necessary to identify the car in such conditions as fog, rain or when driving through a tunnel, he may do so by pulling out the headlight control knob.

An adjustable time delay feature permits the lights to remain "ON" after the ignition switch is turned "OFF" to provide a path of light for driver and passengers as they leave the car. Additional side lighting can be obtained by activating a cornering light with the turn signal lever. For TIME DELAY


Downloaded from www.Manualslib.com manuals search engine

ACTION, move the control lever between "OFF" and "MAX" to the position that provides the desired time delay. Maximum time delay is approximately 90 seconds.

For manual operation of the headlights, move the control lever clockwise to the "OFF" position. This permits conventional operation of lights with the headlight control knob.

RADIOS

The Cadillac AM, AM-FM and AM-FM Stereo radios (all optional at extra cost) are fully transistorized. The AM-FM Stereo radio is available on all model cars except the Fleetwood Seventy-Five sedan and limousine. The following instructions on the use of the AM-FM radio and operation of the controls also apply to the AM-FM Stereo radio. The features that pertain exclusively to the AM-FM Stereo radio are explained in this section beginning on page 31.



The radio is located in the center of the instrument panel. Two control knobs are located to the left of the radio dial. Five push buttons are provided below the dial and a selector bar is provided above the dial.

The left control knob is the "ON," "OFF" and "VOLUME" control. The ring behind the left knob controls the tone. Turned to the left, bass tones predominate—turned to the right, treble tones are accentuated. Balanced tones can be obtained by centralizing the ring in its detent position.

Pushing in on the right knob raises the antenna; pulling out lowers the antenna. The ring behind the right knob controls the operation of the front and rear speakers. Counterclockwise rotation accentuates the rear speaker. Clockwise movement accentuates the front speaker. Balanced sound can be obtained by centralizing the ring.

Manual tuning is accomplished by turning the right control knob to set the pointer at the desired frequency on the dial.

The five push buttons can be pre-set to favorite stations. Tune in the desired station nearest the left end of the dial with the manual tuner knob. Fine tune until best reception is obtained. Pull the first button straight out, then push the button all the way in. The first button will now select that station repeatedly. Continue this process for setting the remaining buttons on other stations.

Downloaded from www.Manualslib.com manuals search engine

Push buttons on the AM-FM radio may be set on AM stations, FM stations, or a combination of both.

The selector bar on the AM radio only permits automatic search tuning. Press the bar and immediately release it. The tuner will then stop at the next station on the dial. A three-position sensitivity control for this automatic tuning is located in the center below the bar. Moving this control to the left allows the tuner to stop only on more powerful stations. In the middle position, stations of slightly lower power will be received in addition to stronger stations. To obtain maximum sensitivity, and bring in weaker stations, move control to the right.

The selector bar above the dial is used on the AM-FM radio to select the desired frequency band. Pressing the left end selects the AM band and pressing the right end, the FM band. The letters "AM" or "FM" will light on the dial to show the frequency band selected.

To obtain best FM reception, the antenna tip should be approximately 30 inches above the fender.

The FM receiver is normally free from most atmospheric and man-made static. The effective range of FM transmitters, however, is usually limited to no more than line-of-sight from the transmitter—or about twenty miles. Moving out of this effective range will produce a "flutter" or a series of noise bursts in the signal. Ignition interference from adjacent vehicles may also be encountered.

Retuning may be necessary when reception becomes slightly noisy while driving through weak signal areas such as the center of a large city. The interference can be quieted by tuning the tone control for more bass, and by shifting the speaker volume to favor the rear seat. When it is not possible to eliminate these effects by retuning, try switching to a stronger FM station or to the AM band.

AM-FM Stereo radio

The Cadillac AM-FM Stereo radio provides a selection of AM, FM monaural or FM stereo reception. Operating instructions are the same as those previously described for the conventional type AM-FM radio.

The AM-FM Stereo radio is pre-set at the factory for balance



Downloaded from www.Manualslib.com manuals search engine

and correct separation of sound and requires no manual adjustment.

Four separate speakers, two in the front and two in the rear, are used in conjunction with the AM-FM Stereo radio to provide rich stereo sound for front and rear seat passengers. The front speakers are located at each end of the instrument panel top cover and the rear speakers are in the left and right corners of the rear parcel shelf. Rear speakers on convertible styles are located behind the back seat on the lower left and right side. Care should be taken not to place objects over the front or rear speakers as this would block the sound.

Stereophonic reception is possible only when there is stereophonic transmission. The letters "STEREO" will light on the center of the dial when the radio is tuned to an FM stereo station. This does not always mean that you are receiving stereo, as the station may not be transmitting stereo at that particular time. Familiarizing yourself with the frequencies of your local FM stereo stations will assist you in station selection.

Front seats—Manual adjustment


If your car is equipped with a manually operated front seat, it can be adjusted forward or rearward. Merely move the lever forward on the driver's side of the seat and adjust to the most comfortable driving position. Then release the lever to lock the seat in this position.

Electrically operated front seats

The controls for electrically operated front seats (optional on some models at extra cost) are mounted on the side of the seat cushion panel to the left of the driver.

For forward and backward adjustment of the two-way electrically operated seat, move the switch lever in the direction of the desired seat movement.

Adjust the six-way electrically operated seat as follows: Move the center switch lever forward or backward to control the horizontal fore and aft movement of the seat. Move the center switch lever up or down to control the vertical movement of the entire seat. Move the front switch lever to raise or lower the front of the seat and to tilt the seat-back accord-



Downloaded from www.Manualslib.com manuals search engine

ingly. Move the rear switch lever to raise or lower the rear of the seat and to tilt the seat-back accordingly.

Additional seat adjustments

Additional rearward seat positioning can be made on all bench type seats by having your Authorized Cadillac Dealer reposition the seat one inch rearward at the attachment to the floor.

If you desire, the two-way electrically operated seat may be lowered by having your dealer remove the shims between seat supports and the floor.

Coupe seat-back lock

The forward folding front seat-backs on all coupe styles incorporate an automatic lock as an additional safety feature to prevent them from tilting forward in cases of sudden stops.



An individual release button is located on the upper portion of the seat side panel. To fold the seat forward, depress the button to unlock the seat-back. The seat-back locks into place automatically when in the upright position.

Bucket seat controls

On cars equipped with bucket seats, two-way electrical controls are provided for fore and aft movement of each seat. The controls are located on the lower outboard side of the seat cushion panels.


Four-way movement of the driver's seat only is optional at extra cost on all cars with bucket seats.

Reclining bucket seat and head restraints

A reclining feature for the front passenger's seat, including an adjustable head restraint for both the driver and passenger seats is optional at extra cost on models with bucket seats. Head restraints only are also available as an extra cost option on all models.

The reclining feature provides manual adjustment of the seat-back so that it can be tilted to a 30° reclining position. The release lever is located on the right side of the seat cushion. To tilt the seat-back, lift the release lever and push the seat-back rearward to the desired position. Release the lever to lock the seat in place. To raise the seat-back, lift the release lever and lean forward to allow the assist spring to move the

Downloaded from www.Manualslib.com manuals search engine



seat. Release the lever to lock the seat in place. The seat-back can be raised from reclined position by hand for the exit of rear seat passengers.

Head restraints can be adjusted to different heights by pulling up or pushing down by hand. Detents provide positive head restraint location. Head restraints should be adjusted to contact the center of the head when moved straight back. To remove the head restraint, first raise head restraint to full up position. Where the head restraint support bars enter the seat back, depress the wire retaining spring sufficiently to allow head restraint and support bars to be removed from the seat back. On bench-type seats, raise the head restraint and facing toward front of car, move it slightly to the right to remove.

Seat belts

Seat belts provide added security and comfort. Front and rear seat belts, factory installed, are standard equipment on all models. An additional front or rear seat belt for a third passenger, is optional at extra cost. Proper usage and care of these belts will provide added security to driver and passengers in case of sudden, unexpected stops.


After the front seat has been positioned to the satisfaction of the driver, grasp the buckle end and the flat metal "eye" end of your individual belt assembly and position the belt across the pelvic area as low on the body as possible (never use the same seat belt for more than one person at any given time). Insert the metal eye into the open end of the buckle until an audible snap is heard. Make sure the connection is secure and adjust the belt firmly by pulling on the end of the belt protruding from the buckle. Pull retractor half of the belt to a solid stop to make sure that the belt webbing is

Downloaded from www.Manualslib.com manuals search engine

completely unwound from the retractor drum, then connect the belt and make the necessary adjustments at the buckle for proper fit. Avoid wearing a seat belt loosely or with slack in the system, or with the webbing wound around the retractor drum.

SHOULDER BELTS

All Cadillacs are equipped with shoulder belt anchors built into the vehicle. Optional shoulder belts are available for the driver and right front seat passenger. *Shoulder belts must* always be worn in conjunction with seat belts and are fastened with individual buckles in the same manner as seat belts. Shoulder belts should be tightened only to the point where controls and switches can be easily reached without restriction from the belt. The use of shoulder belts is not recommended for children under 6 years old. Shoulder belts not in use must be anchored by inserting buckle into retainer to prevent buckle end from swinging around.




RELEASING BELTS—To release the belts, simply depress the button located in the center of the buckle.

CARE OF BELTS—Keep belts clean and dry. Clean with a mild soap solution and lukewarm water. Keep sharp edges and damaging objects away from belts. Periodically inspect belts, buckles, retractors, and anchors for damage that could materially lessen the effectiveness of the belt installation and repair or replace the questionable parts. Do not bleach or dye belts as this may cause severe loss of strength.

POWER WINDOWS

Master controls for the electrically operated windows (optional on some models at extra cost) are located forward of the left front door handle. The control switches are positioned to



Downloaded from www.Manualslib.com manuals search engine

correspond with the windows they control: the left front switch for the left front window, etc.

There are individual controls at each window. The control for the right front window is located on the right door armrest. Controls for the rear door windows are on the rear doors.

The rear quarter windows on coupe styles are individually controlled by switches located on the rear armrests.

Window lock-out switch

A window lock-out switch is standard on all cars equipped with power windows except the Fleetwood Seventy-Five Limousine. The window lock-out switch is located forward of the power window master controls on the driver's door. This switch has three positions marked "EMERG," "NORMAL," and "LOCK".

In the "NORMAL" position with the ignition "ON," all windows may be operated by the master switch or each individual switch. To prevent passengers from operating any windows, as in the case with small children in the car, place the switch in the "LOCK" position. Only the master switch will remain operative.

The "EMERG" (emergency) position permits energizing the master switches with the ignition "OFF," but only while it is held in the "EMERG" position. This will permit lowering or closing the windows without turning the ignition key "ON".

All window switches, including the master switch, are in operative in the "NORMAL" or "LOCK" position with th ignition "OFF."

Power vent windows

Electrically operated power vent windows are standard o some models and optional at extra cost on other models. Maste control switches for both front vent windows are located o the left armrest. There is also a switch for the right-hand ven window on the right armrest.

On the Fleetwood Sixty Special Sedan and Brougham master switches for both rear vent windows are located on th left front door armrest. There are also individual controls o the armrests of the rear doors.

LOCKS

Door locks

Cadillac door lock design contributes to passenger safety an the security of your car and its contents. Always keep th doors locked when driving as well as when leaving the ca unattended.

Manual door locks

Each door on your Cadillac can be locked from the inside b pushing down the door lock button. Doors may also be locke from the outside with this button by pushing the button dow while the door is open, and then holding the door handl

Downloaded from www.Manualslib.com manuals search engine

correspond with the windows they control: the left front switch for the left front window, etc.

There are individual controls at each window. The control for the right front window is located on the right door armrest. Controls for the rear door windows are on the rear doors.

The rear quarter windows on coupe styles are individually controlled by switches located on the rear armrests.

Window lock-out switch

A window lock-out switch is standard on all cars equipped with power windows except the Fleetwood Seventy-Five Limousine. The window lock-out switch is located forward of the power window master controls on the driver's door. This switch has three positions marked "EMERG," "NORMAL," and "LOCK".

In the "NORMAL" position with the ignition "ON," all windows may be operated by the master switch or each individual switch. To prevent passengers from operating any windows, as in the case with small children in the car, place the switch in the "LOCK" position. Only the master switch will remain operative.

The "EMERG" (emergency) position permits energizing the master switches with the ignition "OFF," but only while it is held in the "EMERG" position. This will permit lowering or closing the windows without turning the ignition key "ON". All window switches, including the master switch, are inoperative in the "NORMAL" or "LOCK" position with the ignition "OFF."

Power vent windows

Electrically operated power vent windows are standard on some models and optional at extra cost on other models. Master control switches for both front vent windows are located on the left armrest. There is also a switch for the right-hand vent window on the right armrest.

On the Fleetwood Sixty Special Sedan and Brougham, master switches for both rear vent windows are located on the left front door armrest. There are also individual controls on the armrests of the rear doors.

LOCKS

Door locks

Cadillac door lock design contributes to passenger safety and the security of your car and its contents. Always keep the doors locked when driving as well as when leaving the car unattended.

Manual door locks


Each door on your Cadillac can be locked from the inside by pushing down the door lock button. Doors may also be locked from the outside with this button by pushing the button down while the door is open, and then holding the door handle

Downloaded from www.Manualslib.com manuals search engine

opening button all the way in while closing the door. All door locks are set so that both inside and outside door handles are inoperative when the lock button is depressed. To open any door, lift the lock button before operating the door handle.

Power Door Locks


If your car is equipped with automatically actuated power door locks (optional at extra cost), all doors may be locked or unlocked by operating the switch located on either front door. Push the switch down to lock all doors, and lift up on the switch to unlock the doors. The automatic locking mechanism does not, at any time, interfere with manual operation of any door lock button. The doors will not unlock or open with the inside door handle when the lock button is depressed, but can be unlocked individually by lifting the lock button.



On the Fleetwood Seventy-Five Limousine, the door lock switch located on the left front door operates only to lock the doors. An additional door lock switch is provided on the right rear door on limousine styles for the convenience of rear seat passengers. This switch will lock and unlock all doors in the conventional manner.

Hood latch

The hood latch is operated in two steps by means of a lever. The release lever is accessible between the grille and hood panel, just to the right of center when viewed from front of car. Apply pressure to this lever, forcing it upward. The hood will release but will be prevented from opening further by a secondary latch. Further movement of the lever will release the secondary latch, allowing the hood to be raised. To close



Downloaded from www.Manualslib.com manuals search engine


hood, pull hood down gradually until it will drop of its own weight. Always check to make sure hood is properly secured.

Luggage compartment

The lid on the luggage compartment is counterbalanced for easy opening. It has a key-lock release. To open, insert the key with the rounded head into the lock, which is located behind the crest, turn key in a clockwise direction to release lid. An interior light goes on when lid is raised. To close, pull to a position six or eight inches from closing, remove key and push lid firmly downward. This automatically locks luggage compartment.

Remote-control trunk lock

Cadillac's Remote-Control Trunk Lock (available on some models at extra cost) permits the driver to unlock and slightly raise the trunk lid simply by pushing a button located in the glove box. A red warning light on the left side of the instrument cluster labeled "Trunk" will glow when the trunk lid is unlocked. When the trunk lid is lowered, a latching mechanism pulls the lid firmly closed and locks it. The trunk lid can also be opened in the normal manner with a key from outside the car. To prevent damage to the closing mechanism, avoid slamming the lid when closing. Once unlocked, the lid must be fully opened before the pull-down and locking can be accomplished.



To help prevent illegal entry into the trunk, keep the glove box locked when leaving the car unattended.

AUTOMATIC LEVEL CONTROL

Automatic Level Control maintains the rear height of the car regardless of load in rear passenger compartment or luggage compartment. The leveling system responds to actual changes in load of passengers or luggage, and will compensate for loads up to 500 pounds. A level car improves appearance as well as ride, and reduces "bottoming" on severe bumps or bumper scraping on steep ramps or driveways.

Automatic Level Control is standard on the Fleetwood Sixty Special Sedan and Brougham, and Fleetwood Seventy-Fives, and optional at extra cost on all other models.

Downloaded from www.Manualslib.com manuals search engine

CONTROLLED DIFFERENTIAL


The Controlled Differential (optional at extra cost) provides additional traction on snow, ice, mud, sand and gravel, particularly when one rear wheel is on a surface providing poor traction.

During normal driving and cornering, the controlled unit functions as a standard differential. When one wheel encounters a slippery surface, however, the Controlled Differential directs driving force to the rear wheel having the better traction.

CAUTION: On cars equipped with a Controlled Differential, do not run the engine for any reason with one rear wheel off the ground, as the car may drive through the rear wheel remaining on the ground.

CONVERTIBLE TOP

The convertible top can be raised or lowered with the rear quarter windows either open or closed.



To lower the top, stop the car and rotate the locking handle inboard on each side roof rail until the lock hook lever is disengaged from the striker on the windshield header.

The convertible top control switch is located underneath the left side of the instrument panel upper cover. Move switch lever to the right (under the letters "DN") and hold lever in this position until top is fully lowered.

To install top boot, place boot in position over folded top and engage boot fasteners to the studs along the body molding and on the rear quarter trim. Engage fasteners on front of boot to studs on rear seat back panel. Press down on forward edge of boot to secure hook and pile fastener.

To raise the top, always stop the car first. Then turn down sun visors, and unsnap top boot. Move switch lever to the left (under the word "UP") until top is fully raised and guide-studs on lock assemblies are engaged in striker holes on windshield header. Rotate each locking handle outboard until lock hook lever is fully engaged with striker on windshield header and handle is parallel with side roof rail.


NOTE: Be sure top is securely locked to windshield header before starting car in motion.

For detailed information on the operation and care of the convertible top, refer to the Convertible Top booklet in the glove compartment of all convertibles.

Downloaded from www.Manualslib.com manuals search engine

FOLD-DOWN UTILITY TRAYS

Two fold-down utility trays are provided as standard equipment on the Fleetwood Brougham Sedan for the convenience of rear seat passengers. The trays are hinge mounted and recessed in a panel on the back of the front seat. Depress the release button in the center of the tray to lower it. When the trays are folded down, individual lights in the recess on the seat back illuminate the top surface of the trays. A small storage compartment is provided behind each tray. To close tray, lift up on tray, position it in recess on seat back and snap it shut.




FOOT RESTS

Carpeted foot rests are provided as standard equipment in the rear passenger compartment on the Fleetwood Brougham Sedan. The foot rests are hinged to the back of the front seat near the floor, and may be folded up when not in use.

Downloaded from www.Manualslib.com manuals search engine



FLEETWOOD SEVENTY-FIVE SEDAN AND LIMOUSINE



GENERAL

The Cadillac Fleetwood Seventy-Five represents the finest in formal motoring. Both the Sedan and Limousine styles embody many fine features not found in other models.

An extraordinary complement of powered conveniences accents the luxury of the Fleetwood Seventy-Five. Brakes and steering, window regulators, and front seats are power assisted. A remarkably smooth Turbo Hydra-matic transmission transfers an effortless flow of power. And the long 149.75 inch wheelbase and more than twenty foot over-all length provide exceptional riding comfort and spaciousness.

Additional information given here covers the operating instructions for items exclusive to the Fleetwood Seventy-Five Sedan and Limousine. A complete understanding of these special features will add further to the enjoyment of this majestic 1967 Cadillac.

Downloaded from www.Manualslib.com manuals search engine

Instruments

The instructions on use of the ignition switch and the various instruments and accessories, as explained in Sections 1 and 2, also apply to the Fleetwood Seventy-Five sedan and limousine.


Courtesy lights

Fleetwood Seventy-Five cars are equipped with courtesy lights that illuminate the interior of the car when any door is opened. When the front doors or all doors are closed, full counter-clockwise position of the headlight control knob turns on the front courtesy lights.


When either rear door is opened, the front courtesy lights, front door warning lights, rear door courtesy lights and the reading lights in the air conditioning ceiling outlets operate. When either front door is opened on the sedan style, the front courtesy lights, front door warning lights and rear door courtesy lights operate. Only the front courtesy lights and front door warning lights operate when either front door is opened on the limousine style.

Manual switches for the reading lights are located on the rear quarter trim panels above the armrests.

On Limousine styles, a front compartment map light, located in the headlining between the sun visors, may be operated manually with the switch integral with the light.



Power windows



Downloaded from www.Manualslib.com manuals search engine

Master controls for the electrically operated windows are located forward of the left front door handle. The control switches are positioned to correspond with the windows they control; the left front switch for the left front vent window, etc. On Limousine styles, master control switches for the rear door windows at the driver's door operate only to close the windows. There are also switches for the right front vent window and door window on the right front door.


Operation of the window lock-out switch as explained in Section 2 also applies to the Fleetwood Seventy-Five sedan. The window lock-out switch feature is not used on Limousine styles.

Controls for the rear door windows are located on the rear quarter trim panel above each armrest. Both rear door windows may be operated from either side of car.

On Limousine styles, individual controls are mounted next to the rear door window switches for operation of the partition window between the front and rear compartments.

Ash trays and lighters

Ash trays and lighters are located on the rear door armrests. Individual ash trays are provided on the back of the front seat for the convenience of auxiliary-seat passengers. The ash tray door can be opened by pulling out on the handle.



Automatic climate control heating and air conditioning

The Automatic Climate Control system is provided as standard equipment on the 1967 Cadillac Fleetwood Seventy-Five sedan and limousine. Automatic Climate Control automatically controls the Heating and Air Conditioning system to provide the interior temperature selected on the control panel temperature dial.


Individually controlled front and rear systems are used on Fleetwood Seventy-Five cars. Operating instructions for the front system, as explained in Section 2, also apply to these vehicles, except that the ventilation feature is not used on these cars. The rear system is a completely separate system with a large heater, blower and evaporator assembly mounted in the trunk.


Downloaded from www.Manualslib.com manuals search engine

Rear system controls

The controls for the rear system, consisting of an on-off switch and a temperature dial, are located underneath a hinged cover in the right rear armrest. The rear system may be turned on and off with the switch, and temperature may be controlled by the temperature dial. To reduce or increase the temperature, rotate the temperature dial to the interior temperature desired.

Since the system is completely automatic, it may be set at a comfortable temperature setting and left on with virtually no further adjustments required due to outside weather conditions. In cold weather the heater will automatically turn on when engine water is warm enough. When outside temperatures are high, the system will automatically provide air conditioning.






In cool weather, warm air is delivered from the trunk unit through ducts leading into the rear doors, then into the rear passenger compartment through grilles located beneath the rear door armrests.

In warm weather, cooled, dehumidified air is delivered through ducts in the roof and out of overhead grilles into the rear passenger compartment. The outlet grilles are equipped with a number of small openings for providing diffused cooled air. Each outlet is equipped with a hinged door that may be opened to direct air toward the rear passengers.

Downloaded from www.Manualslib.com manuals search engine




With this system, comfort is automatically maintained to the individual requirements of the front and rear compartment passengers regardless of whether the division glass (on cars so equipped) is up or down, and despite car speed and variations in outside temperature.

Rear comparment radio controls

Rear seat radio controls are optional at extra cost on Fleetwood Seventy-Five cars equipped with a signal seeking selector AM radio. The controls, consisting of an on-off volume control, a sensitivity control and a station selector button, are located underneath a hinged cover in the right rear armrest just forward of the air conditioning controls.

The on-off volume control knob turns the radio on and off or transfers control to the rear seat, if the radio is already on, and



regulates the volume. When the radio is being operated by remote control, the station selector button glows red. To select stations, momentarily depress the station selector button until the desired program is received. The sensitivity control is below the on-off knob. Rotating it counterclockwise will permit the tuner to stop only on the more powerful stations. In the middle position, stations of slightly lower power will also be received. For maximum sensitivity, rotate the control clockwise to bring in the weaker stations.


With the rear seat radio controls on, the driver may turn his speaker on or off with the ring behind the right control knob, and tune the radio manually or with the push buttons. The radio cannot be operated normally from the front seat again until the rear controls are turned off.

Downloaded from www.Manualslib.com manuals search engine



SERVICE FOR YOUR CAR





AUTHORIZED CADILLAC SERVICE

Warranty

When purchased new, your Cadillac is covered by the Manufacturer's New Vehicle Warranty and the Policy on Cadillac Owner Service, both of which are contained in your Owner Protection Plan booklet given to you by your Authorized Cadillac Dealer at the time of delivery.

Downloaded from www.Manualslib.com manuals search engine

Owner Protection Plan Booklet

It is important that the Owner Protection Plan booklet be kept in the glove compartment of your car at all times as it must be presented to your dealer when warranty service is required.

The Protect-O-Plate on the inside back cover of your Owner Protection Plan booklet contains important vehicle data pertaining to your Cadillac. Your dealer may insert your name and address and the delivery date of your new car to provide complete identification. The identification information on the Protect-O-Plate will allow him to proceed with your service requirements with the least amount of inconvenience to you.

Owner responsibility

Your new Cadillac, like all fine machinery, requires regular care to maintain its peak performance and preserve its showroom appearance. Periodic maintenance assures you of many miles of carefree driving, and protects your investment. A recommended maintenance schedule is included in the Owner Protection Plan booklet.

Cadillac service

Authorized Cadillac Dealers are well qualified to assist you in the maintenance of your car because their service personnel have the advantages of:

1. Specialized Cadillac training at General Motors Training Centers.
2. Special tools and equipment designed for Cadillac products.
3. Genuine parts that are engineered for your Cadillac.
4. Factory product information and factory-dealer cooperation that contributes to efficient service and the latest in mechanical procedures.

For the best in Cadillac Guardian Maintenance service, take your Cadillac to an Authorized Cadillac Dealer.

Fuel requirements

Your Cadillac is designed to operate efficiently on "Premium" grade fuels commonly sold in the United States and Canada. Use of a fuel that is too low in anti-knock quality will result in "spark knock." Since the anti-knock quality of all premium grade gasolines is not the same, and factors such as altitude, terrain and air temperature affect operating efficiency, knocking may result even though you are using the grade of fuel recommended for your engine. If persistent knocking is encountered, it may be necessary to change to a higher grade of gasoline and, if knocking continues, consult your Authorized Cadillac Dealer.

In any case, continuous or excessive knocking may result in engine damage and constitutes misuse of the engine for which the Cadillac Motor Car Division is not responsible under terms of the Manufacturer's New Vehicle Warranty.

Downloaded from www.Manualslib.com manuals search engine

Operation in Foreign Countries


If you plan to drive your car outside the continental limits of the United States or Canada, there is a possibility that the best fuels available are so low in anti-knock quality that excessive knocking and serious engine damage may result from their use. To minimize this possibility, write to the Cadillac Motor Car Division, Service Department, Detroit, Michigan giving;

- The car's vehicle identification number (obtain from car registration or title).
- The country or countries in which you plan to travel.

You will be furnished details of adjustments or modifications which should be made to your engine at your Cadillac dealership prior to your departure. Failure to make the necessary changes to your car and subsequent operation under conditions of continuous or excessive knocking constitutes misuse of the engine for which the Cadillac Motor Car Division is not responsible under the terms of the Manufacturer's New Vehicle Warranty. After arriving in a foreign country, contact the nearest authorized General Motors Dealer for brand names of the best fuels available and advice as to where they may be purchased.

Gasoline tank

Capacity of the fuel tank is approximately 26 gallons on all



styles except the Commercial Chassis, which has a 20 gallon capacity fuel tank. The gasoline filler cap is located behind the rear license plate. To reach the cap, pull out on the top of the license plate.

CAUTION: Gasoline is extremely flammable and highly explosive under certain conditions. Always stop the engine and do not smoke or allow open flames or sparks near the vehicle when refueling. If gasoline fumes are noticed while driving, the cause should be determined and corrected without delay.

Downloaded from www.Manualslib.com manuals search engine

Positive Crankcase Ventilation (P.C.V.)

The positive Crankcase Ventilation system, which is standard equipment on your vehicle, helps control air pollution caused by crankcase blow-by gases. The P.C.V. system connects the crankcase and intake manifold of the engine and exhaust blow-by gases are returned through this system to the combustion chamber where they are reburned. Periodic inspection and required servicing of your P.C.V. system assures a cleaner, better-performing, longer-lasting engine and almost 100% elimination of any air pollution caused by crankcase blow-by gases. A plugged P.C.V. system can cause condensation of blow-by gases in the crankcase, resulting in the formation of acids, sludge build-up and oil dilution. Every 12 months or 12,000 miles, whichever occurs first, the P.C.V. valve should be replaced. Also, all hoses, fittings and the inlet air filter should be inspected, cleaned and replaced, if necessary.

NOTE: If the positive crankcase ventilator valve should become clogged, the engine idle will be adversely affected. Therefore, if the engine idle becomes too slow or rough, the ventilator valve should be checked before any carburetor adjustments are made to compensate for the trouble.

Air Injection Reactor (A.I.R.)

The Air Injection Reactor System is an exhaust emission control system installed on all domestic 1967 General Motors cars (and some trucks) destined for initial registration in the State of California. This air pollution control system is entirely separate from the Positive Crankcase Ventilation System. It is designed to reduce air pollution caused by engine exhaust tailpipe gases by "treating" the unburned hydrocarbons and carbon monoxide as they are expelled from the combustion chamber into the exhaust manifold. A sealed bearing pump, driven by the engine, compresses, distributes and injects clean filtered air at the exhaust port of each cylinder. Here it combines with the unburned hydrocarbons and carbon monoxide at high temperatures in a chemical reaction, producing a "treated" exhaust that is below the maximum allowable level for air pollution from this source. This does not reduce the danger of inhaling any concentration of carbon monoxide in a confined area. See Page 62 for carbon monoxide warning.

The A.I.R. pump filter should be serviced every 12 months or 12,000 miles, whichever occurs first, by removing the filter element, washing in kerosene, dipping in SAE 10W-30 oil, and squeezing to remove excess oil.

Check condition and adjustment of pump pulley belt annually. Clean and oil metal gauze strainer, located on wall of carburetor air cleaner at time of engine oil change.

Also, the annual engine tune-up recommended for normal engine efficiency, operation, and performance is important for the A.I.R. system's continued effectiveness.

Downloaded from www.Manualslib.com manuals search engine

ENGINE OIL RECOMMENDATIONS

High quality engine oils are available at your Cadillac dealer and at many service stations. It is recommended that you use an oil which, according to the label on the can, is: (1) intended for service MS, and (2) passes car makers' tests or meets General Motors Standard GM-4745M. Oils conforming to these types contain detergent additives.

If higher detergency is required to reduce varnish and sludge formation, a thoroughly tested and approved concentrate—"High Detergency Concentrate"—is available at your Cadillac Dealer who is qualified to advise you regarding its use. The use of "break-in" oils, "tune-up" compounds, "friction-reducing" compounds, etc. in your Cadillac engine are specifically not recommended.

Checking oil level

Engine oil should be maintained at the proper level. The best time to check it is before operating the engine or as the last step in a fuel stop. This will allow the normal oil accumulation in the engine to drain back in the crankcase. To check the level, remove the oil dipstick, wipe it clean and reinsert it for an accurate reading. The oil dipstick is marked "Add 1 Qt." and "FULL". The oil level should be maintained in the safety margin, neither going above the "FULL" line nor below the "Add 1 Qt." line, Reseat the dipstick firmly after taking the reading.

Engine oil-filler cap

A ventilated oil-filler cap with a metal gauze filter is used on all cars except those delivered in the State of California. The filter must be cleaned in solvent and re-oiled with engine oil whenever the engine oil is changed (more often under dusty conditions). Caution: do not use a non-ventilated cap in place of this ventilated cap as engine damage may result.

Oil change interval

Change engine oil EVERY 60 DAYS even if less than 6,000 miles have been driven. If more than six thousand miles are driven in a 60-day period, change oil every six thousand miles. This interval applies to the initial change as well as subsequent oil changes. An MS oil, that meets General Motors Standards GM-4745M, was installed in your engine at the factory. It is not necessary to drain this original factory installed oil prior to the recommended normal change period. However, the oil level should be checked more frequently during the break-in period since somewhat higher oil consumption is normal until piston rings become seated.

Certain driving conditions, such as dust storms and frequent driving on dusty roads, necessitates more frequent oil changes. Your Cadillac Dealer is qualified to advise you.

Downloaded from www.Manualslib.com manuals search engine

Anticipated Lowest Temperatures	Use SAE Viscosity Number	Change Your Oil
Above Freezing (+32° F.)	SAE 20W SAE 10W-30	Every 60 days, but never to exceed 6,000 miles.
Below Freezing (+32° F.) and above 0° F.	SAE 10W SAE 10W-30	
Below 0° F.	SAE 5W SAE 5W-20	

ENGINE OIL CHANGE AND VISCOSITY RECOMMENDATIONS

The above chart will serve as a guide in selecting the proper oil viscosity. The proper oil viscosity helps assure good cold starting characteristics by reducing friction, thus increasing cranking speed.

NOTE: When changing oil during the Fall and Winter seasons, consider the lowest anticipated temperature for the next 60 days. If the temperature is expected to be occasionally below 0°F., 10W oil is recommended. Where the temperature is frequently below zero, 5W or 5W-20 oil is recommended. SAE 5W oil is not recommended for sustained high speed driving.

Oil filter replacement


A full-flow type oil filter is used on the Cadillac engine. It is recommended that it be replaced at the engine oil change nearest a 6,000 mile interval or every six months, whichever occurs first. The filter change should be performed with an oil change.

ENGINE OIL

Your Cadillac engine requires four quarts of oil on a refill after the crankcase has been drained. One additional quart is required when the oil filter is changed. It is normal to add some oil before the drain period. Requirements will vary, depending on the type of driving you do, but the addition of one quart each 800 to 1,000 miles would not be considered excessive.

Downloaded from www.Manualslib.com manuals search engine

ENGINE COOLING



The cooling system is designed to maintain efficient engine operating temperatures. Check coolant level at each engine oil change to make certain proper level is maintained. Coolant level with engine cold, at room temperature, should be three inches below bottom of filler neck. Coolant level with engine hot, at normal operating temperature, should be one inch below bottom of filler neck. Do not overfill. Proper levels are shown on label below radiator filler cap. Each fall inspect the system for leaks and for adequate freeze protection. Refer to page 53 for the capacity of your car's cooling system.

Caution

When the engine is at normal operating temperature or above, the internal pressure built up in the cooling system will blow out scalding fluid and vapors if the radiator cap is removed. To prevent loss of coolant and to avoid the danger of being burned, the coolant level should be checked or coolant added only when the engine is cool. If the cap must be removed when the engine is hot, place a cloth over the cap and rotate the cap slowly counterclockwise to first stop and allow pressure to escape completely. Then turn cap again slowly counterclockwise to remove.

WARNING: Radiator cap must be tight when re-installed. Make certain red stripe on cap lines up with red stripe on instruction label on radiator cradle.

The temperature gage can sometimes register "H" (Hot) under severe operating conditions. However, this is not necessarily cause for alarm unless accompanied by a buzzing noise from the radiator cap or by loss of coolant by boiling.

CAUTION: If gage indicates above-normal temperature, make certain engine is running, or is allowed to cool down to normal temperature, before adding coolant.

Downloaded from www.Manualslib.com manuals search engine

If gage continues to register above normal with coolant at correct level, have your Authorized Cadillac Dealer make a thorough check of the system.

Cooling system protection

The inhibited year-around (permanent-type) engine coolant used to fill the cooling system at the factory, is a high quality solution that meets General Motors Specification 1899-M. This factory-fill coolant solution is formulated to withstand two full calendar years of normal operation without draining or adding inhibitors, and provides freezing protection to -20°F.

It is the owner's responsibility to keep the freeze protection at a level commensurate with the area in which the vehicle will be operated. Regardless of climate, system protection should be maintained at least to 0°F., with an ethylene-glycol base coolant to provide adequate corrosion protection. When adding solution due to loss of coolant for any reason or in areas where temperatures lower than -20°F. may occur, a sufficient amount of ethylene glycol base coolant that meets GM Specification 1899-M, or equivalent, should be used.

COOLING SYSTEM CAPACITY	
All cars except Fleetwood Seventy-Fives	
with heater only	17 U.S. qts. (14¼ Imperial qts.)
with Air Conditioner	17½ U.S. qts. (14½ Imperial qts.)
without heater or Air Conditioner	16 U.S. qts. (13¼ Imperial qts.)
Fleetwood Seventy-Fives	20½ U.S. qts. (17 Imperial qts.)

Every two years the cooling system should be serviced by flushing with plain water, then completely refilled with a fresh solution of water and a high-quality, inhibited (permanent type) glycol base coolant meeting GM Specification 1899-M, and providing freezing protection at least to -20°F. At this time, also add GM Cooling System Inhibitor and Sealer or equivalent. In addition, Cooling System Inhibitor and Sealer should be added every fall after the car has been driven 24,000 miles. GM Cooling System Inhibitor retards the formation of rust or scale and is compatible with aluminum components.

NOTE: Alcohol or methanol base coolants or plain water are not recommended for your Cadillac at any time.

PREVENTIVE MAINTENANCE

CADILLAC GUARDIAN MAINTENANCE QUALITY SERVICE

Preventive maintenance for your Cadillac is based on the Manufacturer's recommendations. Details are outlined in the

Downloaded from www.Manualslib.com manuals search engine

Cadillac Owner Protection Plan booklet. Consult your dealer for additional services that may be needed due to local climatic conditions or driving habits.

Battery fluid level

Battery fluid level should be checked at every engine oil change. However, in warm weather, fluid level should be checked at two-week intervals. Maintain battery fluid level up to the bottom of the slots in each cell.

A fluid level indicator is provided on top of the second cell cap from the positive battery post. When fluid level is normal, a black spot appears on the "eye" in the top of this cap. An off-white spot indicates that fluid level is low. In such case, check all cells and add water, as necessary, to bring them to their proper level.

Ordinary tap water may be used except in areas where the water is known to be exceptionally hard or to have a high mineral or alkali content. In these areas use distilled water to fill the battery. If water is added during freezing weather, drive the car five or six miles before shutting it off. This mixes the added water with the electrolyte and will prevent it from freezing and damaging the battery.

Have the battery charge checked regularly during extremely cold weather. Make sure the cables are clean and tightly clamped to the battery terminals.

CAUTION: Since the normal battery chemical action generates hydrogen gas which is highly explosive when mixed with air, never expose the battery to an open flame or electric spark. Also, avoid getting battery fluid, which is sulfuric acid solution, on skin, clothing or other fabrics, or on painted surfaces. Eye protection should be worn while working on the battery for any reason.

Windshield washer solution

The recommended mixture of GM Windshield Washer Anti-freeze and Gas Line De-icer or Optikleen Windshield Washer Solvent (or the equivalent) should be added to your windshield washer container during cold weather to retard freezing. CAUTION: Follow the directions on the label for correct mixture, otherwise paint damage may result.

Suspension

The suspension and steering linkage connections do not require periodic lubrication. Suspension connections are packed with a special long-life lubricant and normally need repacking only when damaged seals are replaced. Steering linkage pivots must be replaced when worn or loose.

Carburetor air cleaner and filter

The carburetor air cleaner should be inspected for dust leaks every spring and fall. Inspect more frequently if the car is operated in dusty areas. Install a new filter element if needed

Downloaded from www.Manualslib.com manuals search engine

at time of inspection, or at least every 2 years or 24,000 miles whichever occurs first. The element should not be cleaned.

On California cars, the metal gauze in the strainer, located on the wall of the carburetor air cleaner, should be cleaned in solvent and reoiled with engine oil whenever the engine oil is changed.

Positive crankcase ventilator valve

The positive crankcase ventilator valve should be replaced every 12 months or 12,000 miles, whichever occurs first. Crankcase vapors and other impurities can cause malfunctions of the crankcase ventilator valve. Periodic replacement is necessary for smooth engine operation and to insure efficient functioning of the unit.

Fuel filter

The fuel filter element should be replaced at least every spring and fall. More frequent service is necessary under unusual operating conditions. The filter element stops small dirt particles that may cause carburetor flooding.

Transmission fluid and strainer

The transmission bottom pan should be drained every 24,000 miles or 2 years, whichever occurs first, and new fluid added. For cars in commercial use, and those subjected to heavy city traffic during hot weather or when the engine is idled for long periods, the bottom pan should be drained every 12,000 miles.

The strainer should be replaced only after the first 24,000 miles or 2 years, whichever occurs first.

Manufacturer recommended fluids and lubricants

TRANSMISSION

GM Automatic Transmission Fluid available from Authorized Cadillac Dealers or automatic transmission fluid designated "AQ-ATF", followed by three or four numerals and the suffix letter "A",

POWER STEERING SYSTEM

If adding less than one pint, use recommended transmission fluid, otherwise use special GM Power Steering Fluid.

BRAKE SYSTEM

Delco Supreme 11 Super Heavy Duty Brake Fluid or brake fluids conforming to SAE 70-R3 specifications.

REAR AXLE

Standard Differential—SAE 90 Multi-Purpose Lubricant conforming to MIL-L-2105-B specifications.

Controlled Differential—Special Rear Axle lubricant available from Authorized Cadillac Dealers.

FRONT SUSPENSION SYSTEM

Special lubricant used. Periodic inspection only. See your Authorized Cadillac Dealer.

Downloaded from www.Manualslib.com manuals search engine

HOISTS—SERVICE LIFTING EQUIPMENT

The preferred type of hoist for lifting all 1967 Cadillac cars is one that engages the front suspension and rear axle, or all four wheels.

When using lifting equipment that engages the suspension system, the car should be centered over the hoist so that the hoist arms engage the flattened portion of the front suspension lower arms.


If a frame engaging hoist is used, certain precautions must be observed. Do NOT use a frame engaging hoist to raise the Fleetwood Seventy-Five sedan and limousine, or the commercial chassis.

EMERGENCY WHEEL CHANGING INSTRUCTIONS

The jack supplied with your Cadillac is intended for use only on this vehicle and only for wheel changing purposes.

On cars with a shelf-mounted spare wheel and tire, the rack bar is stored on the shelf in the luggage compartment just forward of the spare tire. The jack base is stored on top of the wheel (secured by a through-bolt and wing nut). The jack handle, jack hook and wedge block are stored under the tire.

The spare wheel and tire on convertible styles and the Fleetwood Seventy-Five sedan and limousine are floor



mounted. Jack components are stored on the right side of the luggage compartment.

CAUTION: For personal safety, never get beneath the car when it is supported only by the bumper jack. Always use stands to support frame if it is necessary to get under car.

NOTE: If your vehicle is equipped with a Controlled Differential, do not run the engine for any reason with one rear wheel off the ground, as the car may drive through the rear wheel remaining on the ground.

To change wheel proceed as follows:


1. If at all possible, park car on level ground, off the highway.

2. Place shift selector in PARK position, shut off engine, and set parking brake.

Downloaded from www.Manualslib.com manuals search engine


3. Remove spare tire and jack components from luggage compartment, install rack bar in jack base. Install jack handle in jack with wrench end in horizontal position.

4. Block the wheel diagonally opposite the wheel to be removed with the wedge block provided.



5. Front or rear bumper—engage jack hook as shown.

CAUTION: Make certain tip of jack hook engages frame and not bumper.



Downloaded from www.Manualslib.com manuals search engine

Holding jack hook against bumper, position and raise jack assembly to engage pin on jack hook.

6. Reposition jack base so that rack bar is vertical and raise jack until snug.

7. When removing rear wheel, remove wheel opening cover by turning the locking rod tab located on the center lower edge of cover with wrench end of jack handle (handle pointing rearward on left side or forward on right side). Rotate handle outward to loosen locking rod. Tip cover outward at the top while raising up and away from the mounting hooks.

8. Remove wheel disc using tip of jack handle.

9. Loosen wheel nuts 1/2 turn (counterclockwise).

10. Raise car on jack and remove wheel mounting nuts.

CAUTION: Before removing deflated tire and wheel assembly, make certain car is raised sufficiently to permit installation of fully inflated tire.

11. Install spare wheel and tire assembly, making certain wheel mounting nuts are tightened securely. Lower car, remove jack and recheck wheel nuts for tightness.

Use rubber covered portion of jack handle to install wheel disc. Reinstall wheel cover if previously removed.

TIRES


The factory installed tires on your car are selected to provide the best all around tire performance for all normal operation. When inflated as recommended in the tire inflation pressure table they have the load carrying capacity to operate satisfactorily at all loads up to and including the specified full rated load at all normal highway speeds.

Tire inflation pressures

To insure the proper tire inflation pressures for your particular requirements, follow the recommendations in the tire inflation pressure table. Keep tires properly inflated, and check inflation pressures periodically. This will ensure you of the best tire life and riding comfort, over the full range of driving conditions.

Tire rotation information


To equalize wear it is recommended that the tires be rotated every 6,000 miles. Upon rotation, tire pressure must be adjusted (front and rear) in accordance with the recommendations in the tire inflation pressure table.



Downloaded from www.Manualslib.com manuals search engine

TIRE USAGE AND INFLATION PRESSURE TABLE

Pounds per square inch (cool)

Series and Tire Size	Standard Inflation Pressure for All Loads Including Full Rated Loads
 9.00 x 15 *(4-Ply Rating 2-Ply)* **Calais and De Ville Fleetwood Sixty Special & Brougham**	1 to 6 passengers plus 200 lb. trunk load *(1100 lb. load)* **Front 24, Rear 24 p.s.i. Front 25, Rear 25 p.s.i.**
 8.20 x 15 *(8-Ply Rating 4-Ply)* **Fleetwood Seventy-Five**	1 to 9 passengers plus 200 lb. trunk load *(1550 lb. load)* **Front 28, Rear 38 p.s.i.**
	Optional Inflation for Reduced Loads: 1 to 5 passengers (750 lb. load) Front 28, Rear 28 p.s.i.
 8.90 x 15 *(8-Ply Rating 6-Ply)* **Commercial Vehicle**	up to and including 7200 lb. Gross Vehicle Weight **Front 24, Rear 40 p.s.i.**
	Optional Inflation for Reduced Loads (6400 lb. Gross Vehicle Weight) Front 24, Rear 32 p.s.i.

- Tire Inflation pressures may increase as much as 6 pounds per square inch (p.s.i.) when tires are hot.
- For continuous high speed operation (over 75 mph) increase tire inflation pressures 4 pounds per square inch over the recommended pressures up to a maximum of 32 pounds per square inch-cool for 4 ply rating tires or 40 pounds per square inch-cool for 8 ply rating tires. Speeds above 75 mph are not recommended when the 4 pounds per square inch adjustment would require pressures greater than the maximum stated above.
- Cool tire inflation pressure: after vehicle has been inoperative for 3 hours or more, or driven less than 1 mile. Hot tire inflation pressure: after vehicle has been driven 10 miles or more at 60-70 miles per hour.
- Vehicles with luggage racks do not have a vehicle load limit greater than specified in the tire inflation pressure table.
- When towing trailers, the allowable passenger and cargo load must be reduced by an amount equal to the trailer tongue load on the trailer hitch.

Downloaded from www.Manualslib.com manuals search engine

APPEARANCE MAINTENANCE

Your Cadillac is finished with General Motors' "Magic-Mirror" acrylic lacquer. This is a finish of maximum beauty which is superior to conventional lacquer finishes in depth of color, gloss retention and durability.

Washing

The best way to preserve the finish is to keep it clean. Frequent washings are required to maintain its original beauty. Wash the car with either warm or cold (never hot) water, not in the direct rays of the sun, and not while the sheet metal surfaces are hot. Never wipe dirt from dry painted surfaces because this may scratch the finish. The use of strong soaps and chemical detergents should be avoided. All cleaning agents should be promptly flushed from the surface and not allowed to dry or they may streak the finish.

Polishing and waxing

Even though the acrylic paint on your car is more durable than conventional finishes, under certain conditions you may wish to wax or polish your car to provide maximum protection.

Calcium chloride and other salts, ice-melting agents, road oil and tar, tree sap, chemicals from factory chimneys and other foreign matter may damage any automobile finish if allowed to remain in contact with paint.

Prompt washing may not thoroughly remove these deposits and, particularly in geographical areas where these exposure conditions are severe, properly applied high quality polishes and waxes will provide the best protection. Authorized Cadillac Dealers offer both GM Magic Mirror and Blue Coral, which have proven their value in maintaining a fine finish.

NOTE: Some chemical cleaners used for removing road oil and tars from painted surfaces have been found to be detrimental to acrylic finishes. When purchasing a cleaner, make sure the instructions specifically state that the contents can be safely used on an acrylic finish.

Chrome

Many parts of your Cadillac, such as the bumpers and body hardware, are chromium plated. Chrome plating is susceptible to the actions of solutions being used on streets and highways to melt ice. Corrosive damage may also be caused by salt air near coastlines, industrial smoke and other conditions found in urban areas. When such conditions exist, frequent washing and waxing are necessary. GM Chrome Cleaner is an excellent material for cleaning the chrome on your car.

Anodized aluminum parts

Caustic cleaning agents will discolor anodized aluminum parts

Downloaded from www.Manualslib.com manuals search engine

such as the grille and exterior trim. Do not permit the use of steam or cleaning solutions containing these agents for the cleaning of your car.

Glass

Dirt and insects can be removed from glass with clear water. Never wipe dirty glass with dry paper or cloth. Do not operate windshield wipers when glass is dry. Periodic inspection and replacement of wiper blades reduce the possibility of glass becoming scratched and assure clear vision under adverse driving conditions.

Leather and vinyl

Cadillac upholstery leathers are made from select hides and are protected by a special finish. They can be kept clean normally by regular dusting. Leather or vinyl that has become soiled can be cleaned with GM Vinyl Cleaner or thick, sudsy lather made from mild soap in lukewarm water. Avoid the use of excessive amounts of water. Remove the suds with a clean, damp cloth and wipe dry. If a sheen is desired, buff with clean cheesecloth. A high quality, glycerine base saddle soap can be used, if desired.

To remove stains such as food, pet accidents and ink, clean as previously explained. For acids and perspiration stains, use cloth dipped in solution of one teaspoon of baking soda to one cup of water, and follow with the soap and water treatment. In the event of blood stains, wipe off with cold water before using soap and water.

Do NOT use naptha, alcohol cleaners, household cleansing and bleaching agents, wax, polish, or oils.

White sidewall tires

GM White Sidewall Tire Cleaner is recommended. Foaming type household cleansers may also be used. Do NOT use gasoline, kerosene, or any oil product that will discolor the tire sidewalls or damage the rubber.

Upholstery and carpets

Dirt and dust in the upholstery and carpets can be removed with frequent vacuuming. GM Kar Kleen is especially recommended for cleaning carpets and upholstery, and restoring them to like-new condition. GM Fabric Cleaner can be used on spots that are difficult to remove.

CAUTION: When cleaning interior fabrics or carpeting, do not use volatile cleaning solvents such as: acetone, lacquer thinners, carbon tetrachloride, enamel reducers, nail polish removers, or laundry soaps, bleaches and reducing agents. NEVER USE GASOLINE OR NAPTHA FOR ANY CLEANING PURPOSE.

Downloaded from www.Manualslib.com manuals search engine

Padded top

To wash the padded top, use lukewarm water and suds from a neutral soap. A cloth or soft-bristled brush is recommended for applying the solution of suds. Deeply embedded dirt can be removed with a nylon bristled brush and a small amount of "foaming" type cleanser. All traces of the cleanser should be removed with clean water. Do NOT use volatile cleaners, naptha, gasoline, harsh household cleaners and detergents, soaps, and bleaching agents. A wire brush will seriously damage the padded top material, and should not be used.

Undercoating

Undercoating should not be applied to any moving or rotating part. It should be kept off air conditioner fittings and lines, body and antenna drainholes, and exhaust systems. On cars equipped with Automatic Level Control, particular care should be taken not to undercoat any fittings, lines, or system components.

SPECIAL NOTES

Extended vehicle storage

If you plan to store your car over an extended period of time, certain steps should be taken to give it maximum protection. It is recommended that you write to the Cadillac Motor Car Division, Service Department, Detroit, Michigan for detailed instructions on how to prepare your Cadillac for storage.

Lights

When the headlights are on high beam a light below the 60 MPH mark on the speedometer glows red. Never leave the high beam on when driving behind another car or approaching oncoming traffic. Have all your lights checked regularly. Your Authorized Cadillac Dealer has the modern equipment and genuine Cadillac parts to handle these services promptly.

Exhaust gas warning

Avoid inhaling exhaust gases when any concentrations of these are present in the air, i.e. in a garage, or when parked for extended periods with the engine running. Exhaust gases may have strong odors which normally should give warning of their presence. However, the exhaust gases from some vehicles may not be noticeable under certain conditions and the senses of people react differently. Exhaust gases contain a percentage of carbon monoxide which is a poisonous gas that, by itself, is tasteless, colorless and odorless.

Controlled differential

On cars equipped with a Controlled Differential, do not run the engine for any reason with one rear wheel off the ground, as the car may drive through the rear wheel remaining on the ground.

Downloaded from www.Manualslib.com manuals search engine

Transmission

The Low "L" range should be used when going down very steep grades. Where traffic signs call for first or second gear, always shift to Low "L" range.

The right-hand "DRIVE" position reduces shifting in heavy traffic and on hills, provides more control on slippery pavement, and decreases brake usage when descending medium grades.

When parking on hills or steep inclines, and when stopping or leaving the car unattended, even for a few moments, place the shift lever in the park "P" position to lock the rear wheels. Also apply the parking brake and turn the front wheels toward curb.

SPECIFICATIONS

Vehicle identification number

The Vehicle Identification Number is used in license and insurance applications and in general reference to the automobile. This number is located on the rear portion of the crankcase behind the intake manifold, and on top of the frame right side rail to the rear of the radiator. For the owner's convenience it also appears on the plastic service notice plate on the left front door lock pillar.

FLUID CAPACITIES

Fuel Tank—approximately 26 U. S. gallons, (21¾ Imperial gallons) except Commercial Chassis—20 U. S. gallons (16¾ Imperial gallons).

Turbo Hydra-matic transmission with strainer change—3½ U. S. quarts (3 Imperial quarts).

Engine Oil—4 U. S. quarts, (3¼ Imperial quarts) with filter change, 5 U. S. quarts (4¼ Imperial quarts).

Rear Axle—5 U. S. pints (4¼ Imperial pints).

Cooling System—See page 53

ENGINE SPECIFICATIONS

Type of Engine	90°, V-8 overhead valve
Bore and Stroke	4.130 in. x 4.000 in.
Piston Displacement	429 cu. in.

BATTERY SPECIFICATIONS

Type of Battery	Delco Energizer No. R71
Capacity, Ampere Hours	73
Plates, Number Per Cell	13
Terminal Grounded	Negative
Volts	12
Full Charge Specific Gravity 80°F.	1.250-1.280
Cranking Power at 0°F.	3350 Watts

Downloaded from www.Manualslib.com manuals search engine

GENERAL SPECIFICATIONS

Description	Style Number	*Vehicle Identification Number	Wheelbase (Inches)	Overall Length (Inches)	Height (Inches)	Maximum Width (Inches)
Fleetwood Sixty Special Sedan	68069	M7100001	133.0	227.5	56.7	80.0
Fleetwood Brougham Sedan	68169	P7100001	133.0	227.5	56.8	80.0
Calais Hardtop Sedan	68249	N7100001	129.5	224.0	54.5	80.0
Calais Coupe	68247	G7100001	129.5	224.0	54.6	80.0
Calais Sedan	68269	K7100001	129.5	224.0	55.6	80.0
Hardtop Sedan de Ville	68349	B7100001	129.5	224.0	54.5	80.0
Coupe de Ville	68347	J7100001	129.5	224.0	54.6	80.0
De Ville Convertible	68367	F7100001	129.5	224.0	54.3	80.0
Sedan de Ville	68369	L7100001	129.5	224.0	55.6	80.0
Fleetwood Eldorado	69347	H7100001	120.0	221.0	53.3	80.0
Fleetwood Seventy-Five Sedan	69723	R7100001	149.8	244.3	57.4	80.0
Fleetwood Seventy-Five Limousine	69733	S7100001	149.8	244.3	57.4	80.0
Commercial Chassis	69890	Z7100001	156.0	249.5	—	—

*All series Cadillacs are built and numbered in numerical order beginning with V. I. Number 100001, regardless of series or style.

WEIGHT—Consult the dealer who sold you the car or the Motor Vehicle Commissioner of your state. Weight information on all body styles is regularly supplied to these authorities.


Downloaded from www.Manualslib.com manuals search engine

FUSES AND BULBS

Fuses and circuit breakers protect the electrical wiring in the car against overloading. All fuses are contained in a fuse panel located behind the lower left side of the instrument panel, except the Guide-Matic fuse, the blower motor fuse on air conditioned cars, and the seat warmer fuse. See fuse chart for location of these fuses and all circuit breakers.

Fuses can be easily replaced by releasing the locking lever on the left side of the fuse panel and moving the panel down far enough to permit tabs to be free of locking lever. Then move fuse panel forward through notch in bracket and pull panel downward as far as wires permit.

Specifications for fuses and bulbs are listed in two charts. Replacement parts should be of same type and capacity characteristics as those listed.



Downloaded from www.Manualslib.com manuals search engine

FUSES

UNIT	FUSE RATING
Accessories Antenna Rear Window De-Fogger Window Control Relay	25 AMP.
Air Conditioner and Heater	25 AMP.
Back-up Lights	10 AMP.
Blower Motor (A/C Cars) (In-line on top of right rocker arm cover)	30 AMP.
Body Feed Cigar Lighter Clock Courtesy Lights *Dome Light, Chauffeur Glove Box Light Interior Body Lights Map Light Trunk Tell-Tale Light	25 AMP.
Guide-Matic (In-line above left kickpad)	4 AMP.
Headlights and Parking Lights (Integral with Headlight Switch)	15 AMP. (CB)
Heater Only	15 AMP.
Horn	25 AMP.
Power Windows (On cars equipped with power windows and/or power seats, and on the convertible style, the 25 AMP. horn fuse, located in the fuse panel, is replaced by a 40 AMP. Circuit Breaker)	40 AMP. (CB)
Instruments and Transmission Controls Cruise Control Indicator Light Downshift and Stator Control Solenoids Tell-Tale Lights and Gages (Except Trunk)	10 AMP.
Panel Lights	4 AMP.
Radio	7½ AMP.
Stop Lights and Hazard Warning Flasher	25 AMP.
Tail Lights Ash Tray Lights Cornering Lights Ignition Switch Light Tail Lights Twilight Sentinel	25 AMP.
Turn Signal	15 AMP.
Windshield Wipers	25 AMP.

Do not use fuses of higher amperage rating than those recommended above.

AMP.—Ampere (CB)—Circuit Breaker
*Fleetwood Seventy-Five limousine only

Downloaded from www.Manualslib.com manuals search engine

BULBS

LOCATION	BULB NO.
Ash Tray-Front	1445
Back-Up Light	1195
Console Compartment	57
Cornering Light-Front Fender	1195
Courtesy Lights:	
Console	212/212-1
Instrument Panel	89
Rear Door	212/212-1
Rear Quarter	90
Rear Quarter Armrest	212/212-1
Cruise Control Speed Selector	1445
Cruise Control (Auto-Lock Indicator)	161
Dome Light, Chauffeur (Limousine only)	90
Generator Indicator	161
Glove Compartment	1895
Headlight:	
Lower	L4001
Upper	L4002
Headlight Switch	1816
Heater or A/C Control	1816
High Beam Indicator	161
Ignition Lock Light	1445
Instrument Panel Cluster Lights	168
License Plate Light	67
Low Brake Indicator	161
Low Oil Pressure Indicator	161
Map Light	89
Park and Turn Signal	1157-A
Radio Dial	1816
†Radio-AM/FM Indicators	250
†Radio-AM/FM and Stereo Indicators	2181-D
*Radio-Rear Control Indicator	250
Reading Spot Lights	1004
Stop, Tail and Signal	1157
Tray, Seat Back (Fleetwood Brougham Sedan)	212/212-1
Trunk Compartment	89
Trunk Lid Indicator	161
Turn Signal Indicator	1445
Warning Lights:	
Front Door	212/212-1
Rear Door	212/212-1
Windshield Wiper Switch	1895

*Fleetwood Seventy-Five sedan and limousine only

†Serviceable only by radio technician

Downloaded from www.Manualslib.com manuals search engine

Cadillac dealers are conveniently located throughout the United States. To assist these dealers, Cadillac Motor Car Division maintains Zone Offices in these strategic locations:

CADILLAC ZONE OFFICES

BOSTON, MASSACHUSETTS
220 Boylston Street
Chestnut Hill, Massachusetts 02167
969-6810 Area Code 617

NEW YORK, NEW YORK
1013 Teaneck Road
Teaneck, New Jersey 07666
833-2240 Area Code 201

PHILADELPHIA, PENNSYLVANIA
Route 38
P. O. Box 9
Moorestown, New Jersey 08057
235-6800 Area Code 609

WASHINGTON, D. C.
Room 413
Wheaton Plaza Office Bldg.
Wheaton, Maryland 20900
949-4570 Area Code 301

DETROIT, MICHIGAN
Room 900
15565 Northland Drive
Southfield, Michigan 48075
442-5692 Area Code 313

CLEVELAND, OHIO
3645 Warrensville
Center Road
Shaker Heights, Ohio 44122
752-7600 Area Code 216

CINCINNATI, OHIO
Carrousel Towers
8075 Reading Road, Room 210
P. O. Box 37404
Cincinnati, Ohio 45237
761-7290 Area Code 513

ATLANTA, GEORGIA
1776 Peachtree Rd., N. W.
Atlanta, Georgia 30309
875-8396 Area Code 404

JACKSONVILLE, FLORIDA
4019 Woodcock Drive
P. O. Box 16352
Jacksonville, Florida 32216
398-1141 Area Code 904

MINNEAPOLIS, MINNESOTA
7701 Normandale Road-Edina
Minneapolis, Minnesota 55435
920-3870 Area Code 612

CHICAGO, ILLINOIS
205 West Touhy Avenue
Park Ridge, Illinois 60068
823-2151 Area Code 312

KANSAS CITY, MISSOURI
Room 306, 4900 Oak Street
Kansas City, Missouri 64112
753-7255 Area Code 816

MEMPHIS, TENNESSEE
2701 Union Extended
P. O. Box 12044
Memphis, Tennessee 38112
324-3621 Area Code 901

DALLAS, TEXAS
1111 Frito-Lay Building
P. O. Box 45006
Dallas, Texas 75235
357-3851 Area Code 214

PORTLAND, OREGON
Room 314, 1500 Plaza
1500 N. E. Irving Street
Portland, Oregon 97232
233-4801 Area Code 503

SAN FRANCISCO, CALIFORNIA
1825 Trousdale Drive
Burlingame, California 94010
697-6080 Area Code 415

LOS ANGELES, CALIFORNIA
Room 605
10850 Riverside Drive
P. O. Box 505
N. Hollywood, California 91603
877-2673 Area Code 213

DENVER, COLORADO
1190 S. Colorado Blvd.
Denver, Colorado 80222
756-3691 Area Code 303

Downloaded from www.Manualslib.com manuals search engine

INDEX

	Page
Air Injection Reactor	49
Aluminum Parts, Anodized	60, 61
Ash Trays and Lighters	14, 43
Appearance Maintenance	60
Authorized Cadillac Service	46
Automatic Climate Control	22, 23, 24, 25, 43
Automatic Level Control	38
Back-Up Lights	11
Battery Fluid Level	54
Battery Specifications	63
Belts, Seat	34, 35
Brake, Parking	17, 18
Brake Pedal Warning Light, Low	7, 8
Brakes	16
Brakes, Power	17
Braking on Hilly Terrain	17
Bulb Chart	67
Bulbs, Fuses and	65
Carburetor Air Cleaner	54, 55
Chrome	60
Climate Control, Automatic	22, 23, 24, 25, 43
Clock, Electric	14
Controlled Differential	39, 62
Controls, Climate Control, Rear System	44, 45
Convertible Top	39
Cooling System Protection	53
Cornering Lights	13, 14
Courtesy Lights	11, 12, 42
Crankcase Ventilator Valve, Positive	55
Cruise Control	27, 28
De-Fogger, Rear Window	25, 26
Differential, Controlled	39, 62
Engine Oil-Filler Cap	50
Engine Cooling	52
Engine Oil	51
Engine Specifications	63

Downloaded from www.Manualslib.com manuals search engine

INDEX (cont'd)

	Page
Exhaust Gas Warning	62
Fleetwood Seventy-Five Sedan and Limousine	41
Flooded Engine, Starting	6
Fluid Capacities	63
Fluids and Lubricants, Manufacturer Recommended	55
Foot Rests	40
Fuel Requirements	47
Fuel Filter	55
Fuel Gage	7
Fuses and Bulbs	65
Fuse Chart	66
Gasoline Tank	48
General Specifications	64
Generator Indicator Light	8
Glass	61
Guide-Matic Power Headlight Control	28, 29
Hazard Warning Flasher	13
Headlight Controls	10, 11
Headlight Dimmer Switch	11
Headlight High-Beam Indicator	11
Heater Controls	19, 20
Heating	19
Hoists-Service Lifting Equipment	56
Hood Latch	37, 38
Ignition Switch	5
Instrument Panel and Controls	8, 9
Instruments	7, 42
Jack, Use Of	56, 57, 58
Keys	4, 5
Leather and Vinyl	61
Level Control, Automatic	38
Lights	62
Lock, Coupe Seat-Back	33
Locks, Manual Door	36, 37
Locks, Power Door	37
Luggage Compartment	38

Downloaded from www.Manualslib.com manuals search engine

INDEX (cont'd)

	Page
Maintenance, Appearance	60
Maintenance, Preventive	53, 54
Map Light	11
Mirrors	20, 21
Oil, Engine, Recommendations	50
Oil, Engine, Change Interval	50
Oil, Engine, Viscosity Chart	51
Oil Filter Replacement	51
Oil Level, Checking	50
Oil Pressure Indicator Light	8
Operating Your Cadillac	4
Operation in a Foreign Country	48
Owner Protection Plan Booklet	47
Owner Responsibility	47
Padded Top	62
Polishing and Waxing	60
Positive Crankcase Ventilation	49
Positive Crankcase Ventilator Valve	55
Power Brakes	17
Power Windows	35, 36, 42
Preventive Maintenance	53, 54
Protection Plan Booklet, Owner	47
Radiator Cap Removal	52
Radio Controls, Rear Compartment	45
Radios	30, 31, 32
Restarting	6
Safe Driver Checklist	2
Safety Inspection, 10-Point	3
Seat Adjustments, Additional	33
Seat and Head Restraints, Reclining Bucket	33, 34
Seat-Back Lock, Coupe	33
Seat Belts	34, 35
Seat Controls, Bucket	33
Seats, Electrically Operated, Front	32, 33
Seats, Front—Manually Operated	32
Service, Cadillac	47
Shoulder Belts	35
Special Notes	62
Specifications	63

Downloaded from www.Manualslib.com manuals search engine

INDEX (cont'd)

	Page
Speedometer and Odometer	8
Starting, Emergency	6
Starting, Normal	5, 6
Starting, Extreme Cold Weather	6
Starting Flooded Engine	6
Steering, Power	18
Steering Wheel, Tilt and Telescope	26, 27
Storage, Vehicle, Extended	62
Suspension	54
Tank, Gasoline	48
Temperature Gage	7
Tire Inflation Pressures	58
Tire Rotation	58
Tires	58
Tire Usage and Inflation Pressure Table	59
Towing	6
Trailer Hauling	6, 7
Transmission	15, 16, 63
Transmission Fluid and Strainer	55
Trays, Utility, Fold-Down	40
Trunk Lock, Remote Control	38
Turn Signal	12
Twilight Sentinel	29, 30
Undercoating	62
Upholstery and Carpets	61
Vehicle Identification Number	63
Ventilation	18, 19
Warranty	46
Washing	60
Weight	64
Wheel Changing Instructions, Emergency	56, 57, 58
White Wall Tires	61
Window Lock-Out Switch	36
Windows, Power	35, 36, 42
Windows, Power Vent	36
Windshield Washer Solution	54
Windshield Wipers and Washers	10
Zone Offices	68

PART NUMBER 109 9197
FOURTH EDITION

LITHO IN U.S.A.

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

The information contained herein is prepared, distributed by, and is solely the responsibility of the automobile manufacturing company to whose products it relates. Questions concerning these specifications should be directed to the manufacturer whose address is shown below. This uniform specification form was developed by the automobile manufacturing companies under the auspices of the Automobile Manufacturers Association.

MANUFACTURER	CAR NAME	
Cadillac Motor Car Division	Cadillac	
MAILING ADDRESS	MODEL YEAR	ISSUED: 10-6-66
2860 Clark, Detroit, Michigan	1967	REVISED (●)

NOTES:

1. The Specifications herein are those in effect at date of compilation and are subject to change without notice by the manufacturer.
2. UNLESS OTHERWISE INDICATED:
   a. Specifications apply to standard models without optional equipment. Significant deviations are noted.
   b. Nominal design dimensions are used throughout these specifications.

TABLE OF CONTENTS

General Specifications 1,2
Engine—Mechanical 3
Electrical 12
Drive Units 14
Brakes 18
Steering 19
Suspensions 21
Weights 24
Index 25

BODY—TYPES AND STYLE NAMES—

Body type, number of passenger & style names; use manufacturer's code for series & body style.

DESCRIPTION	NO. PASS.	STYLE NO.	VEHICLE IDENT. NO.
Fleetwood Sixty Special Sedan	6	68069	M7100001
Fleetwood Brougham	6	68169	M7100001
Calais Hardtop Sedan	6	68249	N7100001
Calais Coupe	6	68247	G7100001
Calais Sedan	6	68269	K7100001
Hardtop Sedan De Ville	6	68349	B7100001
Coupe De Ville	6	68347	J7100001
De Ville Convertible	6	68367	F7100001
Sedan De Ville	6	68369	L7100001
Fleetwood Seventy-Five Sedan	9	69723	R7100001
Fleetwood Seventy-Five Limousine	9	69733	S7100001

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 1

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (e)

GENERAL SPECIFICATIONS

(All dimensions in inches unless otherwise indicated)

MODEL		Additional Information Page No.:	68069 68169	68269 68369	68249 68349	68247 68347 68367	75
Wheelbase (L101)			133.0	129.5			149.8
Track	Front (W101)		62.5				
	Rear (W102)		62.5				
Maximum Overall Dimensions	Length (L103)		227.5	224.0			244.5
	Width (W103)		79.9				
	Height (H101)		56.7	55.6	54.3	54.3	58.1
Transmission (Specify trade name - opt., not available)	Manual - 3 speed	15	None				
	Manual - 4 speed	15	None				
	Overdrive	15	None				
	Automatic	16	Turbo-Hydramatic				
Axle ratio	Manual - 3 speed	17	None				
	Manual - 4 speed	17	None				
	Overdrive	17	None				
	Automatic	17	2.94:1				3.21:1
Tire size		18	9:00 x 15 2 Ply-4 Ply Rating				8.20 x 15 4 Ply - 8 Ply Ratin
Engine	Type, no. cyl., valve arr.	3	O. V. - V8 - 90°				
	Fuel system (Carb., other)	10	Carburetor				
	Bore and stroke	3	4.130 - 4.000				
	Piston displ., cu. in.	3	429				
	Std. compression ratio	3	10.5:1				
	Max. bhp at engine rpm	3	340 @ 4600				
	Max. torque at rpm	3	480 @ 3000				

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 2

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (o)

GENERAL SPECIFICATIONS—DIMENSIONS

(All dimensions in inches unless otherwise indicated)
(Supplemental data available on request)

MODEL	SAE Ref. No.	680 69	681 69	682 69	683 69	682 49	683 49	682 47	683 47	683 67	697 23	75 33
FRONT COMPARTMENT												
Shoulder room	W3	61.3	61.3	60.9	60.8	60.9	60.8	60.0	60.9	60.9	61.9	61.
Hip room	W5	63.6 All										63.
Max. eff. leg room - accelerator	L34	41.1		41.0		41.1	41.0	41.1	41.0	41.0	41.0	40.
Effective head room Old Method	H61	39.5		39.4		38.3	38.1	38.3	38.1	38.8	40.5	39.
H Point to Heel point	H30	8.5		8.6		8.5	8.6	8.5	8.6	8.6	8.0	8
REAR COMPARTMENT												
Shoulder room	W4	59.7		60.4	60.0	60.4	60.0	60.4	60.0	53.4	59.4	59.
Hip room	W6	62.4		62.5		62.8		55.2	55.2		57.7	
Minimum effective leg room	L51	45.4		41.9		39.7			38.9	38.2	45.4	
Effective head room Old Method	H63	38.2		38.3		37.5	37.5	37.5			38.4	
LUGGAGE COMPARTMENT												
Usable luggage capacity	V1	17.134								13.462	16.158	
Liftover height	H195	28.2	26.2								30.1	
Position of spare tire storage		Horizontal										
Method of holding lid open		Spring										
STATION WAGON—THIRD SEAT												
Hip room	W86	N.A.										
Effective leg room	L86	N.A.										
Effective head room	H86	N.A.										
Seat facing direction		N.A.										

STATION WAGON—CARGO SPACE

MODEL	SAE Ref. No.	None Available
Minimum distance between wheel houses at floor level	W201	
Rear end opening width at belt	W204	
Floor length from back of front seat at floor level to inside of closed tail gate	L202	
Minimum horizontal distance from top rear of front seat back to inside of tail gate at belt	L204	
Maximum height - floor covering to headlining at centerline of rear axle	H201	
Maximum height of rear opening - tail and lift gates open	H202	
Cargo volume index (cu. ft.) $\frac{W4 \times L204 \times H201}{1728}$	V2	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 3

AKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (0)

MODEL All Except Eldorado

ENGINE—GENERAL

Type, no. cyls., valve arr.		90° - V-8 - O.V.
Bore and stroke (nominal)		4.13 x 4.00
Piston displacement, cu. in.		429
Bore spacing (C/L to C/L)		4.562
No. system (front to rear)	L. Bank	1 - 3 - 5 - 7
	R. Bank	2 - 4 - 6 - 8
Firing order		1 - 8 - 7 - 2 - 6 - 5 - 4 - 3
Compres. ratio (nominal)		10.5:1
Cylinder Head Material		Cast Iron
Cylinder Block Material		Cast Iron
Cylinder Sleeve-Wet, dry, none		None
Number of mounting points	Front	2
	Rear	1
Engine installation angle		5° 55' 41"
Taxable horsepower $\frac{Dia^2 x No.Cyl.}{2.5}$		54.6
Publishing max. bhp* @ eng. RPM		340 @ 4600
Publishing max. torque* lb. ft. @ RPM)		480 @ 3000
Recommended fuel regular - premium		Premium
Idle speed(spec. neutral or drive)	Manual	N.A.
	Automatic	** 480 Drive

ENGINE—PISTONS

Material			Aluminum Alloy
Description and finish			Slipper Type Cam Ground Control Expansion
Weight (piston only) oz.			21.76
Clearance (limits)	Top land		.033 - .038
	Skirt	Top	.0006 - .0010
		Bottom	.000
Ring groove depth	No. 1 ring		.215
	No. 2 ring		.215
	No. 3 ring		.167
	No. 4 ring		None

*Max. bhp (brake horsepower) and max. torque corrected to 60° F and 29.92 in. Hg atmospheric pressure.

** A/C System on

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 4

'AKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (a)

POWER TEAMS

(Indicate whether standard or optional)

MODEL AVAILABILITY	ENGINE					TRANSMISSION	AXLE RATIO (Std. first) (Indicate A/C ratio)
	Displ. cu. in.	Carburetor	Compr. Ratio	BHP @ RPM	Torque @ RPM		
ALL (Except Eldorado)	429	4BBL	10.5:1	340 @ 4600	480 @ 3000	Hydramatic	2.94:1 All except 75 Limo. 3.21:1 Std. in 75 Limo. & all A/C Cars

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (0)

MODEL All (Except Eldorado)

ENGINE—RINGS

Function (top to bottom)	No. 1, oil or comp.	Comp.
	No. 2, oil or comp.	Comp.
	No. 3, oil or comp.	Oil
	No. 4, oil or comp.	None
Compression	Description - material, coating, etc.	#1 Molybdenum Filled Cast Iron #2 Phosphate Coated Cast Iron
	Width	.0625
	Gap	.013 - .030
Oil	Description - material, coating, etc.	Multi-Piece Steel Chrome Plated - Notched ID Rail
	Width	.1875
	Gap	.015 - .061
Expanders		Yes

ENGINE—PISTON PINS

Material			1045
Length			3.090
Diameter			.9994 - .9997
Type	Locked in rod, in piston, floating, etc.		Locked in Rod
	Bushing	In rod or piston	None
		Material	None
Clearance	In piston		.00005 - .00015
	In rod		Press Fit
Direction & amount offset in piston			.062 Toward Max. Thrust Side

ENGINE—CONNECTING RODS

Material		1041 Steel
Weight (oz.)		19.36 Oz.
Length (center to center)		6.50
Bearing	Material & Type	M-400 Alum. - Steel Backed
	Overall length	.755 - .880
	Clearance (limits)	.0005 - .0021
	End play	.008 - .014 (Total Two Rods)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 6

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (o)

MODEL All (Except Eldorado)

ENGINE—CRANKSHAFT

Material			Pearlitic Malleable Iron
Vibration damper type			Rubber Absorption
End thrust taken by bearing (No.)			#3 Center Main
Crankshaft end play			.001" - .007"
Main bearing	Material & type		M400 Alum. - M100 Babbitt
	Clearance		.0006" to .003
	Journal dia. and bearing overall length	No. 1	3.000" X 1.120"
		No. 2	3.000" X 1.062"
		No. 3	3.000" X 1.138"
		No. 4	3.000" X 1.062"
		No. 5	3.000" X 1.120"
		No. 6	None
		No. 7	None
	Dir. & amt. cyl. offset		See Piston
Crankpin journal diameter			2.25

ENGINE—CAMSHAFT

Location			Center of V
Material			G.M. 120M Cast Iron
Bearings	Material		Steel Backed Babbitt
	Number		5
Type of Drive	Gear or chain		Silent Chain
	Crankshaft gear or sprocket material		Sintered Iron G.M. 3884M
	Camshaft gear or sprocket material		Die Cast Alum. - Nylon Gear
	Timing chain	No. of links	46
		Width	.750
		Pitch	.500

ENGINE—VALVE SYSTEM

Hydraulic lifters (Std, opt, NA)		Std.
Valve rotator, type (intake, exhaust)		None
Rocker ratio		1.65:1
Operating tappet clearance (indicate hot or cold)	Intake	Auto
	Exhaust	Auto
Timing marks on flywheel, damper, other		Crankshaft Balancer

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

AKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (●)

MODEL All (Except Eldorado)

ENGINE—VALVE SYSTEM (cont.)

Timing	Intake	Opens (°BTC)	39° .001 Lift
		Closes (°ABC)	109° " "
		Duration-deg.	328° " "
	Exhaust	Opens (°BBC)	86° " "
		Closes (°ATC)	62° " "
		Duration-deg.	328° " "
	Valve opening overlap		
Intake	Material		1041 Alum. Steel
	Overall length		4.794
	Actual overall head dia.		1.875
	Angle of seat & face		Seat in Head 45° Valve Face 44°
	Seat insert material		None
	Stem diameter		.3415 - .3425
	Stem to guide clearance		.0005 - .0025
	Lift (@zero lash)		.440
	Outer spring press. and length	Valve closed (lb. @ in.)	60-65 @ 1.946"
		Valve open (lb. @ in.)	155 - 165 1.496"
	Inner spring press. and length	Valve closed (lb. @ in.)	None
		Valve open (lb. @ in.)	None
Exhaust	Material		21 - 4N
	Overall length		4.815
	Actual overall head dia.		1.500
	Angle of seat & face		Seat 45° Face 44°
	Seat insert material		None
	Stem diameter		.3415 - .3420
	Stem to guide clearance		.0010 - .0025
	Lift (@zero lash)		.440
	Outer spring press. and length	Valve closed (lb. @ in.)	60-65 @ 1.946"
		Valve open (lb. @ in.)	155 - 165 @ 1.496"
	Inner spring press. and length	Valve closed (lb. @ in.)	None
		Valve open (lb. @ in.)	None

ENGINE—LUBRICATION SYSTEM

Type of lubrication (Pressure, Splash, Pressure, Pressure)	Main bearings	Pressure
	Connecting rods	Pressure
	Piston pins	Splash
	Camshaft bearings	Pressure
	Tappets	Pressure
	Timing gear or chain	Metered Centrifugal Flow
	Cylinder walls	Intermediate Jet

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (a)

MODEL All (Except Eldorado)

ENGINE—LUBRICATION SYSTEM (cont.)

Oil pump type	Spur Gear
Normal oil pressure (lb. @ engine rpm)	30-35 @ 30 MPH
Oil pressure sending unit (elect. or mech.)	Electric
Type oil intake (floating, stationary)	Stationary
Oil filter system (full flow, partial, other)	Full Flow
Filter replacement (element, complete)	Element
Capacity of crankcase, less filter-refill (qt.)	4 Qts. - 1 Qt. Filter
Oil grade recommended (SAE viscosity and temperature range)	+32° F SAE 20W - IOW30 0° to + 32F SAE IOW - IOW30 Below 0°F SAE 5W-5W20
Engine Service Requirement (MM, MS, etc.)	MS - GM 4745M

ENGINE—EXHAUST SYSTEM

Type (single, single with cross-over, dual, other)		Single With Crossover
Muffler No. & type (reverse flow, straight thru, separate resonator)		Co-Axial Resonator Exhaust System
Exhaust pipe dia. (O.D., wall thickness)	Branch	Exhaust 2.00 - 2.50
	Main	Intermediate 2.24
Tail pipe diameter (O.D. & wall thickness)		2.25 - .0598

ENGINE— CRANKCASE VENTILATION SYSTEM

Type (ventilates to atmos., induction system, other)		Standard	Induction System
		Optional	None
Control Unit	Make and model		AC
	Location		On R.H. Rocker Arm Cover
	Energy source (manifold vacuum, carburetor air stream, other)		Manifold Vacuum
	Control method (variable orifice, fixed orifice, other)		Spring Loaded Valve Variable Orifice
Complete system	Discharges (to intake manifold, carb. air intake, air cleaner intake, other)		Intake Manifold
	Air inlet (breather cap, carburetor air cleaner, other)		Breather Cap (Non Calif. Cars) Air Cleaner (Calif. Cars)
	Flame arrestor (screen, check valve, other)		Check Valve

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 9

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL All (Except Eldorado)

ENGINE—EXHAUST EMISSION CONTROL

Type (Air injection, engine modifications, other)			Air Injection Type
Air Injection Pump	Type		Saginaw Steering Gear
	Displacement		19.3 Cu. In.
	Drive ratio		1.5:1
	Drive type		Belt
	Relief valve (type)		Popett
	Filter (describe)		Seperate Air Cleaner
Air Injection System	Air distribution (head, manifold, etc.)		Manifold
	Point of entry		Cylinder Head
	Injection tube I.D.		.244
	Check valve type		Diaphram (Delco)
	Backfire protection (type)		RPD - Anti-Backfire
Carburetor	Make		Rochester
	Model		4BBL Model 4MV
	Barrel size		Pri. 1.375 Sec. 2.250
	Idle speed	Drive	550 A/C Off
		Neutral	-
Distributor	Aux. Adv. Systems (type)		None *
	Make		Same as Std. Car (See Page 13)
	Model		"
	Cent'fgal adv. in crank degrees @ eng. rpm.	Start (rpm)	"
		Intermed. points deg. @ rpm	"
		Max. deg.@rpm.	"
	Vacuum adv. in. crank degrees@ eng. rpm	Start (in Hg) Intermed. points deg.@ in. Hg Max. deg.@ in.	"
	Vacuum Source		"
Timing - Crank degrees @ rpm			Same as Std. Car
Cooling System (describe changes)			Same as Std. Car
Exhaust System (describe changes)			Same as Std. Car

* Thermostat Vacuum Adv. Switch Mounted in Radiator on 75 Series and All A/C Equipped Cars

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 10

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (e)

MODEL All (Except Eldorado)

ENGINE—FUEL SYSTEM

(See supplemental page for Details of Fuel Injection, Supercharger, etc. if used)

Induction type: Carburetor, fuel injection, supercharger.			Carburetor
Fuel Tank	Refill capacity (gals.)		26
	Filler location		Back of License Plate
Fuel Pump	Type (elec. or mech.)		Mechanical
	Locations		Lower Left Side - Front of Eng.
	Pressure range		5.25 - 6.50 @ 1800
Vacuum booster (std., optional, none)			None
Fuel Filter	Type		AC
	Locations		Top Center - Frt. of Engine
Carburetor	Choke type		Remote Pocket In Manifold
	Intake manifold heat control (exhaust or water)		Exhaust
	Air cleaner type	Standard	Dry Pack Single Inlet
		Optional	

CARBURETOR SUPPLEMENTARY INFORMATION

Model Usage	Engine Displ.	Transmission	Carburetors Make	Carburetors Model	No. Used and Type	Barrel Size
Std. Car Exc. Limo. 75 Limo. (A/C Std.) Std. Car With A/C	429	Automatic	Rochester	7027230 7027233 7027231	One 4 BBL Quadra-jet	Pri. 1.375 Sec. 2.250
All California Cars Without A/C				7037230		
All California Cars With A/C Inc. Limo.				7037231		

Form Rev. 4-65

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 11

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL All (Except Eldorado)

ENGINE—COOLING SYSTEM

Type system (pressure, pressure vented, atmospheric, other)			Pressure
Radiator cap relief valve pressure			13.5 - 16.5
Circulation thermostat	Type (choke, bypass)		Choke
	Starts to open at (°F)		172° - 177°
Water pump	Type (centrifugal, other)		Centrifugal Dual Outlet
	GPM @ 1000 pump rpm		19
	Number of pumps		One
	Drive (V-belt, other)		V-Belt
	Bearing type		Double Row Ball Bearing
By-pass recirculation type (internal, external)			Internal
Radiator core type (cellular, tube and fin, other)			Tube & Center
Cooling system capacity	With heater (qt.)		17.2 (Exc. 75 Limo. - A/C Std.)
	Without heater (qt.)		-
	Opt. equipment-specify (qt.)		18.2 A/C 20.7 - 75 Limo. A/C
Water jackets full length of cylinder (yes, no)			Yes
Water all around cylinder (yes, no)			Yes
Radiator hose	Lower	Number and type (molded, straight)	(1) Molded
		Inside diameter	1.75
	Upper	Number and type (molded, straight)	(1) Molded
		Inside diameter	1.50
	By-pass	Number and type (molded, straight)	None
		Inside diameter	None
Fan	Number of blades & spacing		7 @ 54° - 50° - 45° - 40° - 48° - 64° - 59°
	Diameter		18"
	Ratio-fan to crankshaft rev.		1.1:1
	Fan cutout type		None
	Bearing type		Ball
*Drive belts (indicate belt used by letter)	Fan		A B 75 Limo.
	Generator or alternator		A B 75 Limo.
	Water Pump		A B 75 Limo.
	Power Steering	C Std.	D A/C E 75 Limo.
	Air Conditioning		F Exc. Limo.

* Drive Belt Dimensions	A	B	C	D	E	F	G	H	I	J	K
Angle of V	38°	38°	38°	38°	38°	38°					
Nominal length (SAE)	38.08	53.10	49.94	50.24	50.62	56.0					
Width	.380	.460	.380	.460	.460	.460					

Form Rev. 4-65

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (●)

MODEL All (Except Eldorado)

ELECTRICAL—SUPPLY SYSTEM

Battery	Make and Model		Delco Remy
	Voltage Rtg. & Total Plates		12 Volt - 13 Plate
	SAE Designation & Amp Hr. Rtg.		73 Amp. Hrs. @ 20 Hr. Rate
	Location		Right Front Side - Under Hood
	Terminal grounded		Negative
Generator or Alternator	Make		Delco Remy
	Model		1100691 1100760 (75 & A/C)
	Type and rating		42 Amp. 55 (75 & A/C)
	Output at engine idle (neutral)		2.78:1
	Ratio—Gen. to Cr/s rev.		Charge @ Idle
Regulator	Make		Delco Remy
	Model		1119515
	Type		Double Contact
	Cutout relay	Closing voltage @ generator rpm	None
		Reverse current to open	None
	Regulated	Voltage	13.8 - 14.8 @ 100° (Adjust to 14.2)
		Current	None
	Voltage test conditions	Temperature	100 Degrees
		Load	10 Amps.
		Other	

ELECTRICAL—STARTING SYSTEM

Starting motor	Make		Delco Remy
	Model		1108320
	Rotation (drive end view)		Clockwise
	Engine cranking speed		150-200 RPM
	Test conditions		-
	No load test	Amps	70-99
		Volts	10.6
		RPM (min)	7800-12000
Motor control	Switch (solenoid, manual)		Solenoid
	Starting procedure		Cold Start - Depress Acc. to Floor, Remove Foot, Turn Ign. Key Full Right to Start Warm Start - Depress Acc. Halfway Hold Until Engine Starts

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL All (Except Eldorado)

ELECTRICAL—STARTING SYSTEM (cont.)

Motor Drive	Engagement type			Spiral Spline & Over Running Clutch
	Pinion meshes (front, rear)			Front
	Number of teeth	Pinion		9
		Flywheel	Manual	N.A.
			Auto.	166
	Flywheel tooth face width		Manual	N.A.
			Auto.	.500

ELECTRICAL—IGNITION SYSTEM

Coil	Transistorized - Std., Opt., N.A.		N.A.
	Make		Delco Remy
	Model		1115132
	Amps	Engine stopped	2.4
		Engine idling	1.25
stributor	Make		Delco Remy
	Model		1111262
	Cent'fgal adv. in crankshaft degrees @ engine rpm (nominal)	Start (rpm)	0° @ 530 RPM
		Intermediate points deg. @ rpm.	1° - 5° @ 1000 RPM
		Max. deg. @ rpm.	12° - 16° @ 4000 RPM
	Vacuum adv. in crankshaft degrees @ in. Hg. (nominal)	Start (in. Hg.)	10" - 12"
		Intermediate points, deg. @ in. Hg.	0° - 7° @ 12" 11.5° - 19° @ 16"
		Max. deg. in. Hg.	25.5° @ 18.25"
	Breaker gap (in.)		.016"
	Cam angle (deg.)		28° - 32°
	Breaker arm tension (oz.)		19-23 oz
Timing	Crankshaft deg. @ rpm.		5° BTDC
	Mark location		Crankshaft Balancer
Spark Plug	Make		A.C.
	Model		44
	Thread (mm)		14MM
	Tightening torque (lb. ft.)		25 lb/ft.
	Gap		.035
Cable	Conductor type		Resistant Core
	Insulation type		Neoprene
	Spark plug protector		"

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 14

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL All (Except Eldorado)

ELECTRICAL—SUPPRESSION

Locations & type	Packard Electric - Dist. Resistance Wire .3 MFD on Coil Feed Terminal .5 MFD on Gen-Reg. Feed Terminal Two Ground Straps - Rear of Cylinder Head Two Ground Straps - Upper Control Arms.

ELECTRICAL—INSTRUMENTS AND EQUIPMENT

Speedometer	Make	A.C.
	Trip odometer (yes, no)	Yes
Charge indicator—type		Tell-Tale
Temperature indicator—type		Gauge
Oil pressure indicator—type		Tell-Tale
Fuel indicator—type		Gauge
Other		Low Brake - Tell-Tale Cruise Tell-Tale Trunk Warning Lite - Tell-Tale
Windshield wiper	Make	Delco
	Type—Standard	Electric
	Type—Optional	-
	Vacuum booster provision	-
	Washer provision	Yes
Horn	Type	Solenoid Vibrating Diaphram
	Number used	3 (+ Lo D Opt)
	Amp draw (each)	4.5 - 5.5

DRIVE UNITS—CLUTCH (Manual Transmission)

Make & type		None Available
Type pressure plate springs		
Total spring load (lb.)		
No. of clutch driven discs		
Clutch facing	Material	
	Outside & inside dia.	
	Total eff. area (sq. in.)	
	Thickness	
	Engagement cushioning method	
Release bearing	Type & method of lubrication	
Torsional damping	Methods: springs, friction material	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (e)

MODEL All (Except Eldorado)

DRIVE UNITS—TRANSMISSIONS

Manual 3-speed (std. or opt.)	N.A.
Manual 4-speed (std. or opt.)	N.A.
Manual with overdrive (std. or opt.)	N.A.
Automatic (std. or opt.)	Standard

DRIVE UNITS— MANUAL TRANSMISSION

Number of forward speeds			None Available
Transmission ratios	In first		
	In second		
	In third		
	In fourth		
	In reverse		
Synchronous meshing, specify gears			
Shift lever location			
Lubricant	Capacity (pt.)		
	Type recommended		
	SAE viscosity number	Summer	
		Winter	
		Extreme cold	

DRIVE UNITS— MANUAL TRANSMISSION WITH OVERDRIVE

For transmission data see manual transmission section

Type (planetary or other)			None Available
Manual lockout (yes, no)			
Downshift acelerator control (yes, no)			
Minimum cut-in speed			
Gear ratio			
Lubricant	Capacity (pt.) (Overdrive only)		
	Separate filler (yes, no)		
	Type recommended		
	SAE viscosity number	Summer	
		Winter	
		Extreme cold	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 16

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (●)

MODEL All (Except Eldorado)

DRIVE UNITS—AUTOMATIC TRANSMISSION

Trade name		Turbo-Hydramatic
Type describe		Variable Vane Converter With Step Gear Shifts
Method of Selection (Lever, Push Button or other)		Lever
Selector Pattern		P-R-N-DD-L
List gear ratios Selector Pattern and indicate which are used in each selector position		Low Gear 2.48 Intermediate Gear 1.48 High Gear 1.00 Reverse 2.09 Plus Converter Multiplication of 2.00
Max. upshift speeds—drive range		74-90 67-82 (75)
Max. kickdown speeds—drive range		82-64 75-58 (75)
Torque convertor	Number of elements	3
	Max. ratio at stall	2-1
	Type of cooling (air, liquid)	Liquid - Water
Lubricant	Capacity—refill (pt.)	Approx. - 6 Pints
	Type recommended	Fluid Type "A" (Suffix A)
Special transmission atures		

DRIVE UNITS—PROPELLER SHAFT

Number used		1 2 (75)
Type (exposed, torque tube)		Exposed
Outer diameter x length* x wall thickness	Manual 3-speed transmission	Not Available
	Manual 4-speed transmission	Not Available
	Overdrive transmission	Not Available
	Automatic transmission	4.00" X 64.33 X .065 60 Spec. & Brougham 3.50" X 60.83 X .065 62 & 63 Series 2.75 & 2.25 X .083 - 37.80 75 Limo. 2.75 & 2.25 X .083 - 43.65

*Center to center of universal joints, or to centerline of rear attachment.

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 17

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL All (Except Eldorado)

DRIVE UNITS—PROPELLER SHAFT (cont.)

Intermediate bearing	Type (plain, anti-friction)		None on Std. Car Roller Brg. (75)
	Lubrication (fitting, prepack)		Prepack
Universal joints	Make		Saginaw
	Number used		2 3 (75)
	Type (ball and trunnion, cross, other)		Cross - Double Cardon
	Bearing	Type (plain, anti-friction)	Needle
		Lubric. (fitting, prepack)	Prepack
Drive taken through (torque tube or arms, springs)			Four Link Arm
Torque taken through (torque tube or arms, springs)			Four Link Arm

DRIVE UNITS—REAR AXLE

cription			Hypoid
nited Slip differential, type			Cone Clutch
Drive Pinion Offset			1.75
No. of differential pinions			2
Ring gear O.D. (std. ratio)			*
Pinion adjustment (shim, other)			None
Pinion bearing adj. (shim, other)			Collapsable Spacer
Wheel bearing type			Ball
Lubricant	Capacity (pt.)		5
	Type recommended		Mil-L-2105B (Contr. Diff. Spec. Lub)
	SAE viscosity number	Summer	90
		Winter	90
		Extreme cold	90

REAR AXLE RATIO TOOTH COMBINATIONS

(See page 4 for axle ratio usage)

Axle ratio		2.94	3.21
No. of teeth	Pinion	47	45
	Ring gear	16	14

* Ring Gear O.D.
9.424 9.422

2.94 Std. All Series (Exc. 75)
3.21 Std. on 75 Series
Std. on All A/C Cars
Opt. All Series Exc. 75 & A/C

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL All (Except Eldorado)

DRIVE UNITS—WHEELS

Type & material		Slotted Steel Disc
Rim (size and flange type)	Std.	15-6JK
	Opt.	None
Attachment	Type (bolt or stud)	Stud
	Circle diameter	5"
	Number and size	5 1/2 X 20

DRIVE UNITS—TIRES

Standard (List option below)	Size & ply	9.00 2 Ply-4 Ply Rating Black	8.20 4 Ply-8 Ply Rating (75)
	Type - Nylon, etc.	Rayon	
Rev/mile at 50 mph.		714	713
Inflation press. (cold)	Front	24	28
	Rear	24	28
Optional tires - size and ply		9.00 X 15 2 Ply 4 Ply Rating W/W	8.20 X 15 4 Ply 8 Ply Rating W/W

BRAKES—SERVICE

Type (duo-servo, disc, balanced, etc.)			Hydraulic Duo-Servo
Self adjusting (std., opt., N.A.)			Std.
Hydraulic system type (single, dual, etc.)			Dual
Power brake make & type (remote, integral, etc.)			Moraine & Bendix - Direct Hyd. Vacuum
Effective area (sq. in.) *			203.60
Gross lining area (sq. in.) **			233.50
Swept drum area (sq. in.) ***			377.00
Percent brake effectiveness—front			59%
Drum or Rotor	Diameter	Front	12"
		Rear	12"
	Type and material		Composite Cast Iron Finned
	Rotor (vented or solid)		N.A.
	No. pistons per caliper		N.A.
Wheel cylinder bore	Front		1 3/16
	Rear		15/16
Master cylinder bore			1.00
Available pedal travel			4.28
Line pressure at 100 lb. pedal load			930 PSI
Shoe clearance adjustment			.010 - .030

* Excludes rivet holes, grooves, chamfers, etc.

** Includes rivet holes, grooves, chamfers, etc.

*** Total swept area for four brakes:
Widest lining contact width for each brake x its drum circumference.

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 19

'AKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL All (Except Eldorado)

BRAKES—SERVICE (cont.)

Brake lining	Drum or Disc			Drum	
	Bonded or riveted			Riveted	
	Front Wheel	Material		Molded Asbestos	
		Size (length x width x thickness)	Prim. or out-board	11.00 X 2.5 X .26	
			Second. or in-board	11.00 X 2.5 X .24	11.00 X 2.5 X .26 (75)
		Segments per shoe		1	
	Rear Wheel	Material		Molded Asbestos	
		Size (length x width x thickness)	Prim. or out-board	12.36 X 2.5 X .28	
			Second. or in-board	12.36 X 2.5 X .26	12.36 X 2.5 X .28 (75)
		Segments per shoe		1	

BRAKES—PARKING

Type of control		Foot Operated - Vacuum Released
Location of control		Left Side Below Inst. Panel
Operates on		Rear Service Brakes
If separate from service brakes	Type (internal or external)	N.A.
	Drum diameter	N.A.
	Lining size (length x width x thickness)	N.A.

FRAME

Type and description (Separate frame, unitized frame, partially - unitized frame)	Perimeter Frame

STEERING

Manual (std., opt., NA)				N.A.	
Power (std., opt., NA)				Std.	
Adjustable steering wheel (tilt, swing, other)		Type and description		Tilt & Telescope	
		(std., opt., NA)		Opt.	
Wheel diameter		Manual		N.A.	
		Power		15.5"	
Turning diameter	Outside front	Wall to wall (l. & r.)		47.9 (62-63)	48.9 (60-61) 57.4 (75)
		Curb to curb (l. & r.)		44.7 (62-63)	45.8 (60-61) 54.4 (75)
	Inside rear	Wall to wall (l. & r.)		26.5 (62-63)	27.4 (60-61) 35.7 (75)
		Curb to curb (l. & r.)		27.1 (62-63)	28.0 (60-61) 36.3 (75)
Outside wheel angle with inside wheel at 20°				18° - 10'	
ıual	Gear	Type		N.A.	
		Make		N.A.	
		Ratios	Gear	N.A.	
			Overall	N.A.	
	No. wheel turns			N.A.	

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 20

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (a)

MODEL All (Except Eldorado)

STEERING (cont.)

Power	Type (coaxial, linkage, etc.).			Variable Ratio Hydraulic Power *
	Make			Saginaw
	Gear	Type		Concentric Gear / Ball Nut Sector
		Ratios	Gear	16.1 / 17.5
			Overall	16.6 / 18.2
	Pump driven by			Belt
	Number wheel turns			2.7 / 3.7
Linkage	Type			Parallel Draglink
	Location (front or rear of wheels, other)			Rear
	Drag link (trans. or longit.)			Trans.
	Tie rods (one or two)			2
Steering Axis	Inclination at camber (deg.)			6° @ 0°
	Bearings (type)	Upper		Spherical Joints
		Lower		Spherical Joints
		Thrust		Spherical Joints
Wheel Alignment (Knee at curb weight and preferred)	Caster (deg.)			-1° to -2° All 682-683 Exc. ALC - 1/2° to - 1 1/2° All Series With ALC
	Camber (deg.)			Left Side + 3/8° to - 1/8° / Right Side + 1/8° to - 3/8°
	Toe-in (outside track inches)			1/4" to 5/16
Steering spindle & joint type				Spherical
Wheel spindle	Diameter	Inner bearing		1.348 - 1.343
		Outer bearing		.8430 - .8435
	Thread size			3/4 - 20
	Bearing type			Tapered Roller

* Inline Hydr. Power

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 21

KE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (e)

MODEL All (Except Eldorado)

SUSPENSION—GENERAL

(See Supplemental page for details on Air Suspension)*

Provision for car leveling		Auto. Level Control Std. on 60 Spec. & Eldorado
Provision for brake dip control		In Frt. Susp. Design
Provision for acc. squat control		In Rear Susp. Design
Special provisions for car jacking		Bumper Type
Shock absorber front & rear	Type	Direct Action
	Make	Delco
	Piston dia.	1"
Other special features		Nylon Piston Ring. Freon Envelope Eliminates Aeration of Oil

SUSPENSION—FRONT

Type and description		Independent - Coil		
Spring	Type	Coil		
	Material	9260		
	Size (coil design height & I.D.; bar length x dia.)	10.09"x4.00x157.70x680 (62 & 63) 10.09"x4.00x165.70x690 (60 Spec.)	10.44 x 4.00 x 163.50 x 730	(75)
	Spring rate (lb. per in.)	335 (60 & 61)	325 (62-63)	425 (75)
	Rate at wheel (lb. per in.)	89 (60 & 61)	86 (62-63)	120 (75)
Stabilizer	Type (link, linkless, frameless)	Link		
	Material & bar diameter	1085 Steel	.815 (60-62-63)	.875 (75)

SUSPENSION—REAR

Type and description		4 Link Susp.		
Drive and torque taken through		Links		
Spring	Type	Coil		
	Material	9260 Steel		
	Size (length x width, coil design height & I.D.; bar length & dia.	9.00" x 5.50" x 145.9" x .590 9.17 x 5.20 x 149.75 x .695		
	Spring rate (lb. per in.)	95 (60 & 61)	115 (62-63)	250 (75)
	Rate at wheel (lb. per in.)	110 (60 & 61)	110 (62-63)	157 (75)
	Mounting insulation type	Rubber		
	If leaf: No. of leaves	N.A.		
	If leaf: Shackle (comp. or tens)	N.A.		
Stabilizer	Type (link, linkless, frameless)	N.A.		
	Material	N.A.		
Track bar type		N.A.		

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 22

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (●)

MODEL 68069 68367 68269 68247 68249 / 68169 68369 68347 68349 — 75

BODY—MISCELLANEOUS INFORMATION

Drs. hinged (front, rear)	Front doors	Front
	Rear doors	Center
Type of finish (lacquer, enamel, other)		Acrylic
Hood counterbalanced (yes, no)		Yes
Hood release control (internal, external)		External
Vehicle Indent. No. location		R.H. Side Rail at #1 Crossmember
Engine No. location		Rear Top Crankcase
Theft protection - type		Ign. Key Start Door Lock
Vent window control method (crank, friction pivot)	Front	60 & 68467 Eld. - Power Std. All others crank
	Rear	" " " "
Seat cushion type	Front	Zig-Zag Spring - 62 & 63 Coil Spring 60-61-75
	Rear	Zig-Zag Spring - 62 & 63 Coil Spring 60-61-75
	3rd seat	
Seat back type	Front	Zig-Zag Spring - 62 & 63 Coil Spring 60-61-75
	Rear	Zig-Zag Spring - 62 & 63 Coil Spring 60-61-75
	3rd seat	None
Windshield glass type (i.e., ·le curved - laminated plate)		Compound Curve - Laminated
Side glass type (i.e., curved - tempered plate)		Vent Window Curved - Laminated Side Window Curved Tempered
Backlight glass type (i.e., compound curved - tempered plate, three piece)		Tempered Plate

	CC	SC	CC			SC
Windshield glass exposed surface area	1532.2	1467.9	1532.2	1467.9		1532.2
Side glass exposed surface area	1937.7	1917.0	1856.5	1703.1	1711.1	2137.8
Backlight glass exposed surface area	852.8	876.0	1095.0	7432		496.8
Total glass exposed surface area	4322.7	4260.9	4483.7	3914.2	3922.2	4166.8

LAMP HEIGHT AND SPACING

Height above ground to center of bulb	Headlamp	Highest *	31.77	31.43	31.34	31.37	31.41	32.52
		Lowest	25.41	24.78	24.68	24.73	24.76	25.86
	Tail	Highest	25.34	26.42	26.52	62.70	26.44	26.30
		Lowest	-					
Distance from C/L of car to center of bulb	Headlamp	Inside	-					
		Outside *	35.00					
	Tail	Inside	-					
		Outside	34.80					
	Directional	Front	25.12					
		Rear	34.80					

* If single headlamps are used enter here.

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 23

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (e)

MODEL All (Except Eldorado)

CONVENIENCE EQUIPMENT

(Indicate whether standard, optional or NA on each series)

Power windows	Side Windows	Std. on 60 & 61 & 63 & 75 Opt. on 62 Series
	Vent Windows	Std. on 60 & 61 Opt. on all others Exc. Eld
	Backlight or tailgate	N.A.
Power seats (specify type as well as availability)		2 Way Std. 60-61-63 & 75 6 Way Opt. 2 Way Not Available on 62 Series
Reclining front seat back		With Bucket Seats Only
Front seat headrest		With Bucket Seats Only
Radios (specify type as well as availability)		Delco Radio AM-AM-FM - FM Stereo Opt. all Series
Rear seat speaker		Std. With Radio Opt.
Power Antenna		Std. With Radio Opt.
Clock		Std.
Air Conditioner (specify type and availability)		Opt. All Series Exc. 75 Std. on 75 Limo.
Speed warning device		N.A.
Speed control device		Opt.
Ignition lock lamp		Std.
Back up lamp		Std.
Dome lamp		Std.
Glove compartment lamp		Std.
Prkg. brake signal lamp		Std.
Luggage compartment lamp		Std.
Underhood lamp		N.A.
Courtesy lamp		Std.
Map lamp		Std.
Auto. trans. quad. lamp		Std.
Emergency flasher lamp		Std.
Cornering light lamp		Std.
Rear Window Defogger		Opt.

Heater & Defroster - Std. on all Series

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

WEIGHTS

Model	CURB WEIGHT - POUNDS Front	Rear	Total	% PASS. WEIGHT DISTRIBUTION Pass. In Front Front	Pass. In Front Rear	Pass. In Rear Front	Pass. In Rear Rear	SHIPPING WEIGHT
68069	2451	2423	4874					4678
68169	2468	2443	4911					4715
68269	2376	2319	4695					4499
68369	2384	2346	4730					4534
68249	2379	2312	4691					4495
68349	2386	2342	4728					4532
68247	2351	2292	4643					4447
68347	2376	2306	4682					4486
68367	2361	2314	4675					4479
69723	2819	2727	5546					5344
69733	2868	2770	5638					5436

Accessories & Equipment Differential Weights				Remarks
Power Window Regulators	12.5	11.4	23.9	Calais Sedan
Power Window Regulators	14.8	12.7	27.5	Calais Coupe
Power Vent Regulators	4.0	2.5	6.5	
Power Door Lock - Sedan	8.4	4.6	13.0	
Power Door Lock - Coupe	5.8	3.2	9.0	
Power Seat - 6 Way	11.4	6.2	17.6	Calais
Power Seat - 6 Way	7.7	4.2	11.9	DeVille and Fleetwood
Power Trunk Lock	-	9.6	9.6	
Power Trunk Lock	-	8.9	8.9	Installed With Power Door Locks
Guidematic	2.1	-	2.1	
Cruise Control	11.5	1.0	12.5	
T & T Steering Wheel	1.3	.4	1.7	
Automatic Climate Contr.	122.5	2.5	125.0	
Radio & Antenna (AM)	11.0	4.2	15.2	
Radio & Antenna (FM)	11.4	4.2	15.6	
Radio & Antenna (Stereo)	14.5	5.0	19.5	
Rear Window Defogger	-	4.5	4.5	
Padded Roof - Sedan	3.5	5.5	9.0	DeVille
Padded Roof - Coupe	3.7	6.3	10.0	DeVille
Controlled Differential	-	3.5	3.5	
Automatic Leveling	11.2	2.8	14.0	Calais & DeVille

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 25

INDEX

SUBJECT	PAGE NO.
Automatic Transmission	1, 16
Axis, Steering	20
Axle, Rear	1, 17
Battery	12
Bearings, Engine	5, 6, 7
Belts - Fan, Generator, Water Pump	11
Body - General Information, types	Title, 1, 2, 22
Exterior Dimensions	1
Interior Dimensions	2
Brakes - Parking, Service, Power	18, 19
Camber	20
Camshaft	6
Capacities	
Cooling System	11
Fuel Tank	10
Lubricants	
Engine Crankcase	8
Transmission and Overdrive	15, 16
Rear Axle	17
Carburetor	4, 9, 10
Caster	20
Choke, Automatic	10
Clutch - Pedal Operated	14
Coil, Ignition	13
Connecting Rods	5
Convienience Equipment	23
Cooling System	11
Crankcase Ventilation	8
Crankshaft	5
Cylinders and Cylinder Head	3
Distributor - Ignition	13
Electrical System	12, 13, 14
Engine	
Bore, Stroke, Displacement, Type	1, 3
Compression Ratio	1, 3
Firing Order, Cylinder Numbering	3
General Information, H.P. & Torque	1, 3
Lubrication	7, 8
Power Teams	4
Exhaust Emission Control	9
Exhaust System	8
Equipment Availability	22
Fan, Cooling	11
Filters - Engine Oil, Fuel System	8, 10
Frame	19
Front Suspension	21
Fuel, Fuel Pump, Fuel System	1, 3, 10
Fuel Injection	1, 10
Generator and Regulator	12
Glass	22
Height (Lamps)	14
Headroom - Body	2
Heights - Overall	1
Horns	14
Horsepower - Brake	1, 3, 4
Ignition System	13
Inflation - Tires	18
Instruments	8, 14
Kingpin (Steering Axis)	20
Lamp Height & Spacing	22
Legroom	2
Lengths - Overall	1
Lifters, Valve	6
Linings - Clutch, Brake	14, 18, 19
Lubrication	7, 8, 14, 15, 16, 17
Luggage Capacity	2
Motor, Starting	12
Muffler	8
Overdrive	15
Piston Pins & Rings	3, 5
Pistons	3, 5
Power Brakes	18
Power Steering	19
Power Teams	4
Propeller Shaft, Universal Joints	16, 17
Pumps - Oil, Fuel	8, 10
Water	11
Radiator, Hoses	11
Ratios - Axle	1, 4, 17
Compression	1, 3, 4
Steering	19, 20
Transmission	15, 16
Rear Axle	1, 4, 17
Regulator - Generator	12
Rims	18
Rings, Piston	5
Rods - Connecting	5
Shock Absorbers, Front & Rear	21
Spark Plugs	13
Speedometer	14
Springs - Front & Rear Suspension	21
Valve, Engine	6
Stabilizer (Sway Bar) - Front & Rear	21
Starting Motor	12
Steering	19, 20
Suppression - Ignition, Radio	14
Suspension - Front & Rear	21
Tailpipe	8
Thermostat, Cooling	11
Timing, Engine & Valve	6, 7, 13
Tires	1, 18
Toe in	20
Torque Converter	16
Torque - Engine, Rated	1, 3, 4
Transmission - Types	1, 4, 10, 15, 16
Automatic	1, 4, 10, 15, 16
Manual & Overdrive	1, 4, 10, 15
Ratios	15, 16
Track	1
Trunk Luggage Capacity	2
Turning Diameter	19
Unitized Construction	19
Universal Joints, Propeller Shaft	16, 17
Valves - Intake & Exhaust	6, 7
Vibration Damper	6
Voltage Regulator	12
Water Pump	11
Weights - Shipping, Curb	24
Wheel Alignment	20
Wheelbase	1
Wheels & Tires	18
Wheel Spindle	20
Widths - Car & Body	1
Windshield	22
Windshield Wiper	14

Downloaded from www.Manualslib.com manuals search engine

AMA-40A

AMA Specifications—Passenger Car

The information contained herein is prepared, distributed by, and is solely the responsibility of the automobile manufacturing company to whose products it relates. Questions concerning these specifications should be directed to the manufacturer whose address is shown below. This uniform specification form was developed by the automobile manufacturing companies under the auspices of the Automobile Manufacturers Association.

MANUFACTURER	CAR NAME	
Cadillac Motor Car	Cadillac	
MAILING ADDRESS	MODEL YEAR	ISSUED: 10-6-66
2860 Clark Avenue, Detroit, Mich.	1967	REVISED (•)

NOTES:
1. The Specifications herein are those in effect at date of compilation and are subject to change without notice by the manufacturer.
2. UNLESS OTHERWISE INDICATED:
   a. Specifications apply to standard models without optional equipment. Significant deviations are noted.
   b. Nominal design dimensions are used throughout these specifications.

TABLE OF CONTENTS

General Specifications 1,2
Engine–Mechanical 3
Electrical 12
Drive Units 14
Brakes 18
Steering 19
Suspensions 21
Weights 24
Index 25

BODY—TYPES AND STYLE NAMES—

Body type, number of passenger & style names; use manufacturer's code for series & body style.

DESCRIPTION	NO. PASS.	STYLE NO.	VEHICLE IDENT. NO.
Fleetwood Eldorado	5	69347	H7 - 100001

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 1

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

GENERAL SPECIFICATIONS

(All dimensions in inches unless otherwise indicated)

MODEL		Additional Information Page No.:	69347 - Eldorado
Wheelbase (L101)			120
Track	Front (W101)		63.5
	Rear (W102)		63.0
Maximum Overall Dimensions	Length (L103)		221
	Width (W103)		79.9
	Height (H101)		53.8
Transmission (Specify trade name - opt., not available)	Manual - 3 speed	15	None
	Manual - 4 speed	15	None
	Overdrive	15	None
	Automatic	16	Turbo-Hydramatic
Axle ratio	Manual - 3 speed	17	None
	Manual - 4 speed	17	None
	Overdrive	17	None
	Automatic	17	3.21
Tire size		18	9.00 X 15 2 Ply - 4 Ply Rating
Engine	Type, no. cyl., valve arr.	3	O.V. - V8 - 90°
	Fuel system (Carb., other)	10	Carburetor
	Bore and stroke	3	4.130 - 4.000
	Piston displ., cu. in.	3	429
	Std. compression ratio	3	10.5:1
	Max. bhp at engine rpm	3	340 @ 4600
	Max. torque at rpm	3	480 @ 3000

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 2

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (o)

GENERAL SPECIFICATIONS—DIMENSIONS

(All dimensions in inches unless otherwise indicated)
(Supplemental data available on request)

MODEL	SAE Ref. No.	69347 Eldorado
FRONT COMPARTMENT		
Shoulder room	W3	59.6
Hip room	W5	62.2
Max. eff. leg room - accelerator	L34	41.2
Effective head room	H61	37.9
H Point to Heel point	H30	7.6
REAR COMPARTMENT		
Shoulder room	W4	55.7
Hip room	W6	54.2
Minimum effective leg room	L51	36.2
Effective head room	H63	37.7
LUGGAGE COMPARTMENT		
Usable luggage capacity	V1	13.462
Liftover height	H195	27.8
Position of spare tire storage		Vertical Behind Rear Seat
Method of holding lid open		Spring
STATION WAGON—THIRD SEAT		
Hip room	W86	N.A.
Effective leg room	L86	
Effective head room	H86	
Seat facing direction		

STATION WAGON—CARGO SPACE

MODEL	SAE Ref. No.	N.A.
Minimum distance between wheel houses at floor level	W201	
Rear end opening width at belt	W204	
Floor length from back of front seat at floor level to inside of closed tail gate	L202	
Minimum horizontal distance from top rear of front seat back to inside of tail gate at belt	L204	
Maximum height - floor covering to headlining at centerline of rear axle	H201	
Maximum height of rear opening - tail and lift gates open	H202	
Cargo volume index (cu. ft.) $\frac{W4 \times L204 \times H201}{1728}$	V2	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 3

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 - Eldorado

ENGINE—GENERAL

Type, no. cyls., valve arr.		90° - V8 - O.V.
Bore and stroke (nominal)		4.13 X 4.00
Piston displacement, cu. in.		429
Bore spacing (C/L to C/L)		4.562
No. system (front to rear)	L. Bank	1 - 3 - 5 - 7
	R. Bank	2 - 4 - 6 - 8
Firing order		1 - 8 - 7 - 2 - 6 - 5 - 4 - 3
Compres. ratio (nominal)		10.5:1
Cylinder Head Material		Cast Iron
Cylinder Block Material		Cast Iron
Cylinder Sleeve-Wet, dry, none		None
Number of mounting points	Front	1
	Rear	2
Engine installation angle		0°
Taxable horsepower $\frac{Dia^2 \times No.Cyl.}{2.5}$		54.6
Publishing max. bhp* @ eng. RPM		340 @ 4600
Publishing max. torque* (lb. ft. @ RPM)		480 @ 3000
Recommended fuel regular - premium		Premium
Idle speed(spec. neutral or drive)	Manual	N.A.
	Automatic	480 Drive

ENGINE—PISTONS

Material			Aluminum Alloy
Description and finish			Slipper Type Cam Ground Control Expansion
Weight (piston only) oz.			21.76
Clearance (limits)	Top land		.033 - .038
	Skirt	Top	.0006 - .0010
		Bottom	.000
Ring groove depth	No. 1 ring		.215
	No. 2 ring		.215
	No. 3 ring		.167
	No. 4 ring		None

*Max. bhp (brake horsepower) and max. torque corrected to 60° F and 29.92 in. Hg atmospheric pressure.

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 4

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (●)

POWER TEAMS

(Indicate whether standard or optional)

MODEL AVAILABILITY	ENGINE					TRANSMISSION	AXLE RATIO (Std. first) (Indicate A/C ratio)
	Displ. cu. in.	Carburetor	Compr. Ratio	BHP @ RPM	Torque @ RPM		
Eldorado	429	4BBL	10.5:1	340 @ 4600	480 @ 3000	Hydramatic	3.21:1

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 - Eldorado

ENGINE—RINGS

Functon (top to bottom)	No. 1, oil or comp.	Comp.
	No. 2, oil or comp.	Comp.
	No. 3, oil or comp.	Oil
	No. 4, oil or comp.	None
Compression	Description - material, coating, etc.	#1 Molybdenum Filled Cast Iron #2 Phosphate Coated Cast Iron
	Width	.0625
	Gap	.013 - .030
Oil	Description - material, coating, etc.	Multi-Piece Steel Chrome Plated - Notched I.D. Rail
	Width	.1875
	Gap	.015 - .061
Expanders		Yes

ENGINE—PISTON PINS

Material			1045
Length			3.090
Diameter			.9994 - .9997
Type	Locked in rod, in piston, floating, etc.		Locked in Rod
	Bushing	In rod or piston	None
		Material	None
Clearance	In piston		.00005 - .00015
	In rod		Press Fit
Direction & amount offset in piston			.062 Toward Max. Thrust Side

ENGINE—CONNECTING RODS

Material		1041 Steel
Weight (oz.)		19.36
Length (center to center)		6.50
Bearing	Material & Type	M400 Aluminum Steel Backed
	Overall length	.755 - .880
	Clearance (limits)	.0005 - .0021
	End play	.008 - .014

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 Eldorado

ENGINE—CRANKSHAFT

Material			Pearlitic Malleable Iron
Vibration damper type			Rubber Absorption
End thrust taken by bearing (No.)			#3 Center Main
Crankshaft end play			.001" - .007"
Main bearing	Material & type		M400 Aluminum - M100 Babbitt
	Clearance		.0006" to .003"
	Journal dia. and bearing overall length	No. 1	3.000" X 1.120"
		No. 2	3.000" X 1.062"
		No. 3	3.000" X 1.138"
		No. 4	3.000" X 1.062"
		No. 5	3.000" X 1.120"
		No. 6	None
		No. 7	None
	Dir. & amt. cyl. offset		See Piston
Crankpin journal diameter			2.25

ENGINE—CAMSHAFT

Location			Center of V
Material			G.M. 120M Cast Iron
Bearings	Material		Steel Backed Babbitt
	Number		5
Type of Drive	Gear or chain		Silent Chain
	Crankshaft gear or sprocket material		Sintered Iron G.M. 3884M
	Camshaft gear or sprocket material		Die Cast Aluminum - Nylon Gear
	Timing chain	No. of links	46
		Width	.750
		Pitch	.500

ENGINE—VALVE SYSTEM

Hydraulic lifter (Std, opt, NA)		Std.
Valve rotator, type (intake, exhaust)		None
Rocker ratio		1.65:1
Operating tappet clearance (indicate hot or cold)	Intake	Auto
	Exhaust	Auto
Timing marks on flywheel, damper, other		Crankshaft Balancer

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 - Eldorado

ENGINE—VALVE SYSTEM (cont.)

Timing	Intake	Opens (°BTC)	39° With .001 Lift
		Closes (°ABC)	109° " " "
		Duration - deg.	328° " " "
	Exhaust	Opens (°BBC)	86° " " "
		Closes (°ATC)	62° " " "
		Duration - deg.	328° " " "
	Valve opening overlap		
Intake	Material		1041 Alum. Steel
	Overall length		4.794
	Actual overall head dia.		1.875
	Angle of seat & face		Seat in Head 45° Valve Face 44°
	Seat insert material		None
	Stem diameter		.3415 - .3425
	Stem to guide clearance		.0005 - .0025
	Lift (@ zero lash)		.440
	Outer spring press. and length	Valve closed (lb. @ in.)	60-65 @ 1.946
		Valve open (lb. @ in.)	155-165 1.496"
	Inner spring press. and length	Valve closed (lb. @ in.)	None
		Valve open (lb. @ in.)	None
Exhaust	Material		21 - 4N
	Overall length		4.815
	Actual overall head dia.		1.500
	Angle of seat & face		Seat 45° Face 44°
	Seat insert material		None
	Stem diameter		.3415 - .3420
	Stem to guide clearance		.0010 - .0025
	Lift (@ zero lash)		.440
	Outer spring press. and length	Valve closed (lb. @ in.)	60-65 @ 1.946
		Valve open (lb. @ in.)	155-165 @ 1.496
	Inner spring press. and length	Valve closed (lb. @ in.)	None
		Valve open (lb. @ in.)	None

ENGINE—LUBRICATION SYSTEM

Type of lubrication (splash, pressure, nozzle)	Main bearings	Pressure
	Connecting rods	Pressure
	Piston pins	Splash
	Camshaft bearings	Pressure
	Tappets	Pressure
	Timing gear or chain	Metered Centrifugal Flow
	Cylinder walls	Intermediate Jet

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 8

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 - Eldorado

ENGINE—LUBRICATION SYSTEM (cont.)

Oil pump type	Spur Gear
Normal oil pressure (lb. @ engine rpm)	30-35 @ 30 MPH
Oil pressure sending unit (elect. or mech.)	Electric
Type oil intake (floating, stationary)	Stationary
Oil filter system (full flow, partial, other)	Full Flow
Filter replacement (element, complete)	Element
Capacity of crankcase, less filter-refill (qt.)	4 Qts. - 1 Qt. Filter
Oil grade recommended (SAE viscosity and temperature range)	+ 32° F. SAE 20W - IOW 30 0° to 32 F SAE IOW - IOW 30 Below 0°F SAE - 5W - 5W20
Engine Service Requirement (MM, MS, etc.)	MS - GM 4745M

ENGINE—EXHAUST SYSTEM

Type (single, single with cross-over, dual, other)		Dual With Single Outlet
Muffler No. & type (reverse flow, straight thru, separate resonator)		One Muffler Reverse Flow Double Inlet & Single Outlet. One Resonator Straight Thru.
Exhaust pipe dia. (O.D., wall thickness)	Branch	None
	Main	Dual 2.00 X .084 Laminated
Tail pipe diameter (O.D. & wall thickness)		Single 2.24 X .060 Laminated

ENGINE— CRANKCASE VENTILATION SYSTEM

Type (ventilates to atmos., induction system, other)		Standard	Induction System
		Optional	None
Control Unit	Make and model		AC
	Location		In Oil Seperator Mounted In RH Rocker Arm Cove
	Energy source (manifold vacuum, carburetor air stream, other)		Manifold Vacuum
	Control method (variable orifice, fixed orifice, other)		Spring Loaded Valve Variable Orifice
Complete system	Discharges (to intake manifold, carb. air intake, air cleaner intake, other)		Intake Manifold
	Air inlet (breather cap, carburetor air cleaner, other)		Crankcase Breather (Non-Calif. Cars) Air Cleaner (Calif. Cars)
	Flame arrestor (screen, check valve, other)		Check Valve

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 9

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

ENGINE—EXHAUST EMISSION CONTROL

Type (Air injection, engine modifications, other)			Air Injection Type				
Air Injection Pump	Type		Saginaw Steering Gear				
	Displacement		19.3 Cu. In.				
	Drive ratio		1.5:1				
	Drive type		Belt				
	Relief valve (type)		Papett				
	Filter (describe)		Seperate Air Cleaner				
Air Injection System	Air distribution (head, manifold, etc.)		Cylinder Head				
	Point of entry		Manifold				
	Injection tube I.D.		5/16				
	Check valve type		Diaphram (Delco)				
	Backfire protection (type)		RPD - Anti-Backfire				
Carburetor	Make		Carter or Rochester Built Quadrajet				
	Model		4BBL Model 4 MV				
	Barrel size		Pri. 1.375 Sec. 2.250				
	Idle speed	Drive	550 A/C Off				
		Neutral	-				
Distributor	Aux. Adv. Systems (type)		* None				
	Make		Same as Std. Car				
	Model		"	"	"	"	
	Cent'fgal adv. in crank degrees @ eng. rpm.	Start (rpm)	"	"	"	"	
		Intermed. points deg. @ rpm	"	"	"	"	
		Max. deg.@rpm.	"	"	"	"	
	Vacuum adv. in. crank degrees@ eng. rpm	Start (in Hg) Intermed. points deg.@ in. Hg Max. deg.@ in.	"	"	"	"	
	Vacuum Source		"	"	"	"	
Timing - Crank degrees @ rpm			"	"	"	"	
Cooling System (describe changes)			"	"	"	"	
Exhaust System (describe changes)			"	"	"	"	

* A Thermostatic Vacuum Adv. Switch Mounted in Radiator On All A/C Equipped Cars

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac **MODEL YEAR** 1967 **DATE ISSUED** 10-6-66 **REVISED** (e)

MODEL 69347 Eldorado

ENGINE—FUEL SYSTEM

(See supplemental page for Details of Fuel Injection, Supercharger, etc. if used)

Induction type: Carburetor, fuel injection, supercharger.			Carburetor
Fuel Tank	Refill capacity (gals.)		24
	Filler location		Above Rear Bumper - Center of Car
Fuel Pump	Type (elec. or mech.)		Mechanical
	Locations		Lower Left Side of Eng.
	Pressure range		5.25 - 6.50 @ 1800 RPM
Vacuum booster (std., optional, none)			None
Fuel Filter	Type		AC
	Locations		Top Center - Front of Eng.
Carburetor	Choke type		Remote Pocket in Manifold
	Intake manifold heat control (exhaust or water)		Exhaust
	Air cleaner type	Standard	Dry Pack Single Inlet
		Optional	-

CARBURETOR SUPPLEMENTARY INFORMATION

Model Usage	Engine Displ.	Transmission	Carburetors		No. Used and Type	Barrel Size
			Make	Model		
69347	429	Automatic	Rochester		One 4BBL Quadra-jet	Pri. 1.375 Sec. 2.250
Std. Car Non A/C				7027234		
Std. Car - A/C				7027235		
Calif. Car - Non A/C				7037234		
Calif. Car - A/C				7037235		

Form Rev. 4-65

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 11

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

ENGINE—COOLING SYSTEM

Type system (pressure, pressure vented, atmospheric, other)			Pressure
Radiator cap relief valve pressure			13.5 - 16.5
Circulation thermostat	Type (choke, bypass)		Choke
	Starts to open at (°F)		172° - 177°
Water pump	Type (centrifugal, other)		Centrifugal Dual Outlet
	GPM @ 1000 pump rpm		19
	Number of pumps		One
	Drive (V-belt, other)		V-Belt
	Bearing type		Double Row Ball Bearing
By-pass recirculation type (internal, external)			Internal
Radiator core type (cellular, tube and fin, other)			Tube & Center
Cooling system capacity	With heater (qt.)		17.2
	Without heater (qt.)		-
	Opt. equipment-specify (qt.)		18.2 with A/C
Water jackets full length of cylinder (yes, no)			Yes
Water all around cylinder (yes, no)			Yes
Radiator hose	Lower	Number and type (molded, straight)	1-Molded
		Inside diameter	1.75
	Upper	Number and type (molded, straight)	1-Molded
		Inside diameter	1.50
	By-pass	Number and type (molded, straight)	None
		Inside diameter	None
Fan	Number of blades & spacing		7 @ 54° - 50° - 45° - 40° - 48° - 64° - 59°
	Diameter		18"
	Ratio-fan to crankshaft rev.		1.1:1
	Fan cutout type		None
	Bearing type		Ball
*Drive belts (indicate belt used by letter)	Fan		A
	Generator or alternator		A
	Water Pump		A
	Power Steering		A
	Air Conditioning		B Matched 2 Belts

Drive Belt Dimensions	A	B	C	D	E	F	G	H	I	J	K
Angle of V	38°	38°									
Nominal length (SAE)	51.64	55.32									
Width	.380	.460									

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 12

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

ELECTRICAL—SUPPLY SYSTEM

Battery	Make and Model		Delco-Remy
	Voltage Rtg. & Total Plates		12 Volt - 13 Plate
	SAE Designation & Amp Hr. Rtg.		73 Amp. Hrs. @ 20 Hr. Rate
	Location		Right Front Side - Under Hood
	Terminal grounded		Negative
Generator or Alternator	Make		Delco Remy
	Model		1100641 1100760 A/C
	Type and rating		42 Amp. 55 Amp.
	Output at engine idle (neutral)		2.78:1
	Ratio—Gen. to Cr/s rev.		Charge @ Idle
Regulator	Make		Delco Remy
	Model		1119515
	Type		Double Contact
	Cutout relay	Closing voltage @ generator rpm	None
		Reverse current to open	None
	Regulated	Voltage	13.8 - 14.8 @ 100 Deg. (Adjust to 14.2)
		Current	None
	Voltage test conditions	Temperature	100 Deg.
		Load	10 Amps.
		Other	

ELECTRICAL—STARTING SYSTEM

Starting motor	Make		Delco Remy
	Model		1107389
	Rotation (drive end view)		Clockwise
	Engine cranking speed		150-200 RPM
	Test conditions		-
	No load test	Amps.	70-99
		Volts	10.6
		RPM (min)	7800-12000
Motor control	Switch (solenoid, manual)		Solenoid
	Starting procedure		Cold Start - Depress Acc. to Floor, Remove Foot, Turn Ign. Key Full Right to Start Warm Start - Depress Acc. Halfway Hold Until Engine Starts

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 13

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

ELECTRICAL—STARTING SYSTEM (cont.)

Motor Drive	Engagement type			Spiral Spline & Over Running Clutch
	Pinion meshes (front, rear)			Front
	Number of teeth	Pinion		9
		Flywheel	Manual	N.A.
			Auto.	166
	Flywheel tooth face width		Manual	N.A.
			Auto.	.500

ELECTRICAL—IGNITION SYSTEM

Coil	Transistorized - Std., Opt., N.A.		N.A.
	Make		Delco Remy
	Model		1115132
	Amps	Engine stopped	2.4
		Engine idling	1.25
Distributor	Make		Delco Remy
	Model		1111262
	Cent'fgal adv. in crankshaft degrees @ engine rpm (nominal)	Start (rpm)	0° @ 530 RPM
		Intermediate points deg. @ rpm.	1° - 5° @ 1000 RPM
		Max. deg. @ rpm.	12° - 16° @ 4000 RPM
	Vacuum adv. in crankshaft degrees @ in. Hg. (nominal)	Start (in. Hg.)	10" - 12"
		Intermediate points, deg. @ in. Hg.	0° - 7° @ 12" 11.5° - 19° @ 16"
		Max. deg. in. Hg.	25.5° @ 18.25"
	Breaker gap (in.)		.016
	Cam angle (deg.)		28° - 32°
	Breaker arm tension (oz.)		19-23 oz.
Timing	Crankshaft deg. @ rpm.		5° BTDC
	Mark location		Crankshaft Balancer
Spark Plug	Make		A.C.
	Model		44
	Thread (mm)		14MM
	Tightening torque (lb. ft.)		25 lb/ft.
	Gap		.035
Cable	Conductor type		Resistant Core
	Insulation type		Neoprene
	Spark plug protector		"

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 Eldorado

ELECTRICAL—SUPPRESSION

Locations & type	Packard Electric - Dist. Resistance Wire .3 MFD on Coil Feed Terminal .5 MFD on Gen-Reg Feed Terminal Two Ground Straps - Rear of Cylinder Head Two Ground Straps - Upper Control Arms

ELECTRICAL—INSTRUMENTS AND EQUIPMENT

Speedometer	Make	AC
	Trip odometer (yes, no)	Yes
Charge indicator—type		Tell-Tale
Temperature indicator—type		Gauge
Oil pressure indicator—type		Tell-Tale
Fuel indicator—type		Gauge
Other		Trunk Warning Lite - Tell-Tale
Windshield wiper	Make	Delco
	Type—Standard	Electric
	Type—Optional	-
	Vacuum booster provision	-
	Washer provision	Yes
Horn	Type	Solenoid Vibrating Diaphram
	Number used	3
	Amp draw (each)	4.5 - 5.5

DRIVE UNITS—CLUTCH (Manual Transmission)

Make & type		None Available
Type pressure plate springs		
Total spring load (lb.)		
No. of clutch driven discs		
Clutch facing	Material	
	Outside & inside dia.	
	Total eff. area (sq. in.)	
	Thickness	
	Engagement cushioning method	
Release bearing	Type & method of lubrication	
Torsional damping	Methods: springs, friction material	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 15

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

DRIVE UNITS—TRANSMISSIONS

Manual 3-speed (std. or opt.)	N.A.
Manual 4-speed (std. or opt.)	N.A.
Manual with overdrive (std. or opt.)	N.A.
Automatic (std. or opt.)	Standard

DRIVE UNITS— MANUAL TRANSMISSION

Number of forward speeds			None Available
Transmission ratios	In first		
	In second		
	In third		
	In fourth		
	In reverse		
Synchronous meshing, specify gears			
Shift lever location			
Lubricant	Capacity (pt.)		
	Type recommended		
	SAE viscosity number	Summer	
		Winter	
		Extreme cold	

DRIVE UNITS— MANUAL TRANSMISSION WITH OVERDRIVE

For transmission data see manual transmission section			None Available
Type (planetary or other)			
Manual lockout (yes, no)			
Downshift acelerator control (yes, no)			
Minimum cut-in speed			
Gear ratio			
Lubricant	Capacity (pt.) (Overdrive only)		
	Separate filler (yes, no)		
	Type recommended		
	SAE viscosity number	Summer	
		Winter	
		Extreme cold	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

AKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (●)

MODEL 69347 Eldorado

DRIVE UNITS—AUTOMATIC TRANSMISSION

Trade name		Turbo-Hydramatic
Type describe		Variable Vane Converter W/ Step Gear Shifts
Method of Selection (Lever, Push Button or other)		Lever
Selector Pattern		P - R - N - 'D' - L
List gear ratios Selector Pattern and indicate which are used in each selector position		Low Gear 2.48 Intermediate Gear 1.48 High Gear 1.00 Reverse 2.09 Plus Converter Multiplication of 2.00
Max. upshift speeds—drive range		80 - 85
Max. kickdown speeds—drive range		65 - 75
Torque convertor	Number of elements	3
	Max. ratio at stall	
	Type of cooling (air, liquid)	Liquid-Water
Lubricant	Capacity—refill (pt.)	Approx. -
	Type recommended	Fluid Type "A" (Suffix A)
Special transmission features		Driven Through a Chain From Engine Mounted Converter Chain Length Chain Width Chain Pitch

DRIVE UNITS—PROPELLER SHAFT

Number used		Two (1 Piece L. 2 Piece R)
Type (exposed, torque tube)		Exposed
Outer diameter x length* x wall thickness	Manual 3-speed transmission	N.A.
	Manual 4-speed transmission	N.A.
	Overdrive transmission	N.A.
	Automatic transmission	1.29 X 23.53 x N.A.

*Center to center of universal joints, or to centerline of rear attachment.

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (e)

MODEL 69347 Eldorado

DRIVE UNITS—PROPELLER SHAFT (cont.)

Intermediate bearing	Type (plain, anti-friction)		None
	Lubrication (fitting, prepack)		None
Universal joints	Make		Saginaw
	Number used		4 Joints
	Type (ball and trunnion, cross, other)		(2) Ball Spline Rezeppa (Inboard) (2) Rzeppa (Outboard)
	Bearing	Type (plain, anti-friction)	Ball
		Lubric. (fitting, prepack)	Pre-Packed (Permanent)
Drive taken through (torque tube or arms, springs)			Not Applicable
Torque taken through (torque tube or arms, springs)			Not Applicable

DRIVE UNITS—REAR AXLE

Description			
Limited Slip differential, type			
Drive Pinion Offset			
No. of differential pinions			
Ring gear O.D. (std. ratio)			
Pinion adjustment (shim, other)			
Pinion bearing adj. (shim, other)			
Wheel bearing type			
Lubricant	Capacity (pt.)		
	Type recommended		
	SAE viscosity number	Summer	
		Winter	
		Extreme cold	

REAR AXLE RATIO TOOTH COMBINATIONS

(See page 4 for axle ratio usage)

Axle ratio		3.21
No. of teeth	Pinion	14
	Ring gear	45

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 18

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 Eldorado

DRIVE UNITS—WHEELS

Type & material			Spider SAE 1010 Rim SAE 1010
Rim (size and flange type)		Std.	15 X 6 JK
		Opt.	N.A.
Attachment	Type (bolt or stud)		Stud
	Circle diameter		5.00 In.
	Number and size		5 1/2 20

DRIVE UNITS—TIRES

Standard (List option below)	Size & ply	9.00 X 15 4 Ply Rating - 2 Ply Black
	Type - Nylon, etc.	Rayon
Rev/mile at 50 mph.		714
Inflation press. (cold)	Front	24
	Rear	22
Optional tires - size and ply		9.00 X 15 4 Ply Rating - 2 Ply W/W

BRAKES—SERVICE

Type (duo-servo, disc, balanced, etc.)			Hydraulic Duo-Servo
elf adjusting (std., opt., N.A.)			Std.
Hydraulic system type (single, dual, etc.)			Dual
Power brake make & type (remote, integral, etc.)			Moraine - Direct Hyd. Vacuum
Effective area (sq. in.) *			196
Gross lining area (sq. in.) **			228
Swept drum area (sq. in.) ***			328
Percent brake effectiveness—front			62.2
Drum or Rotor	Diameter	Front	11.00
		Rear	11.00
	Type and material		Full Cast Iron Finned Drum
	Rotor (vented or solid)		-
	No. pistons per caliper		-
Wheel cylinder bore	Front		1 1/8
	Rear		7/8
Master cylinder bore			1.00
Available pedal travel			4.50 Min.
Line pressure at 100 lb. pedal load			1100 PSI
Shoe clearance adjustment			.010 - .030

* Excludes rivet holes, grooves, chamfers, etc.

** Includes rivet holes, grooves, chamfers, etc.

*** Total swept area for four brakes:
Widest lining contact width for each brake x its drum circumference.

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 Eldorado

DRIVE UNITS—WHEELS

Type & material		
Rim (size and flange type)	Std.	
	Opt.	
Attachment	Type (bolt or stud)	
	Circle diameter	
	Number and size	

DRIVE UNITS—TIRES

Standard (List option below)	Size & ply	
	Type - Nylon, etc.	
Rev/mile at 50 mph.		
Inflation press. (cold)	Front	
	Rear	
Optional tires - size and ply		

BRAKES—SERVICE

Type (duo-servo, disc, balanced, etc.)			Disc
Self adjusting (std., opt., N.A.)			Self Adjusting
Hydraulic system type (single, dual, etc.)			Dual
Power brake make & type (remote, integral, etc.)			Bendix - Direct Hyd. Vac.
Effective area (sq. in.) *			118
Gross lining area (sq. in.) **			137
Swept drum area (sq. in.) ***			360
Percent brake effectiveness—front			N.A.
Drum or Rotor	Diameter	Front	
		Rear	
	Type and material		Rotor: Cast Iron
	Rotor (vented or solid)		Vented
	No. pistons per caliper		4
Wheel cylinder bore	Front		1 15/16
	Rear		7/8
Master cylinder bore			1.00
Available pedal travel			4.50" Min.
Line pressure at 100 lb. pedal load			1100 PSI
Shoe clearance adjustment			N.A.

* Excludes rivet holes, grooves, chamfers, etc.

(Continued)

** Includes rivet holes, grooves, chamfers, etc.

*** Total swept area for four brakes:
Widest lining contact width for each brake x its drum circumference.

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 19

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 Eldorado

BRAKES—SERVICE (cont.)

Brake lining	Drum or Disc			Drum
	Bonded or riveted			Riveted
	Front Wheel	Material		Marshal 3152 R & F
		Size (length x width x thickness)	Prim. or out-board	12 X 2.75 X .20
			Second. or in-board	12 X 2.75 X .29
		Segments per shoe		1
	Rear Wheel	Material		Marshal 3152 R & F
		Size (length x width x thickness)	Prim. or out-board	12 X 2.00 X .20
			Second. or in-board	12 X 2.00 X .29
		Segments per shoe		

BRAKES—PARKING

Type of control		Foot Operated - Vacuum Released
Location of control		Left Side Below Inst. Panel
Operates on		Rear Service Brakes
If separate from service brakes	Type (internal or external)	N.A.
	Drum diameter	N.A.
	Lining size (length x width x thickness)	N.A.

FRAME

Type and description (Separate frame, unitized frame, partially - unitized frame)	Boxed perimeter frame extending to rear of passenger compartment. Integral construction rear of passenger compartment.

STEERING

Manual (std., opt., NA)				N.A.
Power (std., opt., NA)				Std.
Adjustable steering wheel (tilt, swing, other)		Type and description		Tilt & Telescope
		(std., opt., NA)		Opt.
Wheel diameter		Manual		N.A.
		Power		15.5"
Turning diameter	Outside front	Wall to wall (l. & r.)		44.7
		Curb to curb (l. & r.)		41.3
	Inside rear	Wall to wall (l. & r.)		23.3
		Curb to curb (l. & r.)		23.9
Outside wheel angle with inside wheel at 20°				18.2°
Manual	Gear	Type		N.A.
		Make		
		Ratios	Gear	
			Overall	
	No. wheel turns			

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

BRAKES—SERVICE (cont.)

Brake lining	Drum or Disc			Disc
	Bonded or riveted			Riveted
	Front Wheel	Material		JM 2000B - 44
		Size (length x width x thickness)	Prim. or outboard	5.34 X 1.9 X .43
			Second. or inboard	5.34 X 1.9 X .43
		Segments per shoe		One
	Rear Wheel	Material		Marshal 3152 R & F
		Size (length x width x thickness)	Prim. or outboard	12 X 2.00 X .20
			Second. or inboard	12 X 2.00 X .29
		Segments per shoe		

BRAKES—PARKING

Type of control		
Location of control		
Operates on		
Separate from service brakes	Type (internal or external)	
	Drum diameter	
	Lining size (length x width x thickness)	

FRAME

Type and description (Separate frame, unitized frame, partially - unitized frame)	

STEERING

Manual (std., opt., NA)			
Power (std., opt., NA)			
Adjustable steering wheel (tilt, swing, other)		Type and description	
		(std., opt., NA)	
Wheel diameter		Manual	
		Power	
Turning diameter	Outside front	Wall to wall (l. & r.)	
		Curb to curb (l. & r.)	
	Inside rear	Wall to wall (l. & r.)	
		Curb to curb (l. & r.)	
Outside wheel angle with inside wheel at 20°			
Manual	Gear	Type	
		Make	
		Ratios — Gear	
		Ratios — Overall	
	No. wheel turns		

(Continued)

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 20

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

STEERING (cont.)

Power	Type (coaxial, linkage, etc.).			Linkage - Variable Ratio Hyd. Power
	Make			Sag. Strg. Gear
	Gear	Type		Rack Piston Concentric Valve
		Ratios	Gear	16.0
			Overall	16.3
	Pump driven by			Belt
	Number wheel turns			2.7
Linkage	Type			Parallelogram
	Location (front or rear of wheels, other)			Front
	Drag link (trans. or longit.)			Transverse
	Tie rods (one or two)			Two
Steering Axis	Inclination at camber (deg.)			
	Bearings (type)	Upper		Spherical Joints
		Lower		Spherical Joints
		Thrust		Spherical Joints
Wheel ignment ange at curb weight and pre-ferred)	Caster (deg.)			
	Camber (deg.)			
	Toe-in (outside track inches)			
Steering spindle & joint type				Spherical Joint
Wheel spindle	Diameter	Inner bearing		
		Outer bearing		
	Thread size			
	Bearing type			

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 21

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (*)

MODEL 69347 Eldorado

SUSPENSION—GENERAL

(See Supplemental page for details on Air Suspension)*

Provision for car leveling		Frt. - Torsion Bar Adj. Rear Auto. Level Control
Provision for brake dip control		Anti-Dive Design of Suspension
Provision for acc. squat control		No Torque at Rear Wheels
Special provisions for car jacking		None
Shock absorber front & rear	Type	
	Make	
	Piston dia.	
Other special features		

SUSPENSION—FRONT

Type and description		
Spring	Type	Torsion Bar
	Material	SAE 5160H
	Size (coil design height & I.D.; bar length x dia.)	
	Spring rate (lb. per in.)	
	Rate at wheel (lb. per in.)	
Stabilizer	Type (link, linkless, frameless)	Link
	Material & bar diameter	

SUSPENSION—REAR

Type and description			Single Leaf Springs - 4 Shock Absorbers
Drive and torque taken through			Front
Spring	Type		Single Leaf
	Material		SAE 5160
	Size (length x width, coil design height & I.D.; bar length & dia.		Long Wide
	Spring rate (lb. per in.)		
	Rate at wheel (lb. per in.)		
	Mounting insulation type		Rubber Bushing Shackles & Rubber Insulator @ Axle
	If leaf	No. of leaves	One
		Shackle (comp. or tens)	Compression
Stabilizer	Type (link, linkless, frameless)		None
	Material		
Track bar type			

Form Rev. 4-65

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

BODY—MISCELLANEOUS INFORMATION

Drs. hinged (front, rear)	Front doors	Front
	Rear doors	None
Type of finish (lacquer, enamel, other)		Acrylic
Hood counterbalanced (yes, no)		Yes
Hood release control (internal, external)		External
Vehicle Indent. No. location		L.H. Lock Pillar
Engine No. location		Rear Top Crankcase
Theft protection - type		Ign. Key Start & Door Lock
Vent window control method (crank, friction pivot)	Front	None
	Rear	None
Seat cushion type	Front	Zig Zag Spring
	Rear	Zig Zag Spring
	3rd seat	None
Seat back type	Front	Zig Zag Spring
	Rear	Zig Zag Spring
	3rd seat	None
Windshield glass type (i.e., single curved - laminated plate)		Compound Curve - Laminated
Side glass type (i.e., curved - tempered plate)		Curved - Tempered
Backlight glass type (i.e., compound curved - tempered plate, three piece)		Curved - Tempered
Windshield glass exposed surface area		1372
Side glass exposed surface area		1740
Backlight glass exposed surface area		844
Total glass exposed surface area		3957.2

LAMP HEIGHT AND SPACING

Height above ground to center of bulb	Headlamp	Highest *	-
		Lowest	26.72
	Tail	Highest	-
		Lowest	29.33
Distance from C/L of car to center of bulb	Headlamp	Inside	20.72
		Outside *	-
	Tail	Inside	33.25
		Outside	-
	Directional	Front	23.94
		Rear	33.25

* If single headlamps are used enter here.

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 23

MAKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

MODEL 69347 Eldorado

CONVENIENCE EQUIPMENT

(Indicate whether standard, optional or NA on each series)

Power windows	Side Windows	Standard - Rear Quarter Optional
	Vent Windows	N.A.
	Backlight or tailgate	N.A.
Power seats (specify type as well as availability)		Std. - 6-Way Power Optional **
Reclining front seat back		N.A. Optional (Passenger Only)
Front seat headrest		Optional
Radios (specify type as well as availability)		A.M. Std. - A.M. - F.M. & Stereo Optional
Rear seat speaker		Std.
Power Antenna		Std.
Clock		Std.
Air Conditioner (specify type and availability)		Optional
Speed warning device		N.A.
Speed control device		Optional
Ignition lock lamp		Std.
Back up lamp		Std.
Dome lamp		Std.
Glove compartment lamp		Std.
Prkg. brake signal lamp		Std.
Luggage compartment lamp		Std.
Underhood lamp		N.A.
Courtesy lamp		Std.
Map lamp		Std.
Auto. trans. quad. lamp		Std.
Emergency flasher lamp		Std.
Cornering light lamp		Std.
Heater & Defr.		Std.
Rear Window Defogger		Opt.

** 4-Way Power Bucket Seat Only

Form Rev. 4-65

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 24

AKE OF CAR Cadillac MODEL YEAR 1967 DATE ISSUED 10-6-66 REVISED (•)

WEIGHTS (Est.)

Model	CURB WEIGHT - POUNDS Front	Rear	Total	% PASS. WEIGHT DISTRIBUTION Pass. In Front Front	Pass. In Front Rear	Pass. In Rear Front	Pass. In Rear Rear	SHIPPING WEIGHT
69347	2755	1939	4694					4500

Accessories & Equipment Differential Weights				Remarks
Pwr. Rear Qtr. Windows			6.0	
Pwr. Door Locks			9.0	
6-Way Pwr. Seat			11.9	
Pwr. Trunk Lock			8.9	
Cruise Control			12.5	
Rear Window Defogger			4.5	
Radio A.M.			11.2	
Radio Stereo			15.5	
Pwr. Antenna			4.0	
Air Conditioner			125.0	
Padded Roof			12.0	

Downloaded from www.Manualslib.com manuals search engine

AMA Specifications—Passenger Car

Page 25

INDEX

SUBJECT	PAGE NO.
Automatic Transmission	1, 16
Axis, Steering	20
Axle, Rear	1, 17
Battery	12
Bearings, Engine	5, 6, 7
Belts - Fan, Generator, Water Pump	11
Body - General Information, types	Title, 1, 2, 22
Exterior Dimensions	1
Interior Dimensions	2
Brakes - Parking, Service, Power	18, 19
Camber	20
Camshaft	6
Capacities	
Cooling System	11
Fuel Tank	10
Lubricants	
Engine Crankcase	8
Transmission and Overdrive	15, 16
Rear Axle	17
Carburetor	4, 9, 10
Caster	20
Choke, Automatic	10
Clutch - Pedal Operated	14
Coil, Ignition	13
Connecting Rods	5
Convienience Equipment	23
Cooling System	11
Crankcase Ventilation	8
Crankshaft	5
Cylinders and Cylinder Head	3
Distributor - Ignition	13
Electrical System	12, 13, 14
Engine	
Bore, Stroke, Displacement, Type	1, 3
Compression Ratio	1, 3
Firing Order, Cylinder Numbering	3
General Information, H.P. & Torque	1, 3
Lubrication	7, 8
Power Teams	4
Exhaust Emission Control	9
Exhaust System	8
Equipment Availability	22
Fan, Cooling	11
Filters - Engine Oil, Fuel System	8, 10
Frame	19
Front Suspension	21
Fuel, Fuel Pump, Fuel System	1, 3, 10
Fuel Injection	1, 10
Generator and Regulator	12
Glass	22
Height (Lamps)	14
Headroom - Body	2
Heights - Overall	1
Horns	14
Horsepower - Brake	1, 3, 4
Ignition System	13
Inflation - Tires	18
Instruments	8, 14
Kingpin (Steering Axis)	20
Lamp Height & Spacing	22
Legroom	2
Lengths - Overall	1
Lifters, Valve	6

SUBJECT	PAGE NO.
Linings - Clutch, Brake	14, 18, 19
Lubrication	7, 8, 14, 15, 16, 17
Luggage Capacity	2
Motor, Starting	12
Muffler	8
Overdrive	15
Piston Pins & Rings	3, 5
Pistons	3, 5
Power Brakes	18
Power Steering	19
Power Teams	4
Propeller Shaft, Universal Joints	16, 17
Pumps - Oil, Fuel	8, 10
Water	11
Radiator, Hoses	11
Ratios - Axle	1, 4, 17
Compression	1, 3, 4
Steering	19, 20
Transmission	15, 16
Rear Axle	1, 4, 17
Regulator - Generator	12
Rims	18
Rings, Piston	5
Rods - Connecting	5
Shock Absorbers, Front & Rear	21
Spark Plugs	13
Speedometer	14
Springs - Front & Rear Suspension	21
Valve, Engine	6
Stabilizer (Sway Bar) - Front & Rear	21
Starting Motor	12
Steering	19, 20
Suppression - Ignition, Radio	14
Suspension - Front & Rear	21
Tailpipe	8
Thermostat, Cooling	11
Timing, Engine & Valve	6, 7, 13
Tires	1, 18
Toe in	20
Torque Converter	16
Torque - Engine, Rated	1, 3, 4
Transmission - Types	1, 4, 10, 15, 16
Automatic	1, 4, 10, 15, 16
Manual & Overdrive	1, 4, 10, 15
Ratios	15, 16
Track	1
Trunk Luggage Capacity	2
Turning Diameter	19
Unitized Construction	19
Universal Joints, Propeller Shaft	16, 17
Valves - Intake & Exhaust	6, 7
Vibration Damper	6
Voltage Regulator	12
Water Pump	11
Weights - Shipping, Curb	24
Wheel Alignment	20
Wheelbase	1
Wheels & Tires	18
Wheel Spindle	20
Widths - Car & Body	1
Windshield	22
Windshield Wiper	14

Downloaded from www.Manualslib.com manuals search engine