

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
FRONT:			
Hub nut	104	1,050	77
Tie rod end lock nut	74	750	55
Steering knuckle x Shock absorber	210	2,150	155
Steering knuckle x Brake caliper	107	1,090	79
Steering knuckle x Tie rod end	49	500	36
Axle hub x Drive shaft	294	3,000	217
Lower ball joint x Lower suspension arm	127	1,300	94
Lower ball joint x Steering knuckle	123	1,250	90
Steering knuckle x Dust cover	8.3	85	74 in.·lbf
Drive shaft center bearing lock bolt	32	330	24
Suspension support x Body	80	820	59
Suspension support x Piston rod	49	500	36
ABS speed sensor set bolt	7.8	80	69 in.·lbf
Flexible hose and ABS speed sensor wire harness x Shock absorber	29	300	22
Lower suspension arm set bolt	206	2,100	152
Stabilizer bar bracket x Suspension member	19	195	14
Stabilizer bar link set bolt	39	400	29
PS gear assembly set bolt	181	1,850	134
REAR:			
Hub nut	104	1,050	77
Axle hub set nuts	80	820	59
Shock absorber x Body	25	250	18
Shock absorber x Rear axle beam	37	380	27
Brake line union nut	15	155	11
ABS speed sensor wire harness clamp set bolt	18	185	13
Parking brake cable clamp set bolt	7.8	80	69 in.·lbf
Exhaust front pipe x Exhaust tail pipe	56	550	41
Axle beam x Body	88	900	65