

STEERING

SERVICE DATA

SS05R-02

DRIVE BELT		
Drive belt tension	New belt	150 - 185 lbf
Drive belt tension	Used belt	95 - 135 lbf
POWER STEERING FLUID		
Fluid level rise	Maximum	5 mm (0.20 in.)
Fluid pressure at idle speed with valve closed	Minimum	7,845 kPa (80 kgf/cm ² , 1,138 psi)
STEERING WHEEL		
Steering wheel freeplay	Maximum	30 mm (1.18 in.)
Steering effort at idle speed	Maximum	5.9 N·m (60 kgf·cm, 52 in.·lbf)
PS VANE PUMP		
Vane pump rotating torque	Maximum	0.3 N·m (2.8 kgf·cm, 2.4 in.·lbf)
Oil clearance between pump shaft and bushing	STD	0.03 - 0.05 mm (0.0012 - 0.0020 in.)
Oil clearance between pump shaft and bushing	Maximum	0.07 mm (0.0028 in.)
Vane plate height	Minimum	8.6 mm (0.339 in.)
Vane plate thickness	Minimum	1.397 mm (0.0550 in.)
Vane plate length	Minimum	14.991 mm (0.5902 in.)
Clearance between the rotor groove and plate	Maximum	0.035 mm (0.0014 in.)
Vane plate length	Pump rotor and cam ring mark	
	NONE	14.999 - 15.001 mm (0.59051 - 0.59059 in.)
	1	14.997 - 14.999 mm (0.59043 - 0.59051 in.)
	2	14.995 - 14.997 mm (0.59035 - 0.59043 in.)
	3	14.993 - 14.995 mm (0.59027 - 0.59035 in.)
	4	14.991 - 14.993 mm (0.59020 - 0.59027 in.)
Spring free length	Minimum	32.3 mm (1.272 in.)
PS GEAR		
Steering rack runout	Maximum	0.03 mm (0.0118 in.)
Total preload (Control valve rotating torque)		0.8 - 1.4 N·m (8 - 14 kgf·cm, 6.9 - 12.2 in.·lbf)