

3100 Overview of Technical Data

Front axle G20 ride height hybrid sports suspension settings not low-slung

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).	17" wheel rim	612 mm
	18" wheel rim	625 mm
	19" wheel rim	637 mm
	20" wheel rim	650 mm

Front axle G20 ride height sports suspension settings with low-slung

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).	16" wheel rim	579 mm
	17" wheel rim	594 mm
	18" wheel rim	607 mm
	19" wheel rim	620 mm
	20" wheel rim	632 mm

Front axle G20 ride height, hybrid standard suspension

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).	17" wheel rim	613 mm
	18" wheel rim	625 mm
	19" wheel rim	638 mm
	20" wheel rim	650 mm

Ride height on front axle G20 of standard suspension

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).

16" wheel rim	590 mm
17" wheel rim	606 mm
18" wheel rim	618 mm
19" wheel rim	631 mm
20" wheel rim	643 mm

Track width of front axle G20 for rear wheel drive

	Rim offset 22	
		1589 mm
	Rim offset 25	
		1583 mm
	Rim offset 27	
		1579 mm
	Rim offset 30	
		1573 mm

Wheelbase

	2851 mm
--	---------

31 operating fluid overview

Transmission oil

Technically suitable front axle transmission oils

[Main group 31](#)

cardiagn.com