

GAS STATION INFORMATION

- **Fuel selection:**

Select premium unleaded gasoline with a Research Octane Number of 96 (Octane Rating 91) or higher for optimum engine performance. However, if such premium type cannot be obtained, you may temporarily use unleaded gasoline with an octane number as low as 91.

- **Fuel tank capacity:**

80 L (21.1 gal., 17.6 Imp. gal.)

- **Engine oil:**

API SH, Energy-Conserving II multigrade engine oil or ILSAC multigrade engine oil.

Recommended oil viscosity – SAE 5W-30 if normal temperatures are below 38°C (100°F)

Oil capacity: L (qt., Imp. qt.)

Drain and refill

with filter 5.4 (5.7, 4.8)

without filter 5.1 (5.4, 4.5)

See page 171 for detailed information.

- **Engine coolant:**

Capacity: 7.5 L (7.9 qt., 6.6 Imp. qt.)

Coolant type– Ethylene-glycol coolant (Do not use alcohol coolant.)

For checking the engine coolant, see page 173.

- **Automatic transmission:**

Fluid type – **Automatic transmission fluid Type T-II** or equivalent

- **Tire information:**

See page 180 through 185 for detailed information.

- **Tire pressure:**

Tire size: P215/60R16 94V

Tire pressure: Front 210 kPa

(2.1 kgf/cm² or bar, 30 psi)

Rear 210 kPa

(2.1 kgf/cm² or bar, 30 psi)

For sustained high speeds above 160 km/h (100 mph), in countries where such speeds are permitted by law, add 90 kPa (1.0 kgf/cm², 0.9 bar, 13 psi) to the front tires and rear tires, but never exceed the maximum cold tire pressure molded on the tire sidewall.