

33 00 General - track width E84

Track width for normal position and offset (ET)		
- ET 30	mm	1537
- ET 34	mm	1529
- ET 41	mm	1515

33 00 Rear axle - ride height E84 / AWD

Ride level height in normal position		
Attach tape measure to bottom middle of rim flange and measure to lower edge of wheel arch		
Tolerance ride height in		
- Normal position max. 10 mm		
- Design position max. 2 mm		
Difference ride height between left/right in		
- Normal position 10 mm		
- Design position 2 mm		
Standard suspension		
17" rim	mm $\pm$ 10	629
18" rim	mm $\pm$ 10	642
19" rim	mm $\pm$ 10	654
Sports suspension settings		
17" rim	mm $\pm$ 10	629
18" rim	mm $\pm$ 10	642
19" rim	mm $\pm$ 10	654

33 10 Rear axle final drive 168L

Use only approved final drive oils (refer to BMW Service Operating Fluids).		
New oil quantity	ltr.	0,8

33 10 Rear axle final drive 168L

Use only approved final drive oils (refer to BMW Service Operating Fluids).		
New oil quantity	ltr.	0,8

33 10 Rear axle final drive 188LW

Use only approved final drive oils (refer to BMW Service Operating Fluids).		
New oil quantity	ltr.	0.85

33 10 Rear axle final drive 168L

Use only approved final drive oils (refer to BMW Service Operating Fluids).		
New oil quantity	ltr.	0,8