

3100 Overview of Technical Data

Front axle G20 ride height of standard suspension, all-wheel drive vehicle

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).

17" wheel rim	610 mm
18" wheel rim	623 mm
19" wheel rim	635 mm
20" wheel rim	648 mm

Front axle G20 ride height sports suspension settings not low-slung, all-wheel drive vehicle

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).

17" wheel rim	610 mm
18" wheel rim	622 mm
19" wheel rim	635 mm
20" wheel rim	648 mm

Front axle G20 ride height sports suspension settings, low-slung, all-wheel drive vehicle

Ride height (A): Measured from bottom centre of rim flange (1) to lower edge of wheel arch (2).

17" wheel rim	602 mm
18" wheel rim	614 mm
19" wheel rim	627 mm
20" wheel rim	639 mm

Track width of front axle G20 all-wheel drive vehicle

	Rim offset 25	1583 mm
	Rim offset 27	1579 mm
	Rim offset 30	1573 mm

Wheelbase

	2851 mm
--	---------

31 operating fluid overview

Transmission oil

Technically suitable front axle transmission oils

[Main group 31](#)

cardiagn.com